



**TOOL &  
SAFETY  
DIVISION**

**HARRISONBURG, VIRGINIA**  
(540) 433-7727 • 1-800-796-9027 • [www.specialfleet.com](http://www.specialfleet.com)



Utility, Safety & Construction  
Supply Catalog  
3rd Edition



# Quality Work & Service: It's Who We Are.



Special Fleet Service began in 1983 as an equipment upfitter but with roots in the utility industry since 1937, we quickly realized the need for supplier and service in the tool and safety industry.

We are the only commercial lineman's protective rubber testing facility in Virginia. Our on-site facility is located in the beautiful Shenandoah Valley, centrally located in the middle of the east coast.

We pride ourselves in high standards of quality control and customer service. While we aim to make information accessible quickly and easily, we excel in personal contact and are available by phone, email or in person meetings-at our office, or yours.

**Storm Service**-No matter what the weather, you never stop working-we don't either. We know our customers are on the frontline's during snow, storms and anything else Mother Nature throws at them. When you're fighting the weather, you need the tools in-hand to complete your mission, Special Fleet takes our responsibility during storm duty very seriously. From tool orders, rubber goods, grounds and jumpers, we prioritize storm orders to get them out the door and into the hard working hands that need them. Available 24/7/365, never hesitate to call SFS at our main office or your trusted sales representative.

Let us show you what special service from Special Fleet is all about.





In addition to our complete line of tools and safety products, we also offer:

- Dielectric testing of all lineman's protective rubber products to meet or exceed ANSI/ASTM standards
- Large inventory of rubber goods, quick turn-around to help keep your inventory requirements to a minimum
- Mobile dielectric testing and annual inspection of bucket trucks and Digger Derricks
- Complete tool repair and rebuild capabilities of all hydraulic, pneumatic, electric, manual hand tools, hoist and gas drills
- Fiberglass restoration of hot stick and arms
- Customized repair and testing programs available to meet your price and logistic requirements

**Questions, Comments, Orders & Quotes:**

**Contact us today!**

**Phone: 540-433-7727 or 800-796-9027**

**Fax: 540-438-9502**

**Email: [store@specialfleet.com](mailto:store@specialfleet.com)**



[facebook.com/specialfleet](https://facebook.com/specialfleet)



search: Special Fleet Service



**Special Fleet Service proudly offers tools and equipment from these quality manufacturers:**

- |   |   |   |
|---|---|---|
| <p><b>3M</b>-Cable Locators<br/> <b>A.B. Chance</b>-Utility Construction Tools<br/> <b>AW Sperry</b>-Test Meters<br/> <b>AEMC</b>-Test Meters<br/> <b>Aircraft Dynamics</b>-Robo Tools<br/> <b>Bashlin</b>-Lineman &amp; Arborist Tools<br/> <b>Bethea</b>-Stringing Blocks<br/> <b>Bierer and Associates</b>-Test Meters<br/> <b>Bone</b>-Traffic Signals<br/> <b>Brunner &amp; Lay</b>-Demolition Tools<br/> <b>Buckingham Mfg.</b>-Lineman &amp; Arborist Tools<br/> <b>Burndy</b>-Hydraulic Tools, Dies &amp; Accessories<br/> <b>Capital Safety</b>-Fall Protection<br/> <b>Carolina</b>-Work Gloves<br/> <b>Cembre</b>-Crimping &amp; Cutting Tools<br/> <b>Cementex</b>-Insulated Hand Tools<br/> <b>Condux</b>-Underground/Overhead Utility Tools<br/> <b>Cooper</b>-Utility Construction Tools<br/> <b>Council Tool</b>-Digging &amp; Brush Tools<br/> <b>Current Tools</b>-Electrician Tools<br/> <b>DCD</b>-Cable Installation Products<br/> <b>Dillon</b>-Dynamometers<br/> <b>Dixie Tool</b>-Cant Hooks, Load Binders, Pole Tongs<br/> <b>Eagle Line Tools</b>-Utility Tools<br/> <b>Erin</b>-Rope<br/> <b>Estex</b>-Canvas Products<br/> <b>Global Glove</b>-Work Gloves<br/> <b>GMP</b>-Utility Tools<br/> <b>Golight</b>-Remote Control Spotlights<br/> <b>Greenlee</b>-Battery &amp; Hydraulic Tools</p> | <p><b>H.K. Porter</b>-Bolt &amp; Cable Cutters<br/> <b>Hastings</b>-Fiberglass Products<br/> <b>HD Electric</b>-Electric Test &amp; Measurement<br/> <b>Huskie</b>-Battery/Hydraulic Crimping &amp; Cutting Tools<br/> <b>Irwin</b>-Drill Bits<br/> <b>Jameson</b>-Construction &amp; Maintenance Tools<br/> <b>JBC Safety Plastics</b>-Traffic Cones, Barricade Bars<br/> <b>Jenny Tools</b>-Utility Tools<br/> <b>Justin</b>-FR Clothing<br/> <b>Kinco</b>-Winter Gloves<br/> <b>Klein</b>-Hand Tools<br/> <b>Knopp</b>-Test Meters<br/> <b>Leidy Tool Company</b>-Fiberglass Digging Bars<br/> <b>Lewis Mfg.</b>-Cable Grips, Dirt Tarps<br/> <b>Lincoln Hoist</b>-Strap Hoists<br/> <b>Little Mule</b>-Grips &amp; Hoists<br/> <b>Lugall</b>-Strap &amp; Cable Hoists<br/> <b>Madi</b>-Lineman Tools<br/> <b>MYTE</b>-Winches<br/> <b>OshKosh</b>-Pole Line Construction Tools<br/> <b>Parker</b>-Hydraulic Fittings<br/> <b>Peavey Mfg.</b>-Pole Line Construction Tools<br/> <b>Pengo</b>-Auger &amp; Backhoe Teeth<br/> <b>Pelsue</b>-Manhole Ventilation/Gas Monitors<br/> <b>Plastic Techniques</b>-Bucket/Boom Components<br/> <b>Princeton Tec.</b>-Flashlights/Headlamps<br/> <b>Radians</b>-Safety Vests</p> | <p><b>Rauckman Utility Products</b>-Insulated Wrenches<br/> <b>Ripley</b>-Cable Prep Tools<br/> <b>Ridgid</b>-Power Tools<br/> <b>Rubbermaid</b>-Water Coolers<br/> <b>Salisbury</b>-Lineman's Rubber &amp; Equipment<br/> <b>Safeway Sling</b>-Nylon Slings &amp; Straps<br/> <b>S&amp;C</b>-Load Busters<br/> <b>Sensor Link</b>-Ampstik, Test Meters<br/> <b>Servus Rubber</b>-Protective Footwear<br/> <b>Seymour Mfg.</b>-Fiberglass Hand Tools<br/> <b>Sherman &amp; Reilly</b>-Utility Tools<br/> <b>Slingco</b>-Swivels, Cable Grips<br/> <b>Speed Systems</b>-Cable Prep Tools<br/> <b>Stanley</b>-Hydraulic Tools<br/> <b>Streamlight</b>-Flashlights, LiteBox<br/> <b>Stucchi</b>-Hydraulic Fittings<br/> <b>Tegam</b>-Electronic Test Equipment<br/> <b>Terex Reedrill</b>-Augers &amp; Components<br/> <b>Timco Instruments</b>-Electronic Test Equipment<br/> <b>Tulsa Power Products</b>-Reel Handlers<br/> <b>Utility Solutions</b>-Hot Line Tools<br/> <b>Utility Tool &amp; Body</b>-Pole Trailer Accessories<br/> <b>Wanco</b>-Traffic Control Devices<br/> <b>Warren Heim</b>-Canvas Products<br/> <b>Werner</b>-Ladders<br/> <b>Work Area Protection</b>-Traffic Safety<br/> <b>Youngstown Gloves</b>-Work</p> |
|---|---|---|



## Fully Customized Grounds & Jumpers

Grounds and jumpers protect your employees, keeping them safe from hazardous, potentially fatal occurrences. That's why choosing the best, is a good choice.



Special Fleet Service will custom build grounds and jumpers to your exact specifications. With a large quantity of parts in stock, we waste no time getting your equipment made and shipped to the field.

Quotes available: [store@specialfleettools.com](mailto:store@specialfleettools.com)

### Custom Choices:

- Clamp
- Size & Length
- KV Ratings of Cable (for Jumpers)
- Ferrules Determined through Cable & Clamp Selection
- All Ground Sets will have Heat Shrink Applied



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## On-Site Testing

You have a job to get done. When you don't have time to ship your grounds and jumper to us, let us come to you. Special Fleet will work with your company to set up on-site testing by a trained technician on your home turf. Call us today to set up the most convenient way to get your equipment checked out and back to work.



**Visual Inspection-** Standards set by ASTM and IEEE recommends looking for these signs you're dealing with a potential hazard:

- Damaged, split or cracked clamps
- Cable damage, especially where the cables flexes next to the ferrules
- Wear on clamp tightening bolt threads
- Flattened/smashed section of the cable
- Wear on the clamp jaws
- Corrosion, typically indicated by swollen cable jackets or soft spots
- Difficult to operate threaded clamping mechanism
- Loose connections between the cable and clamps or the ferrules and clamps
- Broken cable strands near connection points



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Full Service Dielectric Test Lab

Our testing facility is over 18,000 square feet, fully staffed and ready to serve all of your testing needs. We are proudly NAIL accredited and closely follow all ASTM standards, including their sequence recommendation.



With over 2 million dollars of rubber goods and tooling inventory in a climate controlled warehouse, SFS can help you avoid costly lead times.



**All rubber goods testing includes the following steps:**

- Check-In
- Washing of Materials
- Preliminary Inspection
- Electrical Testing
- Drying
- Final Inspection
- Record-Keeping and Marking
- Powdering
- Pairing
- Packing



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fiberglass Restoration & Repair

Hard work, is hard on equipment. Fiberglass tools get worn over time. Instead of throwing away these costly tools, or worse yet, using up valuable space storing them; let us repair those tools. Special Fleet will restore your tools to like-new conditions, test your hot sticks and arms and return them to you quickly and efficiently; getting you back to getting the job done, and saving you money while doing it.



Ruined?



Restored!

Our work adheres to all ASTM standards.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Tool Repair

Our tool repair facility is fully equipped with a vast parts inventory to repair a variety of tools, quickly and efficiently. At Special Fleet, we know that down time is costly, our goal is to get the tools you already own back in prime operating condition and back to you. Our facility has over 25 years of tool repair experience so you can feel assured quality work is being done on your tools.

### Types of Tools Serviced:

- Battery Powered Tools
- Hydraulic Tools
- Hot Sticks
- Air Tools
- Chain & Strap Hoists

### Railroad Tools Serviced:

- Geismar
- Matweld
- Racine
- Simplex
- Stanley
- Many others!

### Why SFS Tool Repair?

- Decades of Experience
- Huge Parts Inventory  
On-Site
- Quick Turn-Around
- Factory Trained
- Save Money



### Factory Trained to Repair:

- Burndy
- Cembre
- Fairmont
- Greenlee
- Huskie
- Little Mule
- Stanley

These are just some of the factory trained courses our technicians have completed!

# Same Tools, Better Condition



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools



### EK425L Gator Battery Powered Crimper

- One handed operation
- Crimping jaws open wide to fit easily over connectors
- Jaws can be jogged closed until they just grip the connector, allowing the operator to position the cable in the connector before finishing the crimp
- Crimping tool will complete about 325 crimps per battery charge on 4/0 AWG splices
- When a crimp is fully completed the EK425L signals the operator can simply push a button on the back side of the tool
- Crimping force: 6 tons
- 18V Lithium-ion battery
- Crimping capacity:
  - ☐ 5/8" Service entrance connectors: 10-1/0 AWG
  - ☐ .840 Service entrance connectors: 1/0-4/0 AWG
  - ☐ Aluminum H taps: 6-4/0 AWG
  - ☐ Copper H taps: 10-2 AWG
  - ☐ Copper tension splices: 6-2/0 AWG
  - ☐ All aluminum tension splices: 6-4/0 AWG
  - ☐ 1-Piece ACSR tension splices: 4-1/0 AWG
  - ☐ 2-Piece ACSR tension splices: 2 AWG-477 kcmil
  - ☐ Aluminum jumper splices: 4 AWG-266.8 kcmil
  - ☐ Stirrups: 2-4/0 AWG
  - ☐ Copper color-coded lugs and splices: 8 AWG-500 kcmil
  - ☐ Aluminum color-coded lugs and splices: 8-4/0 AWG
- Weight: 6.8 lbs.

### Crimping and Cutting Jaws



CJXPJ



CJB



CJK



CJD3



Greenlee #	Description
EK425LDO11	Crimping Tool w/CJD3O Jaws w/120V Battery Charger
EK245LDO12	Crimping Tool w/CJD3O Jaws w/12V Battery Charger
EK425LDBG11	Crimping Tool w/CJD3BG Jaws w/120V Battery Charger
EK425LDBG12	Crimping Tool w/CJD3BG Jaws w/12V Battery Charger
EK425LK12	Crimping Tool w/CJK Jaws w/12V Battery Charger
EK425LK11	Tool with Case

Greenlee #	Description
CJD3	Crimping Jaw Unit-"W" Dies
CJD3BG	Crimping Jaw Unit-D3 & B3 Die Grooves
CJD3O	Crimping Jaw Unit-D3 & O Die Grooves
CJK	Crimping Jaw Unit-Thomas & Betts 6 Ton Dies
CJXPJ	Crimping Jaw with Nicopress X, P & J Die Grooves
CJB	Cutting Jaw for One Time Disposable Lock Hasps



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools

### 6 Ton SL-ND Robo-Crimp with Changeable Head

- Forged jaws for long life
- Brush Protection
- Pull-pin design for quick jaw changes
- Bright white, LED lights for working in low light conditions
- Three compression heads-ND, O and BG
- Rotational head
- Audible bypass when predetermined pressure is achieved
- Connector range:
  - ☐ Lugs and splices: #8-500 MCM Cu, #8-350 MCM Al
  - ☐ H-Taps: Up to 4/0-4/0
- Weight: 8 lbs.
- Optional Heads Include:



Huskie #	Description
SL-NDO	D3 Nest w/"O" Jaw, w/AC Charger
SL-NDO-DC	D3 Nest w/"O" Jaw, w/DC Charger
SL-ND-BG	"BG" Jaw, w/AC Charger
SL-ND-BG-DC	"BG" Jaw, w/DC Charger



SLBG-Jaw



SL-CHCUAL



SL-CHACSR



SLND-Jaw



SLO-Jaw



SLCUT-Jaw

Huskie #	Description
ECO-EZOL	w/AC Charger
ECO-EZOL-DC	w/DC Charger
ECO-EZBGL	BG Jaw, w/AC Charger
ECO-EZBGL-DC	BG Jaw, w/DC Charger
ECO-EZOX	Tool Only w/case



### 6-Ton ECO-EZ Robo-Crimp with Changeable Head

- Switch between multiple heads with the pull-pin design
- Swivel head design allows the jaws to rotate 180°
- Brush protection
- Audible bypass when predetermined pressure is achieved
- Accepts all W & X type dies
- Connector Range:
  - ☐ Lugs and splices- #8-500 MCM Cu, #8-300 MCM Al
  - ☐ H-Taps-Up to 4/0-4/0
- Weight: 6 lbs.
- Optional Heads Include:



EZBG



EZND



EZK



EZO



XPJ-Jaw

### 6-Ton Streamline Robo-Crimp Compression Tool

- Lightweight, ergonomic design
- One handed operation
- Tested up to 75kV
- Compatible with all Huskie 14.4V Batteries
- Connector Range:
  - ☐ #8-500 MCM Cu, #8-350 MCM Al

Huskie #	Weight
IL-ND	7.3 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Battery Tools



**Cembre**

Cembre #	Description
B54N-YD6	BG Nose Die
B54N-YD6-8	O Nose Die

### 18.0 V Cordless Hydraulic Crimping Tool

- One handed operation
- Jaws rotate 180° for ease of operation in confined spaces
- Quiet with minimal vibration
- Two batteries, AC charger and vinyl bag included
- Battery equipped with LED indicators that indicate remaining battery life
- 54 kN Force developed
- Capacity:
  - ☐ Copper Lugs & Splices: 300 MCM
  - ☐ Aluminum Lugs & Splices: 4/0
  - ☐ Aluminum H taps: 4/0-4/0
- Weight 6.49 lbs.

### Patriot PATMD6-LI Battery Powered Crimper

- 6 Ton output force
- Refined hydraulic system, field proven electronics
- One handed operation for advance, retracts, and hold
- Overmolded handle, ergonomically balanced design
- Advance design high-speed pump
- 350° Rotatable head
- Pressure “pop-off” valve indicates completed crimp
- Ram holds position when trigger released
- Capable of using all “W” and “X” style dies
- Crimping capacity: CU, AL, ACSR, Steel, CUWeld, ALWeld, compressed/compact conductors, taps, splices, terminators, terminals
- Weight: 7.8 lbs.

Burndy #	Description
PATMD6-LI	18V, Li-Ion Battery with AC Charger Permanent BG (5/8”) and D3 Grooves
PATMD6-LI-DC	18V, Li-Ion Battery with DC Charger Permanent BG (5/8”) and D3 Grooves
PATMD6-8LI	18V, Li-Ion Battery, with AC Charger Permanent O and D3 Grooves
PATMD6-8LI-DC	18V, Li-Ion Battery with DC Charger Permanent O and D3 Grooves



**BURNDY**



**BURNDY**

### Patriot In-Line PATMDCUT Battery Powered Cutter

- One handed operation
- Interchangeable scissor action jaws
- 350° Rotatable jaw assemblies
- Actuated blade guide
- One set of ACSR blades to cut all specified materials
- Includes durable carry bag, two batteries and charger
- Maximum cutting capacity:
  - ☐ CU-500 kcmil
  - ☐ AL-636 kcmil
  - ☐ ACSR-556.5 kcmil
  - ☐ EHS Guy strand/rebar/CUWeld/ALWeld-3/8”
- Weight: 8 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools

**Standard ROBO Kits Include:**

- Battery powered tool
- Carrying Case
- CH-94 Lithium ion charger
- BP-84 Lithium ion battery (2)
- Carrying strap

- 5-year warranty on tool, battery & charger

**The Rec-6 Series Features:**

- Quicker cutting and compression cycles, blue housing with rubber inlay and ergonomic, lighter weight design

**6-Ton Robo-Crimp**

- One handed operation
- Rotational head, rapid advance
- Audible bypass when predetermined pressure is achieved
- Brush protection
- Pull-pin design for quick jaw change
- Interchangeable cutter head optional (25CAT)
- Connector Range:
  - ☐ Lugs & splices-#8-500 MCM CU, #8-300 MCM AL
  - ☐ H-Taps-Up to 4/0-4/0

Huskie #	Description	Weight
REC-658U	w/AC Charger, 1.8" Jaw Opening	8 lbs.
REC-658U-DC	w/DC Charger, 1.8" Jaw Opening	8 lbs.



Burndy #	Description
PAT600-LI	18V, Li-Ion Battery with AC Charger
PAT600-LI-DC	18V, Li-Ion Battery with DC Charger

**Patriot PAT600-LI Battery Powered Crimper**

- 6 Ton output force
- Refined hydraulic system, field proven electronics
- Overmolded comfort-grip handle that allows for one-handed operation for advance, retract, and hold
- Advance design high speed pump completes crimp in 3 seconds
- Specialized latch head design
- Crimping capacity:
  - ☐ CU-#8 up to 600 kcmil
  - ☐ AL-#8 350 kcmil
- Weight: 10.9 lbs.

**6-Ton Robo-Crimp Compression Tool with Changeable Head**

- 1-3/8" Jaw opening
- One handed operation
- Rotational head, rapid advance
- Audible bypass when predetermined pressure is achieved
- Forged jaws for longer life
- 10 Jaw types to choose from, not all pictured
- Connector Range:
  - ☐ Lugs & Splices: #8-500 MCM Cu,
  - ☐ H-Taps: Up to 4/0-4/0

Huskie #	Weight
REC-6NDSL	9.8 lbs.



SLBG-JAW



SLO-Jaw



SL-CHCUAL



SL-CHACSR



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Battery Tools



6750



Huskie #	Description
REC-6750	w/AC Charger
REC-6750-DC	w/DC Charger

### 6.2-Ton Streamline Robo-Crimp Dieless Crimping Tool

- 1.5" Jaw Opening
- Designed to crimp Anderson connectors & other brand connectors manufactured to ANSI C119.4
- Rotational, flip-top head
- Tested up to 75kV
- Bright white, LED lights for working in low lighting
- Audible bypass when predetermined pressure is achieved
- Connector Range:
  - ☐ #6 AWG-750 MCM

Huskie #	Weight
SL-750	10.35 lbs.

### 6.2-Ton Robo-Crimp Dieless Crimping Tool

- 1.5" Jaw opening
- Designed to crimp Anderson connectors & other brands manufactured to ANSI C119.4
- Rotational head, rapid advance
- Audible bypass, when predetermined pressure is achieved
- Ergonomically balanced for one handed operation
- Flip-top head design
- Connector Range:
  - ☐ Lugs and Splices-#6 AWG-750 MCM
- Weight: 12 lbs.



Greenlee #	Description
EK06ATL12	Crimping Tool, Open Head Dieless, 12V Charger
EK06ATCL11	Crimping Tool, Open Rubber Covered Head Dieless, 120V Charger
EK06FTL11	Crimping Tool, Flip-Top Head Dieless, 120V Charger
EK06FTL12	Crimping Tool, Flip-Top Head Dieless, 12V Charger

### EK06 Gator Quad-Point Battery Powered Dieless Crimper

- Utilizes four indentors to make the crimp
- Flip-top style uses a pull pin to open head for easy removal from the connector
- Crimping force: 12,400 lbs.
- Crimping capacity (EK06ATL):
  - ☐ Copper lugs and copper splices: 6 AWG-500 kcmil
  - ☐ Aluminum lugs and aluminum splices: 6 AWG-400 kcmil
- Crimping capacity (EK06FTL):
  - ☐ Copper lugs and copper splices: 6 AWG-750 kcmil
  - ☐ Aluminum lugs and aluminum splices: 6 AWG-750 kcmil
- Weight: 12 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools

**6.2-Ton Robo-Crimp Dieless****Compression Tool**

- .90" Jaw opening
- One handed operation
- Rotational head, rapid advance
- Audible bypass when predetermined pressure is achieved
- Eliminates need for dies
- Tested up to 75kV
- Connector Range:
  - ❑ Lugs & splices: 20 AWG-500 MCM

Huskie #	Weight
REC-6630	11.4 lbs.

**Burndy Patriot Battery Tools Include:**

- 5 year limited warranty on tool
- Lifetime power train warranty on Infinity Drive and 1-year warranty on battery and charger
- Typically comes with a high impact formed carrying case, two batteries, charger and tool lanyard



Burndy #	Description
PAT4PC834-LI	18V, Li-Ion Battery with AC Charger
PAT4PC834-LI-DC	18V, Li-Ion Battery with DC Charger

**Patriot PAT4PC834-LI Battery Powered Dieless Crimper, 4-Point**

- 6 Ton output force
- Refined hydraulic system, field proven electronics
- C-Shaped head design with 360° head rotation
- Overmolded comfort-grip handle that allows for one-handed operation for advance, retract, and hold
- Crimping capacity:
  - ❑ CU-#8 up to 1,000 kcmil
  - ❑ AL-#8 750 kcmil
- Weight: 13.85 lbs.

**Patriot PAT81KFT-LI Battery Powered Dieless Crimper, 4-POINT**

- 12 Ton output force
- Refined hydraulic system, field proven electronics
- One-handed operation for advance, retract, and hold
- 360° Head rotation for tight areas
- No need to purchase and maintain dies
- Ergonomically balanced design
- Crimping capacity:
  - ❑ CU-#8 1,000 kcmil
  - ❑ AL-#8 750 kcmil
- Weight: 13.2 lbs.

Burndy #	Description
PAT81KFT-LI	18V, Li-Ion Battery with AC Charger
PAT81KFT-LI-DC	18V, Li-Ion Battery with DC Charger



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools



Burndy #	Description
PAT46-LI	18V, Li-Ion Battery with AC Charger
PAT46-LI-DC	18V, Li-Ion Battery with DC Charger

### Patriot PAT46-LI Battery Powered Crimping Tool

- 15 Ton output force, 2" jaw opening
- Redesigned field proven electronics
- Y46 Tool head, capable of using all "P" and "U" style dies
- C-Head crimp design with 355° head rotation
- Versatile tool head positioning for tight areas
- Overmolded ergonomic handle
- Retractable assist handle
- Crimping capacity:
  - ❑ CU-8 A WG-1,500 kcmil
  - ❑ AL-8 A WG-1,250 kcmil
- Weight: 25.5 lbs.



### EK1550 Gator 15-Ton Battery Powered Crimper

- Crimping Force: 30,000 lbs.
- Includes handle (23492)
- Crimping capacity: (EK1550FT)
  - ❑ Color-coded copper lugs and splices: 8 A WG-1,500 kcmil
  - ❑ Aluminum lugs and splices; 8 A WG-1,250 kcmil
- Length: 18.5", Weight: 16.3 lbs.
- Crimping capacity: (EK1550L)
  - ❑ Color-coded copper lugs and splices: 8 A WG-1,000 kcmil
  - ❑ Color-coded aluminum lugs and splices; 8 A WG-1,000 kcmil
- Length: 19-5/8", Weight: 19 lbs.
- Accepts Kearney PH4/P14 dies without adapter

Greenlee #	Description
EK1550FTLU11	Crimping Tool w/120V Charger
EK1550FTLU12	Crimping Tool w/12V Charger
EK1550L11	Crimping Tool w/120V Charger
EK1550L12	Crimping Tool w/12V Charger



Cembre #	Weight
B1500A	21.34 lbs.

### 18V Cordless Hydraulic Crimping Tool

- Accepts all "P" dies
- With the AU150-C adapter, it will accept all the semi-circular "U" Dies
- Connector Range
  - ❑ Copper: #8 A WG-1500 MCM
  - ❑ Aluminum: #8 A WG-1250 MCM
- Maximum pressure sensor and pressure relief valve assure greater precision
- 136kN Force developed
- OLED display for battery power, service requirement and crimping force being generated



### 15-Ton Robo-Crimp Compression Tool

- 2" Jaw opening
- Rotational head, rapid advance
- Includes DIE-CASE
- External pressure adjustment
- Audible bypass when predetermined pressure is achieved

Huskie #	Weight
REC-3610	24 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools



Greenlee #	Description
EK12IDL11	Dieless Crimping Tool w/115V Battery Charger
EK12IDL12	Dieless Crimping Tool w/12V Battery Charger

### EK12IDL Gator Dieless Crimper

- Dieless indent style crimping head does not require interchangeable crimping dies
- Crimping force: 24,000 lbs.
- Crimping capacity:
  - ☐ Copper color-coded lugs and splices: 4 AWG-1,000 kcmil
  - ☐ Aluminum color-coded lugs and splices: 6 AWG-1,000 kcmil
- Length: 16-1/2"
- Weight: 15 lbs.

### Patriot PAT644-LI Battery Powered Dieless Crimper

- 11 Ton output force
- Refined hydraulic system, field proven electronics
- Overmolded comfort-grip handle that allows for one-handed operation for advance, retract, and hold
- No need to purchase and maintain dies
- 355° Head rotation for tight areas
- Crimping capacity:
  - ☐ CU-#6 1,000 kcmil
  - ☐ AL-#6 750 kcmil
- Weight: 16.3 lbs.

Burndy #	Description
PAT644-LI	18V, Li-Ion Battery with AC Charger
PAT644-LI-DC	18V, Li-Ion Battery with DC Charger



SL-510



Huskie #	Description	Weight
SL-510	Latched Head that fit's "U" Dies	13.55 lbs.
SL-C510	"C" Head with 1.65" Jaw Opening	14.9 lbs.

### 12-Ton Streamline Robo-Crimp Compression Tool

- One handed operation
- Tested up to 75kV
- Rotational head , rapid advance
- Audible bypass when predetermined pressure is achieved
- Connector Range:
  - ☐ Lugs & Splices-Up to 750 MCM Cu/Al

### 12-Ton Robo-Crimp

- 1.65" Jaw opening
- Accepts Kearney WH-2, PH-2 and WH-3 style dies (REC-5510KAT, 6510KAT)
- Accepts all "U" type dies (REC-5510AT, 6510AT)
- Rotational head, rapid advance
- Brush protection, ergonomically balanced for one handed operation
- Audible bypass when predetermined pressure is achieved
- Connector Range:
  - ☐ Lugs and Splices: Up to 750 MCM Cu/Al
- Weight: 13.5 lbs (6510)

Huskie #	Description
UDK-1	Kearney "U" style adapter for REC-6510K
REC6510K	w/AC Charger
REC-6510K-DC	w/DC Charger
REC-6510	w/AC Charger



REC-6510AT



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools



Burndy #	Description
PAT750K-LI	18V, Ni-MH Battery with AC Charger
PAT750K-LI-DC	18V, Ni-MH Battery with DC Charger

### Patriot PAT750-LI Battery Powered Crimper

- 12 Ton output force
- Refined hydraulic system, field proven electronics
- One-handed operation for advance, retract, and hold
- 355° Head rotation for tight areas
- Capable of using all "U" style dies
- Ergonomically balanced design
- Crimping capacity:
  - Tension sleeves-CU #9 500 kcmil, AL #8 587.2 kcmil, ACSR #4 556.5 kcmil
  - Taps-CU #14 500 kcmil, AL #8 500 kcmil
- Weight: 15.7 lbs.



Burndy #	Description
PAT750-LI	18V, Li-Ion Battery with AC Charger
PAT750-LI-DC	18V, Li-Ion Battery with DC Charger

Cembre #	Crimping Force
B1350L-CA	14.87 Tons

### EK1240 Gator 12-Ton Battery Powered Crimper

- Crimping force: 24,000 lbs.
- Crimping capacity (EK1240KL):
  - 8 AWG-750 kcmil copper color-coded lugs and splices
- Crimping capacity (EK1240KL):
  - ACSR Terminals: 1033 kcmil
  - ACSR Tension fittings: 477 kcmil
- Length: 16-1/4"
- Weight: 15 lbs.

Greenlee #	Description
EK1240L11	Crimping Tool, 1.65" Opening, 120V Charger
EK1240L12	Crimping Tool, 1.65" Opening, 12V Charger
EK1240KL12	Crimping Tool, Kearney Head, 12V Charger
EK1240KL11	Crimping Tool, Kearney Head, 120V Charger

### Patriot PAT750K-18V Battery Powered Crimper

- 12 Ton output force
- One-handed operation for advance, retract, and hold
- Crimp head design with 355° head rotation
- Capable of using Kearney WH1/WH2 dies and all "U" style dies with KUADP adapter
- Ergonomically balanced design
- Smooth, quiet and efficient tool design
- Crimping capacity:
  - Tension sleeves-up to 477 ACSR
  - Taps-through 500 kcmil
  - Terminals-up to 1033 kcmil
- Weight: 18.4 lbs.



### 18V Cordless Hydraulic Crimping Tool

- 1.65" Opening of head
- Maximum pressure sensor and security valve assure greater precision
- OLED display for battery power, service requirement, crimping force being generated
- Low noise and minimal vibration
- 132 kN force developed
- Weight: 18.04 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools

### ESG25L Battery Powered ACSR Cutter

- Designed to cut distribution ACSR cable
- 18V Lithium-ion battery
- LED light
- Lightweight and easy to control
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tool automatically retracts when the cutting cycle is complete
- Overmolded tack grip
- Capacity:
  - ☐ 1" Maximum diameter
  - ☐ ACSR: 636 kcmil
  - ☐ Standard guy strand: 5/8"
  - ☐ Ground rod: 3/8"
  - ☐ Rebar: 3/8"
  - ☐ Wire rope: 1/2"
- Length: 15"
- Weight: 4.6 lbs.



Greenlee #	Description
ESG25L11	Cutter w/120V Charger
ESG25L12	Cutter w/12V Charger
ESG25LB	Bare Tool Only w/Case

### 6-Ton Robo-Crimp Cutting Tool

- Lightweight, ergonomic design
- One handed operation
- Rotational head
- Tested up to 75kV
- Compatible with all Huskie 14.4V Batteries
- Weight: 6.8 lbs.



ECO-500



Huskie #	Cutting Capacities
ECO-336	ACSR-336 MCM Aluminum- 1.2" Copper-500 MCM
ECO-500	ACSR-Do Not Cut Aluminum-Up to 1.5" Copper-Up to 500 MCM

### Gear-Driven Cable Cutter

- 2-1/8" Jaw opening
- One handed operation
- Safety lockout switch
- Upgraded motor and gear system with improved ergonomic handle



Huskie #	Cutting Capacities	Weight
REC-54ACM	Aluminum: 1500 MCM  Copper: 1000 MCM	7.2 lbs.
REC-54M-DC	ACSR: 1590 MCM  Copper: 750 MCM	8 lbs.

### Patriot Jaw Assemblies and Cover Kits

- Designed for use with PATMD in-line tools
- Options for both cutting and crimping



Burndy #	Description
PATJAWS CUT	Cutter Jaw w/Replaceable Blades
PATJAWSMD6	BG & D3 Grooves
PATJAWSMD66	D3 Groove Only (snub-nose)
PATJAWSMD68	O & D3 Grooves
PATJAWSMD6K	Kearney Groove Only (snub-nose)
PATMD66JC	Cover Kit for MD66 Jaw
PATMD6JC	Cover Kit for MD6 and MD68 Jaw
PATMD6KJC	Cover Kit for MD6K Jaw



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools

**8-Ton Robo-Cut**

- Designed to cut the toughest steel used in construction today
- .95" Jaw opening (S524CC, S624CC)
- 1.6" Jaw opening (S540AT, S640AT)
- Flip-top, rotational latching head, one handed operation
- Overload bypass protection
- Cutting capacities (S524CC, S624CC):
  - ☐ ACSR-477 MCM
  - ☐ Standard guy wire-5/8"
  - ☐ EHS Guy wire-9/16"
  - ☐ Ground Rod-5/8"
  - ☐ Rebar (Sc 40)-5/8"
- Cutting capabilities (S540AT, S640AT):
  - ACSR-1590 MCM
  - ☐ Ground rod-5.8"
- Weight: 10 lbs.



Huskie #	Weight
REC-685YC	14.7 lbs.

Huskie #	Description
REC-S624CC	w/AC Charger
REC-S624CC-DC	w/DC Charger
REC-S640	w/AC Charger

Huskie #	Weight
REC-634YC	9.9 lbs.

**9-Ton Robo-Cut Cutting Tool**

- 3.3" Jaw opening
- Open scissor jaw for easy cable insertion
- One handed operation
- Rotational head, rapid advance
- Sidebar handle for stability and balance
- For copper and aluminum only
- Cutting capacities:
  - ☐ Aluminum: 3"
  - ☐ Telecommunication: 3"
  - ☐ Lead Sheath: 2.5"

**6.6-Ton Robo-Cut Cutting Tool**

- 1.4" Jaw opening
- Open scissor jaw for easy cable insertion
- Rotational head, rapid advance
- Overload bypass protection
- For copper and aluminum only
- Cutting Capacities:
  - ☐ Copper-800 MCM
  - ☐ Aluminum 1.4" O.D.

**Patriot PATCUT129-LI Battery Powered Cutter**

- Latch head design
- Overmolded comfort grip handle that allows for one handed operation for advance, retract, and hold
- 180° Head rotation
- Versatile tool head positioning for tight areas
- Maximum Cutting Capacity:
  - ☐ CU/AL-1.29"
  - ☐ ACSR-1,113 kcmil
  - ☐ Ground rod/rebar/soft steel bolts-5/8"
  - ☐ Std Guy wire-1/2"
  - ☐ EHS Guy wire-3/8"
- Weight: 10.2 lbs.

Burndy #	Description
PATCUT129-LI	18V, Li-Ion Battery with AC Charger
PATCUT129-LI-DC	18V, Li-Ion Battery with DC Charger



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools



Burndy #	Description
PATCUT2156-LI	18V, Li-Ion Battery with AC Charger
PATCUT2156-LI-DC	18V, Li-Ion Battery with DC Charger

**Patriot PATCUT2156-LI Battery Powered Cutter**

- Latch head design
- 180° Head rotation
- Versatile tool head positioning for tight areas
- Advance design high-speed pump completes tough cuts faster and provides longer life, efficiency and reliability
- Maximum cutting capacity:
  - ☐ CU/AL-2.0"
  - ☐ ACSR-2,156 kcmil
  - ☐ Ground rod-up to 3/4"
  - ☐ Rebar-up to 5/8"
  - ☐ Soft steel bolts-up to 3/4"
  - ☐ Std Guy wire-up to 9/16"
  - ☐ EHS Guy wire-up to 9/16"
- Weight: 15.5 lbs.

**Patriot In-Line Battery Powered Pole Cutters**

- Used with interchangeable MD6 Series jaw assemblies
- 350° Rotatable jaw assemblies for operation in virtually any position
- Ram holds position when the trigger is released allowing the operator to check alignment prior to the cut
- Interchangeable scissor action jaws allow to crimp or cut with the same tool
- Large hand grip area allows easier operation with gloves
- Ergonomically balanced tool design helps to lessen the operator fatigue
- Tool assembled with quality EPOXIGLAS poles per ASTM F711
- Actuated blade guide, automatically closes for easy positioning on cable and allows large diameter cable to be cut
- Includes durable high strength carry bag, two batteries and charger
- Maximum cutting capacity:
  - ☐ CU-500 kcmil
  - ☐ AL-636 kcmil
  - ☐ ACSR-556.5 kcmil
  - ☐ EHS Guy strand/CUWeld /ALWeld/rebar-3/8" diameter
- Weight:
  - ☐ 48"-12 lbs.
  - ☐ 60"-14 lbs.
  - ☐ 72"-17 lbs.



Burndy #	Description
PATMDCUT48LLI	18V, Li-Ion Battery, 48" w/ AC Charger
PATMDCUT60LLI	18V, Li-Ion Battery, 60" w/ AC Charger
PATMDCUT72LLI	18V, Li-Ion Battery, 72" w/ AC Charger

**Patriot PATCUT245CUAL Battery Powered Cutter**

- Ergonomic design, one hand operation
- Advance design high-speed pump, 180° head rotation
- Versatile tool head positioning for tight areas
- Mechanical ram release
- Maximum cutting capacity:
  - ☐ Copper and aluminum cable only-up to 2.45" OD
- Weight: 14.5 lbs.

Burndy #	Description
PATCUT245-LI	18V, Li-Ion Battery with AC Charger
PATCUT245-LI-DC	18V, Li-Ion Battery with DC Charger



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools



Greenlee #	Description
ESG50L11	Cable cutter w/120V Charger
ESG50L12	Cable cutter w/12V Charger
ESG50LB	Bare Tool Only w/Case

### ESG50L Battery Powered Cable Cutter

- Used for cutting copper and aluminum power cables
- 18V Lithium-ion battery
- Retraction stop allows the operator to stop the ram retraction at any point simply by tapping the trigger
- LED light
- 2-Stage hydraulic system
- Forward handle position
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tools automatically retract when the cutting cycle is complete
- Overmolded tacky grip
- Capacity: 2" diameter aluminum or copper cable
- Length: 15-3/4"
- Weight: 9.8 lbs.

### 18V Cordless Hydraulic Cutting Tool

- Manufactured from high strength, heat treated steel
- Double speed action
- Rotatable head by 180°
- Fitted with a maximum hydraulic pressure valve
- Low noise and minimal vibration
- Specifically designed to cut copper, aldreyl, aluminum, aluminum-steel cables, steel ropes having a max overall diameter of 1", guy wire up to 7/8" and steel ground rod up to 5/8"

Cembre #	Weight
B-TC250YA	10.56 lbs.



### ESG45L Battery Powered ACSR Cutter

- Designed to cut ACSR, guy strand and ground rods
- 18V Lithium-ion battery
- Retraction stop allows the operator to stop the retraction at any point simply by tapping the trigger
- LED light
- 2-Stage hydraulic system
- Forward handle position
- One trigger controls all tool functions
- Cutting head rotates 350°
- Capacity:
  - ☐ ACSR: 1,590 kcmil
  - ☐ EHS Guy strand: 1/2" diameter
  - ☐ Standard guy strand: 5/8" diameter
  - ☐ Ground rod: 5/8" diameter
  - ☐ Rebar: 1/2" diameter
  - ☐ Wire rope: 5/8" diameter
  - ☐ Soft steel bolts: 5/8" diameter
  - ☐ Copper and aluminum cable: 1,500 kcmil
- Length: 16-5/8"
- Weight: 13 lbs.



Greenlee #	Description
ESG45L11	ACSR Cable Cutter with 120V Charger
ESG45L12	ACSR Cable Cutter with 12V Charger
ESG45LB	Bare Tool Only w/Case



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools

### ESG55L Battery Powered ACSR Cutter

- Designed to cut the largest ACSR cables, ground rods and guy strands
- 18V Lithium-ion battery
- Retraction stop allows the operator to stop the ram retraction at any point simply by tapping the trigger
- LED light
- 2-Stage hydraulic system
- Forward handle position
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tool automatically retracts when the cutting cycle is complete
- Overmolded tacky grip
- Capacity:
  - ☐ ACSR: 2515 kcmil
  - ☐ Guy strand: 5/8"
  - ☐ EHS Guy strand: 9/16"
  - ☐ Ground rod: 3/4"
  - ☐ Rebar: 5/8"
  - ☐ Soft steel bolts: 3/4"
- Length: 18"
- Weight: 17.5 lbs.

Greenlee #	Description
ESG55L11	Cutter w/120V Charger
ESG55L12	Cutter w/12V Charger
ESG55LB	Bare Tool Only w/Case



Greenlee #	Description
ES32L11	Cutter with 120V Charger
ES32L12	Cutter with 12V Charger

### ES32L Battery Powered Cable Cutter

- Small size makes this an excellent tool for use inside panel box
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tool automatically retracts when cutting cycle is complete
- Capacity:
  - ☐ 500 kcmil Cu or Al Cable
- Length: 15-1/2"
- Weight: 5 lbs.



### ES20L Battery Powered ACSR Cutter

- Designed to cut distribution ACSR cable
- Scissor style blades make it easy to cut short tag ends on tap cables in H-tap connectors
- One trigger controls all tool functions
- Cutting head rotates 350°
- 18V Lithium ion battery
- LED light
- Capacity:
  - ☐ Cutter head opening 3/4"
  - ☐ ACSR 336 kcmil
  - ☐ Guy strand 3/8"
  - ☐ Ground rod 3/8"
  - ☐ Rebar 3/8"
- Length: 15"
- Weight: 4.6 lbs.

Greenlee #	Description
ES20L11	ACSR Cutter with 120V Charger
ES20L12	ACSR Cutter with 12V Charger
ES20LB	Bare Tool Only w/Case



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools



### “W” Style Dies

Dies for use with service entrance connectors, c-taps, overhead and underground connectors. (Use with EK425L with CJD3, CJD3BG & CJD30 jaws). Use with EK425L with CJK jaws with F020735 adapters.

More popular dies are shown, complete list is available.

#### EK1550L Die Adapters

Greenlee #	Description
48824	Adapter for Kearney PH2/WH2 Dies
48820	Adapter for Burndy “P” Dies (Y46), IlSCO ILD-P Dies
48802	Adapter for Greenlee and Burndy 12-Ton Dies, ILD Dies, T&B and Blackburn 15500 Dies



Greenlee #	Description
930	High Speed Steel Cutter Kit

### High Speed Steel Cutter Kit


- Lasts 10 times longer than standard hole saws
- Precision-ground teeth cuts smooth, burr-free holes
- Capacity: 1/4"
- Durability and speed provide low cost per hole
- Split-point pilot drill prevents “walking”-makes accurate hole placement easy
- Spring-loaded slug ejector
- No tool required to change cutter sizes
- Less chance of broken teeth because the saw body is machined out of solid, high-speed steel
- Includes:
  - ☐ 7/8" to 2-1/2" cutters
  - ☐ Two small arbors for extended assembly to 7/8" and 1-1/8" cutters
  - ☐ Larger arbor
  - ☐ Hex Wrench
  - ☐ Case
- For conduit sizes 1/2" through 2"

### “U” Style Die Adapter Set

- “U” Style for Greenlee and Burndy “U” Style, ILSCO ILD, T&B, 15500, and Blackburn



Greenlee #	Description
UA15T	U-Style Die Adapter Set (EK1550FT)



Burndy #	Description
W-BG	W-Die for 6-Ton Tools
W-C	W-Die for 6-Ton Tools
W-K840	W-Die for 6-Ton Tools
W-O	W-Die for 6-Ton Tools

### Burndy W-Dies

- Most popular versions are shown
- A complete selection of W, U and other die options are available



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Battery Tools

### Type "U" Die Kit

- CU-Comes complete with 15 "U" die sets for crimping #6 AWG through 750 kcmil copper
- AL-Comes complete with 15 "U" die sets for crimping #6 AWG through 750 kcmil aluminum
- HYGRD-Comes complete with eight die sets for crimping HYGROUND irreversible compression grounding connectors

Burndy #	Description
UDIEKITAL	Aluminum Crimping Die Set, with Case
UDIEKITCU	Copper Crimping Die Set, with Case
UDIEKITHYGRD	HYGROUND Crimping Die Set, with Case



**BURNDY**



Huskie #	Description
HTK1-182H	Kearney Equivalent 1-1/8"
HTK-BKT	Kearney Equivalent BKT Die
HTK-D	Kearney Equivalent D Die
HTK-N-3	Kearney Equivalent N Die
HTK-1-516H	Kearney Equivalent 1-15/16" (Hex)

### HTK Series Dies

- Equivalent to Kearney WH-2 (10.77) and WH-3 (12T) type dies

Greenlee #	Description
KD12AL	For 12-Ton Tools, 6 AWG to 750 kcmil Aluminum Connectors
KD06AL	For 6-Ton Tools, 8 AWG to 350 kcmil Aluminum Connectors
KD12CU	For 12-Ton Tools, 6 AWG to 750 kcmil Copper Connectors
K22S1GL	For 6-Ton Tools, 8 AWG to 600 kcmil Copper Connectors



**GREENLEE**  
A Tektren Company

### Die Kits

- For 6 and 12 ton tools
- Includes almost all aluminum and copper dies needed



Huskie #	Description
CH-94	AC Charger Kit
CH-94DC	DC Charger Kit

### CH-94 Battery Charger

- 110V AC Power Cord
- Designed for Huskie Lithium Ion batteries only
- Redesigned contact terminals for stronger engagement with battery
- UL/CUL Agency Approvals
- Monitors battery temperature and battery voltage for correct charging
- One hour charge time



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Battery Tools

### BP-84 Battery Pack, Lithium Ion

- Lightweight, high capacity 4.0Ah Battery Pack
- 50% longer run times as compared to NiCad
- No memory effect
- Impact resistant housing
- Performance is minimally affected by extreme temperatures
- Minimal self-discharge
- Non-hazardous chemistry and environmentally safe
- BP-84 can be charged with any Huskie Lithium Ion chargers (including CH-80, CH-90 & CH-94)

Huskie #	Description
BP-84	4.0Ah Battery Pack



Greenlee #	Description
RAM3GL	9.6V, 3.0Ah Battery

### Battery

- High capacity NIMH battery
- For old style EK425 tools

### 18V LXT Lithium-Ion Battery

- 30-minute charge time when used with Makita's rapid optimum charger
- Battery resists self-discharge and remains ready for use even after long periods of storage
- Compatible with certain Greenlee and Burndy power tools
- Memorizes the usage history for efficient recharges

Makita #	Description
BL1830	18V Lithium-ion, 3Ah



Makita #	Description
DC18RC	18V Rapid Battery Charger, 110V AC
DC18SE	18V Battery Charger, 12V DC

### Li-Ion Battery Charger

- Optimal charging method is achieved using three Active Controls (thermal, voltage, and current) to maximize the effectiveness of the charge and extend the battery's life
- Recognizes battery's history and analyzes battery condition to determine optimal charging method
- Advanced CUP communicates with individual's battery's memory chip
- Built-in fan to cool the battery during charging to maximize the life of the battery



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools

**H8508 1/2" Impact Wrench**

- Twin-hammer impact mechanism provides high performance and reliability
- Button to switch between forward and reverse rotation
- 1-Piece handle and impact housing casting provide long life
- Super Spool permits quick switches between open center and closed center hydraulic systems
- Heat-insulated handle, ergonomically positioned for comfort
- Well balanced for comfortable operation
- Includes the 49314 heavy-duty 1/2" square drive adapter
- Operating pressure: 1,000-2,000 psi
- Maximum torque: 400'-lb @ 8 gpm
- Capacity: 7/16" hex
- Length: 8.2"

Greenlee #	Description
H8508-1	High Torque 1/2" Impact Wrench with 7/16" Hex Quick Change Chuck, 7.4 lbs.
H8508-1V	High Torque 1/2" Impact Wrench w/Flow Control & 7/16" Hex Quick Change Chuck, 7.7 lbs.



Burndy #	Description
HIW716MAG	MAG Hydraulic Impact Wrench, Variable Torque

**HIW716 MAG Low Pressure Hydraulic Impact Wrench**

- Aircraft grade extruded aluminum body and forged handle
- Frictionless gerotor motor
- Injection molded replaceable comfort grips
- Glove-sized handle and activation trigger
- Reduced handle-to-trigger distance
- Reverse flow and hook-up prevention
- Dual spool selector for open and closed center use
- Over 550 ft.-lbs. of torque
- Optimal pressure: 1,000-2,250 psi
- Weight: 7.6 lbs.

**7/16" Quick Connect Hydraulic Impact Wrench**

- Reverse-flow check valve prevents operation if the tools is plumbed backwards
- Built in selector for open center or closed center systems
- 500 ft/lbs. torque
- Large trigger
- Weight: 7 lbs.

Stanley #	Description
ID07810	High Impact Wrench



Burndy #	Description
HIW 716ENF	Enforcer Hydraulic Impact Wrench, Variable Torque

**HIW716 Enforcer Hydraulic Impact Wrench**

- 7/16" Tri-ball quick chuck
- Dual torque selector spool
- CNC Machined billet aluminum
- Dual spool open/closed operation
- Optimal pressure: 750-2,000 psi
- 515 ft/lbs. Torque
- Weight: 5.95 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hydraulic Tools

### HW1 1/2" Hydraulic Impact Wrench

- Impact and temperature resistant replaceable polymer grip designed to dissipate heat from the cast handle
- Improved center-of-gravity for superior ergonomics
- Increased service life with the addition of back-up rings and larger O-rings
- Built-in hydraulic check valve
- Large and strong lifting eye for easy and secure storage
- Longer and wider trigger
- Fast and easy change between open center systems and closed center systems with no disassembly required
- Higher breaking torque in reverse to ensure you can remove tightened bolts
- Cast motor enclosure that better protects the impact mechanism operation versus competing models with stamped steel enclosure
- Includes the 49314 heavy-duty 1/2" square drive adapter
- Operating pressure: 1,000-2,500 psi
- Capacity: 7/16" hex
- Length: 8.2"
- Weight: 6.5 lbs.
- Maximum torque: 500'-lb @ 8 gpm



Greenlee #	Description
HW3	High Torque 3/4" Impact Wrench

### HW3 3/4" Hydraulic Impact Wrench

- High torque 3/4" impact wrench with 3/4" square drive with auxiliary handle
- Forward positioned handle for improved balance and reduced fatigue
- Impact and heat-resistant Cool Grip handle+ dissipates heat
- Large onboard lifting eye for easy and secure storage
- Industry-leading weight to torque ratio
- Quickly change between forward and reverse motions with direct control selector
- Adjustable torque setting with variable flow knob
- Operating pressure: 1,000-2,500 psi
- Capacity: 3/4" square
- System: super spool selector control
- Length: 9.3"
- Weight: 10.5 lbs.



Greenlee #	Description
HW1	High Torque 1/2" Impact Wrench with 7/16" Hex Quick Change Chuck
HW1V	High Torque 1/2" Impact Wrench with Torque Adjustment & 7/16" Hex Quick Change Chuck

### Nail Eater Extreme Auger Bits

- Quickly bore through creosoted and salt-treated utility poles
- Resists wear, eats through nails and staples
- Self-feeding screw point draws the bit through the wood
- 7/16" Hex shank to fit impact drivers
- Available in 18" overall length



Greenlee #	Size	Hole Diameter	Hardware Diameter
37868	9/16"	5/8"	1/2"
37869	11/16"	3/4"	5/8"
37870	13/16"	7/8"	3/4"
37871	15/16"	1"	7/8"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools

**12-Ton Low Pressure Crimper**

- No high pressure intensifier required
- Relief valve signals operator when crimp is complete
- Compatible with dies for:
  - ☐ Burndy Y35
  - ☐ Alcoa 12A, 12AC, 12HA, 12HAC
  - ☐ Anderson HC-12, HC-12H
  - ☐ Thomas & Betts 12-ton (LPK1230)
- Accepts standard "U" style dies (LPK1230)
- Crimps up to 750 MCM copper and aluminum (LPK1240)
- Head rotates for easy tool positioning
- Powered in both the advance and retract directions to prevent hang-ups
- Relief valve assures 12 ton crimp with 1,500-2,500 psi system
- Crimping force: 24,000 @ 1,500 psi
- 3/4-16 SAE O-ring
- Open and closed center hydraulic system



Greenlee #	Length	Weight	Jaw Opening
LPK1230	19.3"	18.5 lbs.	1.20"
LPK1240	20.3"	19.7 lbs.	1.65"

**LPK1240K 12-Ton Kearney Low Pressure Crimper**

- No high pressure intensifier required
- Relief valve signals operator when crimp is complete
- Compatible with dies for Kearney PH-2 and PH-3 tools
- Head rotates for easy tool positioning
- Powered in both the advance and retract directions to prevent hang ups
- Relief valve assures 12 ton crimp with 1,500-2,500 psi system
- Crimping force: 24,000 lbs. @ 1,500 psi
- Open and closed center hydraulic system
- Weight: 19.5 lbs.

Greenlee #	Length
LPK1240K	20.3"

**LHPY750XT Low Pressure Hydraulic Compression Tool**

- 12-Ton output force
- Covers a wide range of applications with 1.65" jaw opening
- 350° Head rotation for versatile tool head positioning in tight areas
- Uses all standard BURNDY "U" dies
- Operates on open center or closed center hydraulic systems
- Double acting tool for hydraulic ram advance and retraction
- Operating pressure: 1,500-2,500 psi (103-172 BAR)
- Weight: 21 lbs.



Burndy #	Description
LHPY750XT	Kompressor Hydraulic Compression Tool



Greenlee #	Length
LPK1550	23.8"

**LPK1550 15-Ton Universal Low Pressure Crimper**

- No high pressure intensifier required and crimps cable 500 MCM and larger
- Relief valve signals operator when crimp is complete
- Compatible with dies for:
  - ☐ Kearney PH2 and PH4/PH14
  - ☐ Burndy Y35 and Y46
  - ☐ Penn-Union TPU-15PH
  - ☐ Thomas & Betts TBM 15 PF
- Operating pressure: 1,500-2,500 psi
- Crimping force: 30,000 lbs. @ 1,500 psi
- Open and closed center hydraulic system
- Weight: 28.6 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools

**LPK1550FT 15-Ton Flip-Top Crimper, Low Pressure**

- Accepts P-style die to crimp splices and lugs up to 1500 kcmil copper and 1250 kcmil aluminum
- Accepts Greenlee KC12, KA12 and KD12 crimping dies as well as industry U-style dies with options UA15T adapters
- Lightweight flip-top head with patented quick release locking pin
- 2" Jaw opening
- Crimping head rotates 350°
- Crimping force: 30,000 lbs.
- Crimping capacity:
  - ❑ Color-coded copper lugs and splices: 8 AWG-1500 kcmil
  - ❑ Aluminum lugs and splices: 8 AWG-1250 kcmil
- Open and closed center hydraulic system



Greenlee #	Length	Weight
LPK1550FT	23.5"	25 lbs.
UA15T	Adapter for Greenlee and Burndy "U" Style Dies, Ilco ILD Dies, T&B and Blackburn 15500 Dies	

**LP6 6-Ton Hydraulic Crimper**

- Interchangeable crimping and cutting jaws
- Spring-loaded quick-release pin
- 350° Rotating head
- Maximum inlet pressure: 2,500 psi
- Operating pressure: 1,500-2,500 psi
- Pressure and return ports: 3/4-16 SAE O-ring
- Weight: 8.4 lbs.

Greenlee #	Description
LP6-01	Bare, No Coupler, Open Center
LP6-02	Bare, No Coupler, Closed Center
LP6-05	CJD3BG Jaw, No Coupler, Open Center
LP6-06	CDJ3BG Jaw, No Coupler, Closed Center
LP6-09	CJD3O Jaw, No Coupler, Open Center
LP6-10	CJD3O Jaw, No Coupler, Closed Center
LP6-13	CJD3 Jaw, No Coupler, Open Center
LP6-14	CJD3 Jaw, No Coupler, Closed Center
LP6-17	CJK Jaw, No Coupler, Open Center
LP6-18	CJK Jaw, No Coupler, Closed Center



Burndy #	Description
RHCC10A	Remote Powered Hydraulic Cable Cutter

**RHCC10 Remote Power Cable Cutter**

- Reinforced C-head design for field and OEM applications
- Interchangeable precision cutting blades for copper, aluminum, ACSR, EHS guy strand, ground rod and rebar
- Steel cylinder
- 10,000 psi, 13.2 lbs.
- Maximum cutting capacity
  - ❑ Cu/Al Cable-up to 1.5" (HCCCUAL blades)
  - ❑ ACSR/ACSS-up to 1,590 kcmil (ACSR/ACSS blades)
  - ❑ Ground Rod-up to 5/8" (HCCSOL blades)
  - ❑ Rebar-up to 1/2" (HCCSOL blades)
  - ❑ Soft steel bolts-up to 5/8"
  - ❑ Std & EHS Guy-9/16" (GUY blades)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hydraulic Tools


**60-Ton Compression Head**

- Ram Stroke: 1.5" Travel
- Designed for ACSR & ACAR Transmission and Distribution Cable
- Ultra light titanium model available
- Extremely portable

Huskie #	Order Data	Oil Volume
EP-60WB	Steel, Single Acting Compression Head	312 cc
EP-60DT	Titanium Model	312 cc
EP-60D	Steel, Double Acting Compression Head	303 cc
EP-60DT	Titanium Model	303 cc



EP-60WB



EP-60DT



Huskie #	Weight
EP-100WD	78 lbs.

**100-Ton Compression Head, Double-Acting**

- 1.16" Ram stroke
- Designed for full tension transmission and substation connections
- Double acting hydraulic cylinder for quicker return times
- Removable die caps for easy cable insertion
- Oil required: 25 cu/in

**RHU600 Hydraulic Presshead Crimper**

- Hydraulic presshead complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 10,000 psi max
- Weight: 49.28 lbs.

Cembre #	Description
RHU600	600 kN Force Developed

**RK6040 Single Acting 60-Ton Crimper**

- Ideal tool for use in substation and transmission construction
- Accepts Burndy L dies and Alcoa 6000 series crimping dies
- After completing a connection, the top of the head easily swivels 90° and can be lifted from the tool to remove the connector
- Removing the tool from the stand exposes a lifting eye for when the tool must be used above ground level
- Requires 10,000 psi single-acting hydraulic power source
- Includes steel carrying case with storage space for dies
- Crimping force: 120,000 lbs @ 10,000 psi
- Capacity:
  - ☐ Copper stranded code cable: 300-2000 kcmil
  - ☐ Aluminum stranded code cable: 250-2000 kcmil
  - ☐ Copper tension sleeves: 1/0 AWG-1000 kcmil
  - ☐ Aluminum tension sleeves: 1/0 AWG-2300 kcmil
  - ☐ ACSR Tension Sleeves: 1/0 AWG-2156 kcmil
  - ☐ Copper aerial connectors: 4/0 AWG-2500 kcmil
  - ☐ Aluminum aerial connectors: 3/0 AWG-2500 kcmil
- Equipped with 3/8" screw type hydraulic couplers
- Weight: 45 lbs.



Greenlee #	Description
RK6040	60-Ton Crimping Tool, Single Acting



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hydraulic Tools

### RHU1000 Hydraulic Presshead

- 123 Ton hydraulic presshead for full tension, transmission and substation connections, complete with quick automatic coupler for connection to hydraulic pumps with a working pressure of 10,000 psi max
- Will accept all semi-circular slotted dies common to most 100 ton heads
- Die cap is removable for an easy connector positioning; the upper part of the cap automatically rotates during the die changing process to present the correct positioning of the die
- Lifting eye included
- Weight: 111.32 lbs.

Cembre #	Description
RHU1000	1100 kN Force Developed



### 12-Ton Remote Compression C-Head

- 1.65" Jaw opening
- Protective rubber boot on "C" Head
- Accepts all "U" type dies
- Connector Range:
  - ☐ Lugs & Splices: Up to 750

Huskie #	Weight
EP-510HC	11 lbs.



### 12-Ton Remote Compression C-Head

- 1.5" Jaw opening
- Protective rubber boot on "C" head
- Accepts PH-2, WH-2 and WH-3 style dies
- Connector Range
  - ☐ Lugs & Splices: Up to 1033 MCM Stranded, 477 ACSR

Huskie #	Weight
EP-510HK	13.5 lbs.



### 15-Ton Remote Compression C-Head

- 2" Jaw opening (1.5" with "U" Die Adapter)
- Protective rubber boot on "C" head
- 3/8" male screw type coupler provided
- Connector Range:
  - ☐ Aluminum: #8 AWG-1250 MCM
  - ☐ Copper: #8 AWG-1500 MCM

Huskie #	Weight
EP-610H	14.5 lbs.



**BURNDY**

Burndy #	Description
Y46	Remote Head Hydraulic Tool
P15K	Cutter Die

### Y46 HYPRESS Remote Operated Hydraulic Tool

- 15-Ton output force
- Works on commonly used copper and aluminum products
- Compact C-shaped head with 2" jaw opening
- Forged steel construction
- Positive push button die lock buttons
- UL Listed and CSA certified compression terminal, splice and tap connectors when tool is used to install
- Operating pressure: 10,000 psi
- Requires "P" Series dies
- Weight: 16 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools

### Long Reach Chainsaws

- Cuts hard-to-reach branches from aerial basket or from the ground
- Super spool selector control for use on open and closed center hydraulic systems
- Insulated fiberglass extension tubes, tested to meet OSHA regulation 1910.269
- Safety features include two-step trigger, trigger guard and fully covered sprocket guard
- Anti-kickback chain and automatic chain oiler
- Rugged high torque gear motor
- Unfilled and foam filled extension tube versions offered
- Cutting capacity: 13"
- Operating pressure: 1,000-2,000 psi

Greenlee #	Length	Weight
43178	62.5"	8.5 lbs.
38568	75.0"	9.25 lbs.
43177	88.5"	9.75 lbs.



Greenlee #	Overall Length	Cutting Capacity
43180	82"	3.5"

### Circular Saw Assembly

- Use for high production utility line clearing and general tree clearing applications
- Super spool selector control for open and closed center hydraulic systems
- Safety features include hand stop collar, trigger guard, two-step trigger and branch stop
- Insulated fiberglass extension tube, tested to meet OSHA regulation 1910.269
- Rugged gear motor
- Angular head design makes flush cuts easier and directs chips away from the operator
- 9" diameter blade standard
- Operating pressure: 1,000-2,000 psi
- Open and closed center system
- Weight: 9 lbs.

### Hydraulic Chainsaws

- Ideal for large trimming applications and cut-up removal jobs
- Chain and bar can be adjusted without removing sprocket cover
- Sprocket cover can be removed without tools for easy saw cleaning
- Handle position can be oriented to horizontal or to 60° or 30° relative to bar and chain to user preference
- Rugged gear motor and expanded chip exit area
- Automatic chain oiler can be adjusted without tools
- Safety features include two-step safety trigger, high impact polymer front handle/shroud, wide lower handle protects hands/knuckles and chain catcher stops chain rotation
- Reduced kickback bar and chain
- Supplied with 12" steel braided whip hoses
- Chain size: 3/8" pitch
- Operating pressure: 1,000-2,000 psi
- Open and close center system
- HCS Standard grip, HPS pistol grip
- HTMA Couplers shown additional

Greenlee #	Length	Cutting Capacity	Weight
HCS816	31.5"	16"	9.5 lbs.
HCS820	35.5"	20"	10.2 lbs.
HCS8160CB (w/chain brake)	31.5"	16"	9.5 lbs.
HPS513	26.5"	13"	8.5 lbs.
HPS513CB (w/chain brake)	26.5"	13"	8.5 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hydraulic Tools

**HRD Ground Rod Driver with Valve**

- Deep rod opening and smooth operation ensures that the driver will not jump off of rods
- Lightweight allows easy mounting on top of rods
- Can be used with open and closed center hydraulic systems
- Dual guide rods provide excellent control for driving rods straight and the remote on/off valve makes it easy to control the depth of the rod
- Maximum input pressure: 2,000 psi

Greenlee #	Jaw Opening	Length	Weight
HRD-58	5/8"	25-1/2"	45 lbs.
HRD-1	1"	25-1/2"	45 lbs.

**Tamper Assembly**

- Makes quick work of setting poles, asphalt patch and general construction backfill compacting
- Only three moving parts for low maintenance
- Kidney-shaped foot included
- Hose end valve-reversible on/off valve for open and closed center hydraulic systems
- Valve on tube-rotate trigger spool for open and closed center hydraulic systems
- H4802-6 unit does not include on/off valve
- Operating pressure: 1,000-2,000 psi
- System: open & closed center
- These items can be ordered with whip hoses and couplers, please contact us for additional info and pricing

Greenlee #	Length	Valve Location	Weight
H4802	60"	Hose End	23 lbs.
H4802-1	85"	Hose End	28 lbs.
H4802-3	72"	On Tube	23 lbs.
H4802-5	60"	On Tube	22 lbs.
H4802-6	60"	Hose End	23 lbs.

**Pole Puller Assembly**

- Heavy-duty construction
- Works in confined areas, next to buildings or out in the open
- Includes proof-certified 6' alloy chains
- Capacity: 56,000 lbs. @ 2,000 psi lift
- Operating pressure: 300-2,800 psi
- Open and closed center system

Greenlee #	Description	Weight
H4910A	Pole Puller Assembly	175 lbs.

**Breaker Assembly**

- Great for breaking sidewalks and curbs or driving ground rod and for other small demolition jobs
- Clean modular design with few protrusions to irritate operators legs
- High blow energy provides maximum breaking power
- Integral rubber damper reduces chisel noise
- Low noise and vibration levels
- AVS Tools have patented spring-dampened handles
- Two-step trigger
- Supplied with 12" steel braided whip hoses
- Open center system

Greenlee #	Length	Weight
HPB55-1A VS	30"	56 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools



Greenlee #	Length	Weight
HPB45-1A VS	28.5"	54 lbs.

**Breaker Assy, 45 lb. 1-1/8x6 DMP HDL**

- Low noise and vibration levels
- Integral rubber damper reduces chisel noise
- Clean modular design with few protrusions to irritate operator's legs
- Two-step trigger
- Supplied with 12" steel braided whip hoses
- Great for breaking sidewalks and curbs or driving ground rod and for other small demolition jobs
- A VS tools have patented spring-dampened handles that reduce vibration transmitted to the operator by 80-90%

**Submersible Pump, 275 gpm**

- Self-priming, compact, lightweight design with carrying handle
- High impact strainer housing
- Capacity: up to 275 gpm
- Can draw water down to depth of 1-3/4"
- Can run dry without damage
- Operating pressure: 0-2,000 psi
- Pressure port: 9/16-18 SAE O-ring
- Return port: 3/4-16 SAE O-ring
- Open and closed center system

Greenlee #	Discharge Size	Suction Size	Weight
H4665A	2" NPT Female	1-15/16"	9 lbs.
156340	2" Diameter by 25' Assembly	Discharge Hose	



Greenlee #	Discharge Size	Suction Size	Weight
H4660B	2-1/2" NPT Female	1-1/2"	23.5 lbs.
156339	2-1/2" Diameter x 25' Hose Assembly	Discharge	

**Submersible Pump, 400 gpm**

- Self-priming, high impact strainer housing with carrying handle
- Capacity: up to 400 gpm
- Can be run dry without damage
- Can draw water down to depth of 2"
- Operating pressure: 0-2,000 psi
- Pressure and return ports: 1/2" male NPTF

**Trash Pump**

- Compact, under 12" diameter to easily fit into small areas
- Self-priming submersible pump can be placed and operated quickly
- Passes up to 3" solids minimizing pump blockage from debris
- Can be run dry without damage for longer working life
- Carry handle with lifting eye
- Includes locking coupler for discharge hose
- Can draw water down to depth of 2-3/4"
- Capacity: up to 500 gpm
- Operating pressure: 0-2,000 psi
- Pressure and return ports: 1/2" male NPTF

Greenlee #	Discharge Size	Suction Size	Weight
H4635	3" NPT Female	3.125"	28.0 lbs.
49499	3" Dia x 25'	Discharge Hose Assembly	
H4670	4" NPT Female	4.0"	59.0 lbs.
154955	4" Dia x 25'	Discharge Hose Assembly	



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hydraulic Tools



Greenlee #	Description
HB10	Hydraulic Intensifier

**Hydraulic Booster Assembly**

- Small and compact
- Operates 10,000 psi remote head tools
- Able to operate on either open or closed center hydraulic systems without making any changes to the tool
- Uses the Dynapress remote control valves and hose sets
- Supplied with pressure and return high pressure screw-type couplers
- Supplied with convenient foldable carrying handle and can be permanently mounted
- Input pressure: 1,000-2,200 psi
- Maximum back pressure: 200 psi
- Output pressure: 10,000 psi
- Port sizes: 1/4-18 NPSM
- Relief valve setting: 10,000 psi
- Return port: 3/4-16 SAE O-ring
- System: open and closed center

**Single Acting Hydraulic Pump**

- 1/2 HP, 10,000 psi
- Remote operation allows full operator control
- Advance and hold feature comes standard
- Manual control directly on pump motor
- Pressure adjustment from 4,000-10,000
- Oil capacity: 2 quarts

Huskie #	Weight
R-14EH	75 lbs. With Oil



Burndy #	Description
EPP10	Electric/Hydraulic Pump

**EPP10 Electric/Hydraulic Pump**

- Small and lightweight
- Factory set relief valve
- Audible recycling of pump to signal completion of crimp cycle
- Sealed electric pendant switch and manual switch
- Quick disconnect hydraulic fitting
- Long, durable life expectancy (100,000+ life cycles)
- Lightweight cast aluminum reservoir body
- Motor: 115V AC/60Hz, 1/2hp @ 3450 rpm
- Weight: 30 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hydraulic Tools

**EHP700LU Hydraulic Power Pump**

- Operates with any 10,000 psi single acting remote heads
- 3-in-1 pressure specific program settings for crimping, cutting and punching
- Dashboard display provides real time monitoring of operation
- On-board and remote rocker switches for pump activation
- Includes shoulder strap and 6' corded magnetic remote
- 2-stage motor
- Weight: 14 lbs.

Greenlee #	Description
EHP700LU11	Battery-Powered Pump w/120V Charger & Two 18V 3.0Ah Li-Ion Batteries
EHP700LU12	Battery-Powered Pump w/12V Charger & Two 18V 3.0Ah Li-Ion Batteries
EHP700LU22	Battery-Powered Pump w/230V Charger & Two 18V 3.0Ah Li-Ion Batteries
EHP700LU120	Power Pump w/120V Adapter
EHP700LU230	Power Pump w/230V Adapter
EHP700LUB	Bare Tool Only
HTA4GL	Remote Control

**High Pressure Couplers**

- 10,000 psi



Greenlee #	Description
130868	Male Coupler, Nose Half 1/4-18 NPSM
130878	Female Coupler, 1/4-18 NPSM
54169	Female Coupler, Nose Half 1/4-18 NPSM
F024631	Female Coupler, 1/4-18 NPTM
22061	Male Coupler, Nose Half 3/8-18 NPTF
F021627	Female Coupler. 3/8-18 NPTM

**Female Couplers**

Greenlee #	Description
3HTM3	3/8" HTMA, External O-Ring Thread
3HTM4	1/2" HTMA, External O-Ring Thread
EC3-21	3/8" NPTF
EC3-26	1/2" NPTF

**Male Couplers**

Greenlee #	Description
HT3M3	3/8" HTMA, External O-Ring Thread
HT3M4	1/2" HTMA, External O-Ring Thread
EP3-21	3/8" NPTF
EP3-26	1/2" NPTF



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools

**HID6506 Rotary Impact Hammer Drill**

- Adjustable flow control prevents over speeding and allows precise control of drilling speed
- Hammer drill in concrete, brick, rock and other difficult to drill materials
- Drill in wood or steel with auxiliary chuck
- Super spool selector control for use on open and closed center hydraulic systems
- Selector for drill or hammer/drill modes
- Rugged gear motor, reversible
- Built-in slip clutch to guard against over torque
- Depth gauge and auxiliary handle are removable for tight areas
- Length: 12"
- Operating pressure: 1,000-2,000 psi
- Speed: 775-1,100 rpm at 6.5 gpm
- Chuck: SDS plus bit shanks
- Capacity:
  - ☐ Steel, 1/2" hole
  - ☐ Wood, 1-1/16" hole
  - ☐ Concrete, 3/4" hole
  - ☐ Core bits, 3"
- Weight: 9 lbs.

Greenlee #	Description
HID6506	SDS Plus Rotary Impact Drill

**35-Ton Hydraulic Steel Punch**

- Punches up to 1/2" mild steel
- 13/16" Max hold diameter
- Will punch: oval, round, square and slotted holes
- Custom sizes available
- Operates from a 10,000 psi pump source
- Round, Square, Oblong and Hex Dies available

Huskie #	Weight
SH-370M	28 lbs.

**Nut Runners**

- Deep well accepts up to 6" excess bolt length
- Includes 7/16" hex quick change adapter
- Slim profile for easy use and storage
- NR1 Diameter: 1-3/4", length with adapter: 9-1/2", length without adapter: 7-3/4"
- NR2 Diameter: 2-3/8", length with adapter: 11", length without adapter: 8-5/8"

Greenlee #	Description
NR1	Nut Sizes 5/8", 3/4", 13/16", 1"
NR2	Nut Sizes 1-1/8", 1-5/16", 1-1/2"
49782	Adapter for NR1
21111	Adapter for NR2
49314	Adapter 7/16" Hex 1/2" Square Drive Shank



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hydraulic Tools



Greenlee #	Description
750	Hydraulic Cutter Only
750H767	Hydraulic Cutter Kit

### Hydraulic Cable Cutter & Ram in Storage Box

- Cuts in 7 seconds
- Jaws slide open quickly to save time between cuts
- 11 Ton ram powers cutting jaws
- Jaws are specially hardened and precision-ground to hold sharpness
- Lightweight
- Capacity: 100 kmil copper or aluminum cable
- Jaw opening 1-15/16"

### Hydraulic Control Valves, High Pressure, For Cutters and Crimping Tools

- May be directly connected to the tool or used remotely with hoses
- Compact 4-way, 3-position valve
- 3,000-4,000 psi return line ground dump safety valve
- Controlled advance and built-in hold feature
- Single-acting valve available to use with existing single-acting tools
- High pressure quick-disconnects included, 10,000 psi

Greenlee #	Description
PVA0021	Control Valve for Single-Acting Tool
PVA0022	Control Valve for Double-Acting Tool



Greenlee #	Hose Diameter	Length
138573	3/16" ID	6' Pair
138574	3/16" ID	10' Pair
F020721	3/16" ID	6' Single Hose
F020723	3/16" ID	10' Single Hose

### Hose Assembly, High Pressure Set

- Certified non-conductive orange rubber
- For use between Dynapress Intensifier or electric pump and control valve (138573, 138574)
- For use between control valve and tool (F020721, F020723)
- 1/4" NPT Male fitting on one end of high-pressure quick-disconnect on the other end (138573, 138574)
- 1/4" NPT Male fitting on both ends (F020721, F020723)
- Working pressure: 10,000 psi



### Hose Assembly, Low Pressure Set

- Certified non-conductive orange rubber
- Double rayon braid
- 3/8" NPTF Male fitting connection
- Working pressure: 2,250 psi

Greenlee #	Hose Diameter	Length
135245	3/8" ID	8'
135247	3/8" ID	10'



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

### H.K. Porter Center Cut Bolt Cutter, Fiberglass Handles

- All-purpose jaws with center-cut blades
- Cuts soft, medium, and hard metals
- Lockplate keeps jaws from loosening
- Screw-type adjustment realigns edges
- Strong, lightweight, fiberglass handles
- Toggle joints turn 50 lb. hand pressure to 4,000 lb. cutting force



**H.K.Porter®**



H.K. Porter #	Length	Weight	Capacity
0090FC	18-1/4"	3.5 lbs.	3/8"
0190FC	24-1/2"	4.5 lbs.	7/16"
0290FC	30"	7.5 lbs.	3/8"
0390FC	36"	11.5 lbs.	7/16"
0013C	Cutterhead for 0090FC & MC		
0113C	Cutterhead for 0190FC & MC		
0213C	Cutterhead for 0290FC & MC		
0313C	Cutterhead for 0390FC & MC		

### H.K. Porter Ratchet-Type Hard Cable Cutter

- Jaw keeper prevents jaws from spreading while under heavy load
- Ratchet and chain increase cutting pressure as handles open and close
- Cuts hard cable, ACSR, ACAR, ZEBRA, and self-supporting telephone cable
- Moderate pressure needed to open and close handles

H.K. Porter #	Length	Weight	Capacity
8690FH	29-1/4"	10-1/2 lbs.	13/16"
8613FH	Cutterhead for 8690FH		



**H.K.Porter®**



**H.K.Porter®**

H.K. Porter #	Length	Weight	Capacity
0090MC	18"	3-1/2 lbs.	3/8"
0190MC	24"	5-1/4 lbs.	7/16"
0290MC	30"	8-1/2 lbs.	1/2"
0390MC	36"	12-7/8 lbs.	9/16"

### H.K. Porter Center Cut Bolt Cutter, Steel Handles

- Recommended for the most demanding hand cutting applications
- Drop-forged, precision ground, alloy tool steel jaws, center-cut blades
- Cuts soft, medium, or hard materials
- Heavy-duty straps support the jaws
- Lockplate keeps jaws from loosening
- Screw-type adjustment realigns edges
- Tubular steel handles
- Toggle joints turn 50 lb. hand pressure to 4,000 lb. cutting force

### H.K. Porter Ratchet-Type Soft Cable Cutter

- Jaw keeper prevents jaws from spreading while under heavy load
- Cuts copper and aluminum
- Improved heavy duty jaw design-built for tough conditions
- Ratchet provides up to five times mechanical advantage over manual cutters

H.K. Porter #	Length	Weight	Capacity
8690FSK	27-1/2"	3-1/2 lbs.	2"
8613FSK	Cutterhead for 8690FSK		



**H.K.Porter®**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Manual Cutting and Compression Tools



Klein Tools #	Overall Length	Soft/Med Cap	Hard Cap
63124	24-1/2"	7/16"	5/16"

**Bolt Cutter**

- Fiberglass handles have heavy vinyl grips with flat grips ends for 90° cuts
- All-purpose, center-cut jaws for soft, medium and hard metals
- Forged, alloy tool steel jaws are precision ground for sure, efficient cutting and long life
- Lockplate reinforcement prevents jaw bolts from loosening or turning, keeps jaws in correct alignment
- One adjustment realigns cutting edges
- 3-Point toggle joint multiplies 50 lbs. of hard pressure on handles to 4,000 pounds of cutting jaws
- Cutting capacities for hard materials is up to Brinell 400, Rockwell C42
- Cutting capacities for soft and medium materials is up to Brinell 300, Rockwell C31

**Bolt Cutter**

- Suitable for cutting hard material
- Short cutting edge for high tensile steel, bolts, wire, rods, chain links, and case hardened chains
- Handles are filled with unicellular foam core

Hastings #	Description	Head Only
10-666	20" Center Cut, 12" Handle	A 11012
10-667	24" Center Cut, 16" Handle	A 11012
10-767	30" Center Cut, 21" Handle	A 11013

**H.K.Porter®**

H.K. Porter #	Length	Weight	Capacity
8690TN	36"	13 lbs.	3/4"
8613TN	Cutterhead for 8690TN		

**H.K. Porter Ratchet-Type Wire Rope Cutter**

- Ratchet-type jaws with notched shear-cut blades
- Blades hold and lock material in place
- Cuts aircraft cable, EHS guy strand, wire rope and stainless steel cable
- Cuts all strands with minimal crushing or distortion

**Heavy-Duty Ratchet Cable Cutter**

- Extra thick blades, ground flat to reduce potential for breakage
- Ratchet action for heavy-duty cutting
- Two cutting actions-fast scissor cutting for small cable and insulation; converts automatically to ratchet mode
- Anti-slip mechanism for positive ratchet action
- Rubber boot protects ratchet mechanism
- Cutting capacity (756):
  - AL & CU: 1500 kcmil
- Cutting capacity (757):
  - ACSR: 954 kcmil
  - Soft steel rod: 1/2"

Greenlee #	Length	Jaw Size	Weight
756	27-1/2"	2"	11.41 lbs.
757	29-1/4"	1.180"	12.22 lbs.
34188	Replacement Cutter Head for 756 (2 blades included)		
34187	Replacement Cutter Head for 757 (2 blades included)		



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Manual Cutting and Compression Tools

### Heavy-Duty Bolt Cutter with Fiberglass Handles

- Unique cam bolt blade adjustment for easy cutter alignment
- Forged steel blades for a long life
- Clevis-mounted blades for greater strength
- Custom rubber grips for maximum power
- Fiberglass handles are tough and lightweight



Greenlee #	Length	Description/Capacity		Weight
		RB85	RC40	
HDFBC18	18"	5/16"	7/32"	3.4 lbs.
HDFBC24	24"	3/8"	9/32"	10.3 lbs.
11367	Replacement Blade Unit for HDFBC18			
11342	Replacement Blade Unit for HDFBC24			

### H.K. Porter Compact Ratcheting Cable Cutter

- For cutting soft cable
- Lightweight cutter for confined spaces
- Ratchet-type jaws with shear-cut blades
- Fiberglass handles with non-slip, plastic grips
- Cutter has self-lubricating ratchet and only six moving parts
- Leaves no burrs or sharp edges

H.K. Porter #	Length	Weight	Capacity
6990FS	14"	3-1/2 lbs.	500 MCM CU, 795 AL
6990FSL	19"	3-1/2 lbs.	500 MCM CU, 895 AL
6912FS	Replacement Blades for 6990FS, FSL		



**H.K.Porter®**

**JennyTools**



Jenny Tools #	Length	Description
7116	20"	Ratchet Action Cutters

### Ratchet Drive Cutter for Cu/Al

- Patented blade design
- Two handed operation
- Maximum cutting capacity: 2000 MCM Cu
- Maximum insulation diameter: 2.375"
- Cutter blades are field replaceable
- Compact and lightweight
- Weight: 4.5 lbs.

### Ratchet Drive Cutters for ACSR

- Heavy duty blade design
- Fiberglass handles with PVC covers and vinyl hand grips
- Smaller and lighter than competitors
- Maximum cutting capacity: 556 MCM ACSR-600 MCM Cu
- Weight: 4.5 lbs.

Jenny Tools #	Length	Description
7118	20"	Ratchet Action Cutters



**JennyTools**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

### Ratcheting Cable Cutter

- High leverage ratchet mechanism for single-handed cutting of copper and aluminum cables
- Patented two-step ratchet requires fewer strokes per cut
- Quick release lever opens blades easily in every cutting position
- Precision ratcheting mechanism holds cable tight and allows rapid, straight cuts with minimum effort
- Hardened steel cutting blades with hand guards
- Copper maximum cable capacity:
  - ❑ 400 MCM (63060)
  - ❑ 1000 MCM (63750)
- Aluminum maximum cable capacity:
  - ❑ 600 MCM (63060)
  - ❑ 1000 MCM (63750)
- Communications cable maximum cable capacity:
  - ❑ 1-1/8" (63060)
  - ❑ 2-1/16" (63750)



Klein Tools #	Description
63060	10-1/4" Ratcheting Cable Cutter
63750	12-1/8" Ratcheting Cable Cutter

### ACSR Ratcheting Cable Cutter

- Cutting inserts are easily replaced by simply removing three screws per blade
- Capacity:
  - ❑ 477 MCM ACSR (26/7)
  - ❑ 1-1/4" Stranded aluminum and copper
  - ❑ 1" Solid copper
  - ❑ 1/2" Guy strand
- Tool can be locked when not in use
- High leverage ratcheting mechanism for easier cutting
- Plastic covered handles with hand guards



Klein Tools #	Description
63800-ACSR	13-3/4" Ratcheting Cable Cutter

### ACSR Cable Cutter

- High leverage ratchet mechanism for single-handed cutting of copper and aluminum cables
- Patented two-step ratchet mechanism requires fewer strokes per cut
- Quick release lever opens blades easily in every cutting position
- Precision ratcheting mechanism holds cable tight and allows rapid, straight cuts with minimum effort
- Hardened steel cutting blades for lasting strength and sharpness
- Plastic covered handles with hand guards
- Capacity:
  - ❑ 336 MCM ACSR
  - ❑ 600 MCM Stranded aluminum and copper
  - ❑ 400 MCM Solid copper



Klein Tools #	Description
63607	10-1/4" Ratcheting Cable Cutter

### Ratchet Cable Cutter

- Simple, one handed operation
- 2-Speed ratcheting mechanism adjusts for light/heavy cutting
- Well-suited for tight working spaces
- Blades can be opened mid-cycle
- Cushioned grip handle type

Greenlee #	Length	Jaw Size	Cutting
45206	10"	1-7/16"	750 kcmil (AL), 500 (CU)
45207	11"	2"	1000 kcmil (AL), 750 (CU)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

**H.K. Porter Shear-Type Hand Operated Cutter**

- Drop-forged, alloy tool steel jaws with shear cut blades
- Cuts copper or aluminum
- Cuts power and communications cable
- Lightweight fiberglass handles for 2-handed control

H.K. Porter #	Length	Weight	Capacity
0290FCS	25"	4-1/2 lbs.	500 MCM CU, 750 AL
0213CSS	Replacement Blades for 0290FCS		
0390FCS	32"	6 lbs.	750 MCM CU, 1200 AL
0313FSS	Replacement Blades for 0390FCS		

**H.K.Porter®**

Klein Tools #	Description
63041	25" Cable Cutter

**Standard Cable Cutter**

- Lightweight with strong fiberglass handles with vinyl grips for slip resistance and comfort
- Replaceable hook-jaw blades
- Heavy-duty pins in head serve as blade-stops
- Jaws made from forged tool steel with black-oxide finish which increases life
- Not designed for cutting steel or ACSR
- MCM Cable-Cutting Maximum Capacity: 500 Copper, 750 Aluminum
- Weight: 5.25 lbs.

**Shear Action Cutters with Replaceable Fiberglass Handles**

- For use on copper and aluminum
- Blades are heat treated and tempered
- Two handed operation
- Replaceable blades and handles

Jenny Tools #	Length	Cutting Capabilities	Weight
1124	21"	600 MCM Cu/ 600 MCM Al	3.5 lbs.
1132	32"	1000 MCM Cu/ 1200 MCM Al	9 lbs.

**JennyTools****H.K.Porter®**

H.K. Porter #	Length	Weight	Capacity
8690CK	28"	8-3/4 lbs.	1/2"
8613CK	Cutterhead for 8690CK		

**H.K. Porter Ratchet-Type Guy Strand Cutter**

- Notched shear-cut blades hold material firmly in place
- Makes clean, square cuts with minimal distortion
- Cuts EHS guy strand, mild steel rods, bolts and similar materials



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Manual Cutting and Compression Tools

**Insulated Handle Cable Slicer**

- For use on soft copper and all aluminum cable only
- Not to be used on steel or ACSR cable
- Replaceable fiberglass handles are electrically tested
- Drop forged cutter blades and fiberglass handles are designed for easy field replacement

Hastings #	Description
10-072	28-3/4" Cable Slicer
10-070	20-1/2" Cable Slicer
A 11058	Blade Assembly for 10-070
A 11006	Cutter Blade for 10-070 Prior to 2006



 **BURNDY**



Burndy #	Description
OH25	Dieless Ratchet Tool

**OH25 Hytool Dieless Ratchet Tool**

- Installs service entrance splice connectors
- Conductor range: #10 through 1/0
- Forged steel jaws and stainless steel indenter
- Ratchet mechanism provides proper uniform crimp
- Spring loaded comfort grip handles
- Maximum handle force: 50 lbs.
- Maximum force developed: 6,000 lbs.

**MRC840 Hytool Rotating Die Crimper**

- Multiple grip selections on rotatable die wheels
- High strength fasteners
- Plated, heat treated, steel jaws
- Engraved crimp groove (Die index number)
- Comfort grip handles
- Crimping capacity: #8-4/0 AWG
- Non-insulated copper terminals and splices
- Weight: 8.25 lbs.

Burndy #	Description
MRC840	Mechanical Rotating Crimp Tool



 **BURNDY**



 **BURNDY**

Burndy #	Description
MY29-3	Dieless Lever-Type Crimper

**MY29 Dieless Lever-Type Hytool Crimper**

- Heavy-duty forged steel construction
- Reinforced back and comfort grip handles
- Adjustable nest die with knurled steel knob and machine threads
- Crimping capacity: #8 str-250 kcmil copper commercial (code) cable, 30 navy-250 navy copper navy cable, #8 str-4/0 str aluminum commercial (code) cable
- Weight: 8 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

### MD6 Hytool Hand-Operated Crimping Tool

- Crimp force: 9,000 lbs.
- Installs full range of connectors (taps, splices, terminals): #14 through 4/0, in full tension and non-tension applications
- Butting steel jaws for proper crimps
- No additional dies required for "O" and "D3" size tap connectors
- Increased strength and greater bearing area provided with larger steel bolts
- Spring loaded positive lock die retainer buttons
- Over center cam action for full crimp force
- Lightweight high strength aluminum alloy castings
- The "D3" groove accommodates the complete line of type-"W"- die inserts
- Weight: 6 lbs.



Burndy #	Description
MD6	Std. MD6 with Permanent "BG" (5/8") and D3 Grooves-Bent Wooden Handles
MD6-8	Std. MD6-8 Head with Permanent "O" Die and D3 Grooves-Bent Wooden Handles

 **BURNDY**



Greenlee #	Description
K425K58	Crimping Tool with Kearney O and 5/8" Die Grooves
K425KO	Crimping Tool with Kearney D and O Die Grooves

### Manual Crimper

- Designed for crimping a wide range of overhead service entrance connections, overhead splices and overhead taps
- Easy-to-use MD-6 type "pop" tool
- Bent fiberglass handles
- Teflon-impregnated bushings at pivot joints
- Complete crimps are assured with an over-center cam mechanism
- Tool can easily be checked visually for proper adjustment and can be adjusted with Allen wrenches
- Length: 25-3/8"
- Weight: 7.1 lbs.



 **BURNDY**

### MD7 Posi-Press Hytool Crimper

- Crimp force: 9,000 lbs.
- Designed for compression of sleeves, lugs and H-frame parallel groove connectors
- Allows use of the complete line of BURNDY "W" and "X" die inserts
- Permanent "D3" die groove
- Ergonomically designed, 1-piece, comfort-grip composite polymer handles
- Butting steel jaws for proper crimps
- Positive lock, spring loaded die retainer buttons
- PTFE Impregnated steel/bronze bushings and stainless steel pins
- Electroless nickel plated jaws and jaw links
- Weight: 6 lbs.

Burndy #	Description
MD7	Permanent "BG" (5/8") and "D3" Grooves; Bent Composite Polymer Handles
MD7-8	Permanent "O" and "D3" Grooves; Bent Composite Polymer Handles



 **BURNDY**

Burndy #	Description
Y750H SXT	Hand Operated Hydraulic Tool

### Y750HSXT 750 HYPRESS Hand Operated Hydraulic Tool

- 12-Ton output force
- C-shaped head with 1.65" opening and 355° rotation
- Patented rapid advance pump
- Exposed positive die lock buttons
- Audible "pop-off" pressure relief valve
- Operating pressure: 10,000 psi
- High-impact plastic carrying case
- Uses all standard "U" Series dies
- Weight: 14.5 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

**EP-750A: 6.2 Ton Flip-Top Dieless Crimping Tool**

- 1.5" Jaw opening
- Rapid advance
- Flip-top head design
- Eliminates need for dies
- Connector Range:
  - ☐ #10 AWG-750 MCM

Huskie #	Length	Weight
EP-750A	23"	11.5 lbs.



Burndy #	Description
Y81KF MBH	Dieless Hand Operated Hydraulic Crimping Tool

**Y81KFT HYPRESS Dieless Hand Operated Hydraulic Crimping Tool, 4-POINT**

- 6-Ton output force
- Dieless installation, 360° head rotation
- Flip top head design, handle trigger ram release
- Advanced high-speed pump design
- Audible pressure "pop-off" valve and die embossment
- UL Listed and CSA certified with range taking capabilities
- Includes: high-impact formed carrying case
- Crimping capacity:
  - ☐ 1000 kcmil Copper
  - ☐ 750 kcmil Flex wire
  - ☐ 750 kcmil Aluminum
- Weight: 12 lbs.

**EP-430: 12 Ton Compression Tool with Rubber Boot**

- Large 1-3/16" jaw openings
- Able to splice up to 600 MCM using 12-ton "U" type dies
- Output: 12 tons
- Lugs up to 750 MCM
- Two-stage pumping piston for rapid advance
- 180 degrees swivel crimping head permits installations in confined areas
- Accepts all "U" type dies
- Twist handle release mechanism

Huskie #	Length	Weight
EP-430	24"	13.5 lbs.



Huskie #	Length	Weight
EP-510C	25"	16.5 lbs.

**EP-510C: 12 Ton Compression Tool with Rubber Boot**

- 1.65" Jaw opening
- Protective rubber boot on "C" head
- External pressure adjustment
- UL Classified
- Connector Range:
  - ☐ Lugs & Splices: Up to 750 MCM Al and Cu



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Manual Cutting and Compression Tools

### EP-510K: 12 Ton Compression Tool with Rubber Boot

- 1.5" Jaw opening
- Protective rubber boot on "C" head
- External pressure adjustment
- Connector Range:
  - ☐ Lugs & Splices: Up to 1033
  - MCM Strand, 47 ACSR

Huskie #	Length	Weight
EP-510K	26"	17 lbs.



**CHANCE**



Chance #	Description
C4032861	6' Hydraulic Cable Cutter
C4032862	8' Hydraulic Cable Cutter

### Insulated Hydraulic Cable Cutters

- For #6 solid copper (0.162" diameter) to 954 kcmil ACSR (1.16" diameter)
- Guillotine-type jaw head
- Operates like a hydraulic jack by simply pumping the handle
- Epoxiglas pole, handle and hydraulic hose
- Hose has minimum burst strength of 12,000 psi
- Pump provides 9,000 psi maximum pressure
- Single control knob selects direction
- Maintenance and operating instructions are included with each tool

### HT-TC, Hydraulic Cable Cutters

- Double speed action
- Automatic safety valve to bypass oil
- Pressure release device
- Steel cutting blade
- Cuts:
  - ☐ Copper
  - ☐ Aldrey
  - ☐ Aluminum
  - ☐ Aluminum/steel cables and rope
  - ☐ Aluminum and steel rods
- HY-TC041 and HT-TC026Y: 180° Rotating head
- HT-TC055: 327° Rotating head

Cembre #	Description	Weight
HT-TC026Y	1" Diameter Max Cut	7.37 lbs.
HT-TC041	1-9/16" Diameter Max Cut	12.76 lbs.
HT-TC055	2-3/16" Diameter Max Cut	18.26 lbs.



Hastings #	Description
11-006	6', with A11055 ACSR Head
11-008	8', with A11055 ACSR Head
11-018	8', with A11056 Soft Wire Cutter Head

### Insulated Ratchet Cutter

- For cutting ACSR and soft wire conductors
- Overhead or underground
- Interchangeable cutting heads
- Upper roller guide minimizes shaft deflection
- Handle folds to store in 6' canister



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hand Tools

**Ratcheting Cable Cutters**

- For stranded and flexible copper and aluminum cable
- Hardened, precision cutting blade for long life
- Locking mechanism for safe transport
- Not for use on steel, aluminum alloy, or hard-drawn copper cables

Cementex #	Size	Capacity
RCC500	10"	Up To 500 MCM or 1.40" Diameter
RCC750	9"	Up To 750 MCM or 1.60" Diameter

**Cementex****KLEIN TOOLS**

Klein Tools #	Description
63050	9-1/2" Cable Cutter

**High Leverage Cable Cutter**

- High leverage design for exceptional cutting capability
- Precision, one-hand shearing action
- Cable gripping shear-type jaws
- Perfect for working in confined spaces
- Maximum cable cutting capacity: 4/0 aluminum, 2/0 soft copper, 100-pair 24 AWG communications cable

**Phillips Tip Screwdrivers**

- Double-insulated Phillips screwdriver
- Insulated shaft and cushion grip handle

Cementex #	Size
P1-3-CG	#1 x 3"
P2-4-CG	#2 x 4"
P2-6-CG	#2 x 6"
P2-8-CG	#2 x 8"

**Cementex****Heavy-Duty Round Shank Screwdriver-Insulated Keystone Tip**

- Individually tested to exceed standards, 1,000 V-rated
- Tips are precision ground to fit screw openings securely and resist slippage
- Cushion grip handles

**KLEIN TOOLS**

Klein Tools #	Shank Tip	Shank Length	Overall Length
602-4-INS	1/4"	4"	8-5/16"
602-6-INS	5/16"	6"	10-15/16"
602-10-INS	3/8"	10"	15-7/16"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**Round Shank Screwdriver-Insulated Cabinet Tip**

- Individually tested to exceed standards, 1,000 V-rated
- Cushion grip handles
- For electrical, telephone, and work in recessed holes and other tight spaces



Klein Tools #	Shank Tip	Shank Length	Overall Length
601-4-INS	3/16"	4"	7-3/4"
601-6-INS	3/16"	6"	9-3/4"

**Round Shank Screwdriver-Insulated Phillips Tip**

- Individually tested to exceed standards, 1,000 V-rated
- Cushion grip handles
- Tips are profilated to provide a more consistent geometric symmetry than conventional Phillips tip screwdrivers

Klein Tools #	Tip Size	Shank Length	Overall Length
603-3-INS	#1	3"	6-3/4"
603-4-INS	#2	4"	8-5/16"



Cementex #	Size
MC4P-CG	3/16" x 4"
MC6P-CG	3/16" x 6"
M4-CG	1/4" x 4"
M6-CG	1/4" x 6"
M8-CG	1/4" x 8"

**Cabinet Tip Screwdrivers**

- Double-insulated cabinet tip slotted screwdriver with insulated shaft and cushion grip handle

**Cementex**



Cementex #	Description
TR-6SD	6-Piece Cushion Grip Screwdriver Set

**6-Piece Screwdriver Roll**

- Double-insulated screwdriver set with black tool pouch
- Each insulated screwdriver features a cushion grip handle
- Includes:
  - ☐ #1 x 3" Phillips tip screwdriver
  - ☐ #2 x 4" Phillips tip screwdriver
  - ☐ 3/16" x 4" Cabinet tip screwdriver
  - ☐ 3/16" and 1/4" x 6" Cabinet tip screwdriver
  - ☐ 5/16" x 6" Mechanic's tip screwdriver



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

**7-Piece Cushion Grip Nut Driver Set-3" Shaft**

- Full hollow shaft for long bolts or studs, with magnetic tip
- 631 Includes:
  - ☐ 3/16" Non-hollow shaft (630-3/16)
  - ☐ 1/4" Hollow shaft (630-1/4)
  - ☐ 5/16" Hollow shaft (630-5/16)
  - ☐ 11/32" Hollow shaft (630-11/32)
  - ☐ 3/8" Hollow shaft (630-3/8)
  - ☐ 7/16" Hollow shaft (630-7/16)
  - ☐ 1/2" Hollow shaft (630-1/2)
- 631M Includes:
  - ☐ 3/16" Non-hollow shaft (630-3/16M)
  - ☐ 1/4" Hollow shaft (630-1/4M)
  - ☐ 5/16" Hollow shaft (630-5/16M)
  - ☐ 11/32" Hollow shaft (630-11/32M)
  - ☐ 3/8" Hollow shaft (630-3/8M)
  - ☐ 7/16" Hollow shaft (630-7/16M)
  - ☐ 1/2" Hollow shaft (630-1/2M)
- All items also available individually

Klein Tools #	Description
631	7-Piece Cushion Grip Nut Driver Set
631M	7-Piece Magnetic Tip Cushion Grip Nut Driver Set



Klein Tools #	Description
85076	7-Piece Set

**7-Piece Cushion Grip Screwdriver Set**

- Includes:
  - ☐ 1/4" Square shank, keystone tip (600-4)
  - ☐ 5/16" Round shank, keystone tip (602-6)
  - ☐ 3/16" Round shank, cabinet tip (601-3)
  - ☐ 3/16" Round shank, cabinet tip (601-6)
  - ☐ 1/4" Round shank, cabinet tip (605-4)
  - ☐ 3" Round shank, No. 1 Phillips tip (603-3)
  - ☐ 4" Round shank, No. 2 Phillip tip (603-4)
- All items also available individually

**5-Piece Cushion Grip Screwdriver Set**

- Includes:
  - ☐ 1/4" Square shank, keystone tip (600-4)
  - ☐ 3/16" Round shank, cabinet tip (601-6)
  - ☐ 5/16" Round shank, keystone tip (602-6)
  - ☐ 4" Round shank No. 2 Phillips tip (603-4)
  - ☐ 1/4" Round shank, cabinet tip (605-6)
- All items also available individually

Klein Tools #	Description
85075	5-Piece Set



Klein Tools #	Tip Size	Blade Length	Overall Length
602-4DD	1/4"	4"	9"
602-7DD	5/16"	7"	12-3/8"

**Demolition Driver-Keystone Tip Screwdriver**

- Plated metal strike cap to protect handle from hammer blows
- Heat treated metal shaft runs complete length of handle to metal strike cap to transfer metal strike force



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

**Heavy-Duty Round Shank Screwdriver-Keystone Tip**

- Built to handle the tough jobs with ease
- Hex bolster reinforces shank for hard use and allows wrench assisted turning

Klein Tools #	Tip Size	Shank Length	Overall Length
602-4	1/4"	4"	8-11/32"
602-6	5/16"	6"	10-15/16"
602-8	3/8"	8"	13-7/16"



Klein Tools #	Tip Size	Shank Length	Overall Length
600-4	1/4"	4"	8-11/32"
600-6	5/16"	6"	10-15/16"
600-8	3/8"	8"	13-7/16"

**Heavy-Duty Square Shank Screwdriver-Keystone Tip**

- Heavy-duty square shank for wrench assisted turning
- Bolster reinforces shank for hard use
- Designed for the most demanding uses

**Heavy-Duty Round Shank Screwdriver-Cabinet Tip**

- Narrow cabinet tip permits blade access where space is limited

Klein Tools #	Tip Size	Shank Length	Overall Length
605-4	1/4"	4"	8-11/32"
605-6	1/4"	6"	10-11/32"



Klein Tools #	Tip Size	Shank Length	Overall Length
603-3	#1	3"	6-3/4"
603-4	#2	4"	8-5/16"
603-6	#3	6"	11"
603-7	#2	7"	11-5/16"

**Round Shank Screwdriver-Profiled Phillips Tip**

- Tips are precision-machined to provide a more consistent geometric symmetry than conventional Phillips tip screwdrivers
- Provides accurate fit and torque without slippage

**Round Shank Screwdriver-Cabinet Tip**

- Narrow cabinet tip permits blade access where space is limited

Klein Tools #	Tip Size	Shank Length	Overall Length
601-4	3/16"	4"	7-3/4"
601-6	3/16"	6"	9-3/4"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Hand Tools



Cementex #	Description
TR-8NDXL	8-Piece Cushion Grip Extra Long Nut Driver Kit, 6" Long
TR-8ND	8-Piece Cushion Grip Nut Driver Kit, 3" Long

**8-Piece Nut Driver Roll Kit**

- Double insulated, cushion grip
- Includes:
  - ☐ Black tool pouch
  - ☐ 3/16", 1/4", 5/16", 11/32", 3/8", 7/16", 1/2" and 9/16"

**Cementex****7-Piece Cushion Grip Nut Driver Set-6" Shaft**

- Full hollow shaft for long bolts or studs, with magnetic tip
- 647 Includes:
  - ☐ 3/16" Non-hollow shaft (646-3/16)
  - ☐ 1/4" Hollow shaft (646-1/4)
  - ☐ 5/16" Hollow shaft (646-5/16)
  - ☐ 11/32" Hollow shaft (646-11/32)
  - ☐ 3/8" Hollow shaft (646-3/8)
  - ☐ 7/16" Hollow shaft (646-7/16)
  - ☐ 1/2" Hollow shaft (646-1/2)
- 647M Includes:
  - ☐ 3/16" Non-hollow shaft (646-3/16M)
  - ☐ 1/4" Hollow shaft (646-1/4M)
  - ☐ 5/16" Hollow shaft (646-5/16M)
  - ☐ 11/32" Hollow shaft (646-11/32M)
  - ☐ 3/8" Hollow shaft (646-3/8M)
  - ☐ 7/16" Hollow shaft (646-7/16M)
  - ☐ 1/2" Hollow Shaft (646-1/2M)
- All items also available individually

Klein Tools #	Description
647	7-Piece Cushion Grip Nut Driver Set
647M	7-Piece Magnetic Tip Cushion Grip Nut Driver Set

**KLEIN TOOLS****Insulated Hand Tool Kits**

- Impact resistant two-color insulating material
- All items also available individually
- Custom kits built to your requirements



TK9



TK30



TK30ETK



TK60

**SALISBURY**

by Honeywell

Salisbury #	Description
TK9	Basic Electricians Roll, 9 Pieces in Tool Roll
TK30	Deluxe Maintenance Tool Kit, 30 Pieces in Plastic Tool Box
TK30ETK	Electrician's Tool Kit, 30 Pieces in Plastic Tool Box
TK60	Hot Box Tool Kit, 60 Pieces in Plastic Tool Box w/Tool Rolls



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**Utility Insulated 13-Piece Tool Kit**

- Individually tested to exceed standards, 1,000 V-rated
- Two layers of insulation provide protection against electric shock
- Custom case includes two pallets with custom-fitted pockets for each tool, piano-hinged case cover has both a combination lock and two key-locked latches for security, storage space behind the pallets
- Kit Includes:
  - ☐ Side-cutting pliers (D2000-9NE-INS)
  - ☐ Diagonal-cutting pliers (D2000-28-INS)
  - ☐ Diagonal-cutting pliers, angle head (D2000-48-INS)
  - ☐ Heavy-duty long-nose pliers, side-cutting (D203-8-INS)
  - ☐ Keystone heavy-duty round shank screwdriver, 1/4" x 4" (602-4-INS)
  - ☐ Keystone heavy-duty round shank screwdriver, 5/16" x 6" (602-6-INS)
  - ☐ Keystone heavy-duty round shank screwdriver, 3/8" x 10" (602-10-INS)
  - ☐ Phillips round shank screwdriver, No. 1 (603-3-INS)
  - ☐ Phillips round shank screwdriver, No. 2 (603-4-INS)
  - ☐ Phillips round shank screwdriver, No. 3 (603-6-INS)
  - ☐ High-leverage cable cutter (63050-INS)
  - ☐ Pump pliers (D502-10-INS)
  - ☐ Cable/lineman's skinning knife (1570-3LR-INS)
- All items also available individually

Klein Tools #	Description
33525	13-Piece Tool Kit



**KLEIN TOOLS** 

**Basic Insulated Tool Set, 24 Piece**

- Double-insulated
- Includes:
  - ☐ 9" Linesman's plier
  - ☐ 6" Diagonal cutting plier
  - ☐ 6" Needle nose plier
  - ☐ 8" Slip join plier
  - ☐ 10" Crimping plier
  - ☐ 10" Water pump plier
  - ☐ 3/16" x 4" Cabinet tip screwdriver
  - ☐ 1/4" x 6" Cabinet tip screwdriver
  - ☐ 1/4" x 4" Mechanic's tip screwdriver
  - ☐ 5/16" x 6" Mechanic's tip screwdriver
  - ☐ #1 x 3" Phillips tip screwdriver
  - ☐ #2 x 4" Phillips tip screwdriver
  - ☐ 3/16", 1/4", 5/16", 3/8", 7/16" and 1/2" Long arm hex wrenches
  - ☐ 1/4", 5/16", 3/8", 7/16" and 1/2" 3" Nut driver
  - ☐ Carrying case



**Cementex**

Cementex #	Description
ITS-24BTK	Insulated Tool Set

**Basic Electrician's Roll Tool Kit, 9 Piece**

- Includes:
  - ☐ 9" Linesman's plier (P9SCNE)
  - ☐ 7" Needle nose pliers (P7CN)
  - ☐ 7" Diagonal pliers (P7D)
  - ☐ 9" Wire stripper (WS19)
  - ☐ 3/16" x 4" Cabinet tip screwdriver, cushion grip (MC4P-CG)
  - ☐ 3/16" x 6" Cabinet tip screwdriver, cushion grip (MC6P-CG)
  - ☐ 1/4" x 6" Cabinet tip screwdriver, cushion grip (M6-CG)
  - ☐ #1 x 3" Phillips tip screwdriver, cushion grip (P1-3-CG)
  - ☐ #2 x 4" Phillips tip screwdriver, cushion grip (P2-4-CG)
  - ☐ Black tool pouch

Cementex #	Description
TR9ELK	Basic Electricians Tool Roll Kit



**Cementex**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools



Klein Tools #	Description
48036	Knife Sharpener

**Combination Knife & Scissors Sharpener**

- High grade, tungsten-carbide inserts sharpen both sides of the blade at the same time
- Restores knife edge in three or four strokes
- Built-in finger guard
- Lightweight, compact size
- Sharpens electrician's scissors, pocket knives, retractable blade utility knives, razor blade knives and serrated knives

**Lightweight Lockback Pocket Knife-Sheepfoot Blade**

- Blades are AUS 8 stainless steel hardened to 58-59 Rc
- Premium quality blade offers superior edge holding
- Impact-resistant nylon resin handle with rubber insert
- Reversible thumb stud provides easy one-handed opening

Klein Tools #	Blade Length	Blade Color
44004	2-3/8"	Silver
44005	2-5/8"	Silver



44004



44000



44001



44000-BLK



44001-BLK



44002

**Lightweight Lockback Pocket Knife-Drop-Point Blade**

- Blades are AUS 8 stainless steel hardened to 58-59 Rc
- Premium quality blade offers superior edge holding
- Slim and comfortable silver anodized-aluminum handle for corrosion-resistance (44000)
- Black chrome blade and black anodized-aluminum handle for corrosion-resistance (44000-BLK)
- Impact-resistant nylon resin handle with rubber insert (44002 & 44003)
- Reversible thumb stud provides easy one-handed opening

Klein Tools #	Blade Length	Blade Color
44000	2-1/4"	Silver
44000-BLK	2-1/4"	Black
44002	2-3/8"	Silver
44003	2-3/4"	Silver
44001	2-1/2"	Silver w/Pocket Clip
44001-BLK	2-1/2"	Black w/Pocket Clip



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**1-Blade Pocket Knife-Sheepfoot Slitting Blade**

- Extra-large curved sheepfoot slitting blade
- Ideal for heavy-duty line work
- Wood grain plastic handle
- Blade locks open

Klein Tools #	Blade Length	Description
1550-4	2-5/8"	Carbon Steel



Klein Tools #	Closed Length	Overall Length
44131	4-1/8"	4-1/2"

**Folding Utility Knife**

- Push button to open and close
- Triple ground blades
- Rubber grips on handle
- Heavy-duty durable construction

**Cable Splicer's Knife**

- Special purpose short blade with comfortable, full-sized, heavy-duty handle
- Coping-type blade made of the finest cutlery steel, tough and carefully tempered to hold its edge
- Handle is textured for comfort and firm grip
- Hang hole for easy storage and portability

Klein Tools #	Overall Length	Blade Length
44200	6-1/4"	1-3/4"



Klein Tools #	Blade Length
1570-3	3"

**Cable/Lineman's Skinning Knife**

- Blade withstands frequent scoring and slitting of cable jacket
- Blade and ring are securely molded in handle
- Notch on blade back for scraping or removing wire insulation
- Comfortable textured handle with finger grooves and guard
- No contact between stainless steel ring and hardened steel blade
- Rectangle-shaped handle design for attachment to some utility hot stick equipment
- 8" Overall length less ring

**Klein Kurve Skinning Knife**

- 2" Blade for increased control when scoring and slitting cable jacket
- Ergonomic handle
- Oversized ring for strength and easy storage
- Notch on blade back for scraping or removing wire insulation
- 8-3/4" Overall length

Klein Tools #	Blade Length
1580-3	2"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hand Tools



Klein Tools #	Blade Length
1571INS	2-3/8"

**Insulated Lineman's Skinning Knife**

- Clearly marked with 1,000 V-rating symbol
- Two-layer insulation
- Molded measuring marks on back of handle
- Large molded handle
- Tough, tempered steel blade provides maximum sharpness and durability to withstand frequent cable scoring
- 8-3/4" Overall length

**BrushBlade The Lineman's Knife**

- Maximum versatility and safety
- Integrated replaceable wire brush for cleaning conductors to make better connections
- Brushes up to 1,000 MCM conductor
- Blade locks in open position and can be closed when not in use
- Blunt tip blade
- Reversible thumb stud for quick one handed opening from left or the right
- Built-in snap ring

Madi #	Description
BB-1	BrushBlade Lineman's Knife
WB-1	Wire Brush Replacement



Greenlee #	Description
UT652-24	Drop Point Folding Knife

**Drop Point Pocket Knife**

- Stainless steel blade for extra durability and corrosion resistance
- Premium finish desert ironwood handle contoured for comfortable hand fit
- Belt clip for added convenience
- Lock-back for increased safety
- Blade 2.25", handle 3.5"

**Titanium Coated Drop Point Pocket Knife**

- Titanium coated stainless steel blade for premium durability and corrosion resistance
- 40 PCT Serrated edge for tough cutting jobs
- Aircraft grade aluminum handle to endure extra rough handling
- Ambidextrous thumb-stud and reversible belt clip for added convenience
- Lock-back for increased safety
- Blade 2.25", handle 3.5"

Greenlee #	Description
UT652-25	Drop Point Folding Knife



Greenlee #	Description
UT652-28	Hawkbill Folding Knife

**Hawkbill Pocket Knife**

- Stainless steel blade for extra durability and corrosion resistance
- Premium finish rosewood handle contoured for comfortable hand fit
- Belt clip for added convenience
- Lock-back for increased safety
- Blade 2.83", handle 4"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

**Skinning Knife with Ergonomic Handle**

- Popular choice
- Durable blade stays sharp

Buckingham #	Description
7090	With Standard Blade and Accessory Ring
70902	With Blunt Point and Accessory Ring



Jameson #	Description
32-24P	Skinning Knife & Leather Pouch Combo
32-24J	Skinning Knife
32-25	Leather Pouch

**Splicer Skinning Knife**

- Straight style blade is molded into and easy-grip polymer handle that remains pliable in subzero temperatures
- Blade is heat treated then ice tempered for a long-lasting edge and is 20-25% thicker than comparable models

**High-Tension Hacksaw**

- Adjustable blade tension up to 30,000 psi for fast, precise cuts
- Soft-touch grips
- Alternative 45° degree mounting for flush cutting
- Front-mount for reciprocating saw blades
- Blade storage in handle
- Includes 12" x 24 TPI bi-metal hacksaw blade and 6" x 24 TPI bi-metal reciprocating saw blade

Klein Tools #	Blade Length	Overall Length
702-12	12"	16-1/4"



Klein Tools #	Blade Length	TPI	PKG
1200B1-P	12"	32, 24, 18	10
1232BI	12"	32	1

**Golden Tri-Cut Blade**

- High-speed steel teeth fused to carbon-steel body
- Withstands greater saw tension for less blade flexing
- Fits 12" hacksaw blades
- Golden finish



Hastings #	Description
A10016	Universal Handle
11000	Pruning Saw
A30007	Saw Scabbard



Jameson #	Description
SB-5U	16" Saw Blade, Teflon Coated w/Universal Adapter

**Conventional Saw Blade**

- Teflon coated
- Fits PS-3 and PH-11 pruner



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

Jameson #	Description
SB-13TE	13" Tri-Cut Saw Blade
SB-16TE	16" Tri-Cut Saw Blade
SB-13TEU	13" Tri-Cut Saw Blade with SB-UC Adapter
SB-16TEU	16" Tri-Cut Saw Blade with SB-UC Adapter
SBL-2	Leather Pole Saw Scabbard for 13" & 16" Saw Blades
24-03F	Long Reach Chainsaw Holder w/Locking Straps & Handle (Fits Greenlee Long Reach Chain Saw 32" x 5")
SB-UC	Saw Blade Adapter (Adapts Blade to Any Universal Hot-Stick)

**Barracuda Tri-Cut Saw Blade and Accessories**

- Hard-chrome plated with impulse hardened teeth
- Tri-cut blades provide a quicker, cleaner cut with less wear on the blade than traditional blades

**FG Series Hollow Core Pole**

- 1.25" Pole diameter
- .125" Wall thickness, hollow core
- Aluminum heavy duty ferrules with external leaf spring locking button
- Batch tested to 1,000KV per foot for five minutes



Jameson #	Description
FG-6	6' Extension Pole, M/F End Fittings
FG-6F	6' Base Pole, F/F End Fittings & Base Cap
FG-6M	6' Head Pole, M Fitting and Eye Bolt for Pruner Rope
FG-6BM	6' Top Pole, M Fitting and Blank End



Klein Tools #	Description
70579	5-1/4" Handle Length, Sizes: 3/16", 7/32", 1/4", 5/16", 3/8"

**Pole Saw Kit**

- Center blade mount (PS-3FP)
- Mounting pin allows easy blade replacement without tools
- Includes pole adapter
- Blade is hard-chrome plated with impulse hardened teeth (Barracuda, SB-16TE)

Jameson #	Description
PS-3FPS2	Pole Saw Head, Adapter & 16" Tri-Cut Blade

**Five Key Hex Set**


- Two key positions (straight-out or right angle) for extra leverage
- Hex ends are square-cut for a secure full depth fit and maximum contact with the hex socket to prevent slippage and stripping of the socket



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools



Klein Tools #	Reading	Length
901-6	Outside	6'

### Wood Folding Ruler

- Strong, 6' long hardwood rules with clear abrasion resistant coating
- Black markings on yellow, with red stud center markings every 16"
- Measurements are marked on both sides and both edges, graduated to 1/16"
- Riveted lock joints are designed for long wear and maintained accuracy
- Engraved graduations on both sides

### Fiberglass Folding Ruler

- Constructed of tough nylon, reinforced with glass fibers for added durability, and resistance to weather, abrasion and most chemicals
- Positive locking joints and stainless steel spring hinges for added strength
- Measurements are marked on both sides and both edges, graduated to 1/16"
- Black markings on yellow, with red stud center markings every 16"
- Engraved graduations on both sides

Klein Tools #	Reading	Length
910-6	Inside	6'
911-6	Outside	6'



93125



Klein Tools #	Length	Hook
93125	25'	Single
93225	25'	Double
93430	30'	Double



93430

93225

### Magnetic Tape Measure

- Nylon-coated hardened steel blade resists abrasion and wear for long life
- Built-in shock absorber to protect blade tip
- True zero feature for accurate inside and outside measuring
- Durable steel belt clip
- Multi-riveted end hook with bottom blade protector reinforces the blade tip and provides maximum pull out strength
- Rare earth magnetic single end hook
- First 11" has oversized, bold numbers
- Easy read fractional scale
- Horizontal and vertical standout for easy one person measurements
- Double sided rule for measurement while using against wall, ceiling or conduit
- Shock and impact resistant case

### Pole Punch

- Ergonomic handle with overstrike protection
- Thermoplastic handle withstands harsh conditions and is resistant to oil and grease
- Large strike plate transfers force directly into the hardware, reducing vibration
- Chamfered tip assists centering and reduces drag
- 18" overall length, 12" punch length

Klein Tools #	Description
66326	3/8" Pole Punch



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hand Tools



MADI#	Head Weight	Length
MLH-1	35 oz.	15.25"

**Lineman Hammer, Milled Face**

- Fiberglass, non- conductive handle
- Longer handle allows for two handed driving
- Small state starter head
- Integrated "J" hook remover
- Large head for driving lag screws

**Lineman's Straight-Claw Hammer**

- Heavy-duty, double-duty hammer drives lags and pulls big nails
- Special high-carbon steel head with solid, octagon-shaped driving end and thick, strong claw
- Straight grain hickory handle, lacquered

Klein Tools #	Head Weight	Length
832-32	32 oz.	15"



Klein Tools #	Head Weight	Length
809-36	36 oz.	14"

**Lineman's Double-Face Hammer**

- Designed for pole line work
- Rugged and well balanced, with the weight to drive lag bolts
- Forged, tempered-steel head is only 3-3/4" long for use in tight areas
- Identical faces with 1-3/4" round crown driving surface and beveled edges

**Straight-Claw Hammer-Heavy-Duty**

- Durable plastic-alloy jacketing helps to protect neck from fraying and splintering if incorrectly struck or over-struck
- High-strength fiberglass shaft absorbs shock and keeps head tight
- Perforated neoprene grip bonded to handle
- Straight-claw design for easy nail pulling in tight quarters

Klein Tools #	Head Weight	Length
808-16	16 oz.	13"



Cementex #	Size
P9SCNE	9"

**New England Style Linesman's Pliers**

- Double-insulated lineman's pliers
- Features New England styled head for easier access to tight areas
- Cutting edges are induction hardened for extended life and high visibility
- Ergonomic comfort grip handles have slip guards



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

### Diagonal Pliers

- Double-insulated diagonal cutting pliers
- Heavy-duty insulated pliers is designed for gripping and cutting thicker gauge wire
- Induction hardened cutting edges for long life and high visibility ergonomic comfort grip handles with slip grip

Cementex #	Size
P7D	7"



**Cementex**



**KLEIN TOOLS**

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D213-9NE-CR-INS	9-5/8"	1-19/32"	1-5/16"

### NE-Type Insulated Side-Cutting Pliers-Connector Crimping

- Individually tested to exceed standards, 1,000 V-rated
- Crimping die behind hinge for superior leverage

### NE-Type Insulated Side-Cutting Pliers

- Individually tested to exceed standards, 1,000 V-rated
- High leverage design provides 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D213-9NE-INS	9-5/8"	1-19/32"	1-5/16"



**KLEIN TOOLS**



**KLEIN TOOLS**

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D2000-9NE-INS	9-5/8"	1-19/32"	1-5/16"

### NE-Type 2000 Series

#### Insulated Side-Cutting Pliers

- Individually tested to exceed standards, 1,000 V-rated
- Provides 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws
- Heavy-duty cutting knives
- Cuts ACSR, screws, nails and most hardened wire



**KLEIN TOOLS**

### Insulated Crimping/Cutting Tool

- Individually tested to exceed standards, 1,000 V-rated
- Insulated crimping tool with tapered nose designed for working in confined spaces
- Crimping dies marked for insulated and non-insulated solderless terminals and connectors
- Accommodates wire from 10 to 22 AWG
- Wire cutter in nose

Klein Tools #	Description
1005-INS	9-3/4" Insulated Crimping/Cutting Tool



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools



Klein Tools #	Description
1010	8-1/4" Wire Stripper

## Long-Nose Multi-Purpose Tool

- Easily cuts and strips wire
- Narrow, serrated pliers nose to pull, loop and bend wire
- Long, curved cutting blade
- Cutters and strippers are in front of the pivot for maximum ease-of-use in reaching into tight places
- Crimps insulated and non-insulated terminals and 7 to 8 mm ignition terminals
- Cleanly shears bolts
- Plastic covered cushioned handles
- Bolt sizes: 4-40, 5-40, 6-32, 8-32, 10-32, 10-24
- Strips and cuts 10 to 22 AWG

## Journeyman Crimping/Cutting Tool-Non-Insulated/Insulated Terminals

- Designed to crimp insulated and non-insulated 10 to 22 AWG solderless terminals and connectors
- Tapered nose design
- Contoured thumb area
- Specially hardened cutter
- Hot-riveted joint

Klein Tools #	Description
J1005	9-3/4" Crimping/Cutting Tool



Klein Tools #	Description
1005	9-3/4" Crimping/Cutting Tool

## Crimping/Cutting Tool-

## Non-Insulated/Insulated Terminals

- Crimping die marked for insulated and non-insulated solderless terminals and connectors
- Tapered nose design
- Specially hardened wire cutter in nose
- Hot-riveted joint
- Crimps 10 to 22 AWG



## Pump Pliers

- Secure tongue and groove design for non-slip grip
- Wide range of versatile jaw positions
- Plastic-dipped handles

Klein Tools #	Overall Length	Max Jaw Cap
D502-6	6-1/2"	7/8"
D502-10	10"	1-3/4"



Klein Tools #	Overall Length	Jaw Length	Jaw Width
J2000-9NETP	9-1/2"	1-19/32"	1-1/4"

## NE-Type Journeyman 2000 Series Side-Cutting Pliers-Fish Tape Pulling

- Pulls 1/8" or 1/4" flat steel fish tape without damaging the tape
- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws
- Heavy-duty cutting knives
- Cuts ACSR, screws, nails and most hardened wire
- Dual material handles



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**NE-Type 2000 Series Side-Cutting****Pliers-Lineman's Bolt-Thread Holding**

- Hinge opening holds and cleans 5/8" pole line and hardware bolts or threaded rods
- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with rounded nose and sure-gripping, cross-hatched knurled jaw
- Heavy-duty cutting knives
- Cuts ACSR, screws, nails and most hardened wire
- Plastic-dipped handles

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D2000-9NETH	9-3/8"	1-19/32"	1-1/4"



**KLEIN TOOLS** 



D2000-9NE



HD2000-9NE



J2000-9NE

**KLEIN TOOLS** 

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D2000-9NE	9-3/8"	1-19/32"	1-1/4"
HD2000-9NE	9-1/2"	1-19/32"	1-1/4"
J2000-9NE	9-1/2"	1-19/32"	1-1/4"

**NE-Type 2000 Series Side-Cutting Pliers-Heavy-Duty Cutting**

- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws
- Cuts ACSR, screws, nails and most hardened wire
- Plastic-dipped handles (D2000-9NE)
- Heavy-duty, oversized plastic-dipped handles (HD2000-9NE)
- Dual material handles (J2000-9NE)

**NE-Type 2000 Series Side-Cutting****Pliers-Connector Crimping**

- Crimping die behind hinge for superior leverage crimping
- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws
- Heavy-duty cutting knives
- Cuts ACSR, screws, nails and most hardened wire
- Plastic-dipped handles (D2000-9NECR)
- Dual material handles (J2000-9NECR)

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D2000-9NECR	9-3/8"	1-19/32"	1-1/4"
J2000-9NECR	9-1/2"	1-19/32"	1-1/4"



**KLEIN TOOLS** 



**KLEIN TOOLS** 

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D213-9NETH	9-3/8"	1-19/32"	1-1/4"

**NE-Type Side-Cutting Pliers-Lineman's Bolt-Thread Holding**

- Hinge opening holds and cleans 5/8" pole line and hardware bolts or threaded rods
- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with rounded nose and sure-gripping, cross-hatched knurled jaw
- Plastic-dipped handles



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hand Tools

**NE-Type Side-Cutting Pliers**

- Rivet is closer to the cutting edge for 46% greater cutting and gripping power
- Streamlined design with sure-gripping, cross-hatched knurled jaws
- Plastic-dipped handles (D213-9NE)
- Heavy-duty, oversized plastic-dipped handles (HD213-9NE)

Klein Tools #	Overall Length	Jaw Length	Jaw Width
D213-9NE	9-3/8"	1-19/32"	1-1/4"
HD213-9NE	9-1/2"	1-19/32"	1-1/4"



D213-9NE



HD213-9NE



Klein Tools #	Description
65508	20-Piece 3/8" Drive Socket Wrench Set

**20-Piece 3/8" Drive Socket Wrench Set**

- Includes:
  - ❑ Four 6-Point sockets: 3/8", 7/16", 1/2" and 9/16"
  - ❑ Five 12-Point sockets: 5/8", 11/16", 3/4", 13/16" and 7/8"
  - ❑ Eight 6-Point deep sockets: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4" and 13/16"
  - ❑ Two extensions: 1-3/4" and 3" long
  - ❑ One ratchet
  - ❑ Hinged metal box

**8-Piece Open End Wrench Set**

- Double-insulated open end wrench set
- Ideal for use around energized bus bars, back-up batteries and in power systems
- Includes:
  - ❑ Black tool pouch
  - ❑ 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4" and 13/16"

Cementex #	Description
IOEWS-8	8-Piece Open End Wrench Set



Cementex #	Description
IGRBWS-11	11-Piece, Ratcheting Box Wrench Set

**11-Piece Ratcheting Box Wrench Set**

- Double-insulated geared box wrench set
- Set contains eleven 5" long ratcheting geared box end wrenches ranging in size from 3/8" to 1"
- High-visibility orange handle with cushion grip
- Includes:
  - ❑ Black tool pouch
  - ❑ 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

**14-Piece Long Arm Hex Wrench Set**

- Double-insulated hex wrenches
- Made of high-torque steel and feature an insulated high-visibility orange handle with cushion grip
- Includes:
  - ❑ Black tool pouch
  - ❑ 1/16", 5/64", 3/32", 7/64", 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 5/16", 3/8", 7/16", 1/2"

Cementex #	Description
HWS-14L	14-Piece Open End Wrench Set

**Cementex****KLEIN TOOLS**

Klein Tools #	Description
65514	8-Piece 1/2" Drive, Deep Socket Set Plus Metal Box

**8-Piece 1/2" Drive Deep Socket Wrench Set**

- Eight 12-Point deep sockets: 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8" and 15/16"
- Hinged metal box

Individual items are also available for all CEMENTEX KITS shown. All tools feature two-coat orange over yellow double insulation for added safety verification and are 1,000V-Rated

**T-Handle Hex Wrenches**


- Double-insulated hex wrench
- Made of high-torque steel and features a six inch insulated high-visibility orange handle with cushion grip

**Cementex**

Cementex #	Size
IHK-316	3/16" X 6"
IHK-140	1/4" X 6"
IHK-516	5/16" X 6"
IHK-380	3/8" X 6"
IHK-120	1/2" X 6"
IHK-716	7/16" X 6"
IHK-916	9/16" X 6"

**T-Handle Socket Wrench**

- For fast and easy installation/extraction of bolted lugs and electrical connections
- Provides convenience of a nut driver with much higher torque capability

**Cementex**

Cementex #	Size
TW 12-16L	1/2" x 12"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**3/8" Square Drive Socket Sets**

- Double-insulated
- 12-Point socket
- Individual IS38 standard and IS38L deep wall sockets also available
- Includes:
  - ☐ Black tool pouch
  - ☐ 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", and 13/16" 12-Point deep wall sockets
  - ☐ 3" and 6" Extension bars
  - ☐ 3/8" Square drive lever control reversible ratchet

Cementex #	Description
ISS38-11L	Deep Wall Socket Set
ISS38-11	Standard Socket Set



**Cementex**



Klein Tools #	Description
NRHD	Distribution Impact Socket
NRHDA	Replacement Socket Adapter
NRHD-3	3-in-1 Deep Impact Socket with Adapter

**Distribution Impact Socket**

- Includes 3/4", 13/16", 1" and 1-1/8" square sizes (3/4" also works on 13/16")
- 7/16" Hex quick change adapter included
- Improved ball detent on socket adapter
- 13/16" Diameter, 6" long hollow shaft allows use on long threaded bolts

**Adjustable Wrenches-Extra Capacity**

- Extra capacity allows use of a similar size wrench to handle bigger jobs, especially in confined spaces
- Forged heat-treated alloy steel for maximum strength and lightweight
- High polish chrome finish

Klein Tools #	Length	Capacity	Handle
507-8	8-1/4"	1-1/8"	Plain
507-10	10-1/4"	1-5/16"	Plain
507-12	12-1/4"	1-1/2"	Plain
D507-8	8-3/8"	1-1/8"	Dipped
D507-10	10-3/8"	1-5/16"	Dipped
D507-12	12-3/8"	1-1/2"	Dipped



507-8



D507-8

**KLEIN TOOLS**



**KLEIN TOOLS**

Klein Tools #	Description
68222	7-Piece Set

**7-Piece Ratcheting Box Wrench Set**

- Set of the ratcheting box wrenches in vinyl roll-up pouch
- 12-Point
- Includes:
  - ☐ 1/4" x 5/16" (68200)
  - ☐ 3/8" x 7/16" (68201)
  - ☐ 1/2" x 9/16" (68202)
  - ☐ 5/8" x 11/16" (68203)
  - ☐ 5/8" x 3/4" (68204)
  - ☐ 11/16" x 3/4" (68205)
  - ☐ 13/16" x 7/8" (68206)
- All items also available individually



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools

### Ratcheting Box Wrench

- Both ends are offset 25°
- Different size at each end
- Laminated construction
- Reverse ratcheting action by turning wrench over
- Chrome-plated finish
- 12-Point

Klein Tools #	Size	Length
68202	1/2" x 9/16"	6-7/8"
68203	5/8" x 11/16"	8-1/4"
68204	5/8" x 3/4"	8-1/4"



Klein Tools #	Description
KT223X4-INS	9" Lineman's Insulating 4-in-1 Box Wrench

### Lineman's Insulating 4-in-1 Box Wrench

- "See-through" insulating handle confirms metal ends are not connected
- 12-Point sockets
- Reverse ratcheting action by reversing switches on each end of the wrench
- Textured grooves in handle prevent slipping
- Chrome-plated finish resists corrosion

### Ratcheting Lineman's Wrench

- Reversible, ratcheting with bolt-through design that allows bolts to pass through the socket
- Combination square socket for most common utility hardware, 3/4" & 1" x 1-1/8" square nut size
- Bright yellow socket for easy visibility
- Works on most common utility pole hardware such as lag bolts, "C" clamps and suspension bolts, 1/2", 5/8", 3/4" bolt size

Klein Tools #	Description
KT151T	13" Ratcheting Lineman's Wrench



Klein Tools #	Description
KT155T	9" Lineman's Wrench
KT155HD	12" Heavy-Duty Design

### 5-in-1 Lineman's Wrench

- Reversible, ratcheting with bolt-through design that allows bolts to pass through the socket
- Combination square socket for most common utility hardware, 3/4" & 1" x 1-1/8" square nut size
- Bright yellow socket for easy visibility
- Works on most common utility pole hardware such as lag bolts, "C" clamps and suspension bolts, 1/2", 5/8", 3/4" bolt size
- Offers two popular wrench sizes: 9/16" and 3/4"

### Lineman's Wrench

- Forged from special bar steel and heat-treated for long life
- Each end has two different size openings
- Hole is provided at larger end for turning-in standard pole steps
- For use on heavy three-bolt guy clamps on which clearance is limited
- For 5/8" hardware, large end has 29/32" and 1-3/32" openings, small end has 5/8" and 13/16" openings

Klein Tools #	Description
3146	13" Lineman's Wrench



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hand Tools



Lowell #	Description
53	20" Handle, for 1-5/16", 1-1/2" Sq Sockets and 1-1/2" Hex

**Lineman's Double Square Transmission Wrench**

- Cast iron
- Two square sizes in one permanent socket; 1-5/16" and 1-1/2"
- Combination socket also turns 1-1/2" hex nuts
- Reversing control in head
- Enclosed ratchet mechanism
- Bolt-Thru design

**Lineman's Triple Square Double End Wrench**

- Combine flexibility and reliability
- Ratcheting socket at one end and a ratcheting box at the other
- Socket is made of cast-iron
- Rugged, fabricated steel handles
- Bolt-thru design
- Control lever in head

Lowell #	Description
103TDE	12" Handle, for 3/4", 1" and 1-1/8" Triple Square with 9/16" & 3/4" Hex on Opposite End
101TDE	9" Handle, for 3/4", 1" and 1-1/8" Triple Square with 9/16" & 3/4" Hex on Opposite End



Lowell #	Description
151T	12" Handle, for 3/4", 1" and 1-1/8" Sq.
150T	10" Handle, for 3/4", 1" and 1-1/8" Sq

**Lineman's Triple Square Wrench**

- Fabricated steel handle
- Lineman's socket wrench
- Fluorescent orange, cast iron sockets
- Three square sizes in one permanent socket: 3/4", 1", 1-1/8"
- Reversing control on side of head
- Semi-Enclosed ratchet mechanism
- Bolt-thru design
- Fits in most common holsters

**Overhead Lineman's Wrench**

- 3/4", 1" and 1-1/8" Square sockets on one end with two-sided 12-point 3/4" and 9/16" ratcheting box wrench on the other end
- Open center for bolt to pass through
- Large reversing lever

Speed Systems #	Description
RBW-OHW	Ratcheting Box Wrench for Overhead Hardware Applications



Speed Systems #	Description
RBW-12916	1/2" x 9/16"
RBW-91634	9/16" x 3/4"
RBW-5834	5/8" x 3/4"
RBW-3478	3/4" x 7/8"

**Quad "Dogbone" Ratcheting Box Wrench**

- 12-Point ratcheting box wrench
- Thick-walled plastic ergonomic handle with center isolation hole
- Rated 1,000V
- Other sizes and configurations not shown available



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## RAUCKMAN™ Utility Products

The BugWrench handle is formulated of high strength and high dielectric polymer. All BugWrench tools equipped with the high dielectric handle include the following features: A see-through port in the center of the handle to confirm that the two ends are not electrically connected tool metal-to-metal electrical isolation superior to others pull-apart strength greater than others indicator ribs for improved safety (1,000V-Rated) high visibility yellow color. The unique patent-pending design and manufacturing process ensures maximum metal-to-metal separation, with unmatched mechanical strength. A complete line of BugWrenches are available. Call for options and sizes.



RAUCKMAN™  
Utility Products

Rauckman #	Description
BW-251	3/8" Penta Socket Ratchet, 5/16" Allen Hex
BW-252	3/8" Penta Socket Ratchet, 3/8" Allen Hex

### Penta Socket BugWrench

- For working on pad-mount transformers and secondary pedestals
- Penta sockets combined with hex (Allen) wrenches
- High-visibility yellow
- Heavy-duty forged steel head
- Ratchet penta fitting with built-in 3/8" hex socket for "Twist-Off" equipment locks
- 2" Working length of hex wrenches for transformer bars with covers

### 4-in-1 Bug Wrench

- High visibility yellow handle (insulated versions)
- Heavy-duty forged head construction
- 1/2" and 9/16" on one end and 5/8" and 3/4" on the other
- Most common sizes on T&D apparatus and connectors

Rauckman #	Description
BW-244	Insulated 4-in-1 HD Ratchet
BW-044	All Metal 4-in-1 HD Ratchet



RAUCKMAN™  
Utility Products



RAUCKMAN™  
Utility Products

Rauckman #	Description
BW-223HD	3/4" x 9/16" Heavy Duty BugWrench

### BugWrench

- For installing or performing maintenance on overhead transformers
- 3/4" and 9/16" Combination ratchet wrench
- Heavy-duty forged fittings

### Ratcheting Box Wrench with Hex Shaft

- For use on secondary set screw bar connectors
- Thick-walled plastic ergonomic handle
- Rated 1,000V

Speed Systems #	Description
RBW-1	5/16" Hex Shaft Extended 1-1/2" One Side
RBW-2	5/16" Hex Shaft Extended 1-1/2" Each Side
RBW-38H	3/8" Hex Shaft Extended 1-1/2" One Side



Speed Systems



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hand Tools

**Tri-Penta Wrench**

- 3/8" Screwdriver for opening the primary door on 3-phase transformers
- Speed Sleeve spins freely to open transformers and switch gears two times faster
- Built-in design for lifting hand hole lids
- Heat-treated alloy steel
- Penta wrench designed for opening all transformers and switch gears
- Now with removable socket for use with different sizes

Madi #	Description
PSD-1	Penta Driver Penta Socket Driver

Madi #	Description
TP-1	Tri-Penta Wrench

**Penta Driver Penta Socket Driver**

- Includes removable drill adapter
- Speed Sleeve spins freely to open transformers and switch gears two times faster



Cementex #	Drive
IR38-LC	3/8" Drive
IR12-LC	1/2" Drive
IB38-3	3" Extension for 3/8" Drive
IB38-6	6" Extension for 3/8" Drive
IB38-12	12" Extension for 3/8" Drive

**Square Drive Lever Control Ratchet**

- Double-insulated ratchet wrench is reversible
- Has lever control and features an audible click and feel impulse
- Measures 7-1/4" in length and is high-visibility orange in color



Residential

**RAUCKMAN™**  
Utility Products



Commercial/Industrial

Rauckman #	Description
M-001	Amber, Residential for Single-Phase Meter
M-002A	Orange, Commercial/Industrial for Ply-Phase Meters
M-009	Meter Puller Storage Bag

**MeterPuller**

- Works with all known meters and sockets
- Release levers
- Solid hand barrier
- High strength handle
- Chrome plated steel engagement clips
- Vent holes to divert gasses
- Optional storage bag available

**Impulse Stapler**

- Cordless, internal gas operated staple gun
- Paslode Frame Fuel
- Fully charged between trigger pulls in only seconds
- No set-up required

Paslode #	Description
ST-315i	Cordless Impulse Stapler



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hand Tools



M&A Products#	Description
SS-2000	Holds 12 Staples

**Stapul-Stik**

- Slots are 3/4" L x 1/8" W
- Overall dimensions: 7/8" x 3/4" x 14-1/4"
- Diameter of the hole to hold the stick is 1/2"

**RK194-2 Wiremike**

- For measuring ACSR, stranded and solid conductors, IPS tubing, rigid and thinwall conduit, and inside and outside dimensions of tubing and pipe sizes
- Stainless steel construction
- Ruler included

Burndy #	Description
RK194-2	Wiremike with Ruler




Madi #	Description
DBWB-1	DogBone Wire Brush
FRWB-1	FlatRound Wire Brush
LWB-1	Large Wire Brush Replacement

**DogBone and FlatRound Wire Brushes**

- Integrated replaceable wire brushes for cleaning conductors to make better connections
- Brushes up to 1590 MCM conductor-FlatRound has a flat profile for hard to brush places
- Use one end for aluminum and the other one for copper
- Durable, lightweight and convenient to carry on climbing belts
- Non-conductive and brushes are not exposed
- Built-in snap ring
- Wire brushes are easily replaceable

**Ratcheting Socket/Ratcheting Penta Wrench**

- Thick walled plastic ergonomic handle with center isolation hole
- Rated 1,000V
- Other sizes and configurations not shown available

Speed Systems #	Description
RBW -34SRP	3/4" Socket with Penta Socket (Opposed)




Speed Systems	Description
PHS-2	1/2" Drive, 3/4" Hex Socket

**Penta/Hex Security Wrench Socket**

- Penta/Hex combination sockets
- Penta and hex socket combined into one socket with common drive
- Reversible when used with socket extension

**Ratcheting Box Wrench with Hex Shaft, Fixed Penta**

- For use on power transformers
- Thick-walled plastic ergonomic handle with center isolation hole
- Rated 1,000V
- Penta on handle

Speed Systems #	Description
RBW -1P	5/16" Hex Shaft Extended 1-1/2" One Side
RBW -2P	5/16" Hex Shaft Extended 1-1/2" Each Side
RBW -3P	5/16" Hex Shaft on One Side, 3/8" Hex Shaft on Other Side, Both 1-1/2" Long




Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Hot-Sticks and Hot-Line Tools

**Fixed Length Shotgun Stick**

- Full open side hook offers unobstructed vision of the hook
- Operating rod guide eliminates trapped dirt and moisture
- Inside area of rod guide can be easily cleaned
- Hook release trigger is shielded
- Requires deliberate action to open hook
- All shotgun sticks are tested per OSHA and ASTM F-711
- For universal fitting on base end add suffix -U to the Mfg #, for bottom break hook add suffix -X

External



Internal



Hastings #	Description
8104	4'6", External Operating Rod
8106	6'6", External Operating Rod
8108	8'6", External Operating Rod
8110	10'6", External Operating Rod
8112	12'6", External Operating Rod
8110-U	10'6", External Operating Rod, Universal Fitting
8204	4'6", Internal Operating Rod
8206	6'6", Internal Operating Rod
8208	8', Internal Operating Rod
8210	10'6", Internal Operating Rod
8212	12'6", Internal Operating Rod
8208-U	8', Internal Operating Rod, Universal Fitting
8208-UX	8', Internal Operating Rod, Universal Fitting, Bottom Break Hook

Chance #	Overall Length
C4030291	1-1/4" x 4'9"
C4030291A	1-1/4" x 4'9"
C4030292	1-1/4" x 6'8"
C4030292A	1-1/4" x 6'8"
C4030293	1-1/4" x 8'7"
C4030293A	1-1/4" x 8'7"
C4030294	1-1/4" x 10'7"
C4030295	1-1/4" x 12'7"

**Grip-All Clampstick, Single-Piece Style**

- Puts an easy-to-control "finger" on an insulated pole
- For installing hot-line and grounding clamps
- "A" Suffix = metal universal fitting on handle end

**CHANCE**

Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hot-Sticks and Hot-Line Tools



8158-98



81-814

**Telescopic Shotgun Sticks**

- Extended length spear offers easy method of locating the eye of hot taps that are otherwise difficult to locate
- Head is molded of non-conductive polycarbonate-durable, impact-resistant and unaffected by temperature extremes
- New operating rod guide eliminates trapped dirt and moisture
- Hook release trigger is shielded and requires deliberate action to open the hook
- Hanger hook is molded in the head, eliminating metal parts
- For universal fitting on base end- add suffix -U to the Mfg #

Hastings #	Operating Length	Retracted Length
8158	5'1", 6'6", 8'	5'1"
8158-U	5'1", 6'6", 8', Universal Fitting	5'1"
8158-80	6'6", 8'	5'1"
8158-98	8'2"	5'1"
81611	6'6", 8', 9'6", 11'	6-1/2'
81611-97	8', 9'6", 11'	6-1/2'
81-811	8', 9'6", 11', 12'6"	8'
81-814	8', 10', 12', 14'	8'
81-814U	8', 10', 12', 14', Universal Fitting	8'
81-1018	9'10", 11'9", 13'6", 15'6", 17'6"	9'10"

**Folding Shotgun Stick with External Operating Rod**

Hastings #	Description
13412	6'6" Folding Shotgun Stick
13413	8'6" Folding Shotgun Stick
13413-U	8'6" Folding Shotgun Stick with Universal Fitting
13414	10'6" Folding Shotgun Stick
13415	12'6" Folding Shotgun Stick

**Grip-All Clampstick, Hinged-Style**

- Ideal for limited tool-storage space
- Puts an easy-to-control "finger" on an insulated pole
- For installing hot-line and grounding clamps
- "A" Suffix = metal universal fitting on handle end

**CHANCE**

Chance #	Overall Length
C4030297	1-1/4" x 8'8"
C4030297A	1-1/4" x 8'8"
C4030298	1-1/4" x 10'6"
C4030298A	1-1/4" x 10'6"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hot-Sticks and Hot-Line Tools

**Grip-All Clampstick, Telescoping**

- Rotating coupler and engineered positive-lock button with safety stop
- Close fit keeps out dirt and moisture
- Foam-center Epoxiglas insulated pole top section
- All controls can be accessed while wearing gloves
- Locks at each length
- Retracted length: 8' 2-3/4"

Chance #	Extended Length
C4031036	8'6-3/4", 10'4-1/2", 12'-1/2", 14'



Hastings #	Operating Length	Retracted	Base Dia
HV-212	12'7"	58"	1.45"
HV-216	16'9"	60"	1.61"
HV-220	21'	62"	1.75"
HV-225	25'6"	64"	1.91"
HV-230	30'	66"	2.07"
HV-235	35'	68"	2.22"
HV-240	39'6"	69"	2.38"

**Tel-O-Pole II Hot Stick**

- "No Twist" stick has a unique triangular design
- Fluorescent green tip section is highly visible and has a foam core
- Sections can be removed or added to make the stick the preferred length
- Ergonomic design gives the operator a better gripping surface for better control

**Tel-O-Pole Hot Stick with Tip Lock Feature**

- Tip retracts and locks into next larger section
- Tip diameter is 7/8" (extended) or 1-3/32" (retracted)



Hastings #	Operating Length	Retracted	Base Dia
ST-225	17' , 25.5'	60"	2-3/16"
ST-230	17', 21.5', 26', 30'	61-5/8"	2-3/8"
ST-235	17', 21.5', 26', 30', 35'	63-3/8"	2-11/16"
ST-240	22', 26', 30', 35', 40'	65-3/5"	2-7/8"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools

Hastings #	Operating Lengths	Retracted	Base Dia
S-212	12'	44"	1-5/8"
S-216	12'4", 16'	56"	1-5/8"
S-220	17', 20'	58"	1-7/8"
S-225	17', 21', 25.5'	60"	2-3/16"
S-230	17', 21.5', 26', 30'	61-5/8"	2-3/8"
S-235	17', 21.5', 26', 30', 35'	63-3/8"	2-11/16"
S-240	22', 26', 30', 35', 40'	65-3/8"	2-7/8"

## Standard Tel-O-Pole Hot Stick

- Can be locked at each length listed
- Tip diameter is 7/8"
- Tip section will not interlock



## Telescoping Disconnect Tool

- Perform routine jobs from ground level
- Universal end fitting on insulated top section
- Heavy-duty, spring-loaded plastic buttons keep extended tool sections locked in place
- Standard duty sticks retract to approximately 5' to 6', compact 2' to 3', and heavy-duty 5'



Utility Solutions #	Operating Lengths
USTS-008	8'
USTS-010	10'
USTS-016	16', 12'
USTS-025	26', 21', 17'
USTS-030	30', 26', 21', 17'
USTS-035	35', 30', 26', 21', 17'
USTS-040	40', 35', 30', 26', 21', 17'
USTS-045	45', 40', 35', 30', 26'
USTS-050	50', 45', 40', 35', 30'

Chance #	Tip Diameter	Extended Length	Base Diameter	# of Sections
C4031017	1-1/16" Standard	8'-12'	1-1/2"	3
C403-1022	1-1/16" Standard	22'-26'-30-1/2'-35'	2-1/2"	6
T403-3349	1-1/16" Standard	22'-28'-34'-40'	2-1/2"	8
T403-2205	1-1/16" Compact	7'	1-7/8"	5
T403-3240	1-1/16" Compact	10'	1-11/16"	4
C4031601	1-1/4" Heavy-Duty	16-1/2'-20-1/2'-25'	2-1/4"	6
C403-1602	1-1/4" Heavy-Duty	17-1/2'-21-1/2'-25-1/2'-30'	2-1/2"	7

**CHANCE**

## BLUE STRIPE Telescopic Hot Stick

- Round telescopic hot stick with large, clear print with BLUE STRIPE patented alignment feature
- Epoxy resin and unique non-woven fiberglass construction creates smoother surface that resists water absorption
- CNC Machined spline end and buttons will hold up to the rigors of daily use
- Tip lock feature that allows operator to lock last two end sections for maximum strength and rigidity
- Exceeds ASTM F711 & F1826



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hot-Sticks and Hot-Line Tools

**Tel-O-Pole Measuring Stick**

- Used to measure overhead lines, telephone, cable-TV, highway clearances and structures
- Eye-level reading, no calculations required
- Positive locking buttons, spring-loaded, easy to extend
- Standardized parts for quick and easy repair and replacement

Hastings #	Operating Length	Retracted Base Dia.
E-25	25'	65-3/4"
E-30	30'	65-3/4"
E-35	35'	65-3/4"
E-40	40'	65-3/4"
E-50	50'	69-3/16"

**Combination Tel-O-Pole Hot Stick and Measuring Stick**

- Open and close switches, disconnects, line fuses, cut outs, as well as measure elevated heights
- Markings are printed in large easy to read numbers
- Eye-level reading, no calculations required

Hastings #	Operating Length	Retracted	Base Dia.
EV-25	25'6"	64"	1.91"
EV-30	30'	66"	2.07"
EV-35	35'	68"	2.22"
EV-40	39'6"	69"	2.38"



**CHANCE**

Chance #	Description
C4031822	6' Long IMPACT Elbow-Puller Tool
C4030704	15kV Plastic Coated Grippers
C4030613	25kV Plastic Coated Grippers


**IMPACT Elbow-Puller Tools**

- Uses slide-hammer mechanism to disengage and replace elbows
- Tool and grippers help operator control elbow and stiff underground cable lead
- 5 lb. Slide hammer is plastisol coated and flared at both ends
- Both front and rear handgrip areas are coated with Griptread

**Strap Hoist Isolating Link**

- Provides extra protection when used with strap hoists on primary voltages
- Fiberglass link helps to overcome the loss of dielectric properties when the web straps become contaminated through field use
- Load limit 4,000 lbs.

Hastings #	Description
3413	6", Std Safety Hook
3414-1	12", Hot Stick Operated Safety Latch



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools

**Strap Hoist Isolating Links**

- Strap hoist isolating links are designed to provide extra protection when used with strap hoists on primary voltages
- Isolating links can be used with most strap hoists
- Standard swivel eye one end and safety hook
- Load limit-4,000 lbs.
- Lightweight

Hastings #	Length of Fiberglass	Weight
3413	6"	2.3 lbs.
3414	12"	2.5 lbs.



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



7546

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment


Hastings #	Description
7546	Super "U" Arm w/Large Hanger Loop, Two Wire Holders, 20.4 lbs.
7547	Standard Super "U" Arm, One Wire Holder, 15.4 lbs.

**Super "U" Arm Extensions**

- Super "U" Arm is designed with a profile "U" shape for greater strength and durability
- All arms include insulated conductor holders to insure dielectric integrity
- Arms are rated for 34.5kV phase-to-phase work applications
- Standard Super "U" accepts 1-1/16" OD or up to 800 MCM conductor
- Large capacity Super "U" holder has an opening of 2-5/8"
- All Super "U" Arms and Super "U" Conductor Supports have a load limit of 200 lbs. per wire holder
- Interchangeable hanger loop kits are available for the different sizes of cross arms on your system

**Fiberglass Extension Arms for Composite or Wood Cross Arms**

- Can be used with both Hastings round and Super "U" Extension Arms
- Fits composite or wood cross arms up to 4-1/2" x 6-3/4"
- Rubber grippers won't damage composite cross arms
- Cross arm loop is powder coated to prevent damage to composite cross arm
- Casting trim on end fitting provides protection on bottom side of composite cross arm



7545-F

Hastings #	Description	Weight
7545	Standard Super "U" Arm with Two Conductor Holders	18.8 lbs.
7547	Standard Super "U" Arm with One Conductor Holder	15.4 lbs.

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

Hastings #	Description	Weight
5001	5', One Wire Holder & Insulator	11.5 lbs.
5007	6', Two Wire Holders & Insulators	15.5 lbs.

**Fiberglass Extension Arms**

- Designed for use as a temporary aid in replacing existing conductors and insulators, or as an aid for moving out conductors to obtain working clearance in congested areas
- Eye bolts are silicon bronze to prevent seizing
- Adjustable
- Load limit 150 lbs. per conductor holder
- Ratings 15kV without insulator and 34.5kV with insulator



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools

**Epoxiglas Extension Arms**

- Designed for use on voltages up to and including 15kV
- For use when redactor reconductoring or insulator replacement is necessary
- Two wireholders
- Maximum cross arm size: 3-3/4" x 4-3/4"
- Maximum vertical loading: 150 lb.

Chance #	Arm Dia x Length
H480072	2-1/2" x 6'

**CHANCE**

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

Hastings #	Description	Weight
5039	34" Overall Length, One Conductor Holder & Insulator	13 lbs.
5041	48-1/2", Two Wire Holders & Insulators	16 lbs.

**Pole-Mounted Support Arm with Ratchet and Nylon Strap**

- Safety ratchet binder and nylon strap eliminates hazards of chains and chain tighteners when being used in primary voltage areas
- Installation and removal of arms is quick and easy
- Ratchet binder has extra wide handle for easy operation when wearing rubber gloves
- 2" wide nylon strap is 44" long to accommodate most structures

**Pole-Mounted Super "U" Conductor Support Arm with Ratchet and Nylon Strap**

- Designed for replacing conductors and insulators and maintenance of line voltages up to and including 34.5kV phase to phase
- Rated with 200 lb. working load per conductor holder
- Includes insulated conductor holders for dielectric integrity

Hastings #	Description	Weight
5047	49-7/8", Two Wire Holders	18 lbs.

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

**CHANCE**

Chance #	Description
T4001939	48" Two Conductor Supports

**Strap-Style Temporary Conductor Support**

- Epoxiglas pole 2-1/2" diameter



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hot-Sticks and Hot-Line Tools

**Strap-Type Transformer Gin**

- Strap-type-ratchet-action mounting mechanism
- Wide handle opening on rapid-action ratchet
- 2,000 lb. Maximum ratings, including load and fall-line pull

Chance #	Description
T4001938	5" Extended-Base Strap Gin

**Chain Binder Type Transformer Gin**

- Standard base unit is for mounting on clear pole sections
- Wheel tightened and 36" chain are part of each unit
- 2,000 lb. Maximum ratings, including hand pull force
- 26" Pole length

Chance #	Description
C4000315	5" Extended Base Chain Gin

**Loadbuster Tool with Case**

- Lightweight and portable
- Interrupts with no external arc
- Simplified switching procedure
- Operation counter feature helps determine maintenance needs

S&C #	Description
5300R3/5381	14.4/25 kV nominal, 27 kV max.
5400R3/5381	25/34.5 kV nominal, 38 kV max.



Hastings #	Operating Length	Retracted	Base Dia
HV-208	8'	26"	1.75"
HV-312	12'	37"	1.61"
06-185	Bucket Storage Canister for HV-208		
06-186	Bucket Storage Canister for HV-312		

**Tel-O-Pole Bucket Stick**

- Ideal for quick access to linemen working from a bucket truck
- Stick collapses below lip of bucket
- Light-weight bucket storage canister available



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hot-Sticks and Hot-Line Tools

Chance #	Description
C4060181	5' Conductor Cover with 4' Epoxiglas Handle, 25kV
P4060184	5' Conductor Cover w/o Adapter or Handle, 25kV
C4060181GA	5' Conductor Cover with Grip-All Adapter, 25kV
C4060514GA	5' Conductor Cover with Grip-All Adapter, 36kV
C4060182	21" Long, 8-1/2" Wide, 6" High Insulator Cover with Grip-All Adapter, 25kV
C4060182L	21" Long, 8-1/2" Wide, 9" High Insulator Cover with Grip-All Adapter, 25kV

## Conductor and Insulator Covers

- Conductor and insulator units mate together to cover pin-type or post-type insulator construction
- Can also be used with deadened cover
- Covers will couple with major brands of rubber line hose and insulator covers of 25kV class
- High-density bright orange polyethylene
- For use with Grip-All adapter for hot stick application or without adapter for rubber glove application



## Pole Covers

- Meets Class 4 requirements
- High-dielectric linear polyethylene covers will not flash flame
- Some softening without deformation at approximately 170°F, and will resist brittleness at -50°F
- Ribbed to reduce cover contact with pole
- Rope handles help spread covers and snap around pole

Chance #	Diameter	Length
M49376	9"	72"
C4060000	12"	72"

## Arc Snuffer Removal Tool

- Specifically for use in Grip-All clampsticks
- Does not de-energize URD bushings
- Designed to ensure adequate electrical clearances
- Integral ring on each tool retracts into clampstick
- Works like bolt extractor

Chance #	Description
C4032037	Removal Tool
403-2036	Replacement Tool



**SALISBURY**  
by Honeywell



Salisbury #	Description
24401	6' Rescue Hook
24403	8' Rescue Hook

## Insulated Rescue Stick

- Used to withdraw an injured worker out of a hazardous area
- Foam filled, fiberglass reinforced handle
- Coated heat treated body hook with an 18" opening



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools

## Extension Arm Accessories

- Epoxy insulator can be added to existing auxiliary arm wireholder to upgrade for 34.5kV
- Wireholder has counterbalanced latch which closes automatically behind the conductor to hold in place
- Complete with 2.5" pole clamp

Chance #	Description
4805-7	Epoxy Insulator, 7/16" Threads
4805-17	1" Fork-Type Wireholder, No Insulator


**CHANCE**

**HASTINGS**  
 A WORLDWIDE SUPPLIER OF  
 Hot Line Tools & Equipment

Hastings #	Description	Weight
12666	Conductor Holder	11 lbs.

## Super Duty Conductor Holder

- For attachment to mast or jib adapters
- Accepts 2" diameter conductors
- Load limit 500 lbs.

Hastings #	Description	Weight
1256-H	6' Hot Stick for Huskie Tool	4.3 lbs.
1258-H	8' Hot Stick for Huskie Tool	5.0 lbs.
1256-G	6' Hot Stick for Greenlee Tool	4.3 lbs.
1258-G	8' Hot Stick for Greenlee Tool	5.0 lbs.

**HASTINGS**  
 A WORLDWIDE SUPPLIER OF  
 Hot Line Tools & Equipment


## Hot Stick for Huskie and Greenlee In-Line Battery Tools

- Battery tool installs quickly and easily on stick
- 6' and 8' Lengths
- Simply push lever to activate tool, pull to release
- Weights shown below are for the stick only and do not include the battery tool
- Battery tools sold separately


**HASTINGS**  
 A WORLDWIDE SUPPLIER OF  
 Hot Line Tools & Equipment

Hastings #	Description
10-178	"V" Brush
10-179	Ten Replacement Brushes

## Conductor Cleaning "V" Brush

- Stainless steel bristles to allow the cleanest connection possible
- Can be used for all conductor cleaning requirements
- Can be used with shotgun sticks

## Conductor Cleaning "U" Brush

- Stainless steel bristles to allow the cleanest connection possible
- "U" Type brushes for tight clearances and easy storage

Hastings #	Description
10-175	Standard "U" Brush, 500 MCM
10-184	Compact "U" Brush, 500 MCM


**HASTINGS**  
 A WORLDWIDE SUPPLIER OF  
 Hot Line Tools & Equipment


Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools



## Universal Tree Pruner

- Drop forged steel double cutting action blades
- Two pulley rope strings triple the power for cutting limbs up to 1-1/2" diameter
- Complete unit mounted on 12" fiberglass shaft with universal adapter and 25' polypropylene rope

Hastings #	Description
10-019	Tree Trimmer



## Photo-Electric Control Tester

- For photo-electric switches and lamps
- Completely eliminates all direct and reflected light
- Designed for use on twist lock type controls up to 4" diameter
- Use with Tel-O-Pole Hot Sticks for test controls and lamps from ground
- Adaptable to all hot sticks equipped with universal type heads

Hastings #	Description
UH-016	4" x 4-1/4"



## Universal Lamp Changer Head

Hastings #	Description
151-ACA	For 100-200W
152-AC	For 300-500W
161-AC	For 175W Mercury



## Universal Extra Large Adjustable Fuse Puller

- Fits fuses 1-1/2" to 3-5/8" diameter
- Jaws are plastic coated

Hastings #	Description
5455-93	Universal XL Fuse Puller



## Static Discharge Stick

- Designed to remove the static charge after de-energizing
- Includes copper "U" hook, 3'6" closed cell foam filled tubular fiberglass stick and 6' of copper grounding cable

Salisbury #	Description
20817	3'8" OAL Static Discharge Stick



**SALISBURY**  
by Honeywell

**SALISBURY**  
by Honeywell



Salisbury #	Length	Diameter	Class
2496	6'	9"	4
2466	6'	12"	4

## Air Gap Pole Guard

- Installed before setting new poles to guard against accidental line contact
- Made from orange, Type I ABS, cold weather, high impact thermoplastic
- Drilled rope handles
- ASTM Class 4



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hot-Sticks and Hot-Line Tools

**Versa Guards**

- Designed so that two guards can be coupled together to cover most 13kV single and double arm, pin and post constructions, 3.92'



Salisbury #	Description
2389	ABS/PVC 4' Stick Type III Class 4, Grade 1

**SALISBURY**

by Honeywell

**DeViner The Vine Removal Utility Tool**

- Two-prong angled tapered designed for quick vine removal in tight spaces
- Fiberglass reinforced nylon for lighter weight and less fatigue
- Made of fiberglass reinforced nylon for non-conductive material
- 300 pound hanging and compression proof load
- Works with all universal tools
- Aircraft aluminum (6063) base for strong, secure fit

Madi #	Description
DV-1	DeViner Vine Removal Utility Tool

**Double-Header Universal Attachment**

- Double-header allows you to attach two different universal tool accessories to one hot stick
- Double-Header is made of aircraft aluminum for maximum durability and minimal weight
- Includes two thumb screws

Madi #	Description
DH-1	Double-Header Universal Attachment



UTILITY SOLUTIONS  
Lineman driven. Field proven.™



USJJ-004

Utility Solutions #	Description
USJJ-001	15kV Standard
USJJ-002	27kV Standard
USJJ-004	15kV Loadbreak Cutout

**Jack Jumper Cutout Bypass Tool**

- Safe and quick method to bypass an overhead cutout without bulky jumper cables
- Tool is indispensable for fuse coordination tasks
- Installation and removal of tool is done with a shotgun stick
- Optional soft carrying case available

Utility Solutions #	Volts/Amps	Head
USBS-15-1-PS	15kV/300A	Floating
USBS-15-2-PS	15kV/300A	Duckbill
USBS-27-1-PS	27kV/300A	Floating
USBS272PS	27kV/300A	Duckbill
USBS-46-1-PS	46kV/200A	Floating
USBS-46-2-PS	46kV/200A	Duckbill



UTILITY SOLUTIONS  
Lineman driven. Field proven.™

**Break-Safe 15kV-46kV Load Break & Pick-Up Tools**

- Safety lockout pin provided
- Clear polycarbonate housing provides clear indication of tool position
- Duckbill option for shotgun stick installation
- Capacity: #6 Copper min up to 954 ACSR (1.1 dia) max
- Optional soft carrying case available



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Hot-Sticks and Hot-Line Tools



Utility Solutions #	Volts/Amps	Head
USBS600-1	7.2-27kV/600A	Floating

**Break-Safe 7kV-27kV/600A Load Break & Pick-Up Tool**

- Extra-large clamp capable of handling all wire sizes up to 2" in diameter
- Conductor bars allow the use of two mechanical jumper clamps
- Internal safety lock, manual locking pin also included
- Durable electrical grade fiberglass housing
- Glove friendly design

**Jumper Hook**

- Designed to eliminate jumper clamp sag and prevent potential cross-phasing situations
- Minimizes a jumper clamp swaying in high wind conditions
- Easily installed by a gloved hand or with a shotgun stick
- Will fit over any class 2 or 3 line hose and exhibits a flash-over resistance of over 50 kV
- Molded from tough weather resistant polymer
- Size: 11" x 4.5" x .5

Utility Solutions #	Description
USJH-001	Jumper Hook



S&C #	Description
4440	Talon Overhead Fuse Handling Tool

**Talon Overhead Fuse Handling Tool**

- Aluminum-bronze
- Two-pronged fitting and pole, one curled and one straight
- Designed for overhead distribution systems
- Used for installing and removing SMD-20 power fuses, Type XS fuse cutouts, Fault Tamer fuse limiters and TripSaver dropout reclosers

**Pole Wrap**

- Worker On Line warning printed
- Reflective striping for night time visibility
- Secured with hook and loop

Estex #	Description
1180-45	6" x 45", Reflective Pole Wrap w/Card Holder

**Hot Stick Accessories**

Hastings #	Description
C40	Vinyl Carrying Case, for HV-225 & 240
P10431	Universal Disconnect Hook
A 10020	Universal Tie Stick Head
A 10023	Universal Wire Tong Head
5455-35	Universal Insulator Controller
5455-46	Universal Socket Wrench, 1/2" Square Drive
5765-13	5/8" Square Magnetic Wrench Socket
A 10400	Fluorescent Universal Disconnect Hook



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hot-Sticks and Hot-Line Tools

## Hot Stick Cleaners

- Helps all telescopic sticks slide freely
- Reduces friction caused by wear and contaminants
- Non-conductive, non-flammable



10-091



10-088



10-188



Hastings #	Description
10-088	Hot Stick Spray
10-091	Hot Stick Wax, 14 oz.
10-188	Hot Stick Wipes, Box/50
P31444	Spray Handles (Sold Separately)

## S-1 Hot Stick Cleaner &amp; Water Repellent Wipe

- Pre-saturated, lint-free wipe
- Dual action-cleans and applies water repellent
- Does not remove or adversely affect gloss coat
- Evaporates quickly, no build-up over time
- Removes grease, dirt and grime
- Designed for one time use and easy disposal

Polywater #	Description
S-1	Saturated Towellette



American  
**Polywater**  
Corporation



Polywater #	Description
B-1	24" x 24" Individual Saturated Wipe in Sealed Foil Pouch
B-D72	72-Count Canister of 10" x 12" Saturated Wipes
BWC-128	1 gal Boom Wash Concentrate

## B-1 Boom Wipes

- Pre-saturated, lint-free wipe
- Does not remove or adversely affect gel coat
- Prevents build-up over time
- Cleans grease, tar, creosote, salt spray, hydraulic fluid, pine pitch and road debris off fiberglass boom arms
- Water soluble for easy water rinsing
- Designed for one time use and easy disposal

American  
**Polywater**  
Corporation

## Epoxiglas Cleaning Kits

- Essential for care and maintenance of Epoxiglas tools
- Cleans insulated boom sections of aerial life trucks
- Do not use on gel-coat or painted boom surfaces
- Includes:
  - ☐ 1 gal Moisture Eater II Cleaner
  - ☐ Box of 20 abrasive cleaning pads
  - ☐ Gloss restorer kit
  - ☐ Hot stick wiping cloth

Chance #	Description
C4002365	Epoxiglas Cleaning Kit
M1904	Hot Stick Wiping Cloths
C4002364	Moisture Eater II Cleaner Solvent (1 gal)
C4001166	Abrasive Cleaning Pads (Box of 20)
C4001520	Gloss Restorer Kit




**CHANCE**



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hot-Sticks and Hot-Line Tools



American  
**Polywater**  
Corporation

Polywater #	Description
W-1	Wax-Saturated Wipe w/Dry Buffing Towel
W-16	16 oz. Fast-Hazing Fiberglass Wax

### W-1 Wax & Buff Wipes for Live-Line Tool Maintenance

- Wax-Saturated, lint-free wipe
- Dual action tandem pack includes dry buffing towel
- Fast-hazing fiberglass wax
- Suitable for rubber and porcelain materials
- Does not remove or adversely affect gel coat
- Leaves non-conductive water-repellent coating
- Prevents continuous water film on stick
- Designed for one time use and easy disposal



**CHANCE**

### Moisture Eater II Wipes

- For cleaning of insulated hot-line tools, line hose and rubber blankets
- Pre-moistened with a half ounce of orange-scented Moisture Eater II solvent
- Lint-free

Chance #	Description
C4002538	Box of 50 Moisture Eater II Wipes



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



Hastings #	Description
01-3200	4-1/2" OD Aluminum Kit, Fits 30/40 PVC
01-3400	6-5/8" OD Aluminum Kit, Fits 30/40 PVC

### Canister Kit

- Latch pin is a captive component and easily operated by a pull or push motion
- Latch pin hinge is stainless steel
- Water and dust proof seal
- Kit includes:
  - ☐ Lid assembly
  - ☐ End cap
  - ☐ Two mounting brackets
  - ☐ Adhesive kit
  - ☐ Required mounting hardware
  - ☐ Instructions



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage

**Canvas Tool Bag**

- Solid, continuous PVC ring in top of polypropylene rope
- 8" x 8" inside pocket
- Molded rubber bottom

Buckingham #	Description
1217Q3	12" x 15" with Special Fleet logo



Klein Tools #	Description
5144	10" x 14"

**Aerial-Basket Oval Bucket**

- Canvas
- Black molded polypropylene bottom
- Two nylon 66 polymer hooks included
- Temperature change resistant hooks
- 15 interior pockets
- 2.05 lbs.



Warren Heim Corporation

**Tool Bucket**

- Canvas
- Rope and Snap
- One inside pocket

Warren Heim #	Description
31-206	12" x 15"



Klein Tools #	Description
5109	Straight-Wall Bucket
5109PS-I	Straight-Wall Bucket with One 8" x 8" Inside Pocket & Swivel Snap (No. 1012)

**Wide-Opening Straight-Wall Bucket**

- Durable No. 6 canvas
- Black molded polypropylene bottom
- Rope handle
- 12" Diameter x 15" height

**Heavy-Duty Tapered-Wall Bucket with Swivel Snap Hook**

- Tough No. 4 canvas
- Black molded polypropylene bottom
- Rope handle
- Riveted leather glove strap
- Equipped with No. 2012 swivel snap hook

Klein Tools #	Size
5103S	12" x 12" x 9"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Tool and Equipment Storage



Estex #	Description
1807-3	16" x 9" x 20"

**Oval Compression Cutter Tool Bag**

- Hard body plastic
- Dividers form five compartments
- Detachable strap sketches across the top of the bag to keep tools in place
- Shock absorbing rubber in the bottom protects tools
- Two grommets allow attachment to the aerial basket with hooks
- Rubber "bumper" is attached to the bottom side of the bag to protect the aerial basket from abrasion

**Hard Body Oval Bucket**

- Fabric constructed of rugged denier polyester to resist wear and tear on the jobsite
- Black molded polypropylene bottom with drain holes
- No. 5144H hooks sold separately
- Orange color
- Dimensions: 10"H x 7"W x 14"L

Klein Tools #	Description
5144BHB-I	14 Pockets



Estex #	Description
2651	10" x 3" x 19", 2 Pockets
2651-2	10" x 3" x 19", 3 Pockets w/Strap & Snap

**Compression Tool & Bolt Cutter Bag**

- Heavy vinyl-coated nylon
- Two Grommets for bucket attachment
- Extended back so tool handle doesn't extend too high above the lip of the bucket

**Aerial Vinyl Tool Apron**

- 10 hand tool pockets
- Two pouches
- Hammer loop and drill bit holders
- Designed to fit flat against liner
- Non conductive rod in the top for support
- Two brass grommets

Estex #	Description
1829-DP	23.8"L x 4"W x 21.25"H



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage



Buckingham #	Size
4500YM2	21-3/4"H x 4W" x 23-7/8"L

### Aerial Basket Tool Apron

- Sewn in stiffener
- 2-Pocket holster
- Hammer loop
- PVC cap bottom
- Two nut and bolt Bags
- Eleven socket pockets
- Two PVC pipe inserts for auger bit holders
- Magnetic strip that allows linemen to store loose hardware and easily access it when required

### Aerial Tool Apron with Inosil and Hard Body

- Inosil corrosion shield
- Hard body stiffener gives the apron the rigidity of a traditional board
- Non-conductive rod in the top for support
- Two brass grommets for hanging

Estex #	Description
1829-HB-7	23.9" x 4" x 21.25"



Buckingham #	Size
4500	18"L x 20"W, w/3 Pocket Holster
45004	18"L x 20"W, w/4 Pocket Holster



### Fiberglass Tool Apron

- 3 or 4 Pocket holster
- Wrench and hammer loops
- Canvas nut and bolt bag

### 24" Tool Bag

- Made from heavy vinyl coated nylon
- Water resistant
- Wooden bottom for extra protection
- 2" web handles
- Box "x" stitches on handles to help prevent tearing

Estex #	Size
2190-1LOSP	24"L x 10"W x 19"H



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage



Klein Tools #	Size
5181ORA	20"H x 10"W x 24"L

**Vinyl Equipment Bag**

- One exterior pocket
- Wide bag opening easily accommodates helmets and other equipment
- Durable, double-stitched plastic bottom
- Webbing extends down side of bag from handles and shoulder strap for extra support and durability
- Right-sized rain flap with Velcro fastening
- Adjustable, padded shoulder strap included
- Orange color

**Lineman's Backpack**

- Wide opening easily accommodates helmets, belts and other equipment
- Large front pocket for separate storage of gafts and rubber gloves
- Padded back area and adjustable padded shoulder straps with adjustable chest strap
- Durable; double-stitched plastic bottom with drain holes

Klein Tools #	Size
5185ORA	23"H x 18"W x 10"D



Estex #	Description
2114-12	12" x 7.5" x 12"
2114-16	16" x 9" x 12"
2114-18	18" x 9" x 12"
2114-22	22" x 10" x 14"
2114-24	24" x 10" x 14"

**Canvas Tool Bag**

- Steel frame keeps bag open and provides security when closed
- Two leather straps secure the opening
- 2" Web handles wrap around the entire bag for added strength
- Bottom is reinforced with heavy vinyl coated nylon and has a double tempered masonite board
- Six brass studs on bottom of the bag to protect against abrasion

**Canvas Tool Bag with Outside Pockets**

- Heavyweight #4 canvas duck
- Top opening has a steel frame
- Bottom is reinforced with heavy vinyl-coated nylon and has a masonite board
- Six brass studs on the bottom of the bag protect against abrasion

Estex #	Description
2100	16" x 9" x 12"
2160	22" x 10" x 14", 7 Inside Pocket



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage



Buckingham #	Description
41333R5SY	19"H x 11"W x 24"L

### Equipment Tool Bag

- Hard rubber bottom equipment bag with 2" molded rubber lip to prevent water seeping into the bottom of the bag
- Heavy gauge rubber bottom is double stitched to the bag and is very durable, even in cold weather

### Heavy-Weight, Vinyl Coated Nylon Tool Bag

- Top zipper opening
- Web handles wrap completely around the bag
- Hard board in the bottom
- Six brass studs on the bottom to prevent abrasion to the bag

Estex #	Description
2180	22" x 11" x 11"



Buckingham #	Color
42266	Tanned
42266-BL	Black
42266-BR	Dark Brown

### Double Back Holster

- Leather
- Five pockets
- 2-Way knife snap
- 10-3/4" x 8"

### Linemen's Holster

- Double backed design
- Russet leather pockets
- Five pockets with a knife snap, fits a screwdriver, a rule, a linemen/slip pliers and a wrench
- Two piece screw rivet set included

Bashlin #	Color
111HLDS	Tan



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Tool and Equipment Storage



Buckingham #	Description
4510	18"L x 9"W x 11"D

### Tool Tray

- Fiberglass storage tray
- May be hung on the inside or outside of an aerial basket
- Can be used to store cabling and other miscellaneous equipment
- Mounts using one pair of 5334 PVC hooks (included)

### Tool Tray

- Copolymer
- Outside mount
- Gray

PTI #	Description
1TB	19 x 8 x 8"



Hastings #	Description
05-929-1	6" x 8" x 20"

### Fiberglass Tool Tray

- Fits buckets with and without liners
- Attaches on outside of bucket
- Tray has five compartments with removable partitions



### Hydraulic Impact Wrench and Drill Holster

- Attaches to buckets with or without liners
- Holder can be mounted inside or outside
- Top bracket can be moved to either side to enable holder to be used right or left handed
- Includes Velcro hold-down strap to keep wrench in place

Hastings #	Description
05-831	Holster
05-832	Holster w/Storage for Drill Bits



Hastings #	Description
05-909-1	Chain Saw Scabbard, 3" x 5-3/4" x 36"
05-910-1	Chain Saw Scabbard, 3" x 5-3/4" x 36"

### Chain Saw Scabbard

- Designed for gasoline or hydraulic powered chain saws
- Mounts on bucket for quick and easy access
- Provides safe and convenient storage on bucket
- Prevents accidental damage to chain
- Non-conductive fiberglass
- Will accommodate saws with blades up to 36"
- Fits buckets with or without liners



Toll Free: 800-796-9027 Fax: 540-438-9502


[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage

### Fiberglass Bucket Step

- Anti-skid material to help prevent slippage
- 26"L x 8-1/2"W x 8"D

Hastings #	Description
05-961	For Buckets w/Liners
05-960	For Buckets w/o Liners



Klein #	Description
5144H	.3 lbs.

### Hooks for Aerial-Baskets

- All weather nylon polymer
- Accommodates most manufacturer's aerial basket trucks
- Includes single replacement hook for Cat. No. 5144 and Cat. No. 5169

### Polymer Hooks

- Injection molded for strength and resistance to cold weather
- Fits all standard buckets
- Also keeps liners from bouncing out

Estex #	Description
1831	Fits 2-3/4" Lip
1833-2	Fits 2" Lip
1833-3	Fits 3" Lip



1250



1250-1



Estex #	Description
1250	8" x 15.5" Canvas
1250-1	6" x 17" Leather

### Ditch Bank Blade Cover

- Sewn construction, rivet stress points
- Double cut bush hook guard
- Snap closure



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool and Equipment Storage

### Aerial Bucket Cover with Foam & Heat Sealed Seams

- 2" Foam block sandwiched between two layers of fabric in the top to repel water so the cover doesn't sag into the bucket
- Rope lanyard with snap is attached to the cover to secure it to the truck
- Heat-welded pocket allows the cover to be used inside-out if the outside cover is ripped
- Bungee cord sewn into hem for a snug fit

Estex #	Description
2715-24-24	24" x 24", One Man
2715-24-48	24" x 48", Two Man



Estex #	Description
2711	Fits 24" x 24" to 24" x 30", One Man
2712	Fits 24" x 48" to 26" x 52", Two Man
2713BC-24-24	Fits 24" x 24" One Man, Collapsible
2713BC-28-34	Fits 28" x 34" One Man, Collapsible
2713BC-24-48	Fits 24" x 48" Two Man, Collapsible
2713WC-24-24	Fits 24" x 24" One Man, Collapsible
2713WC-28-34	Fits 28" x 34", One Man, Collapsible
2713WC-24-48	Fits 24" x 48" Two Man, Collapsible



### Aerial Bucket Cover, Universal Fit and Collapsible

- Stretches to fit all buckets (2711, 2712)
- Rope lanyards with snap is attached to the cover to secure it to the truck
- Bungee cord sewn into hem for snug fit (2711, 2712, 2713BC)
- Web strap closure (2713WC)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools



Slingco #	Color	Conductor Dia	Lattice Length	Breaking Strength
ZCS1710	Dark Green	.25"- .50"	31"	7,000 lbs.
ZCS1711	Brown	.50"- .75"	45"	10,500 lbs.
ZCS1712	Light Blue	.75"-1.00"	43"	14,100 lbs.
ZCS1713	Gold	1.00"-1.25"	65"	25,000 lbs.
ZCS1714	Black	1.25"-1.50"	59"	31,000 lbs.
ZCS1715	Red	1.50"-1.75"	82"	31,000 lbs.
ZCS1716	Dark Blue	1.75"-2.25"	82"	49,000 lbs.
ZCS1750	Yellow	2.00"-2.50"	72"	49,000 lbs.
ZCS1751	Orange	2.50"-3.00"	72"	49,000 lbs.
ZCS1752	Aluminum	3.00"-3.50"	74"	49,000 lbs.
ZCS1753	Light Green	3.50"-4.00"	76"	49,000 lbs.

**MU Type, Multi-Weave Cable Grip**

- Triple weave construction ideal for heavy loads
- Color-coded for ease of identification
- Primarily for pulling overhead aluminum conductor

**Triple Weave-Single Eye-Shoulder Grip**

- Color-coded
- Flexible eye with shoulders and trip weave galvanized wire construction



DCD #	Color Code	Size Range	Approx. Mesh Length	Approx. Breaking Strength	Weight
00681-006	Dark Green	0.25" to 0.49"	28"	6,500 lb.	0.41 lb.
00681-012	Brown	0.50" to 0.74"	33"	10,400 lb.	0.79 lb.
00681-019	Light Blue	0.75" to 0.99"	41"	16,000 lb.	1.47 lb.
00681-025	Gold	1.00" to 1.24"	51"	25,400 lb.	3.46 lb.
00681-032	Black	1.25" to 1.49"	60"	31,700 lb.	4.11 lb.
00681-038	Red	1.50" to 1.99"	75"	32,000 lb.	4.81 lb.
00681-048	Yellow	2.00" to 2.49"	75"	44,600 lb.	8.12 lb.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Grips and Cable Pulling Tools

**A Type, High Strength Cable Grip**

- Can be used for aluminum conductor or for pulling rope
- Color-coded for ease of identification
- Strongest Slingco cable grip
- Feeder tubes are recommended when inserting cable or rope into "A" Type grips

Slingco #	Color	Conductor Dia	Rope Dia	Overall Length	Lattice Length	Breaking Strength	Feeder Tube
ZCS1799	Black	.25"- .40"	.25"- .65"	40"	28"	7,000 lbs.	FTU1890
ZCS1800	Dark Green	.40"- .63"	.50"- .90"	55"	41"	14,000 lbs.	FTU1891
ZCS1801	Red	.63"- .88"	.75"- 1.10"	74"	58"	20,000 lbs.	FTU1892
ZCS1802	Dark Blue	.88"- 1.13"	1.00"- 1.50"	87"	68"	30,700 lbs.	FTU1893
ZCS1803	Yellow	1.13"- 1.38"	1.25"- 1.70"	112"	90"	47,000 lbs.	FTU1894
ZCS1804	Aluminum	1.38"- 1.90"	1.50"- 2.10"	121"	96"	67,000 lbs.	FTU1895

Hubbell #	Cable Diameter Range	Approx Breaking Strength	E Length	M Length
33041082	.50"- .62"	4,500 lbs.	8"	21"
33041083	.63"- .74"	5,600 lbs.	8"	24"
33041084	.75"- .99"	6,800 lbs.	9"	24"
33041085	1.00"- 1.49"	9,600 lbs.	9"	24"
33041086	1.50"- 1.99"	16,400 lbs.	11"	24"
33041087	2.00"- 2.49"	18,500 lbs.	12"	24"
33041088	2.50"- 2.99"	24,500 lbs.	12"	24"
33041089	3.00"- 3.49"	24,500 lbs.	14"	24"
33041090	3.50"- 3.99"	31,000 lbs.	14"	26"

**Kellems Underground T-Type Pulling Grips**

- Flexible eye, double weave, galvanized steel
- Made of high strength galvanized steel strand
- Feature double weave mesh for positive holding power in medium to heavy pulling jobs
- Grip eye will easily attached to a swivel



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools

### Kellems Overhead DUA-PULL Pulling Grips

- Flexible eye, double weave mesh, galvanized steel
- DUA-PULL pulling grips are the highest strength pulling grips manufactured for overhead transmission line stringing applications
- Have a dual function, not provided by any other grip, of working with both bare and insulated conductors and synthetic rope



Hubbell #	Conductor Diameter	Rope Diameter	Approx Breaking Strength	E Length	M Length	Eye B Diameter	Over Cable & Grip	Color Code
33271037	.19"-.37"	.25"-.65"	6,500 lbs.	10"	24"	.220"	.200"	Black
33271038	.38"-.62"	.50"-.90"	14,000 lbs.	12"	36"	.375"	.280"	Dk Green
33271039	.63"-.87"	.75"-1.10"	20,000 lbs.	13"	48"	.437"	.360"	Red
33271040	.88"-1.12"	1.00"-1.50	30,600 lbs.	15"	60"	.500"	.500"	Dk Blue
33271041	1.13"-1.37"	1.25"-1.70"	46,800 lbs.	18"	76"	.625"	.625"	Yellow
33271042	1.38"-1.90"	1.50"-2.10"	66,500 lbs.	24"	89"	.750"	.750"	Aluminum

### R Type, Revolving Multi-Weaver Cable Grip

- Rotating eye cable grip with triple weave construction
- Color-coded for ease of identification
- Steel forged revolving head is ideal for connecting to swivels and shackles
- Primarily for pulling overhead aluminum conductor
- NOTE: Rotating eye does not swivel under load



Slingco #	Color	Conductor Dia	Revolving Eye Dia.	Lattice Length	Breaking Strength
ZCS2177	Dark Green	.25"-.50"	.875"	31"	7,000 lbs.
ZCS2178	Brown	.50"-.75"	1.00"	45"	10,500 lbs.
ZCS2179	Light Blue	.75"-1.00"	1.00"	43"	14,100 lb.
ZCS2180	Gold	1.00"-1.25"	1.625"	65"	25,000 lbs.
ZCS2181	Black	1.25"-1.50"	1.875"	59"	31,000 lbs.
ZCS2182	Red	1.50"-1.75"	1.875"	82"	31,000 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools

DCD #	Locking Part #	3:1 Safe Working Load	5:1 Safe Working Load	A	B	C	D	Weight
00505-015	00505-015A	3,500 lbs.	2,100 lbs.	1"	13/32"	3/8"	3-7/8"	.51 lb.
00505-020	00505-020A	5,000 lbs.	3,000 lbs.	1-1/4"	17/32"	13/32"	4-3/4"	1 lb.
00505-025	00505-025A	7,000 lbs.	4,200 lbs.	1-3/8"	9/16"	1/2"	5-1/8"	1.4 lb.
00505-027	00505-027A	9,000 lbs.	5,400 lbs.	1-1/2"	19/32"	1/2"	5-5/8"	1.8 lb.
00505-030	00505-030A	10,000 lbs.	6,000 lbs.	1-5/8"	11/16"	5/8"	6"	2.1 lb.

## Line Swivels

- Constructed with a thrust bearing for tensile load and a radial bearing for bending load
- Sizes 00505-020 and larger are supplied with a grease point for lubrication
- High safe working load and compact design



DCD

## 808 Champion Swivels

- Designed for underground and overhead cable pulling applications
- Machined from high-strength stainless steel
- Capable of handling all types of utility cables



Condux #	3:1 Safe Working Load	5:1 Safe Working Load	A	B	C	D	E	F	G
08017000	600 lbs.	360 lbs.	5/8"	.28"	3.56"	.79"	.25"	.37"	.295"
08016000	2,500 lbs.	1,500 lbs.	7/8"	.38"	4.51"	1.06"	.31"	.53"	.375"
08016000H	2,500 lbs.	1,500 lbs.	7/8"	.38"	4.51"	1.06"	.31"	.53"	.375"
08080912	5,000 lbs.	3,000 lbs.	1-1/4"	.56"	5.44"	1.34"	.37"	.59"	.565"
08080912H	5,000 lbs.	3,000 lbs.	1-1/4"	.56"	5.44"	1.34"	.37"	.59"	.565"
08080913	7,000 lbs.	4,200 lbs.	1-3/8"	.56"	5.25"	1.31"	.44"	.56"	.530"
08080913H	7,000 lbs.	4,200 lbs.	1-3/8"	.56"	5.25"	1.31"	.44"	.56"	.530"
08080916	10,000 lbs.	6,000 lbs.	1-5/8"	.63"	6.51"	1.59"	.56"	.78"	.530"
08080916H	10,000 lbs.	6,000 lbs.	1-5/8"	.63"	6.51"	1.59"	.56"	.78"	.530"
08080920	15,000 lb.	9,000 lb.	2"	.75"	6.99"	1.78"	.62"	.72"	.750"
08080920H	15,000 lb.	9,000 lb.	2"	.75"	6.99"	1.78"	.62"	.72"	.750"
08080925	25,000 lb.	15,000 lb.	2-1/2"	1"	10.23"	2.80"	.87"	1.23"	1.135"
08080925H	25,000 lb.	15,000 lb.	2-1/2"	1"	10.23"	2.80"	.87"	1.23"	1.135"
08080930	30,000 lb.	18,000 lb.	3"	1.31"	12.04"	3.56"	1.12"	1.37"	1.630"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Grips and Cable Pulling Tools

**821 Champion Swivels**

- Designed for underground and overhead cable pulling applications
- Capable of handling all types of utility cable
- Machined from stainless steel



Condux #	3:1 Safe Working Load	5:1 Safe Working Load	A	B	C	D	E	F	G
08210007	1,800 lbs.	1,080 lbs.	7/8"	.31"	3.09"	.84"	.31"	.38"	.305"
08210012	4,000 lbs.	2,400 lbs.	1-1/4"	.59"	4.52"	1.22"	.38"	.44"	.410"
08210014	7,500 lbs.	4,500 lbs.	1-7/16"	.59"	5.13"	1.41"	.44"	.59"	.600"
08210018	10,000 lbs.	6,000 lbs.	1-7/8"	.75"	7.06"	1.88"	.63"	.81"	.755"

**Stainless Steel Line Pulling Swivel**

- For underground and overhead pulling applications
- High grade stainless steel construction
- Designed to allow easy passage through sheaves

**Rope-to-Swivel Connector**

- Connectors connect the cable pulling rope, up to 1" in diameter, to the pulling swivel
- Makes connecting the pulling rope and the pulling swivel easier
- Connectors feature a removable sheave for rope eye
- Capacity:
  - ☐ 10,000 lbs. maximum rated in conduit
  - ☐ 6,000 lbs. maximum rated overhead

Greenlee #	Description
39902	Rope-to-Swivel Connector



Slingco #	Underground Load	Overhead Load
ZSW2091	2,250 lbs.	1,350 lbs.
ZSW2092	3,500 lbs.	2,100 lbs.
ZSW2093	5,000 lbs.	3,000 lbs.
ZSW2094	7,000 lbs.	4,200 lbs.
ZSW2096	10,000 lbs.	6,000 lbs.
ZSW2097	15,000 lbs.	9,000 lbs.

Lewis #	Overall Length	Pin Diameter	Jaw Opening	Overall Diameter	Working Load	Approx. Breaking Strength
HD-00	4-1/8"	5/16"	3/8"	7/8"	1,500 lbs.	4,500 lbs.
HD-0	5-1/4"	7/16"	1/2"	1-1/8"	5,400 lbs.	16,200 lbs.
HD-1	6"	1/2"	5/8"	1-7/16"	9,000 lbs.	27,000 lbs.
HD-2	7-1/8"	5/8"	5/8"	1-5/8"	12,000 lbs.	36,000 lbs.
HD-3	8-5/8"	3/4"	3/4"	2"	21,000 lbs.	63,000 lbs.
HD-4	10"	7/8"	7/8"	2-3/8"	30,000 lbs.	90,000 lbs.

**Heavy-Duty Ball Bearing Swivels**

- Designed for tension stringing and insuring conductor remains in a neutral position
- Manufactured from high-grade pre-stressed steel
- Pins are screwdriver removable



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Grips and Cable Pulling Tools



**7/16" Cobra Rod  
3/8"-16 End Fitting  
45" Cage**

Condux #	Length	Replacement Rod No.
08083820	200'	08086320
08083830	300'	08086330
08083840	400'	08086340
08083850	500'	08086350
08083860	600'	08086360
08083870	700'	08086370
08083880	800'	08086380
08083890	900'	08086390
08083810	1000'	08086310
08083811	1100'	08086311
08083812	1200'	08086312
08083813	1300'	08086313
08083814	1400'	08086314
08083815	1500'	08086315

**3/16" Mini-Cobra Rod  
#12-24 End Fitting  
16" Cable**

Condux #	Length	Replacement Rod No.
08072405	50'	08073605
08072410	100'	08073610
08072415	150'	08073615
08072420	200'	08073620
08072425	250'	08073625
08072430	300'	08073630

**5/16" Python Rod  
3/8"-16 End Fitting  
30" Cage**

Condux #	Length	Replacement Rod No.
08084320	200'	08082320
08084330	300'	08082330
08084340	400'	08082340
08084350	500'	08082350
08084360	600'	08082360
08084370	700'	08082370
08084380	800'	08082380
08084390	900'	08082390
08084310	1000'	08082310

**9/16" Python Rod  
3/4"-10 End Fitting  
45" Cage**

Condux #	Length	Replacement Rod No.
08083220	200'	08075720
08083230	300'	08075730
08083240	400'	08075740
08083250	500'	08075750
08083260	600'	08075760
08083270	700'	08075770
08083280	800'	08075780
08083290	900'	08075790
08083210	1000'	08075710



**Toll Free: 800-796-9027 Fax: 540-438-9502**

**www.specialfleettools.com**

## Grips and Cable Pulling Tools



**1/4" Mini-Cobra Rod  
5/16"-18 End Fitting  
24" Cage**

Condux #	Length	Replacement Rod No.
08072510	100'	08073710
08072515	150'	08073715
08072520	200'	08073720
08072525	250'	08073725
08072530	300'	08073730
08072535	350'	08073735
08072540	400'	08073740
08072545	450'	08073745
08072550	500'	08073750
08072555	550'	08073755
08072560	600'	08073760



**5/16" Cobra Rod  
3/8"-16 End Fitting  
30" Cage**

Condux #	Length	Replacement Rod No.
08083720	200'	08079120
08083730	300'	08079130
08083740	400'	08079140
08083750	500'	08079150
08083760	600'	08079160
08083770	700'	08079170
08083780	800'	08079180
08083790	900'	08079190
08083710	1000'	08079110



**7/16" Python Rod  
3/8"-16 End Fitting  
45" Cage**

Condux #	Length	Replacement Rod No.
08083920	200'	08086520
08083930	300'	08086530
08083940	400'	08086540
08083950	500'	08086550
08083960	600'	08086560
08083970	700'	08086570
08083980	800'	08086580
08083990	900'	08086590
08083910	1000'	08086510
08083911	1100'	08086511
08083912	1200'	08086512
08083913	1300'	08086513
08083914	1400'	08086514
08083915	1500'	08086515



**Toll Free: 800-796-9027 Fax: 540-438-9502**

**www.specialfleettools.com**

## Grips and Cable Pulling Tools

**Jameson Buddy System**

Fiberglass core is coated with high visibility polymer sheath to protect against rod abrasion and reduce friction. Round, flexible rod slides easily over wires in occupied conduit.

Exceptional bending strength for maneuvering tight turns.

Non-conductive and will not kink.



Jameson #	Description
12-516-300M	300' x 5/16"
12-516-400M	400' x 5/16"
13-716-500M	500' x 7/16"
13-716-600M	600' x 7/16"

**Duct Hunter Detectable Rodder**

- Duct Hunter incorporates a copper trace wire in the rod to meet your locating and tracing requirements on the job
- Trace or map underground conduit or pipe without digging or trenching
- Accessory kit included (12-516-AK or 136-716-AK)

**Easy Buddy Fiberglass Conduit Rodder**

- Designed to handle tight turns and long runs, makes it ideal for 1"-2" conduit
- More flexible and smaller than Good Buddy
- 4" Bend radius; 400-lb. pull/tensile strength
- Drag brake to control payout
- Rod is marked in 5' increments
- Includes end ferrule and pulling eye
- Accessory Kit included (9-25-AK)

Jameson #	Description
6-14-300M	300' x 1/4"
6-14-500M	500' x 1/4"

**Good Buddy Fiberglass Conduit Rodder**

- Unit fold to 10" width for carrying into manholes
- Reel can be detached from frame
- Frame handle for easy transport
- Friction brake and safety roller feed
- Operates vertically or horizontally
- Accessory Kit included (9-25-AK)

Jameson #	Description
9-25-300M	300' x 3/8"
9-25-400M	400' x 3/4"

**Compact Puller**

- Capstan puller for installation of service drops
- 50 lb. pulling capacity
- Reduces risk of installer injury by eliminating hand pulling
- Light weight-less than 40 lbs.
- Portable and wheeled for easy construction-site use
- On board power from a gasoline-powered drill (sold separately)
- Spuds for adapting to various conduit sizes included

Sherman + Reilly #	Description
CP-50	Compact Safety Puller



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools



Greenlee #	Description
6900	UT10-2S Package with Floor Mount
6906	UT10-2S Package with Mobile VersiBoom II
UT10-2S	Puller Assembly

### Ultra Tugger 10 Cable Puller 10,000 lb. Rated

- 2-Speed gear-motor enables 20% faster pulling time
- Shift from high-speed/low-load pulling to low-speed/high-load pulling with a simple double-tap motion on the foot-pedal
- Available with Mobile VersiBoom for less than 2-minute, one person set-up, and 20' tall
- Available with floor mount and chain mount for tighter spaces
- Customized gear motor specifically for heavy-duty cable pulling application and meet UL & cUL safety requirement
- Pulling force: maximum: 10,000 lbs., continuous: 6,500 lbs.

### Ultra Tugger 8 Cable Puller 8,000 lb. Rated

- VersiBoom system provides fast set-up with no anchors to set or chains to mount
- Boom uses 3" rigid steel conduit for easy length adjustment to pull 10' to 20' of cable out of the box fast and easy
- Direct gear drive
- Easy to move around jobsite with mobile carriage

Greenlee #	Description
6800	Cable Puller with Standard Force Gauge & Floor Mount



Greenlee #	Description
6503	Cable Puller Basic Package

### Ultra Tugger 5 Cable Puller, 5,000 lb. Rated

- Pull speed range of 9 to 14 fpm will complete most 500' pulls in one hour or less
- VersiBoom system provides fast setup with no anchors to set or chains to mount
- Boom uses 3" rigid steel conduit for easy length adjustment to pull 10' to 20' of cable out of the box fast and easy
- Cable puller basic package includes:
  - ☐ Standard force gauge
  - ☐ Wheeled carriage
  - ☐ 4' Boom
  - ☐ Boom mount and nose unit
  - ☐ 2-1/2", 3" & 4" Slip-in couplings
  - ☐ 2-1/2", 3" & 4" Screw-on couplings

### Conduit Measuring Tape

- Fish and measure conduit runs in one operation
- Permanently printed measurements every foot from zero to 3,000'
- Made of strong waterproof polyester
- Pay-out dispenser has anti-skid pads, handle and built-in cutter
- Tensile strength: 170 lbs. average breaking strength

Greenlee #	Size
435	3/16" x 3,000'



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Grips and Cable Pulling Tools



Greenlee #	Length	Weight
430	6,500' Green Tracer	11 lbs.
431	5,200' Yellow Tracer	12 lbs.

### Poly Line

- Ready-to-use, pre-punched hole in lid with resealable cap
- Use with power fishing systems directly from the container
- Resists tangling when dispensing
- Rot and mildew resistant
- Handy reusable plastic dispenser pail with handle keeps the line dry
- Use to pull rope through conduit
- Tensile strength: 210 lbs. average breaking strength
- Green color
- Thickness: 1 ply
- Type: twine, spiral wrap, tracer

### ED Junior Digital Dynamometer with 2 Anchor Shackles

- Selectable in lb, kg and newtons
- 7:1 Factor of safety at all capacities
- Accuracy: 0.2% of capacity
- Aircraft quality 500% 2024 aluminum construction
- NEMA 4 Enclosure
- 128 x 64 graphic LCD display shows all digits 1.0" high
- Display update rate: 2 times per second
- Calibration: traceable to the NIST
- Powered by two C batteries
- Battery life: 320 hours typical use
- Batteries, manual and calibration card included



**DILLON**

Dillon #	lbf	Kgf	N
36190-0046	5,000	2,000	20,000
36190-0053	10,000	5,000	50,000



**DILLON**

Dillon #	Dial Size	Capacity x Div Size
30006-0050	5"	5,000 Lbf x 50
30006-0084	5"	10,000 Lbf x 100
30006-0100	5"	20,000 Lbf x 200
30007-0109	10"	20,000 Lbf x 100
30784-0033	10"	50,000 Lbf x 200

### AP Mechanical Dynamometer

- Pound capacities
- Accuracy:  $\pm 0.5$  of capacity
- Temperature range:  $-50^{\circ}\text{F}$  to  $150^{\circ}\text{F}$
- Non-corrosive construction:
  - ☐ Pressure bar-powder coated high grade alloy steel
  - ☐ Shackles-electroless nickel-plated A4140 forged steel
  - ☐ Shackle pins: electroless nickel-plated E4340 steel
- 5" Model have high strength composite plastic case enclosure
- 10" models have cast aluminum enclosure
- Calibration: traceable to NIST
- User's guide and calibration card included
- CE approval

### Clipping Hook

- 6,500 lb. safe working load
- Each unit is tagged showing the safe working load, proof test date, and an identifying serial number



### Sagometer

- Accurate thermometer encased in a section of aluminum conductor
- Helps determine the actual temperature of the conductor being sagged
- Range is  $-40^{\circ}$  to  $160^{\circ}\text{F}$



### Sagwatch

- Used to accurately determine sag simply and rapidly
- Water and shock resistant
- Antimagnetic, housed in a stainless steel case



SFS #	Description
S22-771	Clipping Hook

SFS #	Description
CT40-160	Sagometer

SFS #	Description
SW-E	Sagwatch



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools

**Bulldog-Type Jaw Standard Wire Grip**

- Spring loaded

Little Mule #	Description
LMG2000	2,000 lb., 8 to 4/0 AWG



Little Mule #	Description
LMG4500	5,000 lb., 6 to 4/0 AWG
LMG4500A	5,000 lb., 6 to 4/0 AWG
LMG4600	10,000 lb., 1 AWG to 450 MCM
LMG4700	20,000 lb., .397 to 1130 MCM
LMG4800	12,000 lb., .397 to 1130 MCM
LMG4900	20,000 lb., 1033 to 2500 MCM

**Parallel Jaw Standard Wire Grip**

- Spring loaded
- "A" Suffix indicates aggressive teeth for extra high strength cable

**Parallel Jaw Hot Line Wire Grip**

- Spring loaded
- Notched handle
- "A" Suffix indicates aggressive teeth or extra high strength cable

Little Mule #	Description
LMG4501	5,000 lb., 6 to 4/0 AWG
LMG4501A	5,000 lb., 6 to 4/0 AWG



Little Mule #	Description
LMG4502	5,000 lb., 6 to 4/0 AWG
LMG4702	20,000 lb., .397 to 1130 MCM
LMG4802	12,000 lb., .397 to 1130 MCM

**Parallel Jaw Hot Line Wire Grip Less Spring and Notch**

- No spring or notch

Little Mule wire grips open easily and release instantly to quickly insert or remove wire, have large handle eye openings and are forged steel construction with yellow chromate finish.

Klein Tools offers a large number of grips, please contact us with the specifications of the job so we can happily help you select the necessary items for your needs!

**Parallel Jaw Grip**

- Round jaw
- Large eyelet opening in the handle to accommodate a wide variety of hooks on hoists, winches and tackle blocks

Klein Tools #	Cable Range	Max Load	Jaw Length	Weight
KT4500	.180"- .600"	5,000 lbs	4"	3.75 lbs.
KT4800	.70"-1.25"	12,000 lbs	5-1/8"	9 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools


### Parallel Jaw Grips

- Lightweight, compact grips pull an exceptionally wide range of cable types and sizes
- Designed with a round inside jaw contour for maximum contact to minimize cable deformation
- Lower jaw is serrated to firmly grip insulated cables and conductors
- Design includes a latch that prevents the grip from falling in case of jaw disengagement from the cable
- Large diameter eye accommodates large hooks on hoists, winches and tackle blocks
- 2-1/2" Jaw length (1685-20)
- 4-1/2" Jaw length (1685-31)

1685-31


**KLEIN TOOLS**


1685-20



Klein Tools #	Cable Range	Max Load
1685-20	.157"-.875"	4,500 lbs.
1685-31	.625"-1.250"	7,500 lbs.

**KLEIN TOOLS**



Klein Tools #	Cable Range	Max Load
1656-20	.20"-.40"	4,500 lbs.
1656-30	.31"-.53"	4,500 lbs.
1656-40	.53"-.74"	8,000 lbs.
1656-50	.74"-.86"	8,000 lbs.

### Bare ACSR, Aluminum & Stranded Copper Cable Chicago Grip

- Round, smooth inside jaw contour
- Smooth jaws grip with maximum contact and are less likely to damage conductors
- 4" Jaw length (1656-20)
- 4-3/4" Jaw length (1656-30)
- 5-1/2" Jaw length (1656-40 & 1656-50)

### Extra High Strength Chicago Curved-Jaw Grip

- Double V grooves provide four-point contact, reducing chance of slipping and providing proper alignment of wire and cable
- 5" Jaw length

Klein Tools #	Cable Range	Max Load
1684-74	.218"-.550"	8,000 lbs.

**KLEIN TOOLS**


**KLEIN TOOLS**



Klein Tools #	Cable Range	Max Load
1684-5F	.16"-.550"	8,000 lbs.

### Aircraft Cable, Extra High Strength, Messenger & Guy Strand Chicago Grip with Replacement File

- Double V grooves provide four-point contact, reducing chance of slipping and providing proper alignment of wire and cable
- 5" Jaw length

### Weatherproof Stranded & Solid Chicago Grip

- Round inside jaw contour for weatherproof coated wire
- Notches in jaw provide firm grip on insulation
- 4-3/4" Jaw length

Klein Tools #	Cable Range	Max Loads
1611-30	.31"-.53"	4,500 lbs.


**KLEIN TOOLS**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Grips and Cable Pulling Tools



Klein Tools #	Cable Range	Max Load
1613-40	.12"-.37"	4,500 lbs.
1684-5	.218"-.550"	8,000 lbs.
1628-17	.50"-.75"	15,000 lbs.
1628-18	.75"-1.00"	15,000 lbs.

**Aircraft Cable, Extra High Strength, Messenger & Guy Strand Chicago Grip**

- Double V grooves provide four-point contact, reducing chance of slipping and providing proper alignment of wire and cable
- 4-3/16" Jaw length (1613-40)
- 5" Jaw length (1684-5)
- 7-1/4" Jaw length (1628-17 & 1628-18)

**Bare Wire Chicago Grip**

- Designed for working with solid and stranded bare wire
- Lightweight, especially economical grip
- Single V groove jaw
- 3" Jaw length

Klein Tools #	Cable Range	Max Load
1613-30	.08"-.20"	1,500 lbs.



Klein Tools #	Cable Range	Max Load
1625-20	.28"-.75"	8,000 lbs.
1625-20-1	.50"-1.00"	8,000 lbs.

**Wire Rope Haven's Grip**

- Designed for use when light, compact grip is desired and where cable deformation is not a factor
- Gripping pressure of the knurled jaw is applied to 1/4" cable area
- Switch latch to help hold cable in the jaw

**Haven's Grip**

- Designed for use when light, compact grip is desired and where cable deformation is not a factor
- Gripping pressure of the knurled jaw is applied to 1/4" cable area
- Swing latch to help hold cable in the jaw (1604-20L)

Klein Tools #	Cable Range	Max Load
1604-10	.06"-.25"	2,500 lbs.
1604-20	.125"-.50"	5,000 lbs.
1604-20L	.125"-.50"	5,000 lbs.



Klein Tools #	Cable Range	Max Load
KT4650	16"-.90"	5,000 lbs.

**Wide Range Distribution Grip**

- Large jaw opening accommodates a large range of cables, reducing the number of grips needed
- Combination of a "V" groove jaw and a round jaw allows for a wide range of cables while minimizing cable deformation
- Large handle opening accommodates a wide variety of hooks on hoists, winches, and tackle blocks
- 4-1/2" Jaw length



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Grips and Cable Pulling Tools



Utility Tool #	Description
36000	4x4 Cable Stripper

**4x4 Plus Cable End Stripper**

- For 600V secondary cable
- Cutting heads for #6 AWG to 500 MCM conductors (concentric, compressed or compacted)
- Strips 45 mil to 110 mil secondary insulations
- Strips quickly, even in cold climates
- Guarded cutting blades ensure safety
- Precision stripping with no conductor damage
- Bushings change easily with hex wrench

**2750/2850 600V Secondary Insulation Stripper**

- Designed to end-strip 600V cable (45 mil to 110 mil thickness)
- Cable OD: .31"-1.375" (2750)
- Cable OD: .31"-1.188" (2850)
- No bushing required

Speed Systems #	Description
2750	End Stripper
2850	Mid-Span and End Stripper
2781	Replacement Blade 2750
2787	Replacement Blade 2850




Speed Systems #	Description
1542-2CL	Wedge Blade Installed, Spare Straight Blade
1542-2CL-1	Wedge Blade Installed, Spare Wedge Blade
1542-2CL-2	Straight Blade Installed, Spare Straight Blade

**1542-2CL Series Insulation Stripper**

- Cable OD range: 1/2"-1-3/4"
- Adjustable
- Designed to remove PE, XLR, EPR and other types of insulation from medium voltage power cable
- No bushings required

**1542-2AS Series Insulation Stripper**

- Cable OD range: 1/2"-1-3/4"
- Adjustable
- Designed to strip insulation from power cable and score the semi-conductive outer shield with precise accuracy
- Combines features of 1542-2CL stripper and 1700 scorer
- No bushings required

Speedy Systems #	Description
1542-2AS	Wedge Blade Installed, Spare Wedge Blade
1542-2AS-1	Wedge Blade Installed, Spare Wedge Blade
1542-2AS-2	Straight Blade Installed, Spare Straight Blade




Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools



Utility Tool #	Description
37415	WS-5A for .260" to 1.265" Cable OD

**Adjustable Primary URD End Stripper**

- For 600V to 35kV cables
- Strips XLPE, polyethylene and EPR insulation
- Precise stripping of insulation only or insulation and semicon simultaneously
- New adjustable strip stop with rotary mechanism
- New adjustment window allows easy setting of stop
- Guarded cutting blade prevents injury
- Accepts SW 2 ratchet wrench for leverage
- Bushing insert fits over cable and presets cutting blade depth
- (See Bushing Selection Table for additional options)

**2900 Aerial Tree Wire and Spacer Cable Mid-Span Stripper**

- Cable OD 0.40"-1.66"
- Model 2900 Aerial Tree Wire and Spacer Cable Stripper performs both end and mid-span strips on 5kV through 35kV aerial tree wire and spacer cables

Speed Systems #	Description
2900	Stripper with Standard Handles
2872	Replacement Blade




Utility Tool #	Description
12918	For .960" to 1.9" Cable OD

**Cable End Stripper**

- For 15kV to 46kV cables
- Strips XLPE, polyethylene and EPR insulation
- Precision stripping with no conductor damage
- Guarded cutting blade prevents injury
- Rotating stop bar permits accurate preset stripping lengths of up to 2-7/16"
- WA 3 Adapter included, allows strip lengths up to 5-1/2" and also use of the SW 2 ratchet wrench
- Bushing insert fits over cable and presets cutting blade depth

**SNAP Power Driven End Stripper**

- Bushing quick disconnect feature eliminating the need for a hex wrench
- Ergonomic end stripping tool for 600V secondary cable
- Designed to reduce working time and effort on repetitive stripping functions
- Adjustable strip stop with adjustment window allows easy setup for precise strip lengths 0.625" to 2.5"
- Uses standard 2 x 2 and 4 x 4 bushings, from #6 AWG to 500 MCM (concentric, compressed or compacted)
- Strips quickly, even in cold climates
- Precision stripping with no conductor damage
- Guarded cutting blades ensure safety

Utility Tool #	Description
WS68SNAP	Power Driven End Stripper with 3/8" Drill Adapter




Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Grips and Cable Pulling Tools

**Universal Adjustable Cable Stripper**

- End stripping and mid-span stripping with different blades (interchangeable)
- Dual position jaw is versatile for electric utility applications
- Removes outer jacket on primary power cable
- Adjusts to cable size with spring loaded trigger-action jaw
- Micro-adjustable blade allows accurate setup for a variety of insulation thickness
- Self-feeding tool design
- Compact design for tighter work spaces
- Rugged, all metal body

Utility Tool #	Description
WS64UE	End Stripping Only, Outer Jackets up to 2.5" OD & Insulations to 1.5" OD

**Insulation Stripper Accessories**

- Replacement blades and tool stops

Speed Systems #	Description
1562	Replacement Wedge Blade
1678	Replacement Scoring Blade
MARKII	Tool Stop
MARKI	Tool Stop
1650X	Tool Stop (1542 Series Tools)
1581	Replacement Straight Blade
2672	Replacement Chamfering Blade

**1800 Series Semi-Con Scorer (Scriber)**

- Cable OD: 1-3/4"-3"
- Adjustable blade length
- For scoring (scribing) the semi-conductive shield of medium voltage cable to remove without nicking or damaging the cable insulation
- Square and spiral cut
- Coil springs

Speed Systems #	Description
1800	Adj Blade Scorer
1800-SS	Adj Blade Scorer w/Dial Locking Set Screw
1800-LC	Adj Blade Scorer w/Saddle Relief



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools

**1700 Series Semi-Con Scorer (Scriber)**

- Cable OD: 1/2"-2"
- Adjustable blade length
- For scoring (scribing) the semi-conductive shield of medium voltage cable to remove without nicking or damaging the cable insulation
- Square and spiral cut
- Leaf springs

Speed Systems #	Description
1700	Adj Blade Scorer
1700-SS	Adj Blade Scorer w/Dial Locking Set Screw
1700-LC	Adj Blade Scorer w/Saddle Relief
1700-SS-LC	Adj Blade Scorer w/Dial Locking Set Screw & Saddle Relief

**Banana Peeler Adjustable Blade Semi-Con Scoring Tool**

- Scoring depth from 1 to 90 mils
- For strippable semi-con URD cable shield
- One hand scoring of circumference and length
- Spring-loaded blade assembly assures consistent scoring depth
- Teflon coated cable guide
- Semi-con is cleanly removed with no damage to underlying insulation
- Convertible to a fixed setting

UtilityTool™



Utility Tool #	Description
BP-1A	For .75" to 1.10" Cable OD
BP-2A	For 1.25" to 1.75" Cable OD
34230	Replacement Blade for BP 1A

**Insulation Chamfer Tool**

- Chamfers 15kV to 35kV cable
- Creates a 45° bevel, approximately .125" long
- For XLPE insulations
- Perfect for premolded splices, elbows and terminators
- Complete operation takes 10 seconds or less
- Adjusts easily to fit different cable insulations
- Blades are recessed to prevent injury and blade damage

Utility Tool #	Description
IC1	For .650" to 1.260" Cable OD

UtilityTool™



Speed Systems #	Description
CT-1	Chamfering Tool for 1/2"-1-3/8" Cables
CT-2	Chamfering Tool for 1-1/4"-2-3/4" Cables
2672	Replacement Blade

**CT-1/CT-2 Chamfering Tool**

- Chamfering tools cut a 45° bevel on the cable insulation to ease installation of premolded rubber components



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Grips and Cable Pulling Tools

### TAT/SAT Combination

#### Splice/T-Body Tool

- Combines features of the SAT Splice Assembly Tool and the 800TAT T-Body/Cable Adapter Tool
- Clamp fits 15kV through 35kV components (0.75"-2.625")
- Splice gripping arms open 1-1/2"-3-3/8" (splice sleeve OD range)
- 15" Stroke (two revolutions of drive per inch of stroke)
- Includes carrying bag

Speed Systems #	Description
TAT/SAT	Combination Splice/T-Body Tool



Speed Systems #	Description
SC-13	Semi-Con Roller Grip

#### Semi-Con Roller Grip

- For controlled rolling of the semi-con layer after it is scored
- Broad nose
- Serrated jaws for maximum grip
- Rugged plastic covered handles

Speed Systems #	Description
BIT-TK120X-Q	Fits All Loadbreak Bushing Inserts (130 in-lb. Torque Limiter)
BIT-TK120X-N	Fits All Dead Break Bushing Inserts (130 in-lb. Torque Limited)
FIT-TK120X-X	Feed Thru Loadbreak Insert Tool (120 in-lb. Torque Limiter)



### 200A Clamp-On Bushing Installation Tool

- For installation and removal of bushing inserts
- Preset torque limiter takes guess work out of bushing installation
- Can be used for bushing removal

### 15/25kV Probe Installation Tools

- Provide a means of preventing probe arc follower contamination and other damage when installing 15kV, 25kV and Elastimold 35kV probes
- 120 in-lb. Torque Limiter



Speed Systems #	Description
LPW1525/TK120X-N	Loadbreak Probe Wrench w/Neutral Winder
LPW1525/TK120X	Loadbreak Probe Wrench
LPW1525	Probe Wrench for Use w/1/4" Square Drive
TK120	Torque Limiter w/1/4" Square Drive



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grips and Cable Pulling Tools



Speed Systems #	Description
BIT/E180AT	T-Handle
BIT/E180AH	Operating Eye

**200A Loadbreak Bushing Installation Tools**

- 180 in-lb preset torque limiter
- For installation and removal of bushing inserts with a 5/16" internal hex socket

**600A LRTP Torquing Installation Tool**

- Bushing insert tool
- Preset torque for installation and removal of 600A load reducing tap plug bushings with 5/16" and/or 3/8" internal hex socket

Speed Systems #	Description
LRTP/TK55	55 ft-lb. Torque Limiter



Speed Systems #	Description
LPW/35R/TK120X-N	Loadbreak Probe Wrench w/Neutral Winder
LPW/35R/TK120X	Loadbreak Probe Wrench

**35kV Probe Installation Tool**

- Provide a means of preventing probe arc follower contamination and other damage when installing 35kV Cooper and Hubbell (Chardon) large interface probes
- 120 in-lb. Torque limiter

**Load Break Bushing Insertion Tool**

- For 200A bushing inserts with internal hexagon socket drive
- Secures bushing insert for positive installation and removal
- Multiple drive systems:
  - ☐ Adjustable "T" handle
  - ☐ 1" Square socket drive
  - ☐ 7/8" Hexagon for wrench
  - ☐ Standard "Penta" Head

Utility Tool #	Description
LBIT-1T	Preset Torque Setting of 180 in-lb.



Utility Tool #	Description
PIT-1T	125 in-lb. Torque

**Load Break Elbow Probe Insertion Tool**

- For 15kV to 35kV elbow-small interface
- Quick and easy insertion of the probe inside the elbow
- Prevents load break probe contamination
- Prevents load break probe breakage
- Reduces cross threading
- Provides the proper tightening forces as recommended by the elbow manufacturers
- Multiple torque delivery system
- Adjustable and removable "T" handle
- 7/8" Steel drive and wrench
- 3/8" Square drive socket
- Load break probe removed by simply reversing the tightening action



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Grips and Cable Pulling Tools

### Semi-Con Edge Wedge

- Designed for lifting the front edge of the semi-con layer after it is scored
- Leather sheath included
- SC-11 has an ergonomic safety grip and stainless steel blade

Speed Systems #	Description
SC-10	Edge Wedge w/Leather Sheath
SC-11	Edge Wedge w/Finger Grip & Leather Sheath



SC-11



SC-10



Klein Tools #	Description
25450	Brush Set



### Grip-Cleaning Brush Set

- Set of four wire-bristle brushes designed for cleaning Klein wire and cable-pulling grips
- Brushes have stiff wire bristles
- Available in round and square shapes and two lengths for efficient cleaning of different jaw configurations
- Semi-flexible steel shafts set into comfortable wooden handles provide the necessary reach into grips jaws
- Includes:
  - ☐ Round bristle 3/8" x 3", 12" long
  - ☐ Square bristle 3/8" x 3", 12" long
  - ☐ Round bristle 1-9/16" x 5", 14" long
  - ☐ Square bristle 1-9/16" x 5", 14" long



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hoists

**Lineman's Strap Hoist**

- Hot stick-type gate latch on all hooks
- Hot stick rings on all hooks, control surfaces, and quick disconnect shaft
- Rated load capacities of 1,000 and 1,500 lbs. single line; 2,000 and 3,000 lbs. double line
- Overload protection bending handle
- 360° Swiveling hooks equipped with latches for positive load engagement
- Positive load holding with double interlocking pawl mechanism
- Cast aluminum and zinc alloy housings
- All stainless steel springs and shafts
- All rotating shafts mounted on bronze bushings
- Meets or exceeds minimum 4:1 design factor and all requirements of ASME/ANSI standard B-30.21

Little Mule #	Description
300A	1-1/2 Ton, 10' Strap Length, 20" Handle Length, Standard Hooks w/Safety Latches
300DA	1 1/2 Ton, 10' Strap Length, 20" Handle Length, Hot Stick Ring Hooks w/Safety Latch



**LITTLE MULE®**



**LITTLE MULE®**

Little Mule #	Description
344B	2 Ton Strap Hoist, 11' and 5-1/2' Lift
344DB	2 Ton Strap Hoist with Hot Stick Rings, 11' and 5-1/2' Lift

**Series 322B and 344B Lineman's Lever Hoist**

- Hot stick-type gate latch on all hooks
- Hot stick rings on all hooks and control surfaces
- Rated load capacities of 1,500 and 2,000 lbs. single line; 3,000 and 4,000 lbs. double line
- Overload protection bending handle
- Enhanced reversing mechanism with double interlocking pawls
- 360° swiveling hooks equipped with latches for positive load engagement
- Compact aluminum alloy frame with double flanged strap drum and interrogated hook point
- All stainless steel springs and shafts
- All rotating shafts mounted on bronze bushings
- Meets or exceeds minimum 4:1 design factor and all requirements of ASME/ANSI standard B-30.21



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Hoists

**Lug-All Small Frame Web Strap Ratchet Winch Hoist, Standard Latching Hooks**

- Aluminum alloy frame
- Interlocking pawl systems
- Web strap stores on double flanged drum
- Reversible fiberglass handle
- Nylon web strap
- Standard quick release pulley block double reeved for full capacity
- Open construction
- Easily replaceable stress link gives warning of overload

**LUG-ALL**

Lug-All #	Description	Capacity for Single Line	Capacity for Double Line
2A	Strap Length: 10' Handle Length: 30" Weight: 10.25 lbs.	1/2 Ton Pull Distance: 16"-9'6"	1 Ton Pull Distance: 21"-4'5"
25-A	Strap Length: 8' Handle Length: 20" Weight: 10 lbs.	3/4 Ton Pull Distance: 16"-7'6"	1.5 Tons Pull Distance: 21"-3'5"

**LUG-ALL**

Lug-All #	Description	Capacity for Single Line	Capacity for Double Line
3-A	Strap Length: 11.5' Handle Length: 30" Weight: 14 lbs.	3/4 Ton Pull Distance: 19"-11'3"	1.5 Ton Pull Distance: 27"-5'1"
4-A	Strap Length: 10' Handle Length: 36" Weight: 15.5 lbs.	1 Tons Pull Distance: 19"-9'4"	2 Tons Pull Distance: 27"-4'1"

**Lug-All Medium Frame Web Strap Ratchet Winch Hoist, Standard Latching Hooks**

- Aluminum alloy frame
- Interlocking pawl systems
- Web strap stores on double flanged drum
- Reversible fiberglass handle
- Nylon web strap
- Standard quick release pulley block double reeved for full capacity
- Open construction
- Easily replaceable stress link gives warning of overload



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hoists

**Standard Series Web Strap Ratchet Winch Hoist**

- Load tested to 125% of rated capacity
- Double flanged drum keeps web strap from coming in contact with ratchet teeth
- Breakable stress link-alerts operator to an overload condition
- Reversible handle with two spare stress links
- Interlocking pawl mechanism
- Maintenance free bearings are lubed for life
- RFID traceability
- USA Made 360° swivel hooks are drop forged heat treated steel



2W10



3W08S



4W12

**Lincoln Hoist**

Lincoln Hoist #	Description
2W10	Strap Hoist, 1-Ton with 30" Handle
3W08S	Strap Hoist, 1-1/2-Ton with 20" Handle
3W08SY	Strap Hoist, 1-1/2-Ton, 20" Handle with Hot Stick Rings on Operating Levers Only
3W15Y	Strap Hoist, 1-1/2-Ton with Medium Frame and Hot Stick Rings on Levers Only, 6.2' Lift at Double Line and 14' Lift at Single Line
4W12	Strap Hoist, 2-Ton with 36" Handle
4W12Y	Strap Hoist, 2-Ton with 36" Handle and Hot Stick Rings on Operating Levers Only
4W12B	Strap Hoist, 2-Ton with 36" Handle and Hot Stick Rings on the Handle and Pawl Shafts



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Hoists

Rubber Glove Style



Hotstick Style

**Convertible Strap Hoists, Mechanical**

- For rubber-glove work, select hoist with plastisol cap on handle end
- For hotstick operations, select hoist with swivel eye on the handle
- Designed for heavy-duty applications
- Automatic spring-loaded latches on 360° swivel forged-steel hooks
- Heat-treated aluminum-alloy frame
- Interlocking pawls
- Safety-orange 30" x 1-1/4" Epoxiglas insulated handle

**CHANCE**

Chance #	Rating	Description	Standard Lift Distance (high)	Standard Lift Distance (low)	Weight
PSC3090451	3/4-1-1/2 Ton	Rubber Glove Style	3'	6'	12.5 lbs.
PSC3090452	3/4-1-1/2 Ton	Hotstick Hooks & Handle Style	3'	6'	13.5 lbs.

**Nylon Strap Ratchet Hoists, Mechanical**

- For rubber-glove work, select hoist with plastisol cap on handle end
- For hot-stick operations, select hoist with swivel eye on handle end
- All models have hot-stick rings on hooks and latches
- Single strap of 1-ton units reaches and lifts farther
- 2-Ton units employ a sheave-mounted hook in a double-strap becket

Chance #	Rating	Description	Standard Lift Distance	Handle Length	Weight
PSC3090323	1 Ton	Rubber Glove Style	5'9"	22"	12.75 lbs.
PSC3120000	2 Ton	Rubber Glove Style	3'9"	36"	14.5 lbs.

**CHANCE**

Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Hoists


**G Series Coffing Hoist, Ratchet Lever**

- Riveted construction for tamper-resistance
- Handle stops prevent handle from spinning if it's accidentally released by operator
- Free chaining mechanism allows quick and easy take-up and positioning of slack chain
- Snap hook and links allow the operator to convert unit to next small capacity to give longer lift and faster operation, snap hooks acts as an end stop

Columbus McKinnon #	Number of Chains	Lift	Weight Capacity	Min. Distance Between Hooks	Handle Length	Min. Increment	Weight
AG	One	56"	1,500 lbs.	13"	18-3/4"	.624/.313"	14 lbs.
ATG	Two	60"	3,000 lbs.	15"	18-3/4"	.313/.156"	17 lbs.
FTG	Two	60"	6,000 lbs.	16"	27-5/8"	1.0/.5"	25 lbs.
ZG-6	Four	53"	12,000 lbs.	25"	33-5/8"	0.25"	59 lbs.

**Ratchet Chain Hoists, Link Chain Style**

- High-strength 20" handle and sheave housings are heat-treated aluminum
- All working parts fully enclosed in housing unit
- High-strength alloy steel chain
- Forged steel load hooks with automatic spring-loaded latches
- Two-way handle
- Rounded stop on handle end
- 5-1/2' standard lift distance



3 Ton

4-1/2 Ton

6 Ton

**CHANCE**

Chance #	Rating	Handle Pull at Rating	Hook-to-Hook Minimum	Weight
C3090438	3/4 Ton	65 lbs.	11"	14 lbs.
3011S	1 Ton	90 lbs.	11"	14 lbs.
C3090439	1-1/2 Ton	60 lbs.	16"	22 lbs.
4012	2 Ton	90 lbs.	11"	28-1/2 lbs.
C3090440	3 Ton	60 lbs.	19-3/4"	30-1/2 lbs.
C3090441	4-1/2 Ton	70 lbs.	24-1/2"	47 lbs.
C3090442	6 Ton	70 lbs.	24-1/2"	50 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Earth Handling and Pole Setting

**Standard Kelly Bar Adapters with Bent Arm Pin**

- For installing torques up to 10,000 ft-lb.
- Has six holes for 1/2" bolts on a 5-1/4" bolt circle
- Comes with six 1/2" Grade 5 bolts, nuts, lock washers and bent arm pin with coil lock
- Hex bar shape

Chance #	Description
P630013	2"
630011HD	2-1/2"
P630012HD	2-5/8"

**CHANCE****CHANCE**

Chance #	Description
C3030069H	Complete Standard Locking Dog Assembly
C3030070	Locking Dog Replacement Kit Includes Parts Needed to Replace Both Locking Dogs

**Standard Locking Dog Assembly**

- For installing torques up to 10,000 ft-lb.
- Has six holes for 1/2" bolts on a 5-1/4" bolt circle
- Comes with six 1/2" Grade 5 bolts, nuts and lock washers

Chance #	Description
C1021583 7' C1020595 3-1/2'	Standard Drive-End Wrench Installs 8,000 ft-lb and 10,000 ft-lb Tough One Anchors, 4,000 ft-lb and 6,000 ft-lb PISA Anchors
C3031064 7' C3031063 3-1/2'	Hybrid Drive-End Wrench Installs 10,000 ft-lb Tough One Anchors, 6,000 ft-lb PISA 6 Anchors and 7,000 ft-lb PISA 7 Anchors
C630027	3-1/2' Extension, Fits Std & Hybrid Drive-End Wrenches
C630028	7' Extension, Fits Std & Hybrids Drive-End Wrenches

**Standard and Hybrid Drive-End Wrenches****CHANCE****Tough One Drive-End Wrenches****CHANCE**

Chance #	Description
C3030983	7' Installs 10,000 ft-lb Tough One Anchors and all 1-1/2" Core Anchors
C3030982	3-1/2' Installs 15,000 ft-lb Large Hub, Tough One Anchors
C3030987	3-1/2' Extension for Tough One Drive-End Wrench
C3030988	7' Extension for Tough-One Drive-End Wrench



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Earth Handling and Pole Setting

### Adapters for Installing SS or RR Anchors

- Slide into locking dog adapter and are retained by spring loaded dogs
- Each comes with bolts, nuts and lockwashers
- Requires appropriate kelly bar adapter (sold separately)

Chance #	Description
C3030020	SS5/SS150/RR Drive Tool, Fits Standard Locking Dog Assembly
C3031035	SS5/SS150/RR Drive Tool, Fits Tough One Locking Dog Assembly
T3031403	SS175 Drive Tool, Fits Tough One Locking Dog Assembly
C3031077	SS200 Drive Tool, Fits Tough One Locking Dog Assembly



Chance #	Description
639001	SS5/SS150/RR Drive Tool, Six 1/2" Holes on 5-1/4" Bolt Circle
C3030195	SS175 Drive Tool, Twelve 5/8" Holes on 7-5/8" Bolt Circle
C3030201	SS200 Drive Tool, Twelve 5/8" Holes on 7-5/8" Bolt Circle

### Adapters for Installing SS or RR Anchors

- Includes proprietary alignment window
- Each come with bolts, nuts and lockwashers
- Requires appropriate kelly bar adapter (sold separately)

### Shear Pin Torque Limiter

- For installing torques up to 10,000 ft-lb.
- Offers protection for anchors and installing tools by disconnecting power when the installing torque reaches a pre-selected level
- Useable in very rocky soil
- Does not require special storage or handling
- Top and bottom each has 6 holes tapped 1/2"-13 on a 5-1/4 bolt circle
- Each shear pin provides 500 ft-lb. of torque

Chance #	Description
C3030044	Shear Pin Torque Indicator
C3030045	1 Carton of Shear Pins (Approx 1,700 Pins)
T3031420	1 Box of Shear Pins (Approx 510 Pins)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Earth Handling and Pole Setting



OshKosh #	Description	Weight
2050	Post Hole Digger, 8' Split Handle	14 lbs.
2050A-8	8' Split Replacement Handle	8 lbs.
20510-10	Post Hole Digger, 10' Split Handle	16 lbs.
2050A-10	10' Split Replacement Handle	10 lbs.
2050-12	Post Hole Digger, 12' Split Handle	18 lbs.
2050A-12	12' Split Replacement Handle	11 lbs.

**Split Handle Post Hole Digger**

- Special alloy steel welded blades
- Digger blades make 6" circle
- Used with a front to back movement

**Solid Handle Post Hole Digger**

- Special alloy steel welded blades
- Digger blades make 6" circle
- Handles start together and are then pulled apart when in use

OshKosh #	Description	Weight
2051	Post Hole Digger, 8' Solid Handle	15 lbs.
2051A-8	8' Solid Replacement Handle	8 lbs.
2051-10	Post Hole Digger, 10' Solid Handle	16 lbs.
2051A-10	10' Solid Replacement Handle	9 lbs.
2051-12	Post Hole Digger, 12' Solid Handle	18 lbs.
2051A-12	12' Solid Replacement Handle	11 lbs.




OshKosh #	Description	Weight
2034	9', 10" Blade, Ash Handle	9 lbs.
2034-6	9', 6" Blade, Ash Handle	9 lbs.

**Straight Master Shovel**

- Ash hardwood handles
- Carbon steel blades with boron
- Handles are marked with footage to indicate depth of hole

**Round Point Shovel**

- Front turn step shovel
- 48" fiberglass handle
- Cushion grip

Seymour Midwest #	Description	Weight
S600	Round Point Shovel	5.6 lbs.




Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Earth Handling and Pole Setting



OshKosh #	Description	Weight
2024	8' Master Spoon	10 lbs.
2025	9' Master Spoon	10 lbs.
2026	10' Master Spoon	12 lbs.
2027	12' Master Spoon	14 lbs.

**Spoon Shovels**

- Made of high-carbon steel
- Scoop like shape allows cleaning of mud, water and backfill
- Handles have footage marks to indicate depth of the hole

**Tamp Bars**

- Wood handled, heavy weight straight steel boot

OshKosh #	Description	Weight
1055	8' Tamp Bar	9 lbs.



Dixie #	Diameter	Handle Length
06250	2-1/2"	4-1/2'
06252	Replacement Handle	4-1/2'
06260	2-1/2"	5'
06262	Replacement Handle	5'
06380	2-3/4"	6'
06382	Replacement Handle	6'

**Cant Hook with Extension Toe Ring**

- Manufactured from the highest quality materials
- Handles are top quality straight grain white mountain hickory hardwood, kiln dried to 18% moisture content, then precision cut to an exact fit
- Duckbill hooks are drop forged with the bills ground to a fine point
- Clasps and extension toe rings are ductile iron castings for a long lasting service

**Cant Hooks**

- Hard maple wood handles
- High carbon steel hooks heat treated for strength and durability
- Hook stop to prevent the hook from falling back and damaging the handle
- Hook 479 (3-1/2" x 8" duckbill), Hook 480 (3-1/2" x 9" duck bill)

OshKosh #	Description	Weight
199A	2-1/4" x 4', 479 Hook	7 lbs.
199	2-1/2" x 4', 479 Hook	9 lbs.
200A	2-1/4" x 4-1/2', 479 Hook	8 lbs.
200	2-1/2" x 4-1/2', 480 Hook	9 lbs.
201	2-1/2" x 5', 480 Hook	9 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Earth Handling and Pole Setting



Hastings #	Description
6705	Cant Hook with 36" Fiberglass Handle, 6.0 lbs.

**Fiberglass Handle Cant Hook**

- High strength forged steel hook
- 1-3/4" Diameter fiberglass handle is easily gripped when wearing gloves
- Supplied with heavy-duty base cap to protect butt end
- Protective metal sleeve on head eliminates wear
- Knuckle guard to protect hand if hook swings back to pole

**Round Crow and Digging Bar**

- High carbon steel
- 2" Chisel on one end
- Pointed on other end

OshKosh #	Description	Weight
1065	1-1/8" x 8'	27 lbs.



Dixie #	Diameter	Max Opening
40008	3/4"	16"
40218	1"	20"
40228	1"	25"

**Alloy Steel Timber Lifting Tong**

- Certified and proof tested alloy products should be used for overhead lifting
- Dixie Industries upset forges round alloy steel for optimum tensile strength and durability
- Proof loaded to two times the working load limit then affixed with a permanent metal identification tag
- Lifting tongs are supported by either screw pin shackle or a nut and bolt safety shackle with a ring
- Tong shape has been designed to provide a sure grip on poles and logs
- Painted bright orange for job site identification

**Pole Cant Tool**

- For turning fiberglass, concrete, metal and wood poles during installation
- Nylon strap is coated to grip pole surface
- Heavy duty ratchet has extra wide handle for easy operation when wearing gloves
- Poles can be turned in both positions without reinstalling the tool
- 48" Long x 2" diameter fiberglass handle with solid foam core

Hastings #	Description
6856	Pole Cant Tool with Heavy-Duty Ratchet Binder and 6' Nylon Strap, 10.0 lbs.
6856-3	Pole Cant Tool with Heavy-Duty Ratchet Binder with 8' Nylon Strap, 10.2 lbs.
6856-5	Pole Cant Tool with Heavy-Duty Ratchet Binder and 10' Nylon Strap, 10.4 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Earth Handling and Pole Setting



Chance #	Description
C3020003	Tamping Bar

**Expanding and Tamping Bar**

- Curved head distributes weight of the bar evenly around the anchor rod
- Hook wraps around the anchor rod
- Effectively used for tamping in soil above the installed anchor
- Base casting attached directly to the fiberglass handle
- Length: 10'

**Rowdy's DirtBall Jobsite Debris Tarp**

- Made of heavy-duty, rubberized canvas
- Equipped with lifting handles
- Rated for 1,000 lbs. of jobsite debris and dirt

Lewis #	Description
RDB-8x8-18	8' x 8' with 18 oz. Canvas



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds & Jumpers



Chance #	Description
C6000785	Cutout Grounding Clamp
C6000862	Cutout Grounding Clamp w/L Stud
C6000841	"L" Stud Terminal Only

### Cutout Grounding Clamps

- Bronze clamp used to ground bottom hinge contact on cutouts
- Can be installed with or without grounding cable
- Clamp's drilled terminal accepts threaded-stud cable ferrules
- Also accepts threaded L-stud and T-stud terminals, 3/4" diameter bronze

**CHANCE**



**CHANCE**

### Apparatus Grounding Clamps

- For restricted-space applications and as a truck grounding system
- Wide range of switching equipment applications
- Clamp bodies, eye screws and ball-studs are bronze alloy
- Continuous current: 400 amps

Chance #	Description	ASTM Grade/Class	Mainline Range Min/Max
C6002101	Apparatus Grounding Clamp, Tapped for 5/8-11 UNC Threaded Ferrule	5/A	#2 to 4/0 with Threaded Ferrule
C6002300	Apparatus Grounding Clamp with Pressure Terminal	5/A	#2 to 4/0 with Pressure Terminal



**CHANCE**

Chance #	ASTM Grade/ Class	Mainline Range Min/Max
G3605-1	5/A	#6 Sol Cu. .162" to 2" OD Bus

### Grounding Clamp

- Aluminum body
- Smooth jaws
- Bronze eye screw
- Continuous current AMPS 4000
- Weight: 1.715 lbs.

### All-Angle Grounding Clamps

- Aluminum bodies with serrated jaws
- For installation ease, jaws pivot 75° left or right

Chance #	Description	ASTM Grade/Class	Mainline Range Min/Max
G42291SJ	Pressure Terminal All-Angle Grounding Clamp	5/B	#2 Cu .258" to 954 kcmil ACSR 1.196"
C6001732	All-Angle Grounding Clamp Tapped for 5/8-11 UNC Threaded Ferrule	5/B	#2 Cu .258" to 2-1/2" IPS 2.88"



C6001732



G42291SJ

**CHANCE**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds & Jumpers

### Tower and Flat-Face Grounding Clamps

- Continuous current: 400 RMS Amps

Chance #	Description	ASTM Grade/Class	Mainline Range Min/Max
C6001735	Aluminum Body, Serrated Jaws, Bronze Eyescrew w/Fine Threads, Tapped for 5/8-11 UNC Threaded Ferrule	3/B	1/8" to 1-1/2" Angles, 1-1/2" Flat
T6001798	Aluminum Body, Serrated Jaws, Bronze T-Handle w/Acme Threads, Tapped for 5/8-11 UNC Threaded Ferrule	3/B	1/8" to 1-1/2" Angles, 1-1/2" Flat
C6002231	Bronze Body, Serrated Jaws, Bronze T-Handle w/Acme Threads Drilled for 5/8-11 UNC Threaded Ferrule, Tower & Flat-Face Grounding Clamp	5/B	1/8" to 1-1/2" Angles, 1-1/2" Flat
C6002232	Bronze Body, Serrated Jaws, Bronzed Eye screw w/Acme Threads, Drilled for 5/8-11 UNC Threaded Ferrule, Tower & Flat-Face Grounding Clamp	5/B	1/8" to 1-1/2" Angles, 1-1/2" Flat
G33633SJ	Aluminum Body, Serrated Jaws, Bronze Eyescrew w/Fine Threads, Bronze Pressure-Type Terminal, Tower & Flat-Face Grounding Clamp	3/B	1/8" to 1-1/2" Angles, 1-1/2" Flat
G33634SJ	Aluminum Body, Serrated Jaws, Bronze T-Handle w/Fine Threads, Bronze Pressure-Type Terminal, Tower & Flat-Face Grounding Clamp	3/B	1/8" to 1-1/2" Angles, 1-1/2" Flat



C6001735



T6001798



C6002231



C6002232



G33633SJ



G33634SJ

**CHANCE**


Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)




## Grounds &amp; Jumpers

**C-Type Grounding Clamps**

- Continuous current: 400 RMS Amps

Chance #	Description	ASTM Grade/Class	Mainline Range Min/Max
C6002271	Bronze Body, Smooth Jaws, Bronze Eyescrew with Fine Threads, Tapped for 5/8-11 UNC Threaded Ferrule, C-Type Grounding Clamp	5/A	#6 Sol Cu .162" to 1033 kcmil ACSR 1.25"
C6002276	Aluminum Body, Serrated Jaws, Bronze Eyescrew with Acme Threads, Bronze Pressure-Type Terminals, C-Type Grounding Clamp	5/B	#8 Sol Cu .128" to 1033 kcmil ACSR 1.25"
T6002708	Aluminum Body, Serrated Jaws, Bronze Eyescrew with Acme Threads, Tapped for 5/8-11 UNC Threaded Ferrule, C-Type Grounding Clamp	5/B	#8 Sol Cu .128" to 1033 kcmil ACSR 1.25"
C6001743	Aluminum Body, Smooth Jaws, Bronze Eyescrew with Fine Threads, Tapped for 5/8-11 UNC Threaded Ferrule, C-Type Grounding Clamp	5/A	#6 Sol Cu .162" to 1000 kcmil Cu 1590 kcmil ACSR 1.50"
C6002281	Aluminum Body, Smooth Jaws, Bronze Eyescrew with Acme Threads, Bronze Pressure-Type Terminal, C-Type Grounding Clamp	5/A	#6 Sol Cu .162" to 2" OD Bus
C6002255	Aluminum Body, Smooth Jaws, Bronze Eyescrew with Acme Threads, Tapped for 5/8-11 UNC Threaded Ferrule, C-Type Grounding Clamp	5/A	#6 Sol Cu .162" to 2" OD Bus
T6000658	Aluminum Body, Smooth Jaws, Bronze Eyescrew with Acme Threads, Drilled for 5/8-11 UNC Threaded Ferrule, C-Type Grounding Clamp	5H/A	#6 Sol Cu .162" to 2" OD Bus



C6002271



C6002276



C6002281



C6002255



T6002708



T6000658

**CHANCE**

Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds & Jumpers

### Snap-On (Duckbill-Type) Grounding Clamps

- Continuous current: 400 RMS Amps

Chance #	Description	ASTM Grade/Class	Mainline Range Min/Max
C6001734	Aluminum Body, Smooth Jaws, Bronze Eyescrew with Fine Threads, Tapped for 5/8-11 UNC Threaded Ferrule, Snap-On Grounding Clamp	5/B	#6 Sol Cu .162" to 566 kcmil Cu 900 kcmil ACSR 1.162"
C6000434	Aluminum Body, Serrated Jaws, Bronze Eyescrew with Fine Threads, Bronze Pressure-Type Terminal Snap-On Grounding Clamp	5/B	#6 Sol Cu .162" to 950 kcmil Cu 1510 kcmil ACSR 1.506"
C6000197	Aluminum Body, Serrated Jaws, Bronze Eyescrew with Acme Threads, Tapped for 5/8-11 UNC Threaded Ferrule, Snap-On Grounding Clamp	5H/B	#6 Sol Cu .162" to 950 kcmil Cu 1510 kcmil ACSR 1.506"



C6001734



C6000197

**CHANCE**

### Aluminum Grounding Clamps

Salisbury #	Description	ASTM Grade/Class	Main Line Range	Continuous Current Rating
2553	1.66" Aluminum Duck Bill Clamp, Spring Loaded, "V" Thread	5/B Serrated Jaw	1590 MCM ACSR to #6, 1.65"-1.6"	400 RMS Amps, 60 HZ
1895	1.5" Aluminum "C" Clamp w/Flat Lower Jaw, ACME Thread, Eye w/Strain Relief Sleeve	5/B Serrated Jaw	1431 MCM ACSR To #6	400 RMS Amps, 60 HZ
78000	Pin Threaded, Stainless Steel Eye w/Contact Stud	5/A Smooth Jaw	.125"-1.63"	



2553



1895



78000

**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds &amp; Jumpers

**Grade 5H Clamps**

- Meets requirements of ASTM F855, Table 2
- Rated for increased asymmetrical currents
- For 4/0 copper grounding cable, 47kA for 15 cycles; X/R=30

**SALISBURY**

by Honeywell

Salisbury #	Description	ASTM Grade/Class	Main Line Range	Continuous Current Rating
4295	2.4" Bronze "C" Clamp w/Flat Smooth Lower Jaw, Acme Thread, Eye	5H/A	2.0" IPS to #6, 2.4"-.16"	400 RMS Amps 60 Hz
2991	6.62" Adjustable Aluminum "C" Clamp for Round, Square, Rectangle or "H" Section Substation Buses, w/Flat Lower Jaw, Acme Thread, Eye	5H/A	6.12" IPS, 6.62"-.4"	400 RMS Amps 60 Hz
21953	3.5" Aluminum "C" Clamp for Substation Buses, Acme Thread, Eye Smooth Jaw w/Flat Lower Jaw	5H/A	3.0" IPS to #6, 3.5"-.16"	400 RMHS Amps 60 Hz
20882	Aluminum 2 "C" Clamp w/Curved Serrated Lower Jaw, Eye	5H/B	3,000 MCM ACSR to #6, 2"-.16"	400 RMS Amps 60 Hz
21074	Aluminum 2 "C" Clamp w/Curved Smooth Lower Jaw, Eye	5H/A	3,000 MCM ACSR to #6, 2"-.16"	400 RMS Amps 60 Hz
2567	Heavy-Duty Bronze "C" Type Flat Jaw Clamp for Flats & Angles, Serrated Jaw	5H/B	Angles & Flats: 2.5"-4" WX, Rounds: .25"-.75" Tap Size 5/8"-11 UNC Max Cable Size 4/0 Type V Compression Ferrules	
22675	1" Ball Stud "C" Clamp w/Strain Release	5H/A	1.5"-.16"	400 RMS Amps 60 Hz




4295



2991



21074



22675



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Grounds & Jumpers

### Substation Ground Clamps

- Hanger studs enable substation maintenance crews to utilize their portable grounds on large bus by providing a fault current rated hanger stud as part of the clamp

Hastings #	Description
21056	Bronze, Grade 5, 1-1/4" -5" OD Main Line Range
21057	Aluminum, Grade 5, 1/0 STR .398"-6.625" Diameter Main Line Range



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



Hastings #	Description
13765	Clear, Medium Range to 556 ACSR
13768	Clear, Large Range to 954 ACSR

### Mechanical Jumper Clamps

- Thrust bearing design provides low friction for tightening clamp
- Bronze clamping rings have serrated contact surface to insure good electric contact with conductors
- Grip tabs are molded in for easy gripping with rubber gloves
- Rated for 400A continuous current maximum rating (dependent on the rating of the jumper cable used with the clamps)



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

### Duckbill Ground Clamp

- Spring-loaded, Snap-on Design
- Aluminum Body
- Bronze Eye Screw with Acme Threads
- Smooth Jaws
- Stainless Steel Cable Clamp
- Utilized bolted terminal connection

Hastings #	Description
10478	Meets or Exceeds ASTM 885 Standards


**SALISBURY**  
by Honeywell



Salisbury #	Description
1785	#6 Solid to 477 ACSR
2115	#6 Solid to 954 ACSR

### Mechanical Jumper Clamps

- Clear plastic jumper clamps are compact, lightweight and virtually unbreakable
- Transparency allows easy inspection of the ferrule and cable inside of the handle
- Body and jaw are made from copper based alloy



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment

### Ground Clamp

- Bolted terminal
- Weight: 3.5 lbs.

Hastings #	Description	Max. Jaw Opening	Max. Size Cable
9153CC	Eyescrew	1-1/2"	4/1/2000



Hastings #	Description
3477	Fiberglass, 12" Shaft, 1/2" Hanger Bar

### Insulated Jumper Holder

- Designed to provide the lineman safety when installing and removing energized jumpers
- Allows linemen greater control with all jumpering requirements
- Can be installed with all standard shotgun sticks or rubber gloves

**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Grounds & Jumpers

### Copper Unshrouded Ferrules

- Designed for use with all grounding clamps that feature pressure terminals including the 1" duckbill and 1.5" flat jaw clamp
- Crimped on the conductor strands only
- 99.5% pure copper

Salisbury #	Description
24421	1/0, Strand Die Codes: 50
24422	2/0, Strand Die Codes: 60
24423	4/0, Strand Die Codes: 66



**SALISBURY**  
by Honeywell



**SALISBURY**  
by Honeywell

Salisbury #	Grade	Size
2022	1	#2
2023	2	1/0
2024	3	2/0
2025	5	4/0

### Threaded Unshrouded Grounding Ferrule

- Provides low resistant connection to cable strands with threaded stud that screws into a clamp
- Manufactured with a 5/8-11 UNC threaded stud

### Support Stud

- Can be installed on most ground clamps
- Replaces restraining strap immediately below terminal
- Serves as a mechanical parking stand for a second clamp

Chance #	Description
G3626	Stud for Rear Mount



**SALISBURY**

by Honeywell

21190 & 21277

21191

21192

24082

21236

Salisbury #	Description
21190	Ball Stud/C Clamp w/Strain Relief Sleeve
21277	Ball Stud/C Clamp w/o Strain Relief Sleeve
21191	4.38" Short Ball Stud
21192	6.13" Long Ball Stud
24082	4" Internal Thread Ball Stud
21236	Cover for Ball Stud

### Ball & Socket System and Ball Studs

- Universal clamp that can be used as 1" ball stud and 1-1/2" C clamp
- ASTM Grade 5
- Continuous current rating (amps, RMS, 60 Hz): 400
- Ball studs allow for variable angle accessibility



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds & Jumpers

### Ball Studs

- For restricted-space applications and as a truck-grounding system
- Delivers a high-current rating usually associated with only large clamps
- Applies to a wide range of switching equipment

Chance #	Description
C6002102	4-1/4" Overall Length, 5/8" Diameter Ball Stud
T6002364	7" Overall Length, 5/8" Diameter Long Ball Stud



**CHANCE**



**CHANCE**

Chance #	Description
C4060416	Grounding Stud Cover

### Grounding Stud Cover

- Non-conductive cover
- Not intended for personnel protection and should not be considered as insulative cover-up equipment
- Resilient ozone/corona-resistant thermo-plastic elastomer does not absorb water
- Resists aging/checking and retains high-visibility orange color
- Snap-fit keeps cover in place
- 5/8" ID Loop at top permits hot-line tools to "pop" it on and off



**CHANCE**

### Cluster Support, 1-Terminal Type

- Hangs grounding sets on the pole to facilitate lifting clamps
- Accepts plain ferrules on #2 to 4/0 grounding cable
- Copper bar length is 11"

Chance #	Description
C6000152	Ground Cluster Support

**CHANCE**



Chance #	Description
T6001549	Pole-Mount Grounding Cluster Bar

### Cluster Bar

- Compact 5" aluminum-alloy bar (5/8" diameter) accepts C-type or duckbill clamps
- For phase-to-phase grounding technique
- Adjustable wheel binder and 36" chain for pole applications
- Hook style for attachment to tower angles

### Temporary Ground Rod

- Screw ground rod provides a temporary ground
- For when a system ground is not available
- Reusable ground rod is copper-clad steel
- Helix and handle are bronze

Chance #	Description
G3370	Screw Ground Rod



**CHANCE**



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds & Jumpers



Chance #	Description
C6002989	58" x 58" Kit
C6002990	58" x 120" Kit
C6002991	120" x 120" Kit
C6002850	58" x 58" Mat Only
C6002851	58" x 120" Mat Only
C6002852	120" x 120" Mat Only

### Personal Protective Ground Grid, Pre-Packaged Kit

- For standing on during various energized and de-energized work practices
- Consists of a high-capacity tinned-copper-braid cable sewn in a grid pattern onto a vinyl/polyester fabric
- Includes:
  - ☐ Ground grid with long ball stud and illustrated instructions
  - ☐ Ground set
  - ☐ Storage bag

# CHANCE

### Ground Mat

- Portable mat provides a method to establish an equal potential zone for multiple grounding applications
- Vinyl polyester fabric, with high capacity, tinned-copper braid sewn into a grid pattern
- The copper grid connects to a 6" termination stud on the corner of the mat
- The ground mat is then bonded to the equipment being worked on
- Reversible, easy to store, easy to clean with standard hose pressure

Hastings #	Description
6610	Yellow Mat, 58" x 58"
6615	Yellow Mat, 58" x 120"
6620	Yellow Mat, 120" x 120"
6610-NS	Black Mat, Non-Skid, 58" x 58"
6615-NS	Black Mat, Non-Skid, 58" x 120"
6620-NS	Black Mat, Non-Skid, 120" x 120"



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



Estex #	Description
2629	25-1/2" x 28-1/2"

### Grounding Cluster Bag

- Red vinyl coated nylon with reinforced bottom
- Inside pocket 20"L x 5"H
- Thick web handles
- Protects grounds and jumpers from moisture, dirt, oil and other contaminants



### Grounds Flag

- Hi-Visibility orange grounds flag with two reflective strips on front and back for easy visibility when working at night
- Hook and loop straps for a secure attachment
- Wire attachment for hot line clamp on top and PVC stiffener on bottom
- Includes a space to write truck/radio number and service location

Buckingham #	Description
845403V	17-1/2"H x 16-1/2"W



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Grounds &amp; Jumpers

**SALISBURY**

by Honeywell


**Grounding Jumpers**

- Made of extra flexible soft drawn #30 AWG copper
- Yellow jackets shown in table, also available in black or clear

Salisbury #	Size	Strand Dia.	Jacket	Short Circuit Withstand Amps, RMS, 60HZ		Continuous Current
				15 Cycles	30 Cycles	Amps, Rms, 60HZ
2136	#2-665W	.35"	.50"	1450	1000	200
2137	1/0-1064W	.45"	.62"	21000	15000	250
2138	2/0-1330W	.49"	.65"	27000	2000	300
2139	4/0-2109W	.62"	.83"	43000	3000	400

**Insulated Jumper Cable**

- Lightweight, resistant to oil, heat, moisture, ozone and abrasion
- Embossed every three feet with the conductors size and kV rating

**SALISBURY**

by Honeywell

Salisbury #	Size & Str. Awg	KV Rating Ø to Ø	Nominal Ø to GRD	Str. Dia.	O.A. Dia.	Max Amps Continuous
2756	2/0-427W	15	10	.456"	.90"	300
2757	4/0-437W	15	10	.592"	1.01"	400
21060	2/0-427W	25	15	.456"	1.1"	300
4370	2/0-427W	35	20	.48"	1.31"	300



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Ropes &amp; Handlines

**Handline Hook**

- Constructed from manganese bronze alloy for superior strength
- 600 pounds-maximum safe working load
- 3/4" Eye Opening
- 1" Throat Opening
- Weight: .5 lbs.

Tulsa #	Min/Max Arbor	Capacity
RT-20	2"/4"	3,000 lbs.
RT-40	3"/6"	4,500 lbs.

Hastings #	Description
P10060	5-1/2" x 3-1/8"

**Handline Carrier Hook**

- Nylon handline carrier with a hole to easily secure it to the body belt with a bolt or zip tie
- Will straighten when approximately 14-18 lbs. of pressure is applied to allow the handline to pull free

Buckingham #	Description
2406	Handline Hook

Buckingham #	Description
2402	Handline Carrier Hook

**Headline Hook**

- Reliable tool to raise and lower material at the work site
- Welded eye and formed hook is rated to 500 lbs.



**CHANCE**

Chance #	Description
C4000918	Triple Block without Becket
C4000919	Double Block with Becket

**Glass Fiber Filled Nylon Rope Blocks**

- Shells and sheaves made of high dielectric, fiber-filled natural nylon
- Shaft is silicon bronze and sheave bearings are oil-impregnated bronze
- For working-load considerations, blocks are rated as follows:
  - ☐ Single sheave blocks, max 2,000 lbs.
  - ☐ Double sheave blocks, max 3,500 lbs.
  - ☐ Triple sheave blocks, max 3,500 lbs.
- Dielectric rating in dry weather in 30,000 volts between bearing and mounting bolt nut
- Maximum rope size is 1/2"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Ropes & Handlines

### Replacement Rope for Handline Block

- 1,000 lb. working load
- Safety orange
- Fiberglass reinforced nylon construction
- Opening body design for easy rigging
- 3" Sheave, 5/8" Rope capacity
- Swivel eye allows 360° rotation
- Pull pin with detent ball for easy opening and securing
- Weight: 1-1/2 lbs.

Eagle Line #	Description
HL-80B	80' in Length
HL-100B	100' in Length



Erin Rope #	SFS #	Diameter	Length	Min. Break Strength
PDTW 160600	1/2X600PLU	1/2"	600'	4,818 lbs.
PDTW 120600	3/8X600PLU	3/8"	600'	2,881 lbs.
PDTW 200600	5/8X600PLU	5/8"	600'	7,214 lbs.

### 3 Strand Poly-Dacron Combination Rope

- High tensity polyester fiber wrapped cover over polyolefin core yarns
- Good abrasion resistance and strength
- Meets ANSI & OSHA Standards for fall protection

### Block & Tackle with Snap Hooks

- These are not occupational protective devices
- Not for human support
- Light, galvanized-steel shell blocks are fitted with snubbing hooks to hold the load
- Sheaves are strong, yet are lightweight aluminum alloy with all-bronze bushings
- Choice of forged hook No. 258 or swivel hook No. 259
- Hooks fit under insulator and engage pin on cross arm
- Maximum safe load: 750 lbs.
- Furnished with 25' of 3/8" rope
- No. 267 block with standard snap hook and a detachable drop-forged anchor hook (No. 258) on one end, and block No. 268 with eye and rope tie-off hook on other end
- No. H267 block with guarded snap hook and a detachable drop-forged anchor hook (No. 258) on one end and block No. H268 (with guarded snap hook, eye and rope tie-off hook) on other end

Klein Tools #	Description
1802-30	Block & Tackle with Standard Snap Hooks
1802-30S	Same as 1802-30 Except Supplied w/Detachable Swivel Anchor Hook (No. 259) Instead of Hook No. 258
H1802-30	Block & Tackle with Guarded Snap Hooks
H1802-30S	Same as H1802-30 Except Supplied w/Detachable Swivel Anchor Hook (No. 259) Instead of Hook No. 258
H1802-30S S/R	Same as H1802-30S but with Rope Spliced to No. H268 Block



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Ropes &amp; Handlines



Buckingham #	Description
50061	Ox Block
50061A-4	Ox Block with 4' x 5/8" Adjustable Sling, Aluminum Carabineer
50061A-4/80	Ox Block with 4' x 5/8" Adjustable Sling, Aluminum Carabineer and 80' x 1/2" Handline Assembly

**Ox Block**

- Push button to open, swivel eye, friction bar and gate with audible clicks
- Rope snatch block with an integrated friction bar used for hurt man rescue, lowering loads, snubbing loads and raising loads
- Allows the rigging professional to handle loads with greater control
- Replaces standard handline blocks, parted blocks and various snatch blocks
- Has greater working load limits than blocks of similar size
- For synthetic ropes only, not to be used with wire rope or natural fiber ropes

**Hand Line Blocks**

- Block and sheave constructed of rugged nylon fiberglass reinforced high dielectric material
- Reinforced 1/2" diameter axle and swivel bearings
- 3" Sheaves-block can accommodate rope up to 5/8" diameter
- Provided with either side opening or closed block
- Blocks are rated with 3-1 safety factor
- Working load limit 1,000 lbs.

Hastings #	Description
3550	3" Sheave Block, Side Opening, Swivel Hook and Safety Snap
3551	3" Closed Sheave Block, Swivel Hook and Safety Snap



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



Klein Tools #	Description
267	Plain Block
H267	Plain Block, Nose Extends Over Keeper
268	Block w/Eye to Splice Line to Block & Rope Tie-Off
H268	Block w/Eye to Splice Line to Block & Rope Tie-Off, Nose Extends Over Keeper

**Blocks**

- Blocks without ropes and hooks
- Made of light, galvanized steel and aluminum alloy
- Sheaves have bronze bushings

**Snap Hook**

- General purpose forged snap hook with eye at 90° to opening
- Maximum safe load: 1,500 lbs.
- 1" Eye I.D.

Klein Tools #	Throat Opening	Overall Length
443A	1/2"	5-1/2"



Klein Tools #	Throat Opening	Overall Length
470	5/8"	5"

**Swivel Hook with Plunger Latch**

- Forged steel with swivel clevis and quick-acting plunger-style latch
- Designed to take 1/2" or lighter hand lines
- Swivel action prevents accidental fouling into secondary wires
- Maximum safe load: 750 lbs.
- 1-3/16" x 1" Swivel opening



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Ropes &amp; Handlines

**Anchor Hook**

- Forged hook is designed to slip under insulator and engage pin of cross arm
- Standard on Klein block and tackle 1802-30 and H1802-30
- Maximum safe load: 750 lbs.
- 5/8" Eye I.D.

Klein Tools #	Throat Opening	Overall Length
258	1-7/8"	5-1/2"



Klein Tools #	Throat Opening	Overall Length
259	1-7/8"	6-1/2"

**Swivel Anchor Hook**

- Swivel clevis on this forged hook will engage with snap on Klein block and tackle 1802-30 and H1802-30
- Swivel prevents twisting and kinking of rope
- Maximum safe load: 750 lbs.
- 1-3/16" x 1" Swivel opening

**Swivel Snap Hook**

- Bronze swivel snap hook made for use on canvas buckets
- Maximum safe load: 150 lbs.
- 3/4" Eye I.D.
- 4-3/8" L x 1-5/8" W

Klein Tools #	Throat Opening	Overall Length
2012	5/8"	5"



Klein Tools #	Description
1702-20N	Klein-Kord Strap, 1" x 7'

**Howe Wire Tool**

- Strap is made of tough Klein-Kord
- Swivel hook is forged steel with large opening
- Shank of hook is lengthened to reach under insulator
- Other end has cam-lock to hold the load at any distance
- All metal parts are galvanized
- Maximum safe load: 500 lbs.

Looking for something you don't see in the catalog? Special Fleet Service has inventory and access to thousands of products, call us today and let us help you order exactly what you need to get the job done.




Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Fall Protection Sizing

**How To Size A Body Belt:** The most critical measurement of a body belt, in terms of comfort, is the dee measurement. The proper dee size is normally found by measuring from the prominent part of one hip bone around the back to the same point on the other hip bone. Add 1" (25 mm) for non padded belts and 2" (50 mm) for padded belts so that the dee ring heels are just forward of the hip bones and not on them. All measuring should be done over clothing to be worn under the belt. Normal combinations of dee and belt measurements are shown below.



X - Distance from waist to top of hip bone to where body belt is worn.

Y - Measurement is from front of hip bone around the back to the front of the other hip bone.

Measure - ("Y" distance) is hip to hip and add 2 inches to padded belts and 4" for lightweight dri-lex belts. This measurement is the Dee size.

Rule of Thumb - Measure from seam of pant, around buttocks to other seam and add 2 inches to padded belts and 4 inches to lightweight dri-lex belts.

Dee Size		Belt Strap* Min		Belt Strap Center Hole		Belt Strap Max		No. of Tool Loops
In.	cm.	In.	cm.	In.	cm.	In.	cm.	
D18	46	32	81	36	91	40	102	3
D19	48	33	84	37	94	41	104	3
D20	51	34	86	38	97	42	107	3
D21	53	36	91	40	102	44	112	4
D22	56	37	94	41	104	45	114	4
D23	58	38	97	42	107	46	117	4
D24	61	40	102	44	112	48	122	4
D25	64	41	104	45	114	49	125	4
D26	66	42	107	46	117	50	127	4
D27	69	44	112	48	122	52	132	4
D28	71	45	114	49	125	53	135	4
D29	74	46	117	50	127	54	137	4
D30	76	47	119	51	130	55	140	4

\*Belt Strap Is Not Waist Size.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment

**The Journeyman Body Belt**

- Semi-floating, shifting "D" saddle
- Leather rolled-edge cushion
- Leather tongue, two D-ring

Bashlin #	D-Ring Size
160NL-D18	D18
160NL-D20	D20
160NL-D22	D22
160NL-D24	D24
160NL-D25	D25
160NL-D26	D26
160NL-D28	D28



Bashlin #	D-Ring Size
88-D22	D22
88-D23	D23
88-D24	D24
88-D25	D25
88-D26	D26

**The Floridian Body Belt**

- Padded, contour cushion section
- Flares for the shifting D-rings
- 5-1/2" Back gives support
- Hand-laced top-quality leather

**2019M Lightweight Full Float Body Belt, 4 D-Ring**

- Dri-lex lined
- Stacked dee rings
- Two large full float double bar dee
- Two small dee rings
- Back support, no gut strap



Buckingham #	Dee Size	Belt Strap
2019M-D23	23"	38"-46"
2019M-D24	24"	40"-48"
2019M-D25	25"	41"-49"
2019M-D26	26"	42"-50"
2019M-D27	27"	44"-52"
2019M-D28	28"	45"-53"
2019M-D29	29"	46"-54"
2019M-D30	30"	47"-55"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment



Buckingham #	Dee Size	Belt Strap
20182M-D22	22"	37"-45"
20182M-D23	23"	38"-46"
20182M-D24	24"	40"-48"
20182M-D25	25"	41"-49"
20182M-D26	26"	42"-50"
20182M-D27	27"	44"-52"
20182M-D28	28"	45"-53"

**20182M Buck Mobility Belt, 4 D-Ring**

- No lower strap which provides the mobility and freedom of movement
- 9" high fully padded body
- Lined with quality ultra-soft leather
- Two full float lower primary dee rings
- Two small upper dee rings for secondary lanyard
- Replaceable man rated upper strap

Buckingham #	Dee Size	Belt Strap	Color
2000EM-BL-D20	20"	34"-42"	Black
2000EM-BL-D22	22"	37"-45"	Black
2000EM-BL-D23	23"	38"-46"	Black
2000EM-BL-D24	24"	40"-48"	Black
2000EM-BL-D25	25"	41"-49"	Black
2000EM-BL-D26	26"	42"-50"	Black
200EM-BR-D20	20"	36"-44"	Brown
200EM-BR-D22	22"	37"-45"	Brown
200EM-BR-D23	23"	38"-46"	Brown
200EM-BR-D24	24"	40"-48"	Brown
200EM-BR-D25	25"	41"-49"	Brown
200EM-BR-D26	26"	42"-50"	Brown

**2000EM Full Float Body Belt, 4 D-Ring**

- Hand crafted of the highest quality leather
- 5-1/2" foam cushioned pad reinforced with rawhide lace
- Belt strap is leather with a nylon center to provide strength and longer life
- Four floating in-line dees provide a 4" lateral movement to reduce wear on the pole strap
- To order two D-ring style specify 2000M and size



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Fall Protection &amp; Climbing Equipment

**EZ Rider, Four D-Ring Belt**

- Ergonomic, contoured design allows the belt to be worn comfortably and correctly, without compromising safety
- Supports the lower abdomen, reducing leg discomfort and numbness
- Dramatically improves “on the pole” comfort
- Easily connects pole lariats, pole chokers and similar WPFRDs
- Black leather, nylon cushion



Bashlin #	D-Ring Size
88UX4DMP-D18	D18
88UX4DMP-D20	D20
88UX4DMP-D22	D22
88UX4DMP-D23	D23
88UX4DMP-D24	D24
88UX4DMP-D25	D25
88UX4DMP-D26	D26
88UX4DMP-D27	D27
88UX4DMP-D28	D28

**Four D-Ring Tool Belt**

- Has all the long wearing qualities and a soft cushion for the “broken in” feel
- Features a nylon upper tongue with a quick release buckle or easy donning and adjustment
- D-Rings are sturdy enough to carry a strap, secondary lanyard or wood pole fall restricting device without getting “droopy”
- Black leather



Bashlin #	D-Ring Size
Q88GX4DCC-D18	D18
Q88GX4DCC-D20	D20
Q88GX4DCC-D22	D22
Q88GX4DCC-D23	D23
Q88GX4DCC-D24	D24
Q88GX4DCC-D25	D25
Q88GX4DCC-D26	D26
Q88GX4DCC-D27	D27
Q88GX4DCC-D28	D28

Buckingham #	Dee Size	Belt Strap
2018M-D22	22"	37"-45"
2018M-D24	24"	40"-48"
2018M-D25	25"	41"-49"
2018M-D26	26"	42"-50"
2018M-D27	27"	44"-52"
2018M-D29	29"	46"-54"
2018M-D30	30"	47"-55"

**2018M Lightweight Full Float Body Belt, 4 D-Ring**

- Dri-lex lined
- Two large full float double bar dee
- Two small dee rings
- Removable man rated gut strap



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Fall Protection &amp; Climbing Equipment

**Pole Gaff Maintenance Kit**

- Tools and gauge for inspecting and performing pole gaff maintenance
- Includes:
  - ☐ Smooth single cut file (6058)
  - ☐ New and improved pole gaff gauge (6303); can now gauge CCA gaffs
  - ☐ Finishing hone (6501)

Buckingham #	Description
6025	Pole Gaff Maintenance Kit



Buckingham #	Description
3502C	Angled, Metal Insert
3504C	Straight, Metal Insert

**Cushion Wrap Pad with Cinch Loop & Insert**

- Hook and loop pad that features a continuous wrap with a cinch loop and metal insert
- Strap 4" wide

**Big Buck Wrap Pad**

- Increased surface area to distribute pressure
- Thick, comfortable pad
- Moisture wicking Dri-lex lining
- Adjustability of hook and loop wrap
- Steel "C-Pad" insert for proper climber shank position
- Cinch loop to provide an extra tight fit
- Rolled edge to prevent chafing

Buckingham #	Description
3202C	Big Buck Wrap Pad



Buckingham #	Description
3500	Cushion Wrap w/Metal Insert
3500C	Cushion Wrap with Cinch Loop, No Metal Insert

**Cushion Wrap Pad**

- Hook and loop pad with Velcro
- 3/4" Padding
- Strap 4" wide

**Climber Pad**

- 'L' Tunnel pad has a soft 3/4" cushion sandwiched between two pieces of leather
- All leather construction with 3/4" padding
- Three loops and a tunnel design to keep climber stationary

Buckingham #	Description
3125	Climber Pad



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment

**Standard Buck LineBacker Belt**

- Turns a two dee ring body belt into a four dee ring belt
- Permanent abdominal stabilizer strap
- Permanent lumbar pad

Buckingham #	Size
6263-S	Small, 28"-32"
6263-M	Medium, 32"-36"
6263-L	Large, 36"-40"
6263-XL	X-Large, 40"-44"

Buckingham #	Description
4202-S	Small, 28"-32"
4202-M	Medium, 32"-36"
4202-L	Large, 36"-40"
4202-XL	X-Large, 40"-44"

**Man Rated Gut Strap**

- Able to be used with any two dee body belt and is completely adjustable for users comfort
- 5,000 lb. man rated connections
- Leather lined strap
- Standard tongue buckle



Buckingham #	Description
TB94089A	Titanium Pole Climber with Offset Stirrup & Nylon Foot Straps (21391)
TB91089A	Titanium Pole Climber with Offset Stirrup, Nylon Foot Straps (21391) & CCA Gaff
TB94059A	Titanium Pole Climber with Offset Stirrup, Nylon Foot Straps (21391), Nylon Leg Straps (2239) & Climber Pads (3122)
TB90089A	Titanium Pole Climber with Straight Stirrup, Nylon Foot Straps (21391) & CCA Gaff

**Titanium Contoured Shank Replaceable Gaff Pole Climbers**

- Gold colored with chrome colored gaffs and sleeves
- Contoured shank for ankle relief and comfort
- Straight and offset stirrups
- Dowel and screw style replaceable gaffs with 16° angle
- Climber with gaff weights 1 lb. 2 oz.



Bashlin #	Description
14	Replacement Gaffs, Unpolished 1-5/8" for Poles
14P	Replacement Gaffs, Polished 1-5/8" for CCA Poles
14T	Replacement Gaffs, Unpolished 2-1/2" for Trees

**Replacement Gaffs**

- Fit all Bashlin climbers with replaceable gaffs
- New screw for replacement are included
- Sold in pairs



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment



**BASHLIN INDUSTRIES, INC.**

Bashlin #	Description
BD16BC-1N	Bottom Straps Attached, Unpolished Gaffs

**BD16BC-1N Climber, Steel Alloy**

- Replaceable gaff
- Offset design
- Twisted shank allows the shank to lie flat on the leg
- Top slide adjustment is 15"-18"
- 18"-21" Adjusting top sliders are available; add "A" to the part number

**BD16B-1N Climber, Steel Alloy**

- Adjustable, with a replaceable gaff
- Offset design
- Roomy ankle area and a triangular strap ring
- Includes #2 gaff guard and #5 gaff gauge standard
- Top slide adjustment is 15"-18"
- 18"-21" adjusting top slides are available; add "A" to the part number

Bashlin #	Description
BD16B-1N	Bottom Straps Attached, Unpolished Gaffs

**BASHLIN INDUSTRIES, INC.**



**BASHLIN INDUSTRIES, INC.**



Bashlin #	Description
BD14-1N	Bottom Straps Attached, Unpolished
BD14P-1N	Bottom Straps Attached, Polished
BD14-2N	Top-Bottom Straps Attached, Unpolished
BD14-4N	Top-Bottom Straps Attached, 130D Pads, Unpolished
BD14-5N	Top-Bottom Straps Attached, 140DS Pads, Unpolished

**BD-14P Climber, Aluminum Alloy**

- Contour shank with an offset design
- Replaceable polished gaff
- 17° Gaff angle makes this the most forgiving gaff on the market
- Includes #2 gaff guard and #5 gaff gauge standard
- Top slide adjustment is 15"-18"
- 18"-21" Adjusting top slides are available; add "A" to the part number

**BD12C-1N Climber, Steel Alloy**

- Simple, riveted non-replaceable gaff
- Offset design
- Twisted shank allows the shank to lie flat on the leg
- Top slide adjustment is 15"-18"
- 18"-21" Adjusting top slides are available; add "A" to the part number

Bashlin #	Description
BD12C-1N	Bottom Straps Attached, Unpolished Gaffs

**BASHLIN INDUSTRIES, INC.**



Bashlin #	Description
2011-36	36" Pole Sling

**Pole Sling**

- Made for use with a Grip-All hot stick
- D-Rings are sized so one fits inside the other to choke it on a pole
- Safe working load:
  - ☐ Vertical: 1,000 lbs.
  - ☐ Choker: 1,000 lbs.
  - ☐ Basket: 2,000 lbs.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment

**Polyester Shock Absorbing Lanyard**

- Tubular nylon lanyard with shock absorbing core that eliminates the need for a bulky pack
- Meets ANSI Z359.1 performance standards
- Two snaphooks with 3/4" openings and high strength gates
- Complies with ASTM F887 Arc Flash Standards

Bashlin #	Description
2804-4HL	4' Lanyard



Bashlin #	Description
52N-2HL	6' Pole Strap

**50 Series Pole Strap**

- 6-Ply neoprene coated nylon
- Tongue buckle adjustment
- "Lineman Friendly" snap hooks
- Red wear indicator

**Buck ComboYard Lanyard**

- Tower lanyard that combines the best of multiple common lanyards into one
- 5' Dual tie-back lanyard with wear guard and rescue loops
- 12' Fall ANSI rated shock absorber
- Tie back snaps have a 5,000 lb. rated gate
- Two ANSI 3,600 lb. rated big BuckSnaps

Buckingham #	Description
5V67AQ1	Buck Combo Yard Lanyard



Buckingham #	Description
488R	SuperSqueeze with Rope and Carabiners for Distribution

**488R SuperSqueeze**

- One handed outer strap adjustment with the WebGrab
- One handed adjustment on the inner strap with the BuckGrab
- Outer strap length: 36"
- Inner material: rope
- Inner material length: 70"

**BuckAdjuster Lanyard**

- Fully adjustable positioning lanyard
- 1/2" Diameter
- Full red core wear indicator
- Double locking rope snap
- Clear protective tube to help provide maximum rope life
- Stitched eye allows user to minimize length for easy storage
- May also be used as primary work positioning device

Buckingham #	Length
9-6	6'
9-7	7'
9-8	8'



Buckingham #	Description
488RQ4	SuperSqueeze with Rope & Snaps for Distribution

**488RQ4 SuperSqueeze**

- One handed outer strap adjustment with the WebGrab
- Same one handed adjustment on the inner strap with the BuckGrab
- Outer strap length: 36"
- Inner material: rope
- Inner material length: 70"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Fall Protection &amp; Climbing Equipment

**488TW2 SuperSqueeze**

- One handed outer and inner strap adjustment with the WebGrab
- Same adjustability as the rope BuckGrab but on web
- Outer strap length: 52"
- Inner material: woven
- Inner material length: 78"

Buckingham #	Description
488TW2	SuperSqueeze with Web and Carabiners for Transmission



Buckingham #	Description
488W2Q3	SuperSqueeze with Locking Snap Hooks for Distribution

**488W2Q3 SuperSqueeze**

- One handed outer and inner strap adjustment with the WebGrab
- Same adjustability as the rope BuckGrab but on web
- Outer strap length: 36"
- Inner material: woven
- Inner material length: 48"

**488W2 SuperSqueeze**

- One handed outer and inner strap adjustment with the WebGrab
- Same adjustability as the rope BuckGrab but on web
- Outer strap length: 36"
- Inner material: woven
- Inner material length: 48"

Buckingham #	Description
488W2	SuperSqueeze with Web and Carabiners for Distribution



Buckingham #	Length
84V716-S1	6'
8VVR716	6'

**Buckyard Stretch Lanyard**

- Elastic bungee
- Reduces 6' lanyard to 44"
- Locking snap hook on one end and web loop on the other end
- 8VV-for full body harness w/steel ring dorsal attachment
- 84V-for full body harness w/web loop dorsal attachment
- S1 Suffix-meets ASTM F887 electric arc performance requirements

**BuckStop Lanyard**

- For full body harness with steel ring dorsal attachment
- 6" shock pad covered by a clear shrink tube
- Fixed length woven nylon with 1706 locking snap hook on both ends

Buckingham #	Length
5VV116	6'



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment



Buckingham #	Description
64V116S2+Z	6'

**BuckArrest Lanyard**

- 16" Shock pack covered by water resistant nylon tube
- Meets ASTM F887 electric arc performance requirements
- 3,600 lb. gate and meets ANSI Z359.12-2009

**Buckyard Lanyard**

- Expands to 42"
- 8VV-for full body harness w/steel ring dorsal attachment
- 84V-for full body harness w/web loop dorsal attachment
- S1 Suffix-meets ASTM F887 electric arc performance requirements
- +Z Suffix-all hardware has 3,600 lb. gate and meets ANSI Z359.12-2009
- X6 Suffix-for 6' free fall meeting ANSI Z359.13-2009

Buckingham #	Length
8VV114S1+Z	4'
8VV114.5S1	4.5'
8VV116	6'
8VV116+Z	6'
8VV116S1X6	6'
84V116	6'
84V116S1	6'
84V116+Z	6'
84V116S1+Z	6'



Buckingham #	Length
48129W2Y-6	6'
48129W2Y-7	7'
48129W2Y-8	8'

**SuperStrap Lanyard**

- Features the new patent pending WebGrab for easy adjustment
- Has all the benefits of web combined with the easy adjustment of rope
- Designed to use climbing over obstruction

**Nylon Positioning Strap with Tongue Buckle**

- 6-Ply Neoprene impregnated strap with tongue buckle
- Excellent abrasion resistance
- Most widely used among utility linemen

Buckingham #	Length	Lockers
386099E	6'	99E
386699E	6'6"	99E
387099E	7'	99E
388099E	8'	99E



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Fall Protection &amp; Climbing Equipment



Buckingham #	Description
6008-74DV+Z	W/Steel Carabiner-3600 Gate (50051) and Snap Hook (1706)
6008K-74DV+Z	W/Steel Carabiner-3600 Gate (50051) and Snap Hook (1706) Plus Kevlar to Meet ASTM F887

**BuckLimiter**

- Aluminum alloy construction inside and out
- Tangle free swivel top for added mobility
- 7' Extension for expanded work area
- Braking system designed for smooth consistent operation to prevent "jerky" lock-ups
- Rated to 350 lbs.

**Nylon Positioning Strap, Slide Buckle**

- Neoprene impregnated strap with slide buckle

Buckingham #	Length	Lockers
346699E	6'6"	99E
347099E	7'	99E

**Climber Strap**

- 1" Nylon
- 26" Length

Buckingham #	Description
5V6716RD+HS1	Buck Stop Dual Lanyard

**Buckstop Dual Lanyard**

- Features two 30342 Big BuckSnaps that fit over a 4" angle
- Locking rope snap attachment
- Red rescue loops facilitate the rescue of an injured worker

Buckingham #	Description
2649	1-Piece with Buckle Pad
21391	2-Piece with Split Ring

**Anchorage Ratchet Boom Strap**

- 5,000 lbs. rated
- Designed to be used when your aerial boom truck has no anchor point or your anchor point is in an inconvenient location
- Inside of the strap is lined with gum rubber to eliminate slippage on the boom
- Ratchet is used to cinch the strap snugly on the boom
- Standard length is 50"

**Locking Rope Snap**

- 1" Eye
- 15/16" Opening
- 6" Long
- 3,600 lb. gate load
- Rated to 5,000 lbs.

Buckingham #	Description
1706	Locking Rope Snap



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection &amp; Climbing Equipment



Buckingham #	Description
30342	Large Locking Snap Hook

**Big Buck Snap**

- Larger opening that allows the user to easily connect over 4" single iron
- New design allows for ease of detachment
- Radiused (rounded) inner edge is designed to prevent damage to conductors
- Meets ANSI Z359.12 specification
- 3,600 lb. gate load requirement

**Steel Twist Lock Carabiner**

- 4-1/4" Length, 1" opening, 3,600 lb. gate, minimum breaking load-5,000 lbs.

Buckingham #	Description
5005T	Twist Lock Steel Carabiner



Buckingham #	Description
60092	Pole Gaff Guard

**60092 Gaff Guard**

- Leather pole gaff guard with hook and loop fasteners
- Fits all climbers

**6909U Gaff Guard**

- Universal coated wire universal pole gaff guard that fits all pole climbers: Buckingham, Bashlin, Klein and Stringer Brooks

Buckingham #	Description
6909U	Coated Wire Universal Pole Gaff



Buckingham #	Description
6909A	Snap On Gaff Guard

**Snap On Gaff Guard**

- Fits all Buckingham replaceable pole gaffs with a 16° angle (A Style)

**Leather Gaff Guard**

- Has Velcro top
- Russett leather
- Helps keep gaff edges sharp and protects from cuts or puncture wounds

Bashlin #	Description
2	Leather Gaff Guard (PR)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Fall Protection &amp; Climbing Equipment



BASHLIN INDUSTRIES, INC.

Bashlin #	Description
27	Gaff Shaping Kit

**Gaff Shaping Kit**

- For use on Bashlin Pole Gaffs only
- Includes
  - ☐ Gaff gauge
  - ☐ 6" Mill file with wooden handle
  - ☐ Sharpening stone
  - ☐ Instructions

**603S8C700Z12 X-Style Harness**

- Split tongue quick connect buckles with leather chafes on the leg straps and at the torso for height adjustment
- Web dorsal loop attachment
- Reinforced web front loop that can be used for rescue or rope/cable grab
- Meets ASTM F887 electric arc performance requirements
- 5 Labels inside leather cover with Velcro wrap (wallet style)
- #3B Harness type with quick connect buckles
- Quick connect buckle leg strap attachment
- Web loop fall arrest attachment
- No body belt attachment or shoulder pads

Buckingham #	Description
603S8C700Z12-S	Small
603S8C700Z12-M	Medium
603S8C700Z12-L	Large



Buckingham #	Description
619951-S	Small
619951-M	Medium
619951-L	Large
619951-XL	X-Large
619951-2X	2-Xlarge

**619951 H-Style Summit Lite Harness**

- This "H" style full body harness features a Dri-lex shell that fits like a vest
- Patent Pending quick connect buckles on the chest and leg straps, steel dee dorsal attachment
- Spring loaded friction buckles for height adjustment
- Frontal chest dee ring that adjusts up and down independently of the shoulder straps
- Harness is made from Type 13 nylon webbing
- Grommet tongue buckle to fasten the waist belts, and a 5" wide belt with thick padding and built in stiffener for maximum comfort
- Add "-K1" to Mfg # for arc rated harness meeting ASTM F887 electric arc performance requirements



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Fall Protection &amp; Climbing Equipment

**61991 Mobile 'X' Tower Harness**

- Combination of an 'X' style harness permanently attached to a four dee ring body belt
- Features grommet leg straps and shoulder straps that articulate through the sternum dee ring
- Shoulder straps adjust with a single slide buckle on the upper portion of the harness
- Body belt has four work positioning dee rings
- Body belt is lined with sateen material and features a waist belt made of neoprene sandwiched between leather
- Upper and lower sections are connected together with webbing exceeding 5,000 lbs. tensile strength
- Meets ASTM F887 electric arc performance requirements



Buckingham #	Description
61991-M23	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Full Body Harness
61991-M24	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Harness
61991-M25	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Harness
61991-L23	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Full Body Harness
61991-L24	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Harness
61991-L25	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Harness
61991-L26	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Harness
61991-L28	2100M Stacked 4 D Leather, Full Float Body Belt Permanently Attached Full Body Harness

**637G8C500CK1 'H' Style Full Body Harness**

- 18" Dorsal pigtail with a small dee ring to attach a 4-1/2' shock absorbing lanyard
- Kevlar mesh shell
- FR Foam shoulder and leg pads
- Hook and loop chest strap
- Patented split tongue quick connect buckles with leather chafes on the leg straps
- Spring loaded friction buckles for height adjustment
- Made from Type 13 nylon webbing with silver upper and black lower sections
- Permanently attached fall arrest attachment
- No body belt attachment
- Meets ASTM F887 electric arc performance requirements

Buckingham #	Description
637G8C500CK1-M	Buckfit FR 'H' Style Full Body Harness, Medium
637G8C500CK1-L	Buckfit FR 'H' Style Full Body Harness, Large
637G8C500CK1-XL	Buckfit FR 'H' Style Full Body Harness, X-Large
637G8C500CK1-2XL	Buckfit FR 'H' Style Full Body Harness, 2X-Large



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Fall Protection & Climbing Equipment

### Aerial Basket Rescue Kit

- Provides safe removal of injured personnel from aerial baskets
- Boom strap has special coating to help prevent slippage
- Two Sheave blocks with 75' of 3/8" nylon rope
- 6" Diameter x 18" waterproof storage canister

Hastings #	Description
06-161	55" Boom Strap
06-165	Two Sheave Blocks w/75' of 3/8" Nylon Rope
06-166	Complete Rescue Kit
01-3318	Canister Storage Unit



Buckingham #	Description
105RSK1	BuckStep Rescue System

### BuckStep Suspension Trauma Rescue System

- Designed to alleviate the effects of orthostatic intolerance
- Allows a victim to immediately deploy a body support system that allows for improved blood circulation and the ability to move and flex muscles until rescue
- Attaches to a full body harness and is fully adjustable for any sized user
- For an arc tested system that meets ASTM F887

### High Elevation Self-Rescue System

- Provides all the components required to self-rescue or if the need arises to rescue a fellow employee
- Descender will automatically stop the user until the user compresses the handle allowing a smooth controlled descent
- Built in safety feature stops descent if the user compresses the handle to hard
- Unit will allow the rescuer the advantage of lowering a hurt person with ease as well
- Kit comes with retrofit rappelling straps that can be added to an existing harness for self-rescue

Buckingham #	Description
101SR-50	50' of 1/2" Braided Rope
101SR-100	100' of 1/2" Braided Rope



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment &amp; Meters



AEMC #	Description
511	Jaw Opening is 1.575"

**511 Clamp-On Meters**

- Standard size, full function clamp-on meter
- One-handed operation
- Measures AC Amps, AC Volts, DC Volts, Ohms, Continuity, Frequency and has a Diode Test Function

**6416, 6417 Clamp-On Ground Resistance Tester**

- Touch voltage indication (warns of unsafe conditions)
- Direct reading of ground resistance from 0.01 Ohm to 1,500 Ohm
- Direct reading of continuity and ground loop resistance
- Direct reading of ground leakage or phase current from 2mA to 40A rms
- Jaw design with large 1-1/4" window, accommodates up to 1,000kcmil cables
- Auto-off for power management
- Rugged Lexan head and body construction resists breakage
- Bluetooth communication with Android App (6417)

AEMC #	Description
6416	6416 Ground Resistance Tester
6417	6417 Ground Resistance Tester



Greenlee #	Description
CM-660	AC Clamp-On Meter

**CM-660 AC Clamp-On Meter**

- Auto power off for longer battery life
- Amperage measurement: 600A AC
- Voltage measurement: 600V
- Display: 3-1/2 digit LCD, 2,000 count
- Resistance: 2,000 OHM
- Jaw opening: 1.38"
- Measurement category: CAT III, 600V
- Includes:
  - ☐ 9V battery
  - ☐ Test leads
  - ☐ Carrying case

**Digital Voltage Phasing Meter**

- Instrument for measuring overhead and underground voltages
- AC, Hi-Pot and DC
- Large easy-to-read digital meter and analog bar graph
- Coiled, self-retracting cable; 16" retracted and 10' when fully extended
- Meter reads to nearest 100 volts
- Kit includes: 6702 Voltmeter with case, two 6' universal fiberglass poles with carrying case

Hastings #	Description
6702	0-40 kV Digital Meter
6702-1	15/25kV Loadbreak Bushing Adapter
6702-2	DC Hi-Pot Adapter for Use Up To 35kV
6702-3	35kV Loadbreak Bushing Adapter
6703	Extension Resistors for Use w/6702 (Pair)
6711	0-40kV Digital Meter Kit



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Test Equipment &amp; Meters



Hastings #	Description
6722	Phase-Tell III Wireless Phasing Meter
266	URD Bushing Well Adapter
01-266	Padded Case for Bushing Adapters

**Phase-Tell III Wireless Phasing Meter**

- Used to determine phase relationships on three-phase power systems, overhead and URD applications
- Battery powered, two-piece wireless phasing tool
- Wireless units communicate up to 300' apart
- Voltage range 4kV to 500kV
- Operates on two "AA" batteries, included
- FCC Compliant
- Auto shut-off
- Includes carrying case and instructions

**Cordless Digital Phasing Meter**

- FCC Licensed wireless technology
- Large easy-to-read digital display with backlight
- High intensity color coded LED indicator lights
- Impact and water resistant construction
- Completely shielded to minimize stray field interference
- Direct contact from 120V to 69kV, distribution systems
- Non-contact from 69kV to 800kV, transmission/substation systems
- Automatically alerts user of delta/wye transformation by an indicator light blinking
- Operating range of 100'
- Contained in a highly durable padded carrying case

Bierer Meters #	Description
PD800W	Wireless Phasing Meter & Voltage Detector



Chance #	Description
H18761	16kV Tester Hook Probes, Case and Manual

**Phasing Testers, Analog**

- For distribution circuits
- Determine phase relationships and approximate voltage, line-to-line or line-to-ground
- Two fiberglass poles with end fittings threaded for interchangeable probes
- Probe fittings couple with high-impedance component encased in each pole

**Tester Accessories**

Chance #	Description
H18766	Shepard Hook Probe
H18766S	Straight Probe
C4033409	Voltage Indicator Tester
T4030428	15kV Only Bushing Adapter
T4030857	15-35kV Bushing Adapter
C4031762	16kV Hi-Pot Adapter

**CHANCE**



T4030428



T4030857



C4033409



C4031762



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment &amp; Meters

**Audio/Visual Voltage Detector**

- Used to verify live or de-energized conductors
- For use with rubber insulating gloves or hot sticks using the splined universal end fitting
- Indicates the presence of voltage with an extra bright LED light and a distinctive audible signal
- Includes three C batteries



Salisbury #	Description
4244	Voltage Detector, Phase to Phase Settings: Off/240V/4.2kV/15kV/25kV/35kV/69kV/115kV/230kV
4344	Voltage Detector, Phase to Phase Settings: Off/240V/4.2kV/35kV/69kV/115kV/230kV/345kV/500kV
4444	Voltage Detector, Phase to Phase Settings: Off/Test-240V/Battery/URD:15kV/25kV/35kV
4356	Complete Kit Includes (1) 4244 Tester 240V to 230kV, (1) 21517 Case, (1) 2500 Shotgun Adapter
4367	Complete Kit Includes (1) 4344 Tester 240V to 500kV, (1) 21517 Case, (1) 2500 Shotgun Adapter
4469	Complete Kit Includes (1) 4444 Tester 240V to 69kV, (1) 21517 Case, (1) 2500 Shotgun Adapter
4445	Voltage Detector Tester
2500	Shotgun Adapter

Salisbury #	Description
4544	Voltage Detector, Phase to Phase Settings: Off/240V/4.2Kv/15kV/25kV/35kV/69kV/115kV/230kV
4644	Voltage Detector, Phase to Phase Settings: Off/240V/4.2kV/35kV/69kV/115kV/230kV/345kV/500kV
4744	Voltage Detector, Phase to Phase Settings: Off/Test-240V/Battery/URD:15kV/25kV/35kV
4556	Complete Kit, Includes (1) 4544 Tester 240V to 230kV, (1) 21517 Case and (1) 2500 Shotgun Adapter
4667	Complete Kit Includes (1) 4644 Tester 240V to 500kV, (1) 21517 Case, (1) 2500 Shotgun Adapter
4769	Complete Kit Includes: (1) 4744 Tester 240V to 69kV, (1) 21517 Case, (1) 2500 Shotgun Adapter

**Self Testing Audio/Visual Voltage Detector**

- Used to verify live or de-energized conductors
- For use with rubber insulating gloves or hot sticks using the splined universal end fitting
- Indicates the presence of voltage with an extra bright LED light and a distinctive audible signal
- Includes three C batteries



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment & Meters



Bierer Meters #	Description
VDA-040P	0-40kV Analog Voltage Detector

### Analog Voltage Detector

- Dual application design
- Detects 0-40kV line to ground (0-69kV phase to phase)
- A proximity or direct contact on overhead and underground systems
- Detect voltage from the ground on bare overhead and underground systems
- Test secondary voltage on bare or insulated cables
- Test capacitive test points
- Indicates line to ground values for nominal or induced voltages
- 5-Position selector switch is calibrated for height above ground to compensate for a capacitive coupling effect
- Shielded to minimize stray field interference
- Overload protection up to 500kV
- Water resistant construction
- Contained in a highly durable carrying case

### Multi-Range Voltage Detectors, Analog

- Confirms a line is de-energized
- Calibrated to read approximate line-to-line voltage when connected to any phase conductor
- Gives metered readout capable of distinguishing actual line voltage from static or feedover from an adjacent line

Chance #	Description
C4030979	1-40kV Scales Voltage Detector (Includes Test Point)
C4031140	16-161kV Scales Voltage Detector



HDE #	Description
TAG-200	Voltage Detector
TAG-200MR	Multi-Range Voltage Detector

### Electronic Voltage Detector

- Detects distribution and transmission of voltages
- Emits an audible and visual alarm if conductor is energized
- Requires direct contact with the conductor to detect voltage
- Water resistant housing
- Compact, lightweight and easy to use
- 9V lithium or alkaline battery operated
- For system voltages up to 69kV (Phase-to-phase)

### Phase Sequence Indicators

- Used to determine the phase sequence (A-B-C or C-B-A) of three-phase voltages
- Rotating-disk design
- Color-coded 36" leads
- 3-Phase, 3-Wire 60-600V circuits and 25-60 cycle current

Knopp #	Description
44030	Phase Sequence Rotation Meter
44050	Cordura Carry Case (Sold Separately)



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment &amp; Meters



Hastings #	Description
6709-1	Regulator Neutral Detector

**Regulator Neutral Detector**

- Eliminates high or low voltages caused by cycling the regulator to the upper or lower limit and then counting steps back to neutral
- 0-2,000V range is shown in one volt increments
- Works with all regulators up to and including 34.5kV
- Contact electrodes are knurled to aid in contact with conductors

**Transformer and Capacitor Tester**

- Test new transformers and capacitors, plus troubleshoot in-service units
- Eliminates the blowing of cutout fuses to determine the condition of equipment
- Magnetized back allows hands to be free to install and remove cables and clips
- Weatherproof, high-impact resistant plastic housing
- Operates on 9V battery, included

Hastings #	Description
6793	Tester, w/Battery & Carrying Case



HDE #	Description
VW-30	V-Watch Detector Only
VW-20H	V-Watch with Carrying Case and Lanyard

**V-Watch Personal Voltage Detector**

- Alerts user to proximity of high voltage
- Audible and visual alarms increase in frequency the closer the user gets to energized equipment
- Typical initial warning distance is about 7' from a 4kVAC conductor
- Low battery indicator
- Field replacement 9V battery
- Rugged protective housing
- Built-in self-test
- Operating temperature: -20° to 120°F
- Water withstand: protected from falling rain per IEC-529, level 2
- Voltage range: 2400VAC line-to-ground and above

**Ampstik High Voltage Ammeter**

- Slips on and off the conductor with  $\pm 1\%$  accuracy
- Open CT rejects stray magnetic fields
- Range of operation, voltage: 0-69kV, current: 1-2,000A
- Wide jaw sensor opening: 3.86"
- Shock and water resistant housing
- Non-conductive universal adapter
- One-button operation

Sensor Link #	Description
8-022	Wide Jaw 60hz True RMS w/Soft Case



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Test Equipment &amp; Meters



Sensor Link #	Description
8-020-XT	Std Jaw 60hz True RMS w/Soft Case
8-020-XT PLUS	Std Jaw 60hz True RMS w/Soft Case Stores 4 Readings

**Dual-Range High Voltage Non-Contact Tester**

- Test presence of voltage in overhead conductors or find faults in cables
- Low range for 50V AC to 1.5kV AC
- High range for 1.5kV AC to 132kV AC
- Audible and visual signs indicate presence of voltage
- Water resistant

Klein Tools #	Description
HVNCVT-1	Tester with Durable Carrying Case



**KLEIN TOOLS**

**Ampstik Plus Multiple Reading Ammeter**

- Slips on and off the conductor with  $\pm 1\%$  accuracy
- Open CT rejects stray magnetic fields
- Range of operation, voltage: 0-500kV, current: 1-5,000A
- Standard jaw sensor opening 2.5"
- Shock and water resistant housing
- Non-conductive universal adapter
- One-button operation

**CHANCE**



Chance #	Description
T4032271	5-40 kV Multi-Range Voltage Detector

**Multi-Range Voltage Detectors, Analog**

- For overhead and URD systems to 40kV
- With TP setting for test point on URD elbows
- Test both overhead and underground distribution systems
- For systems in voltage classes from 5 through 40kV
- Interchangeable probes and adapters
- Furnished owner's manual illustrates operating details for all models
- Includes:
  - ☐ Multi-Range voltage detector
  - ☐ Hook and straight probes
  - ☐ Elbows and bushing adapters
  - ☐ Case

**Distribution Auto-Ranging Voltage Indicators (ARVI)**

- 600V to 69kV for overhead and underground
- Automatic-ranging function quickly displays approximate line-to-line voltage class
- Single pushbutton activates the instrument
- Single light indicates power on (by glowing solid) or low battery (by blinking)
- C4033374 Includes:
  - ☐ Tester unit
  - ☐ Shepherd hook probe
  - ☐ Instruction manual
  - ☐ Hard shell padded case
- T4033418 Includes:
  - ☐ Test unit
  - ☐ Shepherd hook probe
  - ☐ Elbow adapter
  - ☐ Bushing adapter
  - ☐ Voltage indicator tester
  - ☐ Instruction manual
  - ☐ Hard shell padded case



**CHANCE**

Chance #	Description
C4033374	Basic Distribution ARVI for Overhead Applications
T4033418	Basic Distribution ARVI for Overhead and Underground Applications



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment &amp; Meters



HDE #	Description
TL-MAN-N	TILT II Transformer Tester with Manual Self-Test, Padded Carrying Bag & Instruction Manual
QC-MAN-N	Quick-Check Transformer & Capacitor Tester with Manual Self-Test, Padded Carrying Bag & Instruction Manual

**Transformer & Capacitor Testers**

- Tests transformers and capacitors for major defects before energizing
- Test overhead, pad-mount and other distribution transformers as well as capacitors and capacitor banks
- Tests the primary and secondary sides of de-energized transformers without disconnecting
- Prevents line workers from installing a fuse on a shortened transformer or capacitor
- Quickly verifies the secondary connections are not shorted
- Compact, lightweight and easy-to-use
- Powered by a 9V alkaline battery
- Super bright LED indicators
- Audible alarm confirms successful test
- Continuous testing while button is pressed
- Includes:
  - ☐ Large copper alligator clips with heavy-duty boots
  - ☐ Heavy-duty rubber insulated coiled test leads

**Protective Grounding Tester Set**

- Used to check resistance in protective grounding sets
- Applies direct current across the test specimen
- Instruction video and manual includes procedure details
- Includes:
  - ☐ Self-contained carry case
  - ☐ Two ball-stud terminals
  - ☐ DVD demonstration video
  - ☐ Two trouble-shooting probes
  - ☐ Self-test cable

Chance #	Description
C4033220	115/120V Protective-Ground-Set Tester



Chance #	Description
C4033178	115V Wet/Dry Hot Stick Tester

**Wet/Dry Hot Stick Testers**

- Portable unit
- Wet and dry modes selected by a toggle switch
- Graduated meter gives precise readout of each tool's leakage current
- For testing any length fiberglass-reinforced plastic hot stick up to 3" in diameter
- For spot checks at field jobsite's or periodic diagnostics in workshops



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Test Equipment &amp; Meters

**Electrical Grounding Set Tester**

- Self contained and portable
- Built in digital meter
- Maximum voltage output limited to protect the operator

Hastings #	Description
7714	Grounding and Jumper Tester



Hastings #	Description
6799	Hot Stick Tester

**Hot Stick Tester**

- Portable and lightweight
- 75,000 volts/ft for wet testing, 100,000 volts/ft for dry testing
- Complies with OSHA regulations
- Dual range selector



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Signs &amp; Safety



Hastings #	Description	Weight
6795	Truck Safety Barricade	12 lbs.
6795-1	4' Fiberglass Barricade Arm	2.2 lbs.

**Truck Safety Barricade**

- Can be installed, positioned, or raised and removed in minutes
- Fiberglass arm is easily positioned to adjust barricade for proper height above the ground and to compensate for parking on uneven terrain
- Design allows fiberglass arm to be quickly locked in eight different positions
- Arm can be moved to "vertical travel position" when movement of truck for a short distance is required
- Includes:
  - ☐ Four 4' Fiberglass arms
  - ☐ Four Signs
  - ☐ 150' Yellow polypropylene rope

**Traffic Cones**

- Heavy-duty, all-weather
- 100% PVC
- Stackable for easy storage
- Reflective collars for added visibility

JBC Safety #	Description	Weight
RS90045CT3M64	36"	10 lbs.



Bone #	Description
4848-MW	Men Working Roll-Up Sign
4848-UWA	Utility Work Ahead Roll-Up Sign
4848-FAS	Flagger Ahead Symbol Roll-Up Sign
4848-LCA	Lane Closed Ahead Roll-Up Sign
4848-LSCA	Left Shoulder Closed Ahead Roll-Up Sign
4848-BPTS	Be Prepared to Stop Roll-Up Sign
4848-RLCA	Right Lane Closed Ahead Roll-Up Sign
4848-OLA	One Lane Ahead Roll-Up Sign
4848-OLRA	One Lane Road Ahead Roll-Up Sign

**SafeZone 48" x 48" Marathon Reflective**

- All signs are designed using the Standard Highway Signs Manual specified in the MUTCD
- Fluorescent orange
- Retroreflective microprisms formed on a flexible glossy and UV-stabilized polymeric film
- Sheeting has protective film on the facing side and backed with a heavy vinyl coated fabric



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Signs &amp; Safety

**Stop-N-Slow Paddles**

- Sign faces are BONELIGHT ACM
- Diamond Grade Material
- Staff included with paddle

Bone #	Description
STOP-2484DG/HI	24"



Bone #	Description
SZ-412-SUB	Single Spring Sign Stand

**Single Spring Loaded Sign Stand, Universal Bracket**

- Bright orange, powder-coated legs allow sign stand to be easily seen
- Universal sign bracket will hold most roll-up signs
- Dual pull pin/kick release lever
- Quick set up and take down
- Spring action allows sign to bend and resist wind
- Weight: 22 lbs.

**Ergonomic Kneeling Pad**

- Heavy duty nitrile foam cushion top
- Bottom layer .25" non-slip rubber
- Relieves lower back and leg stress
- Will not absorb water
- Acts as a thermal barrier to cold ground

Estex #	Description
2735-12-22	12" x 22"
2735-16-20	16" x 20"
2735-18-36	18" x 36"



Rubbermaid #	Size
1683	3 gal
1685	5 gal

**Beverage Coolers**

- Durable construction resists scratching, denting and fading
- Drip-resistant spigot, screw-tight lid
- Extra-thick insulation ensures superior thermal retention
- Stain and odor resistant, easy-to-clean liner
- In-molded handles

**Water Cooler Mounting Bracket**

- Specifically designed for Rubbermaid water coolers, fits any size
- Durable, weather-resistant construction
- Made for horizontal mounting

Rubbermaid #	Description
1640	8" x 13" x 12-1/2" Mounting Bracket with Straps



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Signs &amp; Safety



Youngstown #	Size
03-3450-80-S	Small
03-3450-80-M	Medium
03-3450-80-L	Large
03-3450-80-XL	X-Large
03-3450-80-XXL	2X-Large

**Waterproof Winter Plus Gloves**

- Waterproof, windproof and breathable inner membrane, keeps hands warm and dry
- Durable and form-fit outer shell maintains dexterity
- Durable, flexible non-slip palm reinforcement
- Grips in wet and dry conditions and increases durability
- Internal knuckle protection on top of hand
- Double-stitched bonded nylon thread for extended life
- Terry cloth thumb for wiping sweat and debris

**Safety Lime Waterproof Winter Gloves**

- High-visibility lime coloring on top of hand
- 100% waterproof and windproof to keep hands warm and dry
- Reflective 3M Scotchlite on knuckle and wrist
- Insulating micro-fleece liner warms hand
- Durable, non-slip reinforced palm, fingers and thumb
- Form-fit outer shell maintains dexterity
- Ideal for DOT, airport operations, municipalities and winter road work

Youngstown #	Size
08-3710-10-S	Small
08-3710-10-M	Medium
08-3710-10-L	Large
08-3710-10-XL	X-Large
08-3710-10-XXL	2X-Large



Youngstown #	Size
06-3020-60-S	Small
06-3020-60-M	Medium
06-3020-60-L	Large
06-3020-60-XL	X-Large
06-3020-60-XXL	2X-Large

**Mechanics Plus Gloves**

- Water and oil resistant synthetic suede base layer
- Palm padding dampens vibration
- Breathable stretch nylon on top of hand wicks moisture and heat
- Terry cloth thumb for wiping sweat and debris

**Leather Utility Plus Gloves**

- Arc rated 20.8 cal/cm<sup>2</sup>, HRC 2
- 4" Safety cuff for wrist protection
- Durable high quality goatskin leather
- Ergonomic, 3-D performance glove pattern form-fits to hand
- Extra wide pattern reduces hand fatigue and increases comfort

Youngstown #	Description
11-3245-60-S	Small
11-3245-60-M	Medium
11-3245-60-L	Large
11-3245-60-XL	X-Large
11-3245-60-XXL	2X-Large



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Signs &amp; Safety



Youngstown #	Size
03-3060-80-S	Small
03-3060-80-M	Medium
03-3060-80-L	Large
03-3060-80-XL	X-Large
03-3060-80-XXL	2X-Large

**General Utility Plus Gloves**

- Durable non-slip reinforcement on palm, fingers and thumb
- Neoprene cuff adds support and secures fit
- Breathable stretch nylon on top of hand wicks moisture and heat
- Terry cloth thumb for wiping sweat and debris

**Winter Glove, Water Resistant, Knit Wrist**

- 3M Thinsulate lining
- Long knit wrist to keep out snow and ice
- Wing thumb, gunn pattern

Salisbury #	Size
SP-S	Small/Med
SP-L	Large/XL

**SALISBURY**

by Honeywell

**SALISBURY**

by Honeywell



Salisbury #	Size
UWG-WPGC-S	Small
UWG-WPGC-M	Medium
UWG-WPGC-L	Large
UWG-WPGC-XL	X-Large
UWG-WPGC-2X	2-Xlarge

**Winter Utility Glove, Gauntlet Style Cuff, Waterproof**

- 100% Waterproof, windproof and breathable
- Sport wool liner
- 3M Thinsulate lines top of hand, fingers and cuff
- Reinforced palm, non-slip saddle

**Kevlar Utility Glove**

- 100% Brushed Kevlar lining
- Level 4 (out of 5) on EN388 cut standard
- PVC Reinforced for durability
- Terry cloth brow wipe on back of thumb
- Double stitched

Salisbury #	Size
UWG-KLG/S	Small
UWG-KLG/M	Medium
UWG-KLG/L	Large
UWG-KLG/XL	X-Large
UWG-KLG/XXL	2X-Large

**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Signs &amp; Safety

**SALISBURY**

by Honeywell



Salisbury #	Size
UWG-GPU/S	Small
UWG-GPU/M	Medium
UWG-GPU/L	Large
UWG-GPU/XL	X-Large
UWG-GPU/2X	2X-Large

**Utility Plus Glove**

- All purpose, abrasion resistant
- PVC Reinforcement for durability
- One-piece back of hand with knuckle protection
- Terry cloth brow wipe on back of thumb
- Adjustable hook & pile closure

**Global Gloves 3200**

- Premium grade beige cow grain
- Drive style glove
- Keystone thumb

Global Glove #	Size
3200/S	Small
3200/M	Medium
3200/L	Large
3200/XL	X-Large
3200/2X	2X-Large
3200/3X	3X-Large



  
**Global Glove**  
 & Safety Manufacturing, Inc.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Saf/Grip Round Slings

### Saf/Grip Round Slings



The Saf/Grip Endless Round Sling is the most versatile. Capable of being used in vertical, choker and basket hitches, wear points can be shifted to extend sling life. Pliable body hugs the load and offers super strength and ease of handling. Slings feature identification tags indicating size, type and rated capacity.

Color Code	Stock No.	Approx. Body Diameter in Inches	Approx. Body Wt. Pounds/Ft.	Rated Capacity in Pounds					Minimum Length
				Vertical	Choker	Basket	60°	45°	
Purple	SR-1	0.60	0.20	2,600	2,100	5,200	4,500	3,700	3 ft.
Green	SR-2	0.80	0.30	5,300	4,200	10,600	9,200	7,500	3 ft.
Yellow	SR-3	1.00	0.50	8,400	6,700	16,800	14,500	11,900	3 ft.
Tan	SR-4	1.20	0.60	10,600	8,500	21,200	18,400	15,000	3 ft.
Red	SR-5	1.30	0.75	13,200	10,600	26,400	22,900	18,700	3 ft.
White	SR-6	1.40	0.90	16,800	13,400	33,600	29,100	23,800	6 ft.
Blue	SR-7	1.75	1.15	21,200	17,000	42,400	36,700	30,000	6 ft.
Orange	SR-8	2.00	1.30	25,000	20,000	50,000	43,300	35,400	6 ft.
Orange	SR-9	2.25	1.50	31,000	24,800	62,000	53,700	43,800	6 ft.
Orange	SR-10	2.50	2.00	40,000	32,000	80,000	69,300	56,600	6 ft.
Black	SR-11	3.00	2.50	53,000	42,400	106,000	91,800	74,900	7 ft.
Black	SR-12	3.25	3.50	66,000	52,800	132,000	114,300	93,300	7 ft.
Black	SR-13	3.75	4.00	90,000	72,000	180,000	155,900	127,300	7 ft.
Black	SR-13S	4.00	4.50	100,000	80,000	200,000	173,200	141,400	7 ft.

### Saf/Grip Eye & Eye Round Slings



Extra protective Cordura® cover adds durability. Sling jackets are color-coded by rated capacity. Choose from seven different colors to fit the rated capacity you need for your lift.

Color Code	Stock No.	Rated Capacity in Pounds					Minimum Length
		Vertical	Choker	Basket	60°	45°	
Purple	SR1-EE	2,600	2,100	5,200	4,500	3,700	4 ft.
Green	SR2-EE	5,300	4,200	10,600	9,200	7,500	4 ft.
Yellow	SR3-EE	8,400	6,700	16,800	14,500	11,900	4 ft.
Tan	SR4-EE	10,600	8,500	21,200	18,400	15,000	5 ft.
Red	SR5-EE	13,200	10,600	26,400	22,900	18,700	5 ft.
White	SR6-EE	16,800	13,400	33,600	29,100	23,800	7 ft.
Blue	SR7-EE	21,200	17,000	42,400	36,700	30,000	7 ft.

**The body of all Safeway Eye & Eye Round Slings is protected with a Cordura® Tubular Jacket for extra protection. Special Note: SR8-EE and larger now available. See SR chart above for capacities.**



Warning! Failure to follow proper care, use and inspection criteria may result in personal injury. Do not exceed rated capacities. Horizontal sling angles less than 30° shall not be used.

Cordura® is a registered trademark of DuPont.

**Consult factory prior to use in a chemically active environment and for capacities when used in multi-leg bridles or as towing slings.**




Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)




## Standard Nylon and Polyester Web Slings

### Eye & Eye Flat (Type 3)



### Eye & Eye Twist (Type 4)



Stock No.	Width	Ply	Rated Capacity in Pounds						Eye Length	Eye Width
			Vertical	Choker	Basket	60°	45°	30°		
EE1-601	1"	1	1,200	900	2,400	2,100	1,700	1,200	8"	1"
EE1-901	1"	1	1,600	1,200	3,200	2,800	2,300	1,600	8"	1"
EE2-601	1"	2	2,400	2,000	4,800	4,200	3,400	2,400	8"	1"
EE2-901	1"	2	3,200	2,500	6,400	5,500	4,500	3,200	8"	1"
EE3-601	1"	3	3,600	2,900	7,200	6,200	5,100	3,600	12"	1"
EE3-901	1"	3	4,100	3,300	8,200	7,100	5,800	4,100	12"	1"
EE4-601	1"	4	4,800	3,800	9,600	8,300	6,800	4,800	12"	1"
EE4-901	1"	4	6,100	4,900	12,200	10,500	8,600	6,100	12"	1"
EE1-6015	1.5"	1	1,650	1,320	3,300	2,850	2,300	1,650	8"	1.5"
EE2-6015	1.5"	2	3,300	2,640	6,600	5,700	4,650	3,300	8"	1.5"
EE1-9015	1.5"	1	2,350	1,860	4,700	3,900	3,200	2,350	8"	1.5"
EE2-9015	1.5"	2	4,650	3,720	9,300	8,050	6,570	4,650	8"	1.5"
EE1-60175	1.75"	1	2,100	1,600	4,200	3,600	2,950	2,100	8"	1.75"
EE2-60175	1.75"	2	4,200	3,200	8,400	7,270	5,900	4,200	8"	1.75"
EE1-602	2"	1	2,400	2,000	4,800	4,200	3,400	2,400	10"	2"
EE1-902	2"	1	3,200	2,500	6,400	5,500	4,500	3,200	10"	2"
EE2-602	2"	2	4,800	3,800	9,600	8,300	6,800	4,800	10"	2"
EE2-902	2"	2	6,400	5,000	12,800	11,100	9,000	6,400	10"	2"
EE3-602	2"	3	7,000	5,200	14,000	12,100	9,900	7,000	12"	2"
EE3-902	2"	3	8,200	6,600	16,500	14,300	11,600	8,200	12"	2"
EE4-602	2"	4	8,900	7,100	17,800	15,540	12,500	8,900	12"	2"
EE4-902	2"	4	12,200	9,800	24,400	21,100	17,200	12,200	12"	2"
EE1-603	3"	1	3,600	2,900	7,200	6,200	5,100	3,600	11"	1.5"
EE1-903	3"	1	4,800	3,800	9,600	8,300	6,800	4,800	11"	1.5"
EE2-603	3"	2	6,650	5,300	13,300	11,500	9,400	6,700	11"	1.5"
EE2-903	3"	2	8,900	7,200	17,800	15,400	12,600	8,900	11"	1.5"
EE3-603	3"	3	10,000	8,000	20,000	17,300	14,100	10,000	15"	1.5"
EE3-903	3"	3	12,300	9,900	24,600	21,300	17,400	12,300	15"	1.5"
EE4-603	3"	4	13,300	10,700	26,600	23,100	18,800	13,300	15"	1.5"
EE4-903	3"	4	18,000	13,500	36,000	31,100	25,400	18,000	15"	1.5"
EE1-604	4"	1	4,800	3,800	9,600	8,300	6,800	4,800	12"	2"
EE1-904	4"	1	6,400	5,000	12,800	11,100	9,000	6,400	12"	2"
EE2-604	4"	2	8,600	6,900	17,200	15,000	12,200	8,600	12"	2"
EE2-904	4"	2	12,000	9,600	24,000	20,800	17,000	12,000	12"	2"
EE3-604	4"	3	13,000	10,000	26,000	22,500	18,300	13,000	16"	2"
EE3-904	4"	3	15,300	12,200	30,600	26,500	21,800	15,300	16"	2"
EE4-604	4"	4	17,300	13,800	34,600	30,000	24,400	17,300	16"	2"
EE4-904	4"	4	22,000	17,600	44,000	38,100	31,100	22,000	16"	2"
EE1-905	5"	1	8,000	6,400	16,000	13,800	11,300	8,000	14"	1.75"
EE2-905	5"	2	14,250	11,400	28,500	24,600	20,100	14,250	14"	1.75"
EE3-905	5"	3	22,500	18,000	45,000	38,900	31,800	22,500	18"	2.5"
EE4-905	5"	4	30,000	22,500	60,000	51,900	42,400	30,000	18"	2.5"
EE1-606	6"	1	7,200	5,800	14,400	12,500	10,200	7,200	16"	2"
EE1-906	6"	1	9,600	7,600	19,200	16,600	13,600	9,600	16"	2"
EE2-606	6"	2	12,200	9,800	24,500	21,200	17,300	12,200	16"	2"
EE2-906	6"	2	17,000	13,000	34,000	29,400	24,000	17,000	16"	2"
EE3-606	6"	3	18,000	14,500	36,000	31,100	25,400	18,000	18"	3"
EE3-906	6"	3	23,000	18,400	46,000	39,800	32,500	23,000	18"	3"
EE4-606	6"	4	24,500	19,600	49,000	42,400	34,600	24,500	18"	3"
EE4-906	6"	4	33,000	24,600	66,000	57,100	46,700	33,000	18"	3"
EE1-908	8"	1	12,800	10,000	25,600	22,200	18,100	12,800	20"	3"
EE2-908	8"	2	22,800	18,000	45,600	39,500	32,200	22,800	20"	3"
EE3-908	8"	3	30,700	24,500	61,400	53,100	43,400	30,700	24"	4"
EE4-908	8"	4	44,000	35,200	88,000	76,200	62,200	44,000	24"	4"
EE1-910	10"	1	16,000	12,800	32,000	27,700	22,600	16,000	24"	3.5"
EE2-910	10"	2	28,000	22,500	56,000	48,500	39,500	28,000	24"	3.5"
EE3-910	10"	3	36,000	28,500	72,000	62,300	50,900	36,000	24"	5"
EE4-910	10"	4	55,000	44,000	110,000	95,200	77,700	55,000	24"	5"
EE1-912	12"	1	19,200	15,400	38,400	33,200	27,100	19,200	24"	4"
EE2-912	12"	2	33,600	26,750	67,200	58,200	47,500	33,600	24"	4"
EE3-912	12"	3	46,000	36,500	92,000	79,600	65,000	46,000	26"	6"
EE4-912	12"	4	66,000	52,800	132,000	114,300	93,300	66,000	32"	6"

\* Please specify Flat Eyes (Type 3) or Twist Eyes (Type 4) when ordering.  
 \* Slings 3" wide and over have tapered eyes.



**Warning:** Horizontal sling angles less than 30° shall not be used. Do not exceed rated capacity.









Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Standard Nylon and Polyester Web Slings

### Endless (Type 5)

The Endless is the most versatile sling. Wear points can be rotated and sling used in vertical, choker & basket hitches.

Stock No.	Width	Ply	Rated Capacity in Pounds					
			 Vertical	 Choker	 Basket	 60°	 45°	 30°
EN1-601	1"	1	2,400	2,000	4,800	4,200	3,400	2,400
EN1-901	1"	1	3,200	2,500	6,400	5,500	4,500	3,200
EN2-601	1"	2	4,800	3,800	9,600	8,300	6,800	4,800
EN2-901	1"	2	6,400	5,000	12,800	11,100	9,000	6,400
EN3-601	1"	3	7,200	5,800	14,400	12,500	10,200	7,200
EN3-901	1"	3	9,000	7,200	18,000	15,500	12,700	9,000
EN4-601	1"	4	9,600	7,700	19,200	16,600	13,600	9,600
EN4-901	1"	4	11,000	8,800	22,000	19,000	15,500	11,000
EN1-6015	1.5"	1	3,300	2,640	6,600	5,700	4,650	3,300
EN2-6015	1.5"	2	6,600	5,280	13,200	11,400	9,300	6,600
EN1-9015	1.5"	1	4,650	3,720	9,300	8,050	6,570	4,650
EN2-9015	1.5"	2	9,300	7,440	18,600	16,100	13,100	9,300
EN1-60175	1.75"	1	4,200	3,400	8,400	7,270	5,900	4,200
EN2-60175	1.75"	2	8,400	6,700	16,800	14,500	11,800	8,400
EN1-602	2"	1	4,800	3,800	9,600	8,300	6,800	4,800
EN1-902	2"	1	6,400	5,000	12,800	11,100	9,000	6,400
EN2-602	2"	2	9,600	7,700	19,200	16,600	13,600	9,600
EN2-902	2"	2	12,800	10,200	25,600	22,200	18,100	12,800
EN3-602	2"	3	13,300	10,700	26,600	23,100	18,800	13,300
EN3-902	2"	3	16,500	13,200	33,000	28,500	23,300	16,500
EN4-602	2"	4	17,800	14,200	35,500	30,800	25,100	17,800
EN4-902	2"	4	22,000	17,600	43,900	38,000	31,000	22,000
EN1-603	3"	1	7,200	5,700	14,400	12,500	10,200	7,200
EN1-903	3"	1	9,600	7,600	19,200	16,600	13,600	9,600
EN2-603	3"	2	13,300	10,500	26,600	23,100	18,800	13,300
EN2-903	3"	2	18,000	14,000	36,000	31,100	25,400	18,000
EN3-603	3"	3	20,000	16,000	40,000	34,600	28,200	20,000
EN3-903	3"	3	24,700	19,800	49,400	42,800	34,900	24,700
EN4-603	3"	4	26,700	21,300	53,300	46,200	37,600	26,700
EN4-903	3"	4	32,900	26,300	65,800	57,700	46,600	32,900
EN1-604	4"	1	9,600	7,700	19,200	16,600	13,600	9,600
EN1-904	4"	1	12,000	9,600	24,000	20,700	16,900	12,000
EN2-604	4"	2	17,300	13,500	34,600	30,000	24,400	17,300
EN2-904	4"	2	24,000	18,000	48,000	41,500	33,900	24,000
EN3-604	4"	3	25,900	20,700	51,800	44,800	36,600	25,900
EN3-904	4"	3	34,400	27,500	68,800	59,500	48,600	34,400
EN4-604	4"	4	34,600	27,600	69,100	59,900	48,800	34,600
EN4-904	4"	4	40,800	32,600	81,500	70,600	57,000	40,800
EN1-905	5"	1	16,000	12,000	32,000	27,700	22,600	16,000
EN2-905	5"	2	28,000	22,400	56,000	48,400	39,500	28,000
EN3-905	5"	3	42,000	33,600	84,000	72,700	59,300	42,000
EN4-905	5"	4	56,000	44,800	112,000	97,000	79,100	56,000
EN1-606	6"	1	14,400	11,500	28,800	25,000	20,300	14,400
EN1-906	6"	1	17,000	13,000	34,000	29,400	24,000	17,000
EN2-606	6"	2	24,500	19,600	49,000	42,400	34,600	24,500
EN2-906	6"	2	32,600	26,100	65,300	56,500	46,200	32,600
EN3-606	6"	3	36,800	29,400	73,400	63,700	51,900	36,800
EN3-906	6"	3	45,900	36,700	91,700	79,400	64,900	45,900
EN4-606	6"	4	49,000	39,200	97,900	84,500	69,200	49,000
EN4-906	6"	4	61,200	48,900	122,300	105,900	86,500	61,200
EN1-908	8"	1	25,600	20,500	51,200	44,300	36,200	25,600
EN2-908	8"	2	41,000	32,800	81,900	70,900	57,900	41,000
EN1-910	10"	1	32,000	25,600	64,000	55,400	45,200	32,000
EN2-910	10"	2	48,000	38,000	96,000	83,100	67,900	48,000
EN1-912	12"	1	38,400	30,700	76,800	66,500	54,300	38,400
EN2-912	12"	2	53,700	43,000	107,400	93,000	76,000	53,700

- Endless Slings are tapered upon special request only and at additional cost. Three and four ply slings cannot be tapered.
- For information on 3 and 4 ply slings not listed, please contact factory.



**Warning:** Horizontal sling angles less than 30° shall not be used. Do not exceed rated capacity.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Lighting



Streamlight #	Description
45116	LiteBox Rechargeable Lantern w/Shoulder Strap, Chargers & Charge Rack, Orange 8W Spot Bulb

**LiteBox Rechargeable Lantern**

- High-intensity halogen bi-pin bulb
- High-impact ABS thermoplastic housing with rubberized impact bumper, lens ring, and cushioned-grip handle
- 8WS Bulb: 150 lumens, 9 hour run time
- 20WS Bulb: 400 lumens, 3.5 hour run time

**E-Spot LiteBox Rechargeable Lantern**

- Three C4 LEDs with a 50,000 hour lifetime produce a uniform spot pattern
- Zero-maintenance 6V, 12Ah sealed lead acid battery
- High-impact ABS thermoplastic housing, rubberized impact bumper, lens ring and cushioned-grip handle
- Red and green LEDs give charge status feedback
- Includes AC/DC charge cords, shoulder strap and mounting rack
- 540 Lumens (high), 330 lumens (low)

Streamlight #	Description
45851	E-Spot LiteBox Rechargeable Lantern, Orange
45871	E-Spot LiteBox Rechargeable Lantern, Yellow



Streamlight #	Description
45937	Sealed Lead Acid Battery
45845	E-Spot LiteBox Upgrade Kit

**LiteBox Accessories**

- Battery; zero maintenance 6V, 12Ah, rechargeable up to 500 times
- Upgrade kit; converts halogen to LED, 540 lumens

**RADIORAY Halogen Portable**

- Includes:
  - ☐ Wireless hand-held remote
  - ☐ Suction cup and permanent mount shoe (7900)
  - ☐ Suction cup and magnetic mount shoe (7901/7951)
  - ☐ 15' cord with cigarette plug for 12V DC
- Unit size: 7" x 7" x 8"

Golight #	Description
7900	White w/Permanent Mount
7901	White w/Magnetic Shoe
7951	Black w/Magnetic Shoe



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Lighting



Streamlight #	Description
44900	Waypoint Pistol-Grip Spotlight with DC Cord, Yellow
44902	Waypoint Pistol-Grip Spotlight with DC Cord, Black

**Waypoint Pistol-Grip Battery-Powered Spotlight**

- Three modes: high, low, strobe
- C4 LED Illumination output
- 210 Lumens
- Powered by four C batteries (not included) or 12V DC power cord (included)
- Unlimited run time when using 12V DC cord
- High impact polycarbonate housing
- Includes lanyard
- Integrated stand for scene lighting

**Waypoint Rechargeable Pistol-Grip Spotlight, 44910**

- Three modes: high, low, strobe
- C4 LED Illumination output
- 370 Lumens (high), 30 lumens (low)
- Powered by rechargeable lithium ion battery
- Full recharges in four hours
- Rechargeable up to 800 times
- Trigger-style switch
- High impact polycarbonate housing, rubberized lens protector
- Includes high-strength adjustable lanyard
- Integrated stand for scene lighting
- Light will float, IPX 8 rated, waterproof to two meters

Streamlight #	Description
44910	Waypoint Rechargeable Pistol-Grip Spotlight, Yellow
44900	Waypoint NON-Rechargeable Pistol-Grip Spotlight, Yellow



Streamlight #	Description
61052	Septor LED, Yellow Headlamp

**Septor LED Headlamp**

- Class 1, Div 2 rating
- Low level battery indicator
- Soft flood light; good for up close work
- Powered by three AAA alkaline batteries (included)
- Seven 100,000 hr life ultra-bright, white LEDs
- 120 Lumens (7 LEDs), 45 lumens (3 LEDs), 13 lumens (1 LED)
- Runs up to 55 hrs. (single LED)
- 5.50 oz., 90° tilting head
- Adjustable elastic head strap, mounting plate and rubber hard hat strap included

**Trident HP Headlamp**

- Class 1, Div 2 rated
- Water resistant lightweight thermoplastic construction
- 80 lumens typical (C4 LED), 35 lumens typical (3 white), 11 lumens typical (1 LED)
- White C4 LED technology, shock resistant, with a 50,000 hour lifetime, three 5mm white LEDs
- Three AAA alkaline batteries
- 5.5 oz., 90° tilting head
- Adjustable elastic head strap, mounting plate and rubber hard hat strap included



Streamlight #	Description
61050	Trident HP, Yellow Headlamp



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Lighting



Streamlight #	Description
61200	3AA HAZ-LO, Yellow Headlamp

**3AA HAZ-LO Div 1 Headlamp**

- Class 1, Div 1 rated
- Powered by three AA alkaline batteries (included)
- One C4 LED 50,000 hour lifetime
- 11 hour run time, 120 lumens
- All openings O-ring sealed
- Unbreakable polycarbonate lens
- Push-button switch
- 7.1 oz, impact-resistant housing
- 90° tilting head
- Adjustable elastic head strap, mounting plate and rubber hard hat strap included

**Knucklehead Rechargeable Worklight**

- Shockproof dual C4 premium LED technology, impact-resistant
- 210° Articulating head that rotates a full 360°
- Four modes-high, low, moonlight and flash
- Dual power source: accepts rechargeable NiCd battery pack or four AA alkaline batteries (included)
- Rubber dome push-bottom actuator
- Removable magnet with 135 lb. pull strength; integrated storable hanghook
- High-impact nylon polymer construction
- 200 lumens (high); 63 lumens (low)

Streamlight #	Description
90627	Knucklehead LED Rechargeable Worklight, Yellow
90657	Knucklehead LED Rechargeable Worklight, Orange
90607	Knucklehead LED Rechargeable Worklight, Black



Streamlight #	Description
76132	PolyStinger LED Rechargeable Flashlight, Black

**PolyStinger LED Rechargeable Flashlight**

- Non-conductive nylon polymer with non-slip rubberized comfort grip
- Unbreakable polycarbonate lens with scratch-resistant coating
- Fits existing Stinger snap-in chargers
- Ten hour steady charge, 2.5 hour fast charge
- C4 LED Technology, shock-proof with a 50,000 hour lifetime
- 3-Cell, 3.6V NiCd sub-C battery is rechargeable up to 1,000 times
- Multi-function on/off push button switch, 385 lumens

**Stinger LED Rechargeable Flashlight**

- Light source: C4 LED technology, with a 50,000 hour lifetime
- 3-Cell, 3.6V nickel-cadmium sub-C battery is rechargeable up to 1,000 times
- 175 lumens
- 10 hours to fully recharge or 2.5 hour fast charger available
- Deep-dish parabolic reflector
- Machined aircraft aluminum body with non-slip rubberized comfort grip and anti-roll rubber ring
- Unbreakable polycarbonate lens with scratch-resistant coating
- 8.41" long, 12.4 oz.
- IPX4 rated for water-resistant operation
- Serialized for positive identification
- Black

Streamlight #	Description
75710	Stinger LED Flashlight without Charger
75715	Stinger LED Flashlight w/DC Fast Charger



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Lighting



Streamlight #	Description
25006	SI-20XP Rechargeable Flashlight with Charge Cord and Case, Black

**SL-20XP Rechargeable Flashlight**

- 8 Watt halogen bulb with 100 hour lifetime
- Lightweight nylon polymer case with non-slip rubber comfort grip
- Runs 1.5 hours, 145 lumens
- Three position push-button switch
- 5-Cell, 6.0-volt NiCd sub-C battery, rechargeable up to 1,000 times
- 13" long, water-resistant

**Stinger DS LED HP Rechargeable Flashlight**

- Dual switch technology
- Head switch operates independently from the tail cap switch
- Deep-dish parabolic reflector produces a long range targeting beam
- 350 Lumens
- 6,000 series machined aircraft aluminum with non-slip rubberized comfort grip
- Unbreakable polycarbonate lens with scratch-resistant coating
- O-ring sealed construction
- C4 LED Technology, impervious to shock with a 50,000 hour lifetime
- 3-Cell, 3.6V Ni-Cd sub-C battery is rechargeable up to 1,000 times

Streamlight #	Description
75863	Stinger DS LED HP Rechargeable Flashlight 120V AC/12V DC Black



Streamlight #	Description
74301	Strion LED Rechargeable Flashlight w/120V AC/DC Holder, Black
74303	Strion LED Rechargeable Flashlight w/120V AC, Black

**Strion LED Rechargeable Flashlight**

- C4 LED Technology, shock-resistant with a 50,000 hour lifetime
- 4-Modes: high (260 lumens), medium (130 lumens), low (65 lumens), and strobe
- Machined aircraft aluminum with anodized finish
- 5.90" long
- Push-button tailcap momentary switch; rotate tailcap constant on
- Lithium ion with on-board safety control circuit battery
- Snap-in charger holder that mounts in any position
- Water-resistant

**Stylus Pro Alkaline Battery-Powered Pen Light**

- Corrosion and water resistant
- Machined aircraft-grade aluminum alloy, Type II MIL-Spec anodize plating
- C4 LED lasts 30,000 hours
- 65 lumens
- Push button tail switch
- Powered by two AAA alkaline batteries
- Runs up to 6.5 regulated hours
- 5.3", 1.64 oz. with battery (included)

Streamlight #	Description
66118	Stylus Pro, Black Pen Light



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



<b>ASTM Labeling Chart</b> <b>Natural Rubber Electrical Insulating Gloves</b>			
Class Color	Proof Test Voltage AC/DC	Max. Use Voltage AC/DC	Insulating Rubber Glove Label
00 Beige	2,500 / 10,000	500 / 750	<b>10</b> ASTM D120 CLASS 00 MAX USE VOLT 500V AC EN60903 TYPE I 500V AC
0 Red	5,000 / 20,000	1,000 / 1,500	<b>10</b> ASTM D120 CLASS 0 MAX USE VOLT 1000V AC EN60903 TYPE I 1000V AC
1 White	10,000 / 40,000	7,500 / 11,250	<b>10</b> ASTM D120 CLASS 1 MAX USE VOLT 7500V AC EN60903 TYPE I 7500V AC
2 Yellow	20,000 / 50,000	17,000 / 25,500	<b>10</b> ASTM D120 CLASS 2 MAX USE VOLT 17000V AC EN60903 TYPE I 17000V AC
3 Green	30,000 / 60,000	26,500 / 39,750	<b>10</b> ASTM D120 CLASS 3 MAX USE VOLT 26500V AC EN60903 TYPE I 26500V AC
4 Orange	40,000 / 70,000	36,000 / 54,000	<b>10</b> ASTM D120 CLASS 4 MAX USE VOLT 36000V AC EN60903 TYPE I 36000V AC



Measure the circumference around the palm to determine the correct glove size. Allow for additional room if fabric glove liners are to be worn, especially with thermal liners.




Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Sleeve &amp; Leather Protector Sizing

Sizing Linemen's Sleeves			
STRAIGHT ARM SLEEVE-Figure 1			
A (in.)	B (in.)	C (in.)	D (in.)
<b>Regular</b>			
26.25	15.5	11.25	5.5
<b>Large</b>			
28.5	17	12.87	6.87
<b>Extra-Large</b>			
30	19	13.25	6.87
CURVED ARM SLEEVE-Figure 2			
A (in.)	B (in.)	C (in.)	D (in.)
<b>Regular</b>			
26.5	15.5	12.25	5.25
<b>Large</b>			
27.75	16	12.87	6.87
<b>Extra-Large</b>			
29.5	17.5	12.87	7



When choosing the proper sleeve size, they should fit comfortably, covering from the top of the shoulder to just inside the top of the glove. Select the shortest length possible while maintaining complete coverage to the shoulder.

This clearance table shows minimum distance allowed between protector glove cuff and the bead of the rubber glove, per ASTM F496 Specs.

Leather gloves are to be worn over rubber insulating gloves.

	Glove Class	Leather Protector Cuff	
		----- Cuff Line -----	
Minimum Distance from Protector and Rubber Glove	00, 0	1/2	1/2" from cuff
	1	1	1" from cuff
	2	2	2" from cuff
	3	3	3" from cuff
	4	4	4" from cuff



Leather Protectors are NOT to be used alone for electric shock protection. Always use gloves with appropriately insulated voltage ratings.



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

All Salisbury Gloves, Protectors and Sleeves shown are sold in pairs.

### Glove, Class 00, 11", Type I

- Black and red gloves are TYPE I natural rubber
- Blue gloves are TYPE II synthetic rubber

**SALISBURY**  
by Honeywell



Salisbury #	Size	Color
E0011B7	7	Black
E0011B8	8	Black
E0011B8H	8H	Black
E0011B9	9	Black
E0011B9H	9H	Black
E0011B10	10	Black
E0011B10H	10H	Black
E0011B11	11	Black
E0011B12	12	Black
E0011BL7	7	Blue
E0011BL8	8	Blue
E0011BL8H	8H	Blue
E0011BL9	9	Blue

E0011BL9H	9H	Blue
E0011BL10	10	Blue
E0011BL10H	10H	Blue
E0011BL11	11	Blue
E0011BL12	12	Blue
E0011R7	7	Red
E0011R8	8	Red
E0011R8H	8H	Red
E0011R9	9	Red
E0011R9H	9H	Red
E0011R10	10	Red
E0011R10H	10H	Red
E0011R11	11	Red
E0011R12	12	Red

### Glove, Class 0, Blue, 11" or 14", Type II

**SALISBURY**  
by Honeywell



Salisbury #	Size	Class	Length
E011BL7	7	0	11"
E011BL8	8	0	11"
E011BL8H	8H	0	11"
E011BL9	9	0	11"
E011BL9H	9H	0	11"
E011BL10	10	0	11"
E011BL10H	10H	0	11"
E011BL11	11	0	11"
E011BL12	12	0	11"
E014BL8	8	0	14"
E014BL8H	8H	0	14"
E014BL9	9	0	14"
E014BL9H	9H	0	14"
E014BL10	10	0	14"
E014BL10H	10H	0	14"
E014BL11	11	0	14"
E014BL12	12	0	14"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

Glove, Class 0, Black, 11", Type I

**SALISBURY**

by Honeywell

Salisbury #	Size	Class	Length
E011B8	8	0	11"
E011B8H	8H	0	11"
E011B9	9	0	11"
E011B9H	9H	0	11"
E011B10	10	0	11"
E011B10H	10H	0	11"
E011B11	11	0	11"
E011B12	12	0	11"

GK0011B Glove Kit, Class 00 Includes Black 11" Gloves, Leather Protectors and Glove Bag

**SALISBURY**

by Honeywell

Salisbury #	Size		
GK0011B7	7	GK0011B9H	9H
GK0011B8	8	GK0011B10	10
GK0011B8H	8H	GK0011B10H	10H
GK0011B9	9	GK0011B11	11
		GK0011B12	12

Glove, Class 0, Red 11" or 14", Type I



Salisbury #	Size	Class	Length
E011R7	7	0	11"
E011R8	8	0	11"
E011R8H	8H	0	11"
E011R9	9	0	11"
E011R9H	9H	0	11"
E011R10	10	0	11"
E011R10H	10H	0	11"
E011R11	11	0	11"
E011R12	12	0	11"
E014R7	7	0	14"
E014R8	8	0	14"
E014R9	9	0	14"
E014R9H	9H	0	14"
E014R10	10	0	14"
E014R10H	10H	0	14"
E014R11	11	0	14"
E014R12	12	0	14"

**SALISBURY**

by Honeywell

Glove, Class 0, Yellow, 11", Type I



Salisbury #	Size	Class	Length
E011Y7	7	0	11"
E011Y8	8	0	11"
E011Y8H	8H	0	11"
E011Y9	9	0	11"
E011Y9H	9H	0	11"
E011Y10	10	0	11"
E011Y10H	10H	0	11"
E011Y11	11	0	11"
E011Y12	12	0	11"
E014Y7	7	0	14"
E014Y8	8	0	14"
E014Y8H	8H	0	14"
E014Y9	9	0	14"
E014Y9H	9H	0	14"
E014Y10	10	0	14"
E014Y10H	10H	0	14"
E014Y11	11	0	14"
E014Y12	12	0	14"

**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Rubber Insulating PPE and Accessories

**GK0011BL Glove Kit, Class 00 Includes Blue 11" Gloves, Leather Protectors and Glove Bag**

**GK0011R Glove Kit, Class 00 Includes Red 11" Gloves, Leather Protectors and Glove Bag**

**GK011B Glove Kit, Class 0 Includes Black 11" Gloves, Leather Protectors and Glove Bag**

**SALISBURY**

by Honeywell



Salisbury #	Size
GK0011BL7	7
GK0011BL8	8
GK0011BL8H	8H
GK0011BL9	9
GK0011BL9H	9H
GK0011BL10	10
GK0011BL10H	10H
GK0011BL11	11

**SALISBURY**

by Honeywell



Salisbury #	Size
GK0011R7	7
GK0011R8	8
GK0011R8H	8H
GK0011R9	9
GK0011R9H	9H
GK0011R10	10
GK0011R10H	10H
GK0011R11	11
GK0011R12	12

**SALISBURY**

by Honeywell



Salisbury #	Size
GK011B8	8
GK011B8H	8H
GK011B9	9
GK011B9H	9H
GK011B10	10
GK011B10H	10H
GK011B11	11
GK011B12	12

**GK011BL Glove Kit, Class 0 Includes Blue 11" Gloves, Leather Protectors and Glove Bag**



**SALISBURY**

by Honeywell

Salisbury #	Size
GK011BL7	7
GK011BL8	8
GK011BL8H	8H
GK011BL9	9
GK011BL9H	9H
GK011BL10	10
GK011BL10H	10H
GK011BL11	11
GK011BL12	12

**GK011R Glove Kit, Class 0 Includes Red 11" Gloves, Leather Protectors and Glove Bag**



**SALISBURY**

by Honeywell

Salisbury #	Size
GK011R7	7
GK011R8	8
GK011R8H	8H
GK011R9	9
GK011R9H	9H
GK011R10	10
GK011R10H	10H
GK011R11	11



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Rubber Insulating PPE and Accessories

Glove, Red/Black, Straight Cuff



**SALISBURY**

by Honeywell

Salisbury #	Size	Class	Length
E114RB8	8	1	14"
E114RB8H	8H	1	14"
E114RB9	9	1	14"
E114RB9H	9H	1	14"
E114RB10	10	1	14"
E114RB10H	10H	1	14"
E114RB11	11	1	14"
E114RB12	12	1	14"
E214RB8	8	2	14"
E214RB8H	8H	2	14"
E214RB9	9	2	14"
E214RB9H	9H	2	14"
E214RB10	10	2	14"
E214RB10H	10H	2	14"
E214RB11	11	2	14"
E214RB12	12	2	14"
E216RB7	7	2	16"
E216RB8	8	2	16"

E216RB8H	8H	2	16"
E216RB9	9	2	16"
E216RB9H	9H	2	16"
E216RB10	10	2	16"
E216RB10H	10H	2	16"
E216RB11	11	2	16"
E216RB12	12	2	16"
E316RB8	8	3	16"
E316RB8H	8H	3	16"
E316RB9	9	3	16"
E316RB9H	9H	3	16"
E316RB10	10	3	16"
E316RB10H	10H	3	16"
E316RB11	11	3	16"
E316RB12	12	3	16"
E418RB9	9	4	18"
E418RB9H	9H	4	18"
E418RB10	10	4	18"
E418RB10H	10H	4	18"
E418RB11	11	4	18"

**GK011Y Glove Kit, Class 0 Includes  
Yellow 11" Gloves, Leather Protectors  
and Glove Bag**

Glove, Red/Black,  
Contour Cuff

**SALISBURY**

by Honeywell



Salisbury #	Size	Class	Length
E218CRB7	7	2	18"
E218CRB8	8	2	18"
E218CRB8H	8H	2	18"
E218CRB9	9	2	18"
E218CRB9H	9H	2	18"
E218CRB10	10	2	18"
E218CRB10H	10H	2	18"
E218CRB11	11	2	18"
E218CRB12	12	2	18"
E318CRB8	8	3	18"
E318CRB8H	8H	3	18"
E318CRB9	9	3	18"
E318CRB9H	9H	3	18"
E318CRB10	10	3	18"
E318CRB10H	10H	3	18"
E318CRB11	11	3	18"
E318CRB12	12	3	18"

Salisbury #	Size
GK011Y7	7
GK011Y8	8
GK011Y8H	8H
GK011Y9	9
GK011Y9H	9H
GK011Y10	10
GK011Y10H	10H
GK011Y11	11
GK011Y12	12



**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

Glove, Red/Black, Bell Cuff

**SALISBURY**

by Honeywell

Salisbury #	Size	Class	Length
E214BCRB9	9	2	14"
E214BCRB9H	9H	2	14"
E214BCRB10	10	2	14"
E214BCRB10H	10H	2	14"
E214BCRB11	11	2	14"
E216BCRB9	9	2	16"
E216BCRB9H	9H	2	16"
E216BCRB10	10	2	16"
E216BCRB10H	10H	2	16"
E216BCRB11	11	2	16"
E216BCRB12	12	2	16"
E218BCRB9	9	2	18"
E218BCRB9H	9H	2	18"
E218BCRB10	10	2	18"
E218BCRB10H	10H	2	18"
E218BCRB11	11	2	18"
E218BCRB12	12	2	18"
E316BCRB9	9	3	16"
E316BCRB9H	9H	3	16"
E316BCRB10	10	3	16"
E316BCRB10H	10H	3	16"
E316BCRB11	11	3	16"

Glove, Black, Straight Cuff

Salisbury #	Size	Class	Length
E116B7	7	1	16"
E116B8	8	1	16"
E116B8H	8H	1	16"
E116B9	9	1	16"
E116B9H	9H	1	16"
E116B10	10	1	16"
E116B10H	10H	1	16"
E116B11	11	1	16"

**SALISBURY**

by Honeywell

**SALISBURY**

by Honeywell

Glove, Red/Black, Straight Cuff



Glove, Red/Black, Contour Cuff



Salisbury #	Size	Class	Length
E318CRB8	8	3	18"
E318CRB8H	8H	3	18"
E318CRB9	9	3	18"
E318CRB9H	9H	3	18"
E318CRB10	10	3	18"
E318CRB10H	10H	3	18"
E318CRB11	11	3	18"
E318CRB12	12	3	18"

**SALISBURY**

by Honeywell

Salisbury #	Size	Class	Length
E218RB8	8	2	18"
E218RB8H	8H	2	18"
E218RB9	9	2	18"
E218RB9H	9H	2	18"
E218RB10	10	2	18"
E218RB10H	10H	2	18"
E218RB11	11	2	18"
E218RB12	12	2	18"



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Rubber Insulating PPE and Accessories

### Leather Protector, Cowhide, OAL 14"

- Top grain cowhide
- Provides excellent protection for rubber insulating gloves
- Features adjustable strap with non-metallic buckles
- Orange cuff



**SALISBURY**  
by Honeywell

Salisbury #	Size
ILP5S8	8/8H
ILP5S9	9/9H
ILP5S10	10/10H
ILP5S11	11/11H
ILP5S12	12

### Leather Protector, Cowhide, OAL 12"

- Top grain cowhide
- Provides excellent protection for rubber insulating gloves
- Orange cuff



**SALISBURY**  
by Honeywell

Salisbury #	Size
ILP3S/8	8/8H
ILP3S/9	9/9H
ILP3S/10	10/10H
ILP3S/11	11/11H
ILP3S/12	12

### GK214YB Glove Kit, Class 2 Includes 14" Yel/Blk Gloves, Leather Protectors and Glove Bag



**SALISBURY**  
by Honeywell

Salisbury #	Size	Type
GK214YB/8	8	Straight Cuff
GK214YB/8H	8H	Straight Cuff
GK214YB/9	9	Straight Cuff
GK214YB/9H	9H	Straight Cuff
GK214YB/10	10	Straight Cuff
GK214YB/10H	10H	Straight Cuff
GK214YB/11	11	Straight Cuff
GK214YB/11H	11H	Straight Cuff
GK214BCYB/9H	9H	Bell Cuff
GK214BCYB/10	10	Bell Cuff
GK214BCYB/10H	10H	Bell Cuff
GK214BCYB/11	11	Bell Cuff
GK214BCYB/11H	11H	Bell Cuff
GK214BCYB/12	12	Bell Cuff

### Glove and Sleeve Bag

- Heavy duty canvas
- Hook and loop closure
- Double stitched rolled edges add extra strength
- Grommet holes in the bottom of bag for ventilation
- Back snap for hanging



Buckingham #	Description
521	Glove Pocked Measures 17" x 4", Sleeve Pocket Measured 20" x 4"

### Leather Protector, Goatskin, OAL 10"

- Top grain goatskin
- Pull strap with non-metal buckle
- Provides excellent protection for rubber insulating gloves
- For Class 0 or 00 rubber gloves



**SALISBURY**  
by Honeywell

Salisbury #	Size
ILPG10A7	7
ILPG10A8	8/8H
ILPG10A9	9/9H
ILPG10A10	10/10H
ILPG10A11	11/11H
ILPG10A12	12



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

### Sleeve and Combo Bags

- Canvas duck with double stitching
- Flap over top with snap fasteners
- Reinforced quick-release snap for attachment to belt
- Grommets in the bottom provide drainage



Estex #	Description
2449-CE	12" x 4" x 29.5", Sleeve Bag, Canvas
2449-TU-C	12" x 4" x 29", Combo Sleeve and Glove Bag, Canvas
2449-TU-V	12" x 4" x 29", Combo Sleeve and Glove Bag, Vinyl

### Glove Bag, 1-Pocket

- Canvas duck with double stitching
- Flap over top with snap fasteners
- Reinforced quick-release snap for attachment to belt
- Grommets in the bottom provides drainage



Estex #	Description
2210	8" x 2" x 12", for 11" Gloves
2220	8" x 4" x 15", for 14" Gloves
2223	8" x 4" x 18", for 16" Gloves
2226	8" x 4" x 20", for 18" Gloves

### Line Hose Bag

- Rated at 80 lbs. working load limit
- Heavy weight canvas duck
- Black engineered polymer bottom
- Drainage holes
- Polymer ring, IZOD impact strength, 0.65 ft lbs. per in as per ASTM D256
- Brass swivel snap



Estex #	Description
1950-60	12" x 60"
1950-66	12" x 66"
1950-96	12" x 96"

### Dipped Sleeve, Red/Yellow, Extra Curved Arm



by Honeywell

Salisbury #	Size	Class
D2RRY-EC	Reg	2
D2LRY-EC	Large	2
D2XLRY-EC	X-Large	2
D3RRY-EC	Reg	3
D3LRY-EC	Large	3
D3XLRY-EC	X-Large	3

### Dipped Sleeve, Straight Arm



by Honeywell

Salisbury #	Size	Class	Color
D2RRB-ST	Reg	2	Red/Black
D2LRB-ST	Large	2	Red/Black
D2XLRB-ST	X-Large	2	Red/Black
D2RYB-ST	Reg	2	Yellow/Black
D2LYB-ST	Large	2	Yellow/Black
D2XLYB-ST	X-Large	2	Yellow/Black



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Rubber Insulating PPE and Accessories

**SALISBURY**

by Honeywell

**Dipped Sleeve,  
Extra Curved Arm**

Salisbury #	Size	Class	Color
D2RRB-EC	Reg	2	Red/Black
D2LRB-EC	Large	2	Red/Black
D2XLRB-EC	X-Large	2	Red/Black
D3RRB-EC	Reg	3	Red/Black
D3LRB-EC	Large	3	Red/Black
D3XLRB-EC	X-Large	3	Red/Black
D2RRY-EC	Reg	2	Red/Yellow
D2LRY-EC	Large	2	Red/Yellow
D2XLRY-EC	X-Large	2	Red/Yellow


**Molded Sleeves****SALISBURY**

by Honeywell

Salisbury #	Size	Class	Color
2RY	Reg	2	Yellow
2LY	Large	2	Yellow
2XLY	X-Large	2	Yellow
2RB	Reg	2	Black
D2LB	Large	2	Black
D2XLB	X-Large	2	Black
3RY	Reg	3	Yellow
3LY	Large	3	Yellow
3XLY	X-Large	3	Yellow

**Slotted Style Blanket**

- Type II SALCOR
- Reinforced beaded edge and 28 eyelets




Salisbury #	Description
15	22" x 22", Orange, ASTM Class 4, Type II
1100	36" x 36", Black, ASTM Class 2, Type II
1300	36" x 36", Orange, ASTM Class 4, Type II

**SALISBURY**

by Honeywell

**Solid Eyelet Style Blanket**

- Type II SALCOR or Type 1 natural rubber
- Reinforced beaded edge and eyelets



Salisbury #	Description
13	22" x 22", Orange, ASTM Class 4, Type II, 28 Eyelets
1000E	27" x 36", Orange, ASTM Class 4, Type II, 6 Eyelets
300E	36" x 36", Orange, ASTM Class 2, Type I, 6 Eyelets
900E	36" x 36", Orange, ASTM Class 4, Type II, 6 Eyelets
901E	36" x 36", Black, ASTM Class 4, Type II, 6 Eyelets

**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Rubber Insulating PPE and Accessories

### Switchboard Matting

- Placed permanently in front of switchgear, motor control centers and other high voltage apparatus
- Corrugated surface acts as safety tread
- ASTM Class 2

Matting Cross-Section



Salisbury #	Description
M30-2	Class 2, 1/4" x 30" x 25 yds
M36-2	Class 2, 1/4" x 36" x 25 yds
M48-2	Class 2, 1/4" x 48" x 25 yds

### Roll Blanket

- Made from a high strength fabric reinforced type II rubber
- Easy to cut
- Flexible to -40°F/C
- Highly puncture and tear resistant
- ASTM Class 0 or 1



Salisbury #	Description
RLB0	3' x 30', Yellow, Class 0
RLB1	3' x 30', Yellow/Orange, Class 1
RLBPVC1-36	3' x 30', Clear PVC, Class 1
RLBPVC1-48	4' x 30', Clear PVC, Class 1

### Straight Line Hose, Conventional System

- Flexible in cold weather; not damaged by ozone or ultraviolet rays
- RIB-GRIP Locking System
- Type II SALCOR
- ASTM Class 2 or 3



Salisbury #	ID x Length	Case	Type
OR100-6	1" x 6"	2	II
OR125-45	1.25" x 4.5"	2	II
OR125-6	1.25" x 6"	2	II
OR150-6	1.5" x 6"	3	II

### Connector End Line Hose, Conventional System

- Flexible in cold weather; not damaged by ozone or ultraviolet rays
- RIB-GRIP Locking System
- Type II SALCOR
- ASTM Class 2 or 3



Salisbury #	ID x Length	Class	Type
OR100-6C	1" x 6"	2	II
OR100-45C	1" x 4.5"	2	II
OR125-45C	1.25" x 4.5"	2	II
OR125-6C	1.25" x 6"	2	II
OR150-45C	1.5" x 4.5"	3	II
OR150-6C	1.5" x 6"	3	II



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

### Insulator Cover, Conventional System

- Orange, weather resistant Type II SALCOR
- RIB-GRIP Locking System
- Large Diameter arm overlaps the small arm to provide complete insulation
- ASTM Class 2 or 3

**SALISBURY**

by Honeywell



Salisbury #	Description
OJRG	16" x 6.5", Class 2, for Use with Insulator Class 55-4, 1" Line Hose Size
OKRG	16" x 8", Class 3, for Use with Insulator Class 55-5, Line Hose Size 1.25", 1.5"

### Dead End Protector, Extended Lip SU System

- Quickly cover dead-ends or polymer insulators
- RIB-GRIP Locking System
- Type II SALCOR
- ASTM Class 4
- The only complete flexible cover up for use on voltages through 34.5kV



**SALISBURY**

by Honeywell

Salisbury #	Description
OR134	5" x 37" Class 4 Type II, Fits Bell Size 3"-4.25", Orange

### Straight Line Hose, Extended Lip SU System

- Flexible in cold weather; not damaged by ozone or ultraviolet rays
- RIB-GRIP Locking System
- Type II SALCOR
- ASTM Class 4

**SALISBURY**

by Honeywell



Salisbury #	ID x Length	Class	Type
SU150-45	1.5" x 4.5"	4	II
SU150-6	1.5" x 6"	4	II

### Connector End Line Hose, Extended Lip SU System

- Flexible in cold weather; not damaged by ozone or ultraviolet rays
- RIB-GRIP Locking System
- Type II SALCOR
- ASTM Class 4

**SALISBURY**

by Honeywell



Salisbury #	ID x Length	Class	Type
SU150-45C	1.5" x 4.5"	4	II
SU150-6C	1.5" x 6"	4	II

### Cross Arm Cover, Conventional System

- Reduces stress on line hose or jumpers
- Fits standard cross arm pin spacing and each unit has interior ribs to minimize shifting on the arm
- Type II SALCOR
- ASTM Class 2

Salisbury #	Description
145	Use on Cross Arms Up To 4" x 4.5", Class 2



**SALISBURY**

by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

### Cutout Cover, Conventional System

- Can be used for overhead cutouts as well as for underground pad-mount applications
- Type II SALCOR
- ASTM Class 2 or 4



**SALISBURY**


by Honeywell

Salisbury #	Description
CC24	24" x 15" x 3.5", Class 2
CC30	30" x 20" x 7", Class 4

### Self-Securing Cable End Cap

- Keep moisture and contamination off trimmed cable ends
- For underground distribution
- Applied with rubber gloves
- Type II SALCOR
- ASTM Class 2

Salisbury #	ID x Length	Class	Type
117	1.38" x 10"	2	II
173	.81" x 6"	2	II
178	3.19" x 16"	2	II



**SALISBURY**

by Honeywell

### Tagging Device

- Used to tag opened disconnect switches
- Fits over the head of switch sticks for application
- Molded orange SALCOR

Salisbury #	Description
TD	7.25" Long Slot: 2.13" x .63" Cup: 2.5" x 1.75"



**SALISBURY**

by Honeywell

### Lightning Arrester Cover

- Can be applied with rubber gloves or hot stick
- Slot allows cap to fit directly over arrester and line connection
- Type II SALCOR
- ASTM Class 4



**SALISBURY**

by Honeywell

Salisbury #	ID x Length	Class	Type
536A	4.5" x 15"	4	II

### Spade Cover

- Provide temporary insulation when working in pad mount transformers and other electrical apparatus
- Molded orange SALCOR
- ASTM Class 2



**SALISBURY**

by Honeywell

Salisbury #	Description
SC4	2.75" x 4.4" x 10.75", 1" Lip Extension
SC5	3" x 6" x 10", 2" Lip Extension



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Rubber Insulating PPE and Accessories

### Air Gap Pole Guard

- Installed before setting new poles to guard against accidental line contact
- Made from orange, Type I ABS, cold weather, high impact thermoplastic
- Drilled rope handles
- ASTM Class 4

Salisbury #	Length	Diameter	Class
2496	6'	9"	4
2466	6'	12"	4



**SALISBURY**  
by Honeywell



**SALISBURY**  
by Honeywell

Salisbury #	Description
2389	ABS/PVC 4' Stick Type III Class 4, Grade 1

### Versa Guards

- Designed so that two guards can be coupled together to cover most 13 kV single and double arm, pin and post constructions, 3.92'

### Polyethylene Line Guard

- 1/3 the weight of similar rubber hose
- Snap together feature with male and female connecting ends
- High visibility yellow color
- Large I.D. than traditional rubber hoses (1.77" compared to 1.25")
- Brush contact only

Hastings #	Description
6050	5', 15kV
6060	6', 15kv
6055	5', 25kV
6065	6', 25kV



**HASTINGS**  
A WORLDWIDE SUPPLIER OF  
Hot Line Tools & Equipment



**SALISBURY**  
by Honeywell

Salisbury #	Description
21116	Standard Bushing Cover Only
21317	Tri-Port Bushing Cover Only

### Silicone Bushing Covers

- Protect against wildlife contacts
- Ozone and UV resistant silicone rubber
- RUS Accepted

### Rubber Overshoes

- Ozone resistant yellow rubber-100% waterproof
- Lined in fabric for easy slip on and off
- Available in whole and half sizes (6-12) and whole sizes (13-17)

Salisbury #	Description
51510	Deep Heel



**SALISBURY**  
by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

### Overshoe Non-Buckle, Dielectric 20kV

- 100% Waterproof and made from premium grade ozone resistant rubber
- Non-skid bar tread outsole
- Deep heel cavity can lock onto ladder rungs
- 100% Tested to requirements of ASTM F1116
- Available in whole sizes (7-16) only



**SALISBURY**

by Honeywell

Salisbury #	Description	Size
51511/9	Non-Buckle Overshoe, Bob Sole	9
51511/10	Non-Buckle Overshoe, Bob Sole	10
51511/11	Non-Buckle Overshoe, Bob Sole	11
51511/12	Non-Buckle Overshoe, Bob Sole	12
51511/13	Non-Buckle Overshoe, Bob Sole	13
51511/14	Non-Buckle Overshoe, Bob Sole	14

### Overshoe Non-Buckle, Dielectric 20kV

- Ozone resistant yellow rubber-100% waterproof
- Outsole t tested to ASTM F2413-05
- Available in whole sizes (6-17) only



**SALISBURY**

by Honeywell

Salisbury #	Description	Size
51581/9	Storm Rubber	9
51581/10	Storm Rubber	10
51581/11	Storm Rubber	11
51581/12	Storm Rubber	12
51581/13	Storm Rubber	13
51581/14	Storm Rubber	14
51581/15	Storm Rubber	15

### 17" Full Cut Overboot, Dielectric 20kV

- Ozone resistant yellow rubber-100% waterproof
- Outsole tested to ASTM F2413-05
- Anti-skid bar tread sole
- Available in whole sizes (7-17) only



**SALISBURY**

by Honeywell

Salisbury #	Description	Size
21402/9	Full Cut Overshoe, 17"	9
21402/10	Full Cut Overshoe, 17"	10
21402/11	Full Cut Overshoe, 17"	11
21402/12	Full Cut Overshoe, 17"	12
21402/13	Full Cut Overshoe, 17"	13
21402/14	Full Cut Overshoe, 17"	14
21402/15	Full Cut Overshoe, 17"	15



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

### Overshoe 2-Buckle, Dielectric 20kV

- 100% Waterproof and made from premium grade ozone resistant rubber
- Non-skid bar tread outsole
- Deep heel cavity can lock onto ladder rungs
- 100% Tested to requirements of ASTM F1116
- Available in whole sizes (7-17) only

Salisbury #	Description	Size
51512/9	2-Buckle Overshoe, Bob Sole	9
51512/10	2-Buckle Overshoe, Bob Sole	10
51512/11	2-Buckle Overshoe, Bob Sole	11
51512/12	2-Buckle Overshoe, Bob Sole	12
51512/13	2-Buckle Overshoe, Bob Sole	13
51512/14	2-Buckle Overshoe, Bob Sole	14
51512/15	2-Buckle Overshoe, Bob Sole	15



**SALISBURY**  
by Honeywell

**SALISBURY**  
by Honeywell



Salisbury #	Description	Size
21405WT/11	Full Cut Overboot, 17"	11
21405WT/12	Full Cut Overboot, 17"	12
21405WT/13	Full Cut Overboot, 17"	13
21405WT/14	Full Cut Overboot, 17"	14
21405WT/15	Full Cut Overboot, 17"	15

### Electrigrard, 20kV Dielectric Overboot

- 100% Waterproof and made from premium grade ozone resistant rubber
- 14" and 17" available
- Wider opening and pull handles
- 100% Tested to requirements of ASTM F1116
- Available in whole sizes (7-16) only

**SALISBURY**  
by Honeywell

### Ten-Four Glove Dust

- Absorbs moisture and perspiration when wearing rubber gloves

Salisbury #	Description
10-4	5 oz. Squeeze Bottle



**SALISBURY**  
by Honeywell

### Super SALCO Detergent

- Concentrated detergent with grease release formula
- Suitable for washing rubber gloves, sleeves and other specialty equipment

Salisbury #	Description
S4	1 gal Jug
S5	5 gal Drum



### SALCON Silicone Spray

- Reduces friction on SALCOR or natural rubber products
- May be used to spray spark plugs and battery terminals in damp weather

Salisbury #	Description
S99	16 oz. Aerosol Can



**SALISBURY**  
by Honeywell



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Rubber Insulating PPE and Accessories

American  
**Polywater**  
Corporation



Polywater #	Size
RBG-D72	72-Count Saturated Wipe Dispenser
RBG-1	Individual Saturated Wipe
RBG-35LR	1 qt. Bottle with Sprayer
RBG-128	1 gal. Bottle
RBG-640	5 gal. Pail

### Rubber Goods Cleaner

- Specially formulated water-based cleaner for removing dirt, grease and grime from linemen's gloves, sleeves, jumper cables and other rubber goods
- Safe for use on all natural and synthetic rubbers
- Contains no hazardous ingredients and is pH neutral
- Completely biodegradable and safe for the environment

### Blanket Accessories



Blanket Canister



MB6



20



HS21



21



Salisbury #	Description
20	8.5" Wood Blanket Clamp Pin w/Pin Boots
21	9.5" Nylon Blanket Clamp Pin w/Pin Boots
25	7" Wood Blanket Clamp Pin w/o Pin Boots
HS21	9.5" Nylon Blanket Clamp Pin w/Pin Boots
MB6	Magnetic Blanket Button
P2	5" x 37" Orange, Hi-Impact Polyethylene Blanket Canister for 1-2 Blankets
P4	7" x 37" Orange, Hi-Impact Polyethylene Blanket Canister for 1-4 Blankets
P6	9" x 37" Orange, Hi-Impact Polyethylene Blanket Canister for 1-6 Blankets

**SALISBURY**

by Honeywell

### Sleeve Accessories



**SALISBURY**  
by Honeywell



Salisbury #	Description
B-22	Two-Piece Sleeve Buttons (4)
H1-NB	Sleeve Harness w/o Buttons
S1	15" Sleeve Strap w/Buttons
S1-NB	15" Sleeve Strap w/o Buttons



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Rubber Insulating PPE and Accessories

### Stinger Cover

- Protect against phase to phase and phase to ground wildlife contacts
- Can be installed without disconnecting the lead wire from the bushing
- Made from ozone and UV resistant SALCOR elastomer in grey color

Salisbury #	ID x Length
38-50SC	3/8" x 50'
38-100SC	3/8" x 100'
58-12SC	5/8" x 12'
58-50SC	5/8" x 50'
58-100SC	5/8" x 100'
34-12SC	3/4" x 12'
34-25SC	3/4" x 25'



**SALISBURY**  
by Honeywell

### Glove Accessories



**SALISBURY**  
by Honeywell

Salisbury #	Description
G99	Glove Inflator Kit
G100	Glove Inflator Kit with Adapter
INF-2	Standard Bench Model Inflator with Air-Line Connection
INF-3	Standard Floor Model Inflator



Utility Solutions #	Pole Range	Length
USCP-001	6"-11" Diameter	16"
USCP-002	11"-20" Diameter	23"

### Klondike Clamps

- Quickly and safely secures rubber blankets in position on poles without damaging the blankets
- Molded from tough weather-resistant polymer
- Assembled completely with stainless steel hardware

### Wildlife ZapShield

- Designed for distribution substation equipment bushing of 15kV and 25kV
- Rauck-Shock technology engineered polymer
- Minimizes occurrences of animal related electric service interruptions
- Delivers non-lethal electrostatic discharge when contacted by animal

Rauckman #	Description
W-1525R	Red Wildlife Animal Guard
W-1525G	Gray Wildlife Animal Guard



**RAUCKMAN**  
Utility Products



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Clothing



Justin FR #	Colors
JW 11000	Navy, Tan

**Justin FR J-TEK Tough Ripstop Pants**

- 100% Cotton Mini Ripstop fabric
- Straight legged design to allow an easy fit over work boots
- Weather-washed so they have broken in comfort from first wear
- Dual certified to NFPA 2112 and 70E
- ATPV rating of 11

**Available Sizes:**

Waist	Inseam (even sizes only)
28"	30"
30"	30"-32"
32"	30"-34"
34"	30"-36"
36"-50"	32"-36"

**Justin FR J-TEK Treater Canvas Pants**

- 88% cotton and 12% nylon canvas fabric
- ATPV rating of 15 and a predicted 7% body burn
- Dual certified to NFPA 2112 and 70E
- Straight leg design to fit easily over work boots
- Weather-washed for comfort from first wear

**Available Sizes:**

Waist	Inseam (even sizes only)
28"	30"
30"	30"-32"
32"	30"-34"
34"	30"-36"
36"-50"	32"-36"

Justin FR #	Colors
JW 11001	Navy



Justin FR #	Colors
JW 11002	Realtree

**Justin FR J-TEK Realtree Camo Pants**

- 100% cotton twill fabric
- Dual-certified NFPA 2112 and 70E
- ATPV rating of 8.5
- Straight leg design to fit easily over work boots
- Weather-washed for a comfortable fit

**Available Sizes:**

Waist	Inseam (even sizes only)
28"	30"
30"	30"-32"
32"	30"-34"
34"	30"-36"
36"-50"	32"-36"



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Clothing

**Justin FR J-TEK Relaxed Fit Jeans**

- 100% cotton denim with a relaxed, comfortable fit
- Dual certified to NFPA 2112 and 70E
- ATPV rating of 17
- Dark wash with wide waistband and wide belt loops

Justin FR #	Colors
JW11006	Indigo

**Available Sizes:**

Waist (even sizes)  
30"-50"

Inseam (even sizes only)  
30"-36"



Justin FR #	Colors
JW22000	Red, Navy

**Justin FR J-TEK Breathable Cotton Polo**

- 100% Cotton for a comfortable yet professional feel
- Raglan sleeves and gusseted sides to allow flexibility and increased mobility
- No-roll collar and ribbed cuffs gives this shirt a clean look and feel

**Available Sizes:**

Regular      Long  
S-5XL      L-2XL

**Justin FR J-TEK Shift Crew Tee**

- 100% cotton, this tee is breathable and absorbent
- Raglan sleeves and gusseted sides gives ease of movement without restraint
- Crew neck collar with a V-front stitch
- ATPV rating of 9.6.

Justin FR #	Colors
JW22005	Grey/Navy, Navy/Grey, Tan/Black

**Available Sizes:**

Regular      Long  
S-5XL      L-2XL



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Clothing



Justin FR #	Colors
JW44010	Black

**Justin FR J-TEK Polartec Jacket**

- Highly compact knit fabric of Polartec Wind Pro FR fleece
- Wind and water resistant
- Mock neck collar adds protection against
- Dual certified to NFPA 2112 and 70E
- ATPV rating of 16.

**Available Sizes:**

Regular  
S-5XL

**Justin FR J-TEK Polartec Hoodie**

- Polartec Wind Pro FR Fleece with highly compact knit
- Wind and water resistant
- Hoodie includes mock neck collar
- Front pockets with zip closure and contrast stitching for increased durability.

**Available Sizes:**

Regular  
S-5XL

Justin FR #	Colors
JW44030	Navy



Justin FR #	Colors
JW44010RT	Black/Realtree

**Justin FR J-TEK Realtree Polartec Jacket**

- Polartec Wind Pro FR Fleece with highly compact knit
- Wind and water repellent
- Dual certified to NFPA 2112 and 70E, along with an
- ATPV rating of 8.5.
- Mock neck collar to help fight the elements.

**Available Sizes:**

Regular  
S-5XL



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Clothing

**Justin FR J-TEK Realtree Polartec Vest**

- Polartec Wind Pro FR Fleece with highly compact knit which repels wind and water to keep you comfortable while you work.
- Dual certified to NFPA 2112 and 70E
- ATPV rating of 8.6.
- Can be layered with other flame resistant clothes for full body protection.
- Mock neck collar for added protection against the elements.

**Available Sizes:**

Regular  
S-5XL

Justin FR #	Colors
JW44015	Black/Realtree



**TINGLEY**  
A TRADITION SINCE 1896

Tingley #	Sizes
O44122	S-5XL

**Eclipse Overall**

- Quad-Hazard, High Visibility
- Liquid Proof, Arc Flash and Flash Fire Protection
- Snap fly front
- Non-conductive hardware
- Heavy duty quick release buckles and crossover
- Hook & loop take-up straps on ankle cuffs for adjustable fit
- ASTM F2733, ASTM F1891, ANSI 107 Class 3

**Eclipse Jacket**

- Quad-Hazard protection, high visibility, liquid proof, arc flash and flash fire protection
- Thermo-Grid technology helps block out heat energy
- Chemically resistance to many acids, oils, alcohols, salts and alkalizes
- Zipper/storm fly front with snap closure and hidden hardware
- Oversized 3 piece hood with adjustable hook & loop take-up straps
- Non-conductive, non-corrosive hardware
- D-ring access for fall protection harness
- Hook & loop take-up straps on wrists for adjustable fit
- Adjustable elastic draw cord for added protection
- Full-vented cape back for improved air circulation
- ASTN F2733, ASTM F1891, ANSI 107 Class 3

Tingley #	Sizes
J44122	S-5XL



**TINGLEY**  
A TRADITION SINCE 1896



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Application For Credit

SPECIAL FLEET SERVICE, INC.  
 2500 S. MAIN STREET  
 HARRISONBURG, VA 22801  
 PHONE: 540-433-7727  
 FAX: 540-438-9502

OUR NORMAL CREDIT TERMS: NET 30 DAYS

NAME OF FIRM OR INDIVIDUAL	YEARS AT THIS ADDRESS
----------------------------	-----------------------

NAME OF OWNER

ADDRESS

CITY	STATE	ZIP	AREA CODE PHONE #
------	-------	-----	-------------------

ACCOUNTING CONTACT: \_\_\_\_\_ FAX: \_\_\_\_\_

THE FOLLOWING INFORMATION MUST BE PROVIDED. IT WILL BE HELD IN THE STRICTEST CONFIDENCE.

FINANCE: _____			
BANK	BANK ADDRESS		
BANK OFFICER OR DEPARTMENT	PHONE	FAX	

REFERENCES:

1	BUSINESS NAME	COMPLETE ADDRESS	ZIP	PHONE	FAX
2	BUSINESS NAME	COMPLETE ADDRESS	ZIP	PHONE	FAX
3	BUSINESS NAME	COMPLETE ADDRESS	ZIP	PHONE	FAX
4	BUSINESS NAME	COMPLETE ADDRESS	ZIP	PHONE	FAX

\*\*\*\*\* IF TAX EXEMPT, PLEASE PROVIDE EXEMPTION FORM



**Toll Free: 800-796-9027 Fax: 540-438-9502**

**[www.specialfleettools.com](http://www.specialfleettools.com)**

# Rubber Goods Testing Form

Customer Info: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Bill To: (if different): \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Purchase Order #: \_\_\_\_\_

Date: \_\_\_\_\_

Contact Person: \_\_\_\_\_

Phone #: \_\_\_\_\_

	<u>Class 00</u>	<u>Class 0</u>	<u>Class 1</u>	<u>Class 2</u>	<u>Class 3</u>	<u>Class 4</u>
Pairs of Gloves	_____	_____	_____	_____	_____	_____
Pairs of Sleeves	_____	_____	_____	_____	_____	_____
Number of Blankets	_____	_____	_____	_____	_____	_____
Number of Line Hose	_____	_____	_____	_____	_____	_____
Number of Hoods/Covers	_____	_____	_____	_____	_____	_____

Should we call you if items fail? \_\_\_\_\_ Should we replace failed items? \_\_\_\_\_ Should we return failed items? \_\_\_\_\_

Comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Signature: \_\_\_\_\_

## Special Fleet Service: Tool & Safety Divisions

2500 S. Main Street

Harrisonburg, VA 22801



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Tool Repair Form

Customer Info: \_\_\_\_\_

Bill To: (if different): \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Purchase Order #: \_\_\_\_\_

Date: \_\_\_\_\_

Contact Person: \_\_\_\_\_

Phone #: \_\_\_\_\_

Description of item to be repaired: \_\_\_\_\_

\_\_\_\_\_

Mfg # and Name: \_\_\_\_\_

Serial #: \_\_\_\_\_

Under Warranty?: \_\_\_\_\_

# of Batteries: \_\_\_\_\_

Tool Accessories Included: \_\_\_\_\_

Reason for Repair: \_\_\_\_\_

\_\_\_\_\_

### SFS Tool Repair Policies:

- There will be a charge for estimates if the customer requires an estimate on every tool before it is repaired and if the tool is not repaired or replaced in 30 days.
- If the cost of the repair on the tool is 50% or less of the replacement value, we will proceed with the repair unless otherwise agreed upon
- If the cost of the repair exceeds 50% we will notify you for approval prior to repair

Signature: \_\_\_\_\_

**Special Fleet Service: Tool & Safety Divisions**

2500 S. Main Street

Harrisonburg, VA 22801



**Toll Free: 800-796-9027   Fax: 540-438-9502**

**[www.specialfleettools.com](http://www.specialfleettools.com)**



## Grounding Order Form

Customer Info: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Bill To: (if different): \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Purchase Order #: \_\_\_\_\_

Date: \_\_\_\_\_

Contact Person: \_\_\_\_\_

Phone #: \_\_\_\_\_

Cable Size (#2, 1/0, 2/0, 4/0): \_\_\_\_\_

Cable Color (Clear or Yellow): \_\_\_\_\_

Cable Length: \_\_\_\_\_

Clamp Part #: \_\_\_\_\_

**OR**

C-Clamp (Include Largest Conductor to be used on): \_\_\_\_\_

Duckbill (Include Largest Conductor to be used on): \_\_\_\_\_

Flatface (Eye Screw or T-Handle): \_\_\_\_\_

Bus Clamp (Include Largest Bus to be used on): \_\_\_\_\_

All-Angle Clamp: \_\_\_\_\_

Ball Stud Clamp: \_\_\_\_\_

\*\*Customer is responsible for specifying if they need unshrouded ferrules with heat shrink tubing instead of shrouded ferrules\*\*

Signature: \_\_\_\_\_

**Special Fleet Service: Tool & Safety Divisions**

2500 S. Main Street

Harrisonburg, VA 22801

**Toll Free: 800-796-9027 Fax: 540-438-9502****[www.specialfleettools.com](http://www.specialfleettools.com)**

**Jumpers Order Form**

Customer Info: \_\_\_\_\_ Bill To: (if different): \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Purchase Order #: \_\_\_\_\_ Date: \_\_\_\_\_  
Contact Person: \_\_\_\_\_ Phone #: \_\_\_\_\_

Cable Size (#2=200A, 1/0=250A, 2/0=300A, 4/0=400A): \_\_\_\_\_

Voltage (15KV, 25KV, 35KV): \_\_\_\_\_

Cable Length: \_\_\_\_\_

Jumper Head (Orange or Clear): \_\_\_\_\_

Largest conductor that the head will need to fit: \_\_\_\_\_

For Ground Clamps Installed (C-Clamp or Duckbill): \_\_\_\_\_

Largest conductor that the clamp will need to fit: \_\_\_\_\_

Signature: \_\_\_\_\_

**Special Fleet Service: Tool & Safety Divisions**

2500 S. Main Street

Harrisonburg, VA 22801



**Toll Free: 800-796-9027 Fax: 540-438-9502**

**[www.specialfleettools.com](http://www.specialfleettools.com)**

## Reference

## ACSR (Aluminum Conductor Steel Reinforced)

## For Cable Diameter

## 4 AWG - 636 MCM

.250" - .953" (6.35 mm - 24.21 mm)

## MAXIMUM SAFE LOAD

See facing page  
for grip details.

AWG or MCM Cable Size	Diameter inches (mm)	No. of Alum. & Steel Strands	Code Word	MAXIMUM SAFE LOAD			
				A 4,500 lbs (2041 kg)	B 8,000 lbs (3629 kg)	C 15,000 lbs (6803 kg)	D 20,000 lbs (9072 kg)
Cat. No.							
4	.250" (6.35 mm)	6 x 1	Swan	1656-20, 1656-20H & S1656-20H			
4	.257" (6.53 mm)	7 x 1	Swanate	1656-20, 1656-20H & S1656-20H			
2	.316" (8.03 mm)	6 x 1	Sparrow	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H & S1656-30H		1628-16PE*	
2	.325" (8.26 mm)	7 x 1	Sparate	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H & S1656-30H		1628-16PE*	
1	.354" (9.02 mm)	6 x 1	Robin	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H & S1656-30H		1628-16PF*	
1/0	.398" (10.11 mm)	6 x 1	Raven	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H & S1656-30H		1628-16PG*	
2/0	.447" (11.35 mm)	6 x 1	Quail	1656-30, 1656-30H & S1656-30H		1628-16PG*	
3/0	.502" (12.75 mm)	6 x 1	Pigeon	1656-30, 1656-30H & S1656-30H		1628-16PH*	
4/0	.563" (14.30 mm)	6 x 1	Penguin		1656-40, 1656-40H & S1656-40H	1628-16PI*	
266.8 MCM	.609" (15.47 mm)	18 x 1	Waxwing		1656-40, 1656-40H & S1656-40H	1628-16PJ*	
266.8 MCM	.642" (16.31 mm)	26 x 7	Partridge		1656-40, 1656-40H & S1656-40H	1628-16PK*	
300 MCM	.680" (17.27 mm)	26 x 7	Ostrich		1656-40, 1656-40H & S1656-40H	1628-16PK*	
336.4 MCM	.684" (17.37 mm)	18 x 1	Merlin		1656-40, 1656-40H & S1656-40H	1628-16PK*	
336.4 MCM	.720" (18.31 mm)	26 x 7	Linnet		1656-40, 1656-40H & S1656-40H	1628-16PL*	
336.4 MCM	.741" (18.82 mm)	30 x 7	Oriole			1628-16PL*	
397.5 MCM	.743" (18.87 mm)	18 x 1	Chickadee		1656-50, 1656-50H & S1656-50H	1628-16PL*	
397.5 MCM	.772" (19.61 mm)	24 x 7	Brant		1656-50, 1656-50H & S1656-50H	1628-16PM*	
397.5 MCM	.783" (19.89 mm)	26 x 7	Ibis		1656-50, 1656-50H & S1656-50H	1628-16PM*	
397.5 MCM	.806" (20.47 mm)	30 x 7	Lark		1656-50, 1656-50H & S1656-50H	1628-16PM*	
477 MCM	.814" (20.68 mm)	18 x 1	Pelican		1656-50, 1656-50H & S1656-50H	1628-16PM*	
477 MCM	.846" (21.49 mm)	24 x 7	Flicker		1656-50, 1656-50H & S1656-50H	1628-16PN*	1628-30N*
477 MCM	.858" (21.79 mm)	26 x 7	Hawk		1656-50, 1656-50H & S1656-50H	1628-16PN*	1628-30N*
556.5 MCM	.879" (22.33 mm)	18 x 1	Osprey		1656-60, 1656-60H & S1656-60H	1628-16PN*	1628-30N*
477 MCM	.883" (22.43 mm)	30 x 7	Hen		1656-60, 1656-60H & S1656-60H	1628-16PN*	1628-30N*
556.5 MCM	.914" (23.22 mm)	24 x 7	Parakeet		1656-60, 1656-60H and S1656-60H		1628-300*
556.5 MCM	.927" (23.55 mm)	26 x 7	Dove		1656-60, 1656-60H & S1656-60H		1628-300*
636 MCM	.940" (23.88 mm)	18 x 1	Kingbird		1656-60, 1656-60H & S1656-60H		1628-300*
556.5 MCM	.953" (24.21 mm)	30 x 7	Eagle		1656-60, 1656-60H & S1656-60H		1628-300*
605 MCM	.953" (24.21 mm)	24 x 7	Peacock		1656-60, 1656-60H & S1656-60H		1628-300*

"S" is for spring. "H" is for hot latch.

\*Special order only. Please allow 30 days for delivery. These are not returnable.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Reference

## ACSR (Aluminum Conductor Steel Reinforced)

## For Cable Diameter

## 605 - 2515 MCM

## .966" - 1.88" (24.54 mm - 47.75 mm)

## MAXIMUM SAFE LOAD

See facing page  
for grip details.

MCM Cable Size	Diameter inches (mm)	No. of Alum. & Steel Strands	Code Word	A	B	C	D	E
				5,500 lbs (2,495 kg) Cat. No.	8,000 lbs (3,636 kg) Cat. No.	20,000 lbs (9,072 kg) Cat. No.	25,000 lbs (11,340 kg) Cat. No.	25,000 lbs. with bolt on jaw (11,340 kg) Cat. No.
605 MCM	.966" (24.54 mm)	26 x 7	Squab		1678-20	1628-30P*		1628-50P*
636 MCM	.977" (24.82 mm)	24 x 7	Rook		1678-20	1628-30P*		1628-50P*
636 MCM	.991" (25.15 mm)	26 x 7	Grosbeak		1678-20	1628-30P*		1628-50P*
605 MCM	.994" (25.25 mm)	30 x 19	Teal		1678-20	1628-30P*		1628-50P*
605 MCM	.994" (25.25 mm)	30 x 7	Wood Duck		1678-20	1628-30P*		1628-50P*
666.6 MCM	1.00" (25.40 mm)	24 x 7	Flamingo		1678-20	1628-30P*		1628-50P*
666.6 MCM	1.014" (25.76 mm)	26 x 7	Gannet		1678-20	1628-30P*		1628-50P*
636 MCM	1.019" (25.88 mm)	30 x 19	Egret		1678-20	1628-30R*		1628-50R*
636 MCM	1.019" (25.88 mm)	30 x 7	Scoter		1678-20	1628-30R*		1628-50R*
795 MCM	1.040" (26.41 mm)	36 x 1	Coot	1678-30		1628-30R*		1628-50R*
715.5 MCM	1.051" (26.70 mm)	26 x 7	Starling	1678-30		1628-30R*		1628-50R*
795 MCM	1.063" (27.00 mm)	45 x 7	Tern	1678-30		1628-30R*		1628-50R*
715.5 MCM	1.081" (27.46 mm)	30 x 19	Redwing	1678-40		1628-30S*		1628-50S*
795 MCM	1.092" (27.76 mm)	54 x 7	Condor	1678-40		1628-30S*		1628-50S*
795 MCM	1.092" (27.74 mm)	24 x 7	Cuckoo	1678-40		1628-30S*		1628-50S*
795 MCM	1.107" (28.14 mm)	26 x 7	Drake	1678-40		1628-30S*		1628-50S*
900 MCM	1.131" (28.73 mm)	45 x 7	Ruddy	1678-40		1628-30S*		1628-50S*
795 MCM	1.140" (28.96 mm)	30 x 19	Mallard	1678-40		1628-30S*		1628-50S*
900 MCM	1.162" (29.51 mm)	54 x 7	Canary	1678-50		1628-30T*		1628-50T*
954 MCM	1.165" (29.59 mm)	20 x 7	Corncrake	1678-50		1628-30T*		1628-50T*
954 MCM	1.165" (29.59 mm)	45 x 7	Rail	1678-50		1628-30T*		1628-50T*
954 MCM	1.175" (29.85 mm)	48 x 7	Towhee	1678-50		1628-30T*		1628-50T*
954 MCM	1.196" (30.38 mm)	54 x 7	Cardinal	1678-50		1628-30T*		1628-50T*
954 MCM	1.196" (30.38 mm)	24 x 7	Redbird	1678-50		1628-30T*		1628-50T*
1033.5 MCM	1.212" (30.81 mm)	45 x 7	Ortolan			1628-30U*	1628-40U*	1628-50U*
1033.5 MCM	1.245" (31.65 mm)	54 x 7	Curlew			1628-30U*	1628-40U*	1628-50U*
1113 MCM	1.258" (31.95 mm)	45 x 7	Bluejay			1628-30U*	1628-40U*	1628-50U*
1113 MCM	1.292" (32.84 mm)	54 x 19	Finch				1628-40W*	1628-50W*
1192.5 MCM	1.302" (33.07 mm)	45 x 7	Bunting				1628-40W*	1628-50W*
1272 MCM	1.317" (33.45 mm)	36 x 1	Skylark				1628-40W*	1628-50W*
1192.5 MCM	1.337" (33.99 mm)	54 x 19	Grackle				1628-40X*	1628-50X*
1272 MCM	1.345" (34.16 mm)	45 x 7	Bittern				1628-40X*	1628-50X*
1272 MCM	1.381" (35.10 mm)	54 x 19	Pheasant				1628-40X*	1628-50X*
1351.5 MCM	1.386" (35.20 mm)	45 x 7	Dipper				1628-40X*	1628-50X*
1351.5 MCM	1.424" (36.17 mm)	54 x 19	Martin				1628-40Y*	1628-50Y*
1431 MCM	1.427" (36.25 mm)	45 x 7	Bobolink				1628-40Y*	1628-50Y*
1431 MCM	1.465" (37.21 mm)	54 x 19	Plover				1628-40Z*	1628-50Z*
1590 MCM	1.504" (38.15 mm)	45 x 7	Lapwing				1628-40Z*	1628-50Z*
1590 MCM	1.544" (39.24 mm)	54 x 19	Falcon				1628-40A*	1628-50A*
1780 MCM	1.602" (40.69 mm)	84 x 19	Chukar					1628-50B*
2034.5 MCM	1.681" (42.70 mm)	72 x 7	Mockingbird					1628-50C*
2167 MCM	1.735" (44.12 mm)	72 x 7	Kiwi					1628-50D*
2156 MCM	1.762" (44.75 mm)	84 x 19	Bluebird					1628-50D*
2312 MCM	1.802" (45.77 mm)	76 x 19	Thrasher					1628-50E*
2515 MCM	1.88" (47.75 mm)	76 x 19	Joree					1628-50F*

\*Special order only. Please allow 30 days for delivery. These are not returnable.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Reference

## AAC (All Aluminum Conductor)

## For Cable Diameter

## 4 AWG - 650 MCM

.231" - .928" (5.87 mm - 23.57 mm)

## MAXIMUM SAFE LOAD

See facing page  
for grip details.

AWG or MCM Cable Size	Diameter inches (mm)	No. of Alum. Strands	Code Word	A 4,500 lbs (2041 kg)	B 8,000 lbs (3629 kg)	C 15,000 lbs (6803 kg)	D 20,000 lbs (9072 kg)
				Cat. No.	Cat. No.	Cat. No.	Cat. No.
4	.231' (5.87 mm)	7	Rose	1656-20, 1656-20H and S1656-20H			
2	.292' (7.42 mm)	7	Iris	1656-20, 1656-20H and S1656-20H			
1	.328' (8.33 mm)	7	Pansy	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H and S1656-30H		1628-16PE*	
1/0	.369' (9.36 mm)	7	Poppy	1656-20, 1656-20H, S1656-20H, 1656-30, 1656-30H and S1656-30H		1628-16PF*	
2/0	.414' (10.51 mm)	7	Aster	1656-30, 1656-30H and S1656-30H		1628-16PG*	
3/0	.465' (11.81 mm)	7	Phlox	1656-30, 1656-30H and S1656-30H		1628-16PH*	
4/0	.522' (13.25 mm)	7	Oxlip	1656-30, 1656-30H and S1656-30H		1628-16PI*	
250 MCM	.567' (14.40 mm)	7	Sneezewort		1656-40, 1656-40H and S1656-40H	1628-16PI*	
250 MCM	.574' (14.58 mm)	19	Valerian		1656-40, 1656-40H and S1656-40H	1628-16PI*	
266.8 MCM	.586' (14.88 mm)	7	Daisy		1656-40, 1656-40H and S1656-40H	1628-16PJ*	
266.8 MCM	.593' (15.05 mm)	19	Laurel		1656-40, 1656-40H and S1656-40H	1628-16PJ*	
300 MCM	.628' (15.95 mm)	19	Peony		1656-40, 1656-40H and S1656-40H	1628-16PJ*	
336.4 MCM	.665' (16.90 mm)	19	Tulip		1656-40, 1656-40H and S1656-40H	1628-16PK*	
350 MCM	.678' (17.22 mm)	19	Daffodil		1656-40, 1656-40H and S1656-40H	1628-16PK*	
397.5 MCM	.724' (18.38 mm)	19	Canna		1656-40, 1656-40H and S1656-40H	1628-16PL*	
450 MCM	.769' (19.53 mm)	19	Goldentuft		1656-50, 1656-50H and S1656-50H	1628-16PM*	
477 MCM	.792' (20.12 mm)	19	Cosmos		1656-50, 1656-50H and S1656-50H	1628-16PM*	
477 MCM	.794' (20.18 mm)	37	Syringa		1656-50, 1656-50H and S1656-50H	1628-16PM*	
500 MCM	.811' (20.60 mm)	19	Zinnia		1656-50, 1656-50H and S1656-50H	1628-16PM*	
500 MCM	.813' (20.65 mm)	37	Hyacinth		1656-50, 1656-50H and S1656-50H	1628-16PM*	
556.5 MCM	.856' (21.73 mm)	19	Dahlia		1656-50, 1656-50H and S1656-50H	1628-16PN*	1628-30N*
556.5 MCM	.858' (21.80 mm)	37	Mistletoe		1656-50, 1656-50H and S1656-50H	1628-16PN*	1628-30N*
600 MCM	.891' (22.63 mm)	37	Meadowsweet		1656-60, 1656-60H and S1656-60H		1628-300*
636 MCM	.918' (23.31 mm)	37	Orchid		1656-60, 1656-60H and S1656-60H		1628-300*
650 MCM	.928' (23.57 mm)	37	Heuchera		1656-60, 1656-60H and S1656-60H		1628-300*

\*S" is for spring. "H" is for hot latch.

\*Special order only. Please allow 30 days for delivery. These are not returnable.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Reference

## AAC (All Aluminum Conductor)

### For Cable Diameter

### 700 - 2500 MCM

.963" - 1.823" (24.46 mm - 46.30 mm)

### MAXIMUM SAFE LOAD

See facing page  
for grip details.

MCM Cable Size	Diameter inches (mm)	No. of Alum. & Steel Strands	Code Word	5,500 lbs (2,268 kg)	8,000 lbs (3,629 kg)	20,000 lbs (9,072 kg)	25,000 lbs (11,340 kg)	25,000 lbs. (11,340 kg) with bolt on jaw
				Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.
700 MCM	.963" (24.46 mm)	37	Verbena		1678-20	1628-30P*		1628-50P*
700 MCM	.964" (24.49 mm)	61	Flag		1678-20	1628-30P*		1628-50P*
715.5 MCM	.974" (24.73 mm)	37	Violet		1678-20	1628-30P*		1628-50P*
715.5 MCM	.975" (24.76 mm)	61	Nasturtium		1678-20	1628-30P*		1628-50P*
750 MCM	.997" (25.32 mm)	37	Petunia		1678-20	1628-30P*		1628-50P*
750 MCM	.998" (25.35 mm)	61	Cattail		1678-20	1628-30P*		1628-50P*
795 MCM	1.026" (26.07 mm)	37	Arbutus	1678-30		1628-30R*		1628-50R*
795 MCM	1.028" (26.11 mm)	61	Lilac	1678-30		1628-30R*		1628-50R*
800 MCM	1.029" (26.14 mm)	37	Fuchsia	1678-30		1628-30R*		1628-50R*
800 MCM	1.031" (26.19 mm)	61	Heliotrope	1678-30		1628-30R*		1628-50R*
874.5 MCM	1.076" (27.37 mm)	37	Anemone	1678-30		1628-30R*		1628-50R*
874.5 MCM	1.077" (27.36 mm)	61	Crocus	1678-30		1628-30R*		1628-50R*
900 MCM	1.092" (27.74 mm)	37	Cockscomb	1678-40		1628-30S*		1628-50S*
954 MCM	1.124" (28.55 mm)	37	Magnolia	1678-40		1628-30S*		1628-50S*
954 MCM	1.126" (28.60 mm)	61	Goldenrod	1678-40		1628-30S*		1628-50S*
1000 MCM	1.152" (29.26 mm)	61	Camellia	1678-50		1628-30T*		1628-50T
1000 MCM	1.152" (29.26 mm)	37	Hawkweed	1678-50		1628-30T*		1628-50T*
1033.5 MCM	1.170" (29.71 mm)	37	Bluebell	1678-50		1628-30T*		1628-50T*
1033.5 MCM	1.172" (29.76 mm)	61	Larkspur	1678-50		1628-30T*		1628-50T*
1113 MCM	1.216" (30.88 mm)	61	Marigold			1628-30U*	1628-40U*	1628-50U*
1192.5 MCM	1.258" (31.96 mm)	61	Hawthorn			1628-30U*	1628-40U*	1628-50U*
1272 MCM	1.297" (32.94 mm)	61	Narcissus				1628-40W*	1628-50W*
1351.5 MCM	1.339" (34.02 mm)	61	Columbine				1628-40X*	1628-50X*
1431 MCM	1.379" (35.02 mm)	61	Carnation				1628-40X*	1628-50X*
1510.5 MCM	1.417" (35.98 mm)	61	Gladiolus				1628-40Y*	1628-50Y*
1590 MCM	1.454" (36.93 mm)	61	Coreopsis				1628-40Z*	1628-50Z*
1750 MCM	1.524" (38.72 mm)	61	Jessamine				1628-40A*	1628-50A*
2000 MCM	1.630" (41.41 mm)	91	Cowslip					1628-50B*
2250 MCM	1.729" (43.92 mm)	91	Sagebrush					1628-50D*
2500 MCM	1.823" (46.30 mm)	91	Lupine					1628-50E*

\*\* Maximum safe stringing tension 12,500 lbs to minimize cable deformation.

\* Special order. Please allow 30 days for delivery. These are not returnable.



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Manufacturers Websites

<b>3M</b> - <a href="http://www.3m.com">www.3m.com</a>	<b>H.K. Porter</b> - <a href="http://www.apexhandtools.com">www.apexhandtools.com</a>	<b>Salisbury</b> - <a href="http://www.salisburybyhoneywell.com">www.salisburybyhoneywell.com</a>
<b>A.B. Chance</b> - <a href="http://www.hubbellpowersystems.com">www.hubbellpowersystems.com</a>	<b>Hastings</b> - <a href="http://www.hfgp.com">www.hfgp.com</a>	<b>Safeway Sling</b> - <a href="http://www.safewaysling.com">www.safewaysling.com</a>
<b>AW Sperry</b> - <a href="http://www.sperryinstruments.com">www.sperryinstruments.com</a>	<b>HD Electric</b> - <a href="http://www.hdelectriccompany.com">www.hdelectriccompany.com</a>	<b>S&amp;C</b> - <a href="http://www.sandc.com">www.sandc.com</a>
<b>AEMC</b> - <a href="http://www.aemc.com">www.aemc.com</a>	<b>Huskie</b> - <a href="http://www.huskiertools.com">www.huskiertools.com</a>	<b>Sensor Link</b> - <a href="http://www.sensorlink.com">www.sensorlink.com</a>
<b>Aircraft Dynamics</b> - <a href="http://www.aircrafterdynamics.com">www.aircrafterdynamics.com</a>	<b>Irwin</b> - <a href="http://www.irwin.com">www.irwin.com</a>	<b>Servus Rubber</b> - <a href="http://www.servusproducts.com">www.servusproducts.com</a>
<b>Bashlin</b> - <a href="http://www.bashlin.com">www.bashlin.com</a>	<b>Jameson</b> - <a href="http://www.jamesonllc.com">www.jamesonllc.com</a>	<b>Seymour Mfg.</b> - <a href="http://www.seymourmidwest.com">www.seymourmidwest.com</a>
<b>Bethea</b> - <a href="http://www.betheatoolandequipment.com">www.betheatoolandequipment.com</a>	<b>JBC Safety Plastics</b> - <a href="http://www.jbcsafety.com">www.jbcsafety.com</a>	<b>Sherman &amp; Reilly</b> - <a href="http://www.sherman-reilly.com">www.sherman-reilly.com</a>
<b>Bierer and Associates</b> - <a href="http://www.bierermeters.com">www.bierermeters.com</a>	<b>Jenny Tools</b> - <a href="http://www.jennytools.com">www.jennytools.com</a>	<b>Slingco</b> - <a href="http://www.slingco.com">www.slingco.com</a>
<b>Bone</b> - <a href="http://www.bonesafety.com">www.bonesafety.com</a>	<b>Justin FR</b> - <a href="http://www.justinfr.com">www.justinfr.com</a>	<b>Speed Systems</b> - <a href="http://www.spdsystems.com">www.spdsystems.com</a>
<b>Brunner &amp; Lay</b> - <a href="http://www.brunnerlay.com">www.brunnerlay.com</a>	<b>Kinco</b> - <a href="http://www.kinco.com">www.kinco.com</a>	<b>Stanley</b> - <a href="http://www.stanleyhydraulics.com">www.stanleyhydraulics.com</a>
<b>Buckingham Mfg.</b> - <a href="http://www.buckinghammfg.com">www.buckinghammfg.com</a>	<b>Klein</b> - <a href="http://www.kleintools.com">www.kleintools.com</a>	<b>Streamlight</b> - <a href="http://www.streamlight.com">www.streamlight.com</a>
<b>Burndy</b> - <a href="http://www.burndy.com">www.burndy.com</a>	<b>Knopp</b> - <a href="http://www.knoppinc.com">www.knoppinc.com</a>	<b>Stucchi</b> - <a href="http://www.stucchiusa.com">www.stucchiusa.com</a>
<b>Capital Safety</b> - <a href="http://www.capitalsafety.com">www.capitalsafety.com</a>	<b>Leidy Tool Company</b> - <a href="http://www.leidytool.com">www.leidytool.com</a>	<b>Tegam</b> - <a href="http://www.tegam.com">www.tegam.com</a>
<b>Carolina</b> - <a href="http://www.carolinaglove.com">www.carolinaglove.com</a>	<b>Lewis Mfg.</b> - <a href="http://www.lewismfg.com">www.lewismfg.com</a>	<b>Terex Reedrill</b> - <a href="http://www.terex.com">www.terex.com</a>
<b>Cembre</b> - <a href="http://www.cembre.com">www.cembre.com</a>	<b>Lincoln Hoist</b> - <a href="http://www.lincolrhoist.com">www.lincolrhoist.com</a>	<b>Timco Instruments</b> - <a href="http://www.timcoinstruments.com">www.timcoinstruments.com</a>
<b>Cementex</b> - <a href="http://www.cementexusa.com">www.cementexusa.com</a>	<b>Little Mule</b> - <a href="http://www.cmworks.com/little-mule-hoists">www.cmworks.com/little-mule-hoists</a>	<b>Tulsa Power Products</b> - <a href="http://www.tulsapower.com">www.tulsapower.com</a>
<b>Condux</b> - <a href="http://www.condux.com">www.condux.com</a>	<b>Lugall</b> - <a href="http://www.lug-all.com">www.lug-all.com</a>	<b>Utility Solutions</b> - <a href="http://www.utilitysolutionsinc.com">www.utilitysolutionsinc.com</a>
<b>Cooper</b> - <a href="http://www.apextoolgroup.com">www.apextoolgroup.com</a>	<b>Madi</b> - <a href="http://www.madillc.com">www.madillc.com</a>	<b>Utility Tool &amp; Body</b> - <a href="http://www.uttwi.com">www.uttwi.com</a>
<b>Council Tool</b> - <a href="http://www.counciltool.com">www.counciltool.com</a>	<b>MYTE</b> - <a href="http://www.myte.com">www.myte.com</a>	<b>Wanco</b> - <a href="http://www.wanco.com">www.wanco.com</a>
<b>Current Tools</b> - <a href="http://www.currenttools.com">www.currenttools.com</a>	<b>OshKosh</b> - <a href="http://www.oshkoshtools.com">www.oshkoshtools.com</a>	<b>Warren Heim</b> - <a href="http://www.warrenheimcorp.com">www.warrenheimcorp.com</a>
<b>DCD</b> - <a href="http://www.dcdesign.com">www.dcdesign.com</a>	<b>Parker</b> - <a href="http://www.parker.com">www.parker.com</a>	<b>Werner</b> - <a href="http://www.wernerco.com">www.wernerco.com</a>
<b>Dillon</b> - <a href="http://www.dillondynamometers.com">www.dillondynamometers.com</a>	<b>Peavey Mfg.</b> - <a href="http://www.peaveymfg.com">www.peaveymfg.com</a>	<b>Work Area Protection</b> - <a href="http://www.workareaprotection.com">www.workareaprotection.com</a>
<b>Dixie Tool</b> - <a href="http://www.dixie-tool.com">www.dixie-tool.com</a>	<b>Pengo</b> - <a href="http://www.pengoattachments.com">www.pengoattachments.com</a>	<b>Youngstown Gloves</b> - <a href="http://www.ytgloves.com">www.ytgloves.com</a>
<b>Eagle Line Tools</b> - <a href="http://www.eaglelinetools.com">www.eaglelinetools.com</a>	<b>Pelsue</b> - <a href="http://www.pelsue.com">www.pelsue.com</a>	
<b>Erin</b> - <a href="http://www.erinrope.com">www.erinrope.com</a>	<b>Plastic Techniques</b> - <a href="http://www.buckettruckaccessories.com">www.buckettruckaccessories.com</a>	
<b>Estex</b> - <a href="http://www.estexmfg.com">www.estexmfg.com</a>	<b>Princeton Tec.</b> - <a href="http://www.princetonotec.com">www.princetonotec.com</a>	
<b>Global Glove</b> - <a href="http://www.globalglove.com">www.globalglove.com</a>	<b>Radians</b> - <a href="http://www.radians.com">www.radians.com</a>	
<b>GMP</b> - <a href="http://www.gmptools.com">www.gmptools.com</a>	<b>Rauckman Utility Products</b> - <a href="http://www.rauckmanutility.com">www.rauckmanutility.com</a>	
<b>Golight</b> - <a href="http://www.golight.com">www.golight.com</a>	<b>Ridgid</b> - <a href="http://www.ridgid.com">www.ridgid.com</a>	
<b>Greenlee</b> - <a href="http://www.greenlee.com">www.greenlee.com</a>	<b>Ripley</b> - <a href="http://www.ripley-tools.com">www.ripley-tools.com</a>	
	<b>Rubbermaid</b> - <a href="http://www.rubbermaid.com">www.rubbermaid.com</a>	



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

A

**Adapters**  
 Chance 121, 122  
 Greenlee 24

**AEMC**  
 Meters 156  
 Resistance Tester 156

**American Polywater**  
 Cleaner 86, 87, 192

**Animal Guards**  
 Rauckman 193

**Application for Credit 198**

**Aprons**  
 Buckingham 90  
 Estex 89, 90

**Arc Snuffer Removal Tool**  
 Chance 81

**Arm Extensions**  
 Hastings 78, 79

**Assemblies**  
 Chance 121

**Auger Bits**  
 Greenlee 28

**B**

**Ball Studs**  
 Chance 134  
 Salisbury 133

**Ball & Socket Systems**  
 Salisbury 133

**Barricade Bars**  
 Hastings 164

**Bashlin**  
 Body Belt 142, 144  
 Climbers 147  
 Gaff Guard 152  
 Gaff Shaping Kit 153  
 Lanyard 148, 149, 150, 151  
 Pole Sling 147  
 Replacement Gaffs 146

**Batteries**  
 Greenlee 26  
 Makita 26  
 Streamlight 172

**Battery Chargers**  
 Huskie 25  
 Makita 26

**Battery Packs**  
 Huskie 26

**Battery Tools 10-26**

**Bierer Meters**  
 Phasing Meters 157  
 Voltage Detectors 159

**Blade Covers**

Estex 94

**Blanket Accessories**  
 Salisbury 192

**Blocks**  
 Klein 139

**Block & Tackle**  
 Klein 138

**Body Belts**  
 Bashlin 142, 144  
 Buckingham 142, 143, 144

**Bolt Cutters**  
 Greenlee 42  
 Hastings 41  
 H.K. Porter 40  
 Klein 41

**Bone Safety Signs**  
 Sign Stands 165  
 Traffic Signs 164, 165

**Boosters**  
 Greenlee 36

**Breaker Assy.**  
 Greenlee 34, 35

**Brush Sets**  
 Klein 115

**Bucket Covers**  
 Estex 95

**Bucket Steps**  
 Hastings 94

**Bucket Sticks**  
 Hastings 80

**Bucket Storage Bags**  
 Buckingham 88  
 Estex 89  
 Klein 88, 89  
 Warren Heim 88

**Buckingham Mfg.**  
 Apron 90  
 Body Belt 142, 143, 144  
 Boom Strap 151  
 Buck Limiter 151  
 Carabiner 152  
 Climber Strap 151  
 Gaff Guard 152  
 Gaff Maintenance Kit 145  
 Gaff Pole Climbers 146  
 Glove and Sleeve Bag 183  
 Ground Flag 135  
 Gut Strap 146  
 Handline Hook 137  
 Harness 153, 154  
 Headline Hook 137  
 Holster 92  
 Knives 58



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Index

**Buckingham cont.**

Lanyards 148, 149, 150, 151  
 Ox Blocks 139  
 Pads 145  
 Pole Climbers 146  
 Positioning Straps 150, 151  
 Rescue Systems 155  
 Snap 151, 152  
 Tool Bag 88, 92  
 Tool Tray 93

**Burndy**

Cable Cutter 30  
 Crimping Tool 12, 13, 15, 16, 17, 18, 45, 46, 47  
 Compression Tool 29  
 Cutting Tool 12, 20, 21  
 Dies 24, 25  
 Hydraulic Tool 46  
 Impact Wrench 27  
 Jaw Assemblies 19  
 Pole Cutter 21  
 Pump 36  
 Ratchet Tool 45  
 Remote Operated Hydraulic Tool 32  
 Wiremike 72

**Bushing Covers**

Salisbury 189

**Bypass Tool**

Utility Solutions 84

**C****Cable Cutters**

Burndy 30  
 Cembre 48  
 Cementex 49  
 Chance 48  
 Greenlee 22, 23, 39, 41, 43  
 H.K. Porter 40, 42  
 Huskie 19  
 Jenny Tools 44  
 Klein 43, 44, 49

**Cable End Strippers**

Utility Tool 109, 110, 111

**Cable Grips**

DCD 96  
 Hubbell 97, 98  
 Slingco 96, 97, 98

**Cable Pullers**

Greenlee 104  
 Sherman & Reilly 103

**Cable Slicer**

Hastings 45

**Cable Stripper**

Speed System 110  
 Utility Tool 110

**Canister Kits**

Hastings 87

**Cant Hook**

Dixie 124  
 Hastings 125  
 OshKosh 124

**Cant Tool**

Hastings 125

**Carabiner**

Buckingham 152

**Cembre**

Cable Cutter 48  
 Crimping Tool 12, 16, 18  
 Cutting Tool 22  
 Presshead 31, 32

**Cementex**

Cable Cutters 49  
 Nut Drive Set 53  
 Pliers 61, 62  
 Ratchet 71  
 Screwdrivers 49, 50  
 Screwdriver Sets 50  
 Socket Sets 67  
 Tool Sets 54  
 Wrenches 66  
 Wrench Sets 65, 66

**Chainsaws**

Greenlee 33

**Chamfer Tools**

Speed Systems 112

**Chance**

Adapters 121, 122  
 Arc Snuffer Removal Tool 81  
 Assemblies 121  
 Cable Cutters 48  
 Clampstick 73, 74, 75  
 Cleaners 86, 87  
 Cluster Bar 134  
 Cluster support 134  
 Conductor Support 79  
 Covers 81  
 Disconnect Tool 76  
 Drive-End Wrenches 121  
 Elbow Puller Tool 77  
 Extension Arm 79  
 Extension Arm Accessories 82  
 Grounding Clamps 127, 128, 129, 130  
 Ground Grid Kit 135  
 Ground Rod 134  
 Grounding Stud Cover 134  
 Hoists 119, 120  
 Rope Blocks 137  
 Studs 133, 134



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

- Stud Cover 134
- Tamping Bar 126
- Testers 157, 162
- Tester Accessories 157
- Torque Limiter 122
- Transformer Gin 80
- Chance cont.**
  - Voltage Detector 159, 161
  - Voltage Indicator 161
- Clamps**
  - Utility Solutions 193
- Clamp-on Meters**
  - AEMC 156
  - Greenlee 156
- Clampsticks**
  - Chance 73, 74, 75
- Cleaners**
  - American Polywater 86, 87, 192
  - Chance 86, 87
  - Hastings 86
  - Salisbury 191
- Cleaning Brushes**
  - Hastings 82
- Climbers**
  - Bashlin 147
- Clipping Hooks 105**
- Clothing 194-197**
  - Justin FR 194, 195, 196, 197
  - Tingley 197
- Cluster Bag**
  - Estex 135
- Cluster Bars**
  - Chance 134
- Cluster Supports**
  - Chance 134
- Columbus McKinnon**
  - Hoists 120
- Combination Splice/T-Body Tools**
  - Speed Systems 113
- Compact Pullers**
  - Sherman & Reilly 103
- Compression Head**
  - Huskie 31, 32
- Compression Tools**
  - Burndy 29
  - Huskie 11, 47, 48
- Conductor Supports**
  - Chance 79
  - Hastings 82
- Conduit Measuring Tape**
  - Greenlee 104
- Condux**
  - Rodders 101, 102
- Swivels 99, 100
- Control Testers**
  - Hastings 83
- Control Valves**
  - Greenlee 39
- Couplers**
  - Greenlee 37
- Covers**
  - Chance 81, 134
  - Salisbury 187, 188, 189
- Crimping/Cutting Tools**
  - Greenlee 10
  - Klein 63
- Crimping Jaws**
  - Greenlee 10
  - Huskie 11, 13
- Crimping Tools**
  - Burndy 12, 13, 15, 16, 17, 18, 45, 46, 47
  - Cembre 12, 18
  - Greenlee 10, 14, 16, 17, 18, 29, 30, 31, 46
  - Huskie 11, 13, 14, 15, 16, 17, 19, 47
- Cutting Kits**
  - Greenlee 24
- Cutting Tools**
  - Burndy 12, 20, 21
  - Cembre 16, 22
  - Greenlee 19, 22, 23
  - H.K. Porter 41, 44
  - Huskie 19, 20

**D****DCD**

- Cable Grips 96
- Swivels 99

**Die Crimper**

- Burndy 45

**Die Kits**

- Burndy 25
- Greenlee 25

**Dies**

- Burndy 24
- Greenlee 25
- Huskie 25

**Digging Bars**

- OshKosh 125

**Dillon**

- Dynamometer 105

**Disconnect Tools**

- Chance 76

**Discharge Stick**

- Salisbury 83



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

**Dixie Tool**

Cant Hook 124  
Tongs 125

**Driver End Wrenches**

Chance 121

**Dynamometers**

Dillon 105

**E****Eagle Line Tools**

Rope 138

**Earth Handling and Pole Setting 121-126****Edge Wedges**

Speed Systems 115

**Elbow-Pullers**

Chance 77

**Erin**

Combination Rope 138

**Estex**

Apron 89, 90  
Blade Cover 94  
Bucket Cover 95  
Cluster Bag 135  
Glove Bag 184  
Hooks 94  
Kneeling Pad 165  
Line Hose Bag 184  
Pole Wrap 85  
Sleeve Bag 184  
Tool Bag 89, 90, 91, 92

**Extension Arm Accessories**

Chance 82

**Extension Arms**

Chance 79  
Hastings 78

**F****Fall Protection & Climbing Equipment 142-155****Fall Protection Sizing 141****Ferrules**

Salisbury 133

**Flashlights**

Streamlight 174, 175

**Fuse Handling Tools**

S&C 85

**Fuse Pullers**

Hastings 83

**G****Gaffs**

Bashlin 146

**Gaff Guards**

Bashlin 152  
Buckingham 152

**Gaff Kits**

Bashlin 153

Buckingham 145

**Gaff Pole Climbers**

Buckingham 146

**Global Glove**

Gloves 168

**Gloves**

Salisbury 167  
Youngstown 166, 167, 168

**Glove Accessories**

Salisbury 193

**Glove Bags**

Buckingham 183  
Estex 184

**Glove Dust**

Salisbury 191

**Golight**

Portable Light 172

**Greenlee**

Adapters 24  
Auger Bits 28  
Batteries 26  
Bolt Cutters 42  
Booster Assy. 36  
Breaker Assy. 34, 35  
Cable Cutters 22, 23, 39, 41, 43  
Cable Puller 104  
Chainsaws 33  
Circular Saw Assy. 33  
Clamp-on Meters 156  
Connectors 100  
Control Valves 39  
Couplers 37  
Crimping Tool 14, 16, 17, 18, 29, 30, 31, 46  
Crimper/Cutter 10  
Cutter Kit 24  
Cutting Tool 19, 23  
Dies 25  
Ground Rod Driver 34  
Hammer Drill 38  
Hose Assy. 39  
Impact Wrench 27, 28  
Jaws 10  
Knives 57  
Measuring Tape 104  
Nut Runners 38  
Pole Puller Assy. 34  
Poly Line 105  
Pump 35, 37  
Tamper Assembly 34

**Grips**

Klein 106, 107, 108



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

**Grips cont.**

Little Mule 106

**Grips, Cable Prep & Pulling Tools 96-115****Ground Clamps**

Chance 127, 128, 129, 130

Hastings 132

Salisbury 130, 131

**Ground Flag**

Buckingham 135

**Ground Grid Kits**

Chance 135

**Grounds & Jumpers 127-136****Ground Mats**

Hastings 135

**Ground Rods**

Chance 134

**Ground Rod Driver**

Greenlee 34

**Grounding Clamps**

Chance 127, 128, 129, 130

Hastings 132

Salisbury 130, 131

**Grounding Jumpers**

Salisbury 136

**Grounding Order Form 201****Grounding Stud Covers**

Chance 134

**Gut Straps**

Buckingham 146

**H****H.K. Porter**

Bolt Cutter 40

Cable Cutter 40, 42

Cutters 41, 44

**Hacksaws**

Klein 58

**Hacksaw Blades**

Klein 59

**Hammers**

Klein 61

Madi 61

**Hammer Drills**

Greenlee 38

**Hand Tools 49-72****Handline Hooks**

Buckingham 137

Hastings 137

**Handline Blocks**

Hastings 139

**Harnesses**

Buckingham 153, 154

**Hastings**

Barricades 164

Bolt Cutters 41

Bucket Step 94

Cable Slicer 45

Canister Kit 87

Cant Hook 125

Cant Tool 125

Capacitor Tester 160

Chain Saw Scabbard 93

Cleaners 86

Cleaning Brush 82

Conductor Holder 82

Control Tester 83

Detectors 160

Extension Arms 78

Fuse Puller 83

Ground Clamp 132

Ground Mat 135

Hand Line Block 139

Handline Hook 137

Holsters 93

Hot Stick 75, 76, 77, 82

Hot Stick Accessories 85

Isolating Link 77, 78

Jumper Clamp 132

Jumper Holder 132

Line Guard 189

Lamp Changer Head 83

Pruner 83

Pruning Saw 58

Phasing Meter 156, 157

Ratchet Cutter 48

Rescue Kit 155

Shotgun Stick 73, 74

Support Arm 79

Tel-O-Pole 75, 76, 77, 80

Testers 163

Tool Tray 93

**HD Electric**

Tester 162

Voltage Detector 159, 160

**Headlamps**

Streamlight 173, 174

**Headline Hook**

Buckingham 137

**Hex Key Set**

Klein 59

**Hoists 116-120****Hoist Isolating Links**

Hastings 77, 78

**Hole Diggers**

OshKosh 123

**Hollow Core Poles**

Jameson 59



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com



## Index

**Holsters**

Buckingham 92  
Hastings 93

**Hooks**

Estex 94  
Klein 94

**Hose Assembly**

Greenlee 39

**Hot Stick Accessories**

Hastings 85

**Hot Stick Cleaners**

American Polywater 86, 87  
Chance 86, 87  
Hastings 86

**Hot Sticks**

Hastings 75, 76, 77  
Utility Solutions 76

**Hot-Sticks and Hot-Line Tool 73-87****Hubbell**

Grips 97, 98

**Huskie**

Battery 25, 26  
Cable Cutters 19  
Compression Head 31, 32  
Compression Tool 47, 48  
Crimping Tool 47  
Dies 25  
Pump 36  
Robo-Crimp 11, 13, 14, 15, 16, 17, 19  
Robo-Cut 20  
Steel Punch 38

**Hydraulic Tools 27-39****I****Impact Socket**

Klein 67

**Impact Wrenches**

Burndy 27  
Greenlee 27, 28  
Stanley 27

**Impulse Stapler**

Paslode 71

**Insertion Tools**

Utility Tool 114

**Installation Tools**

Speed Systems 113, 114

**Insulated Jumper Cables**

Salisbury 136

**Insulation Strippers**

Speed Systems 109, 110

**Insulation Stripper Accessories**

Speed Systems 111

**Insulator Covers**

Salisbury 187

**Isolating Link**

Hastings 77, 78

**J****Jameson**

Hollow Core Pole 59  
Knives 58  
Pole Saw 59  
Rodders 103  
Saw Blade 58, 59

**Jaw Grips**

Klein 106, 107, 108

**JBC Safety Plastics**

Traffic Cones 164

**Jenny Tools**

Cable Cutters 44  
Ratchet Cutters 42

**Jumper Clamps**

Hastings 132  
Salisbury 132

**Jumper Holders**

Hastings 132

**Jumper Hook**

Utility Solutions 85

**Jumper Order Form 202****Justin FR**

Clothing 194-197

**K****Kelly Bar Adapters**

Chance 121

**Klein**

Adjustable Wrenches 67  
Backpack 91  
Blocks 139  
Block & Tackle 138  
Bolt Cutters 41  
Cable Cutters 43, 44, 49  
Cleaning Brush Set 115  
Grips 106, 107, 108  
Hacksaw 58  
Hacksaw Blades 58  
Hammers 61  
Hex Set 59  
Hooks 94, 139, 140  
Impact Socket 67  
Knives 55, 56, 57  
Measuring Tape 60  
Nut Driver Sets 51, 53  
Pliers 62, 63, 64, 65  
Pole Punch 60  
Ruler 60  
Screwdrivers 49, 50, 51, 52  
Screwdriver Sets 51  
Sharpener 55



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

Tool Bag/Bucket 88, 89, 91  
 Tool Kit 54  
 Voltage Detector 161  
 Wire Tool 63, 140  
 Wrenches 68  
 Wrench Sets 65, 66, 67  
**Kneeling Pads**  
     Estex 165  
**Knives**  
     Buckingham 58  
**Knives cont.**  
     Greenlee 57  
     Jameson 58  
     Klein 55, 56, 57  
     Madi 57  
**Knopp**  
     Sequence Indicator 159  
**L**  
**Lamp Changers**  
     Hastings 83  
**Lanterns**  
     Streamlight 172  
**Lanyards**  
     Bashlin 148  
     Buckingham 148, 149, 150  
**Leather Protectors**  
     Salisbury 183  
**Lewis Mfg.**  
     Debris Tarp 126  
     Swivels 100  
**Lighting 172-175**  
**Lincoln Hoist**  
     Hoists 118  
**Line Guard**  
     Hastings 189  
**Line Hose**  
     Salisbury 186, 187  
**Line Hose Bags**  
     Estex 184  
**Little Mule**  
     Grips 106  
     Hoists 116  
**Load Break Tools**  
     S&C 80  
     Utility Solutions 84, 85  
**Locking Dog Assembly**  
     Chance 121  
**Lowell**  
     Wrenches 69  
**Lugall**  
     Hoists 117

**M**

**M&A Products**  
     Stapul-Stik 72  
**Madi**  
     Knives 57  
     Socket Driver 71  
     Hammer 61  
     Universal Attachment 84  
     Utility Tool 84  
     Wire Brushes 72  
     Wrench 71  
**Makita**  
     Batteries 26  
**Manual Cutting & Compression Tools 40-48**  
**Mats**  
     Salisbury 186  
**Meters**  
     SensorLink 160, 161  
**Meter Pullers**  
     Rauckman 71  
**N**  
**Nut Driver Set**  
     Cementex 53  
     Klein 51, 53  
**Nut Runners**  
     Greenlee 38  
**O**  
**OshKosh**  
     Cant Hook 124  
     Digging Bar 125  
     Post Hole Digger 123  
     Shovel 123, 124  
     Tamp Bar 124  
**Ox Block**  
     Buckingham 139  
**P**  
**Pads**  
     Buckingham 145  
**Paslode**  
     Stapler 71  
**Penlight**  
     Streamlight 175  
**Phasing Meters**  
     Bierer Meters 157  
     Hastings 156, 157  
**Pliers**  
     Cementex 61, 62  
     Klein 62, 63, 64, 65  
**Pole Climbers**  
     Buckingham 146  
**Pole Guard**  
     Salisbury 83, 189



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

**Pole Punch**

Klein 60

**Pole Puller Assembly**

Greenlee 34

**Pole Saw Kit**

Jameson 59

**Pole Slings**

Bashlin 147

**Pole Wraps**

Estex 85

**Poly Line**

Greenlee 105

**Portable Lighting System**

Golight 172

**Pressheads**

Cembre 31, 32

**Pruning Saw**

Hastings 58

Jameson 58

**Pruners**

Hastings 83

**Pullers**

Greenlee 34

**Pulling Grips**

Hubbell 97, 98

**Pumps**

Burdby 36

Greenlee 35, 37

Huskie 36

**PTI**

Tool Tray 93

**R*****Rauckman***

Meter Puller 71

Wildlife Zap Shield 193

Wrenches 70

**Ratchet Tools**

Burdby 45

Cementex 71

**Reel Thing**

Tulsa Power 137

**Rescue Kits**

Hastings 155

**Rescue Systems**

Buckingham 155

Salisbury 81

**Rodders**

Condux 101, 102

Jameson 103

**Roll Blankets**

Salisbury 186

**Roller Grips**

Speed Systems 113

**Rope**

Eagle Line 138

Erin 138

**Rope Blocks**

Chance 137

**Ropes & Handlines 137-140****Rubber Blanket**

Salisbury 185

**Rubber Gloves**

Salisbury 178, 179, 181, 182, 183

**Rubber Glove Sizing 176****Rubber Goods Testing Form 199****Rubber Insulating PPE & Accessories 178-193****Rubber Overshoes/Boots**

Salisbury 189, 190, 191

**Rubber Sleeves**

Salisbury 184, 185

**Rubber Sleeve Sizing 177*****Rubbermaid***

Mounting Bracket 165

Water Cooler 165

**Ruler**

Klein 60

**S****Sagometer 105****Sagwatch 105*****S&C***

Handling Tool 85

Loadbuster 80

***Salisbury***

Ball &amp; Socket System 133

Blanket Accessories 192

Bushing Cover 189

Cable End Cap 188

Clamps 130, 131, 132

Cleaners 191

Discharge Stick 83

Ferrules 133

Gloves 167, 168

Glove Accessories 193

Glove Bags 183, 184

Glove Dust 191

Guards 83, 84, 189

Grounding Jumpers 136

Insulator Cover 187, 188

Jumper Cables 136

Leather Protectors 183

Line Hoses 186, 187

Line Hose Bag 184

Rescue Stick 81

Roll Blanket 186



Toll Free: 800-796-9027 Fax: 540-438-9502

www.specialfleettools.com

## Index

**Salisbury cont.**

Rubber Blanket 185  
 Rubber Gloves 178, 179, 180, 181, 182, 183  
 Rubber Overshoes/Overboots 189, 190, 191  
 Rubber Sleeves 184, 185  
 Silicone Spray 191  
 Sleeve Accessories 192  
 Sleeve Bags 183, 184  
 Stinger Cover 193  
 Switchboard Matting 186  
 Tagging Device 188  
 Tool Kit 53  
 Voltage Detector 158

**Saws**

Greenlee 33  
 Hastings 58  
 Jameson 58, 59  
 Klein 58

**Saw Blades**

Jameson 58, 59

**Scabbards**

Hastings 93

**Scoring Tools**

Utility Tool 112

**Screwdrivers**

Cementex 49, 50  
 Klein 49, 50, 51

**Screwdriver Sets**

Cementex 50  
 Klein 51

**Scribers**

Speed Systems 111, 112

**Sensor Link**

Voltage Meters 160, 161

**Sequence Indicators**

Knopp 159

**Seymour Midwest**

Shovel 123

**Sharpening Tools**

Klein 55

**Sherman & Reilly**

Compact Puller 103

**Shotgun Sticks**

Hastings 73, 74

**Shovels**

OshKosh 123, 124  
 Seymour Midwest 123

**Signs**

Bone 164, 165

**Signs & Safety 164-168****Sign Stands**

Bone 165

**Sleeve Accessories**

Salisbury 192

**Sleeve Bags**

Buckingham 183  
 Estex 184

**Sleeve & Leather Protector Sizing 177****Slingco**

Cable Grips 96, 97, 98  
 Swivels 100

**Snaps**

Buckingham 151, 152

**Sockets**

Speed Systems 72

**Socket Drivers**

Madi 71

**Socket Sets**

Cementex 67  
 Klein 65, 66

**Speed Systems**

Chamfering Tool 112  
 Combination Splice/T-Body Tool 113  
 Edge Wedge 115  
 Installation Tool 113, 114  
 Scribers 111, 112  
 Strippers 109, 110  
 Stripper Accessories 111  
 Sockets 72  
 Wrench 69, 70, 72

**Spotlights**

Streamlight 173

**Stanley**

Impact Wrench 27

**Stapler**

Paslode 71

**Stapul-Stik**

M&A Products 72

**Steel Punch**

Huskie 38

**Stinger Cover**

Salisbury 193

**Streamlight**

Battery 172  
 Flashlight 174, 175  
 Headlamps 173, 174  
 Lantern 172  
 LiteBox Accessories 172  
 Pen Light 175  
 Spotlight 173  
 Worklight 174

**Support Arms**

Hastings 79



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



## Index

**Support Studs**

Chance 133

**Swivels**

Condux 99, 100  
 DCD 99  
 Greenlee 100  
 Lewis 100  
 Slingco 100

**T****Tagging Devices**

Salisbury 188

**Tamp Bars**

Chance 126  
 OshKosh 124

**Tampers**

Greenlee 34

**Tape Measure**

Klein 60

**Tarps**

Lewis 126

**Test Equipment & Meters 156-163****Testers**

AEMC 156  
 Chance 157, 162  
 Hastings 160, 163  
 HDE 162

**Tester Accessories**

Chance 157

**Tingley**

Clothing 197

**Tongs**

Dixie 125

**Tool & Equipment Storage 88-95****Tool Bags & Buckets**

Buckingham 88, 92  
 Estex 89, 90, 91, 92  
 Klein 88, 89, 91  
 Warren Heim 88

**Tool Kits**

Cementex 54  
 Klein 54  
 Salisbury 53

**Tool Repair Form 200****Tool Trays**

Buckingham 93  
 Hastings 93  
 PTI 93

**Torque Limiter**

Chance 122

**Traffic Cones**

JBC 164

**Transformer Testers**

Chance 80

***Tulsa Power Products***

Reel Thing 137

**U****Universal Attachment**

Madi 84

**Utility Solutions**

Bypass Tools 84  
 Clamps 193  
 Jumper Hook 85  
 Load Break & Pick-Up Tools 84, 85  
 Measuring Hot Sticks 76

**Utility Tool**

Chamfering Tool 112  
 Insertion Tool 114  
 Scoring Tool 112  
 Strippers 109, 110, 111

**Utility Tools**

Madi 84

**V****Versa Guards**

Salisbury 84, 189

**Voltage Detectors**

Bierer Meters 159  
 Chance 159, 161  
 Hastings 160  
 HDE 159, 160  
 Klein 161  
 Salisbury 158

**Voltage Indicators**

Chance 161

**Voltage Meters**

SensorLink 160, 161

**W*****Warren Heim***

Tool Bucket 88

**Water Cooler**

Rubbermaid 165

**Water Cooler Brackets**

Rubbermaid 165

**Wire Brushes**

Madi 72

**Wire Tools**

Burndy 72  
 Klein 63, 140

**Work Lights**

Streamlight 174

**Wrenches**

Cementex 66  
 Klein 67, 68  
 Lowell 69  
 Madi 71



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)

## Index

Rauckman 70

Speed Systems 69, 70, 72

**Wrench Sets**

Cementex 65, 66

Klein 65, 66, 67

**Y**

***Youngstown Gloves***

Gloves 166, 167



Toll Free: 800-796-9027 Fax: 540-438-9502

[www.specialfleettools.com](http://www.specialfleettools.com)



**U.S. Toll Free: 800-796-9027**

**Phone: 540-433-7727**

**Fax: 540-438-9502**

**[store@specialfleettools.com](mailto:store@specialfleettools.com)**